

## TORQUE SPECIFICATION

| Part Tightened                                            | N·m  | kgf·cm | ft·lbf    |
|-----------------------------------------------------------|------|--------|-----------|
| Shock absorber x Body                                     | 39   | 400    | 29        |
| Shock absorber x Rear axle carrier                        | 255  | 2,600  | 188       |
| Flexible hose x Shock absorber                            | 19   | 194    | 14        |
| ABS speed sensor wire harness x Shock absorber            | 5.5  | 56     | 49 in·lbf |
| Piston rod set nut                                        | 49   | 500    | 36        |
| Shock absorber x Stabilizer bar link                      | 39   | 400    | 29        |
| Rear suspension member x Rear suspensio arm assy No. 1 LH | 100  | 1,020  | 74        |
| Rear suspension member x Body                             | A, B | 55     | 41        |
|                                                           | C    | 38     | 28        |
| Rear suspension arm assy No. 1 x Rear axle carrier        | 100  | 1,020  | 74        |
| Rear suspension arm assy No. 2 x Rear axle carrier        | 100  | 1,020  | 74        |
| Stabilizer bar bracket                                    | 19   | 195    | 14        |
| Stabilizer bar x Stabilizer bar link                      | 39   | 400    | 29        |
| Strut rod x Body                                          | 113  | 1,150  | 83        |
| Strut rod x Rear axle carrier                             | 113  | 1,152  | 83        |
| Parking brake cable x Body                                | 5.4  | 55     | 48 in·lbf |
| Hub nut                                                   | 103  | 1,050  | 76        |