TORQUE SPECIFICATION

2AZ-FE

Part Tightened	N⋅m	kgf⋅cm	ft·lbf
Engine mounting bracket No. 2 RH x Timing chain cover	52	531	38
Engine moving control rod w/ bracket x Engine mounting bracket No. 2 RH	64	653	47
Engine moving control rod w/ bracket x Fender apron RH	64	653	47
Engine mounting stay No. 2 RH x Cylinder head	64	653	47
Engine mounting stay No. 2 RH x Engine mounting bracket No. 2 RH	64	653	47
Drain plug (A/T)	49	500	36
Drain plug (M/T)	49	500	36
Engine hanger No. 1 x Cylinder head	38	387	28
Engine hanger No. 2 x Cylinder head	38	387	28
ECT sensor x Cylinder head	20	204	15
Knock sensor x Cylinder block	39	398	29
Engine oil pressure switch assy x Cylinder head	15	153	11
Water by-pass pipe No. 1 x Cylinder block	9.0	92	80 in.·lbf
Transverse engine engine mounting bracket x Cylinder block	54	551	40
Drive shaft bearing bracket x Cylinder block	64	653	47
V–ribbed belt tensioner assy x Timing chain cover	59.5	607	44
Ignition coil assy x Cylinder head	9.0	92	80 in.·lbf
Water inlet x Cylinder block	9.0	92	80 in.·lbf
Exhaust manifold converter x Cylinder head	37	378	27
Exhaust manifold stay x Exhaust manifold converter	44	449	32
Manifold converter insulator No. 1 x Exhaust manifold converter	12	122	9
Oil level gage guide x Water by-pass pipe No. 1	9.0	92	80 in.·lbf
Intake manifold x Cylinder head	30	306	22
Drive plate & ring gear (A/T) x Crankshaft	98	1,000	72
Flywheel sub-assy (M/T) x Crankshaft	130	1,330	96
Starter assy x Automatic transaxle assy	39	398	29
Starter assy x Manual transaxle assy	39	398	29
Engine mounting insulator LH x Automatic transaxle assy	95	969	70
Engine mounting insulator LH x Manual transaxle assy	143	1,459	105
Engine mounting insulator RH x Engine mounting bracket RH	95	969	70
Engine mounting insulator FR x Engine mounting bracket FR	87	888	64
Engine mounting bracket rear No. 2 x Engine lateral control rod (M/T)	89	910	66
Vane pump assy x Timing chain cover	43	439	32
Frame side plate x Front frame assy Bolt A	85	867	63
Frame side plate x Body Bolt B	32	326	24
Front suspension member brace rear x Front frame assy Bolt C	85	867	63
Front suspension member brace rear x Body Bolt D	32	326	24
Steering intermediate shaft	35	357	26
Drive plate & ring gear x Torque converter	41	418	30
Front suspension arm sub–assy lower No. 1 x Lower ball joint	75	764	55
Tie rod assy x Steering knuckle	49	500	36
Speed sensor front LH (w/ ABS) x Steering knuckle	8.0	82	71 in.·lbf
Speed sensor front RH (w/ ABS) x Steering knuckle	8.0	82	71 in.·lbf
Front axle hub LH nut x Front drive shaft	294	3,000	217
Front stabilizer link assy x Front suspension	74	755	55
Air cleaner assy x Body	5.0	51	44 in.·lbf
Balanceshaft housing x Stiffening crankcase assy 1st 2nd	22 Turn 90°	220 Turn 90°	16 Turn 90°
Stiffening crankcase assy x Cylinder block	33	332	24
Outliering Granicase assy & Cyllinder Diock	აა	332	24

030EU-04

SERVICE SPECIFICATIONS - ENGINE MECHANICAL

Part Tightened	N⋅m	kgf⋅cm	ft·lbf
w/ head taper screw plug No. 1 x Cylinder block	26	265	19
Oil control valve filter x Cylinder block	30	306	22
Cylinder block water drain cock x Stiffening crankcase assy	25	255	18
Cylinder head x Cylinder block 1s	79	806	58
2nd	Turn 90°	Turn 90°	Turn 90°
Camshaft timing gear assy x Camshaft	54	551	40
Camshaft timing sprocket x Camshaft	54	551	40
Camshaft bearing cap No. 1 x Cylinder head	30	301	22
Camshaft bearing cap No. 2 x Cylinder head	30	301	22
Camshaft bearing cap No. 3 x Cylinder head	9.0	92	80 in.·lbf
Oil pump assy x Stiffening crankcase assy	19	194	14
Chain tensioner plate x Stiffening crankcase assy	12	122	9
Oil pump drive sprocket x Oil pump	30	301	22
Chain vibration damper No. 1 x Cylinder head	9.0	92	80 in.·lbf
Chain vibration damper No. 1 x Cylinder block	9.0	92	80 in.·lbf
Chain tensioner slipper x Cylinder block	19	194	14
Timing chain guide x Crankshaft bearing cap No. 1	9.0	92	80 in.·lbf
Timing chain cover (See page 14–75) Bolt A	9.0	92	80 in.·lbf
Bolt E	21	214	15
Bolt C		438	32
Nu	9.0	92	80 in.·lbf
Oil pan x Stiffening crankcase assy	9.0	92	80 in.·lbf
Oil pan drain plug x Oil pan	25	250	18
Water pump assy x Cylinder block	9.0	92	80 in.·lbf
Water pump pulley x Water pump assy	26	265	19
Crankshaft position sensor x Timing chain cover	9.0	92	80 in.·lbf
Crankshaft pulley x Crankshaft	170	1,733	125
Chain tensioner assy No. 1 x Timing chain cover	9.0	92	80 in.·lbf
Camshaft position sensor x Cylinder head	9.0	92	80 in.·lbf
Cylinder head cover x Cylinder head	11	110	8
Oil filter union x Stiffening crankcase assy	30	306	22
Spark plug x Cylinder head	19	194	14
Ventilation valve x Cylinder head cover	19	194	14
Front suspension brace x Body	80	816	59
Stud bolt (See page 14–108) Bolt A	-	51	44 in.·lbf
Bolt E		51	44 in.·lbf
Bolt (97	84 in.·lbf
Bolt [97	84 in.·lbf
Stud bolt (See page 14–120) Stud bolt A Stud bolt A		51 97	44 in.·lbf 84 in.·lbf
Stud bolt 0		51	84 in.·lbf 44 in.·lbf
Crankshaft bearing cap x Cylinder block 1s		204	15
2nd		408	29
Connecting rod cap x Connecting rod 1s	25	250	18
2nd		Turn 90°	Turn 90°

1MZ-FE/3MZ-FE

Part Tightened	N⋅m	kgf⋅cm	ft·lbf
Engine hanger No. 2 x Cylinder head	20	204	15
Knock sensor x Cylinder block 1MZ-FE	39	398	39
3MZ-FE	20	204	15
Oil pressure switch assy x Cylinder block	15	152	11
Compressor mounting bracket No.1 x Cylinder block	25	255	18
Generator bracket No. 1 x Cylinder block	58	591	43
Pump bracket x Cylinder head	32	326	24
Drive shaft bearing bracket x Cylinder block	64	653	47
Exhaust manifold converter sub-assy No. 2 x Cylinder head	49	500	36
Exhaust manifold heat insulator No. 2 x Cylinder head	8.5	87	75 in.·lbf
Exhaust manifold converter sub-assy RH x Cylinder head	49	500	36
ntake manifold x Cylinder head	15	153	11
gnition coil assy x Cylinder head cover	8.0	82	71 in.·lbf
ntake air surge tank x Intake manifold	28	286	21
Surge tank stay bolt	20	204	15
Engine hanger No. 2 x Cylinder head	39	398	29
Engine hanger No. 1 x Intake air surge tank	39	398	29
Manifold stay No. 2 x Exhaust manifold converter sub-assy	49	500	36
Manifold stay No. 2 x Automatic transaxle assy	49	500	36
Engine mounting insulator RH x Engine mounting bracket	95	969	70
Engine mounting insulator LH x Automatic transaxle assy	95	969	70
Engine mounting insulator FR x Automatic transaxle assy	87	887	64
/ane pump assy x Pump bracket	43	439	32
/ane pump assy x Engine mounting bracket	43	439	32
Frame side rail plate sub-assembly x Front frame assy		.00	02
See page 14–164) Bolt A	85	867	63
Bolt B	32	326	24
Nut	32	326	24
Front suspension member brace rear x Front frame assy			
See page 14–164) Bolt C	85	867	63
Bolt D	32	326	24
Nut	32	326	24
Compressor and magnetic clutch x Compressor mounting bracket No.1 (See page 14–164) Bolt	05	250	40
Nut	25 26	250 260	18 19
Generator belt adjusting bar x Cylinder block	20	200	15
See page 14–164) Nut A	43	438	32
Bolt B	18	184	13
Bolt C	8.0	82	71 in.·lbf
Generator bracket No. 2 x Transverse engine engine mounting bracket	28	286	21
ntermediate shaft sub-assy	35	357	26
Orive plate & ring gear x Torque converter	41	418	30
Flywheel housing under cover x Automatic transaxle assy	7.8	80	69 in.·lbf
Front suspension arm x Lower ball joint	75	764	55
Fie rod end x Steering knuckle	49	500	36
Front axle hub nut x Front drive shaft	294	2,998	217
Front stabilizer link assy x Front suspension	74	755	55
√-bank cover x Cylinder head cover	7.9	81	70 in.·lbf
Engine mounting stay No. 2 RH x Engine engine mounting bracket	64	653	47
Engine moving control rod (See page 14–164) Bolt A	64	653	47
Bolt B	23	235	17
Camshaft sub-gear x Main gear	5.4	55	48 in.·lbf
		i	<u> </u>

Dest Talance d	k1	1	fr 11. f
Part Tightened	N·m	kgf-cm	ft-lbf
Engine rear oil seal retainer x Cylinder block	8.0	82	71 in.·lbf
Oil pump assy x Cylinder block (See page 14–186) 10 mm head	8.0	82	71 in.·lbf
12 mm head 14 mm head	20 43	204 439	15 32
Crank position sensor x Oil pump assy	8.0	82	71 in.·lbf
Oil pan baffle plate x Oil pan sub–assy	8.0	82	71 in.·lbf
		 	-
Oil pan sub-assy x Cylinder block (See page 14–186) 10 mm head 12 mm head	8.0 20	82 204	71 in.·lbf 15
Oil strainer sub–assy x Oil pan sub–assy	8.0	82	71 in.·lbf
Oil pan sub–assy No. 2 x Oil pan sub–assy	8.0	82	71 in.·lbf
Oil pan drain plug x Oil pan sub–assy No. 2	45	459	33
Water inlet housing x Cylinder block	8.0	82	71 in.·lbf
Cylinder head x Cylinder block 12 pointed head 1st	54	551	40
2nd	Turn 90°	Turn 90°	Turn 90°
Recessed head	19	189	14
Camshaft bearing cap x Cylinder head	16	163	12
Timing belt plate x Oil pump assy	8.0	82	71 in.·lbf
Water pump assy x Cylinder block	8.0	82	71 in.·lbf
Oil level gage guide x Cylinder block	8.0	82	71 in.·lbf
Oil filter union x Cylinder block	30	306	22
Timing belt idler bracket x Cylinder block	28	286	21
Timing belt No. 3 cover x Cylinder head	8.5	87	76 in.·lbf
Camshaft timing pulley x Camshaft	125	1,275	92
Timing belt idler sub–assy No. 2 x Timing belt idler bracket	43	438	32
Timing belt idler sub–assy No. 1 x Cylinder block	34	347	25
Chain tensioner assy No. 1 x Oil pump assy	27	280	20
Transverse engine engine mounting bracket x Cylinder block	28	286	21
Timing belt No. 2 cover x Timing belt No. 3 cover	8.5	87	76 in.·lbf
Timing belt No. 1 cover x Oll pump assy	8.5	87	76 in.·lbf
Crankshaft pulley x Crankshaft	215	2,192	159
Camshaft position sensor x Cylinder head	8.0	82	71 in.·lbf
Cylinder head cover x Cylinder head	8.0	82	71 in.·lbf
Spark plug x Cylinder head	18	184	13
Vane pump assy x Adjusting strut	43	439	32
Generator x Generator bracket	58	591	43
Generator x Adjusting bar	18	184	13
Front suspension brace upper x Body	80	816	59
Water outlet x Cylinder head	15	153	11
Exhaust manifold heat insulator No. 2 x Exhaust manifold LH	8.5	87	55 in.·lbf
Exhaust pipe support bracket No. 1 x Automatic transaxle assy	21	214	15
Drive plate & ring gear sub-assy x Crankshaft	83	846	61
w/ head straight screw plug No. 1 x Cylinder head	44	449	32
w/ head straight screw plug No. 2 x Cylinder head	44	449	32
Main bearing cap x Cylinder block 12 pointed head 1st	22	224	16
2nd	Turn 90°	Turn 90°	Turn 90°
6 pointed head	27	275	20
Connecting rod cap x Connecting rod 1st 2nd	25 Turn 90°	250 Turn 90°	18 Turn 90°
Cylinder block w/ head straight screw No. 1 plug x Cylinder block	30	306	22
Cylinder block w/ head straight screw No. 2 plug x Cylinder block	50	510	37
Cylinder block w/head straight screw No. 3 plug x Cylinder block	30	306	22

SERVICE SPECIFICATIONS - ENGINE MECHANICAL

Part Tightened	N⋅m	kgf⋅cm	ft·lbf
Water seal plate x Cylinder block	18	184	13
Cylinder block water drain cock sub–assy x Cylinder block	39	398	29