

# IGNITION

## SERVICE DATA

030GN-01

### 1AZ-FE

Spark plug Recommended spark plug	DENSO NGK	SK20R11 IFR6A11
Electrode gap	Standard Maximum	1.0 – 1.1 mm (0.039 – 0.043 in.) 1.3 mm (0.051 in.)
Camshaft position sensor Resistance	at cold at hot	835 – 1,400 $\Omega$ 1,060 – 1,645 $\Omega$
Crank position sensor Resistance	at cold at hot	985 – 1,600 $\Omega$ 1,265 – 1,890 $\Omega$

### 2AZ-FE

Spark plug Recommended spark plug	DENSO NGK	SK20R11 IFR6A11
Electrode gap	Standard Maximum	1.0 – 1.1 mm (0.039 – 0.043 in.) 1.3 mm (0.051 in.)
Camshaft position sensor Resistance	at cold at hot	835 – 1,400 $\Omega$ 1,060 – 1,645 $\Omega$
Crank position sensor Resistance	at cold at hot	985 – 1,600 $\Omega$ 1,265 – 1,890 $\Omega$

### 1MZ-FE

Spark plug Recommended spark plug	DENSO NGK	SK20R11 IFR6A11
Electrode gap	Standard Maximum	1.0 – 1.1 mm (0.039 – 0.043 in.) 1.2 mm (0.047 in.)
Camshaft position sensor Resistance	at cold at hot	835 – 1,400 $\Omega$ 1,060 – 1,645 $\Omega$
Crank position sensor Resistance	at cold at hot	1,630 – 2,740 $\Omega$ 2,065 – 3,225 $\Omega$