0527M-42

PROBLEM SYMPTOMS TABLE

HINT:

If a normal code is displayed during the diagnostic trouble code check although the trouble still occurs, check the electrical circuits for each symptom in the order given in the charts on the following pages and proceed to the page given for troubleshooting.

The Matrix Chart is divided into 2 chapters.

1. Chapter 1: Electronic Circuit Matrix Chart

- Refer to the table below when the trouble cause is considered to be electrical.
- If the instruction "Proceed to next circuit inspection shown on matrix chart" is given in the flow chart of each circuit, proceed to the circuit with the next highest number in the table to continue the check.
- If the trouble still occurs even though there are no abnormalities in any of the other circuits, check and replace the ECM.

HINT:

*1: When the circuit on which mark *1 is attached is defective, DTC could be output (see page 05–1280).

Symptom	Suspected Area	See page
No down–shift (A particular gear, from 1st to 4th gear, is not down–shifted)	1. Shift solenoid valve (SL1) circuit *1 2. Shift solenoid valve (SL2) circuit *1 3. Shift solenoid valve (SL3) circuit *1 4. Shift solenoid valve (SR) circuit *1 5. ECM	05–1308 05–1325 05–1337 05–1320 01–32
No down–shift (5th \rightarrow 4th)	Transmission control switch (O/D OFF) circuit Shift solenoid valve (S4) circuit *1 ECM	05–1358 05–1315 01–32
No up-shift (A particular gear, from 1st to 4th gear, is not up-shifted)	Shift solenoid valve (SL1) circuit *1 Shift solenoid valve (SL2) circuit *1 ECM	05–1308 05–1325 01–32
No up–shift (4th \rightarrow 5th)	Transmission control switch (O/D OFF) circuit Shift solenoid valve (S4) circuit *1 ECM	05–1358 05–1315 01–32
No lock-up	Shift solenoid valve (DSL) circuit *1 Stop light switch circuit *1 Engine coolant temp. sensor circuit *1 ECM	05–1303 05–1300 05–543 01–32
No lock-up off	Shift solenoid valve (DSL) circuit *1 ECM	05–1303 01–32
Shift point too high or too low	Throttle position sensor circuit *1 Shift solenoid valve (SLT) circuit *1 ECM	05–543 05–1351 01–32
Up-shift to 5th from 4th while shift lever is D (O/D OFF) position	Transmission control switch (O/D OFF) circuit ECM	05–1358 01–32
Up-shift to 5th from 4th while engine is cold	Engine coolant temp. sensor circuit *1 ECM	05–543 01–32
Up–shift to 2nd from 1st while shift lever is L position	Transmission control switch (2 ⇔ L position) circuit *1 ECM	05–1282 01–32
Harsh engagement (N \rightarrow D)	Shift solenoid valve (SL1) circuit *1 ECM	05–1308 01–32
Harsh engagement (Lock-up)	Shift solenoid valve (SL2) circuit *1 ECM	05–1325 01–32
Harsh engagement (Any driving position)	Shift solenoid valve (SLT) circuit *1 ECM	05–1351 01–32

DIAGNOSTICS - ELECTRONIC CONTROLLED AUTOMATIC TRANSAXLE [ECT] (U151E)

Poor acceleration	Shift solenoid valve (SLT) circuit *1 ECM	05–1351 01–32
No kick-down	ECM	01–32
Engine stalls when starting off or stopping	Shift solenoid valve (DSL) circuit *1 ECM	05–1303 01–32
Malfunction in shifting	Park/neutral position switch circuit *1 Transmission control switch (O/D OFF) circuit ECM	05–1282 05–1358 01–32

2. Chapter 2: On-Vehicle Repair and Off-Vehicle Repair (★: U151E, U151F AUTOMATIC TRANSAXLE Repair Manual Pub. No. RM1021U)

Symptom	Suspected Area	See page
Vehicle does not move in forward position and in reverse position	1. Valve body assy	40–37
	on 2. U/D brake (B ₃)	*
	3. Torque converter clutch	40–27
	1. Valve body assy	40–37
Vehicle does not move in R position	2. Reverse clutch (C ₂)	*
	3. 1st & reverse brake (B ₂)	*
No up shift (1st > 2nd)	1. Valve body assy	40–37
No up–shift (1st \rightarrow 2nd)	2. 2nd & O/D brake (B ₁)	*
No up–shift (2nd \rightarrow 3rd)	1. Valve body assy	40–37
	2. Direct and O/D clutch (C ₀)	*
No use shift (One) at the	1. Valve body assy	40–37
No up–shift (3rd \rightarrow 4th)	2. 2nd & O/D brake (B ₁)	*
No consist (Alb. 15th)	1. Valve body assy	40–37
No up–shift (4th \rightarrow 5th)	2. U/D clutch (C ₃)	*
No down–shift (5th \rightarrow 4th)	Valve body assy	40-37
No down–shift (4th \rightarrow 3rd)	Valve body assy	40–37
No down–shift (3rd \rightarrow 2nd)	Valve body assy	40–37
No down–shift (2nd → 1st)	Valve body assy	40–37
	Valve body assy	40–37
No lock-up or No lock-up off	2. Torque converter clutch	40–27
	Valve body assy	40–37
	2. C ₁ accumulator	*
Harsh engagement (N \rightarrow D)	3. Forward clutch (C ₁)	*
	4. One–way clutch No.1 (F ₁)	*
	5. U/D one-way clutch (F ₂)	*
Harah angagamant (Logic up)	1. Valve body assy	40–37
Harsh engagement (Lock-up)	2. Torque converter clutch	40–27
Harsh engagement (N \rightarrow R)	1. Valve body assy	40–37
	2. C ₂ accumulator	*
	3. Reverse clutch (C ₂)	*
	4. 1st & reverse brake (B ₂)	*
Harsh engagement (1st \rightarrow 2nd \rightarrow 3rd \rightarrow 4th \rightarrow 5th)	Valve body assy	40-37
Llovoh ongogoment (4st.) 2nd)	1. Valve body assy	40–37
Harsh engagement (1st \rightarrow 2nd)	2. 2nd & O/D brake (B ₁)	*
Harsh engagement (2nd \rightarrow 3rd)	1. Valve body assy	40–37
	2. C ₀ accumulator	*
	3. Direct and O/D clutch (C ₀)	*
Harsh engagement (3rd \rightarrow 4th)	1. Valve body assy	40–37
	2. 2nd & O/D brake (B ₁)	*
Harsh engagement (4th \rightarrow 5th)	1. Valve body assy	40–37
	2. C ₃ accumulator	*
	3. U/D clutch (C ₃)	*
Harsh engagement (5th \rightarrow 4th)	1. Valve body assy	40–37
Taisii engagement (Sui → 4tii)	2. B ₃ accumulator	*

DIAGNOSTICS - ELECTRONIC CONTROLLED AUTOMATIC TRANSAXLE [ECT] (U151E)

	4. Value hade access	40.07
Slip or shudder (Forward and reverse: After warm-up)	Valve body assy Oil strainer	40–37 40–37
	3. Direct and O/D clutch (C ₀)	±
	4. Forward clutch (C ₁)	\ \hat{\sigma}
	5. U/D clutch (C ₃)	*
	6. 2nd & O/D brake (B ₁)	*
	7. U/D brake (B ₃)	*
	8. One–way clutch No.1 (F ₁)	*
	9. U/D one-way clutch (F ₂)	*
	10.Torque converter clutch	40–27
Slip or shudder (Particular position: Just after engine starts)	Torque converter clutch	40–27
Slip or shudder (R position)	1. Reverse clutch (C ₂)	*
	2. 1st & reverse brake (B ₂)	*
	1. Forward clutch (C ₁)	,
Slip or shudder (1st)	2. One–way clutch No.1 (F ₁)	*
	3. U/D one-way clutch (F ₂)	*
Slip or shudder (2nd)	2nd & O/D brake (B ₁)	*
Slip or shudder (3rd)	Direct and O/D clutch (C ₀)	*
Slip or shudder (4th)	2nd & O/D brake (B ₁)	*
Slip or shudder (5th)	U/D clutch (C ₃)	*
No engine braking (1st – 4th: D position)	U/D brake (B ₃)	*
No engine braking (1st: L (1) position)	1. Valve body assy	40–37
	2. 1st & reverse brake (B ₂)	*
No engine braking (2nd: 2 position)	Valve body assy	40-37
	2. 2nd & O/D brake (B ₁)	*
No engine braking (3rd: 3 position)	U/D brake (B ₃)	*
Poor acceleration (All positions)	Torque converter clutch	40–27
Poor acceleration (5th)	1. U/D clutch (C ₃)	*
	2. U/D planetary gear unit	*
Engine stalls when starting off or stopping	Torque converter clutch	40–27
No kick-down	Valve body assy	40-37