

TORQUE SPECIFICATION

| Part Tightened | N·m | kgf·cm | ft·lbf |
|---|------|--------|------------|
| Transmission case x Manual transaxle case | 29 | 296 | 21 |
| Manual transaxle case x Transmission case | 29 | 296 | 21 |
| Bearing retainer RR x Transmission case | 42 | 428 | 31 |
| Manual transaxle case receiver x Manual transaxle case | 7 | 71 | 62 in.·lbf |
| Gear shift head No.1 x Gear shift fork shaft No.2 | 24 | 245 | 18 |
| Gear shift fork No.1 x Gear shift fork shaft No.1 | 24 | 245 | 18 |
| Reverse shift arm bracket x Manual transaxle case | 17 | 173 | 13 |
| Reverse restrict pin plug x Transmission case | 13 | 133 | 9.6 |
| Oil receiver pipe No.1 x Transmission case | 17 | 173 | 13 |
| Oil receiver pipe No.2 x Transmission case | 17 | 173 | 13 |
| Clutch tube bracket x Transmission case | 17 | 173 | 13 |
| Reverse idler gear shaft bolt x Transmission case | 30 | 306 | 22 |
| Shift detent ball plug x Manual transaxle case | 25 | 250 | 18 |
| Transmission clutch hub No.3 gear shift fork shaft x input shaft | 24 | 245 | 18 |
| Manual transmission output rear set nat. x Output shaft | 123 | 1,254 | 91 |
| Drain (MTM) plug sub-assy x Transmission case | 49 | 500 | 36 |
| Manual transmission filler plug x Transmission case | 49 | 500 | 36 |
| Back up lamp switch assy x Transmission case | 40 | 408 | 30 |
| Manual transmission breather plug x Transmission case | 49 | 500 | 36 |
| Lock ball assy No.1 x Transmission case | 29 | 296 | 21 |
| Control shift cover x Transmission case | 20 | 204 | 15 |
| Control shift lever x Shift & select lever assy | 6.4 | 65 | 57 in.·lbf |
| Selecting bell crank assy x Transmission case | 20 | 204 | 15 |
| Speedometer driven hole cover x Transmission case | 5.5 | 56 | 48 in.·lbf |
| Selecting bellcrank support x Selecting bellcrank No.2 plate washer | 12 | 122 | 9 |
| Release fork support x Manual transaxle case | 47.1 | 480 | 35 |
| Front differential ring gear x Front differential case | 106 | 1,081 | 78 |