ENGINE HOOD/DOORTORQUE SPECIFICATION

030FI _03

Part Tightened	N⋅m	kgf⋅cm	ft·lbf
HOOD	-	-	-
Hood x Hood hinge	26	265	19
Hood lock x Body	8.0	82	71 in.·lbf
FRONT DOOR	-	_	-
Door frame sub–assy front lower x Door panel	7.0	71	62 in.·lbf
Door frame sub-assy rear lower x Door panel	7.0	71	62 in.·lbf
Door glass x Window regulator	5.5	56	49 in.·lbf
Door hinge x Body	26	265	19
Door hinge x Door panel	26	265	19
Door lock striker x Body	23	235	17
Door window regulator x Body	8.0	82	71 in.·lbf
Door w/ motor lock x Door panel	5.0	51	44 in.·lbf
Outer rear view mirror x Door panel	5.5	56	49 in.·lbf
Outside handle sub-assy x Door panel	4.0	41	37 in.·lbf
Power window regulator motor x Window regulator	5.4	55	48 in.·lbf
Nindow regulator x Door panel	8.0	82	71 in.·lbf
REAR DOOR	_	_	_
Door glass x Window regulator	5.5	56	49 in.·lbf
Door hinge x Body	26	265	19
Door hinge x Door panel	26	265	19
Door lock striker x Body	23	235	17
Door outside handle cover x Door panel	4.0	41	37 in.·lbf
Door window division bar x Door panel	5.5	56	49 in.·lbf
Door window regulator x Body	8.0	82	71 in.·lbf
Door window regulator x Body	8.0	82	71 in.·lbf
Door w/ motor lock x Door panel	5.0	51	44 in.·lbf
Outer rear view mirror x Door panel	5.5	56	49 in.·lbf
Outside handle frame x Door panel	4.0	41	37 in.·lbf
Power window regulator motor x Window regulator	5.4	55	48 in.·lbf
Vindow regulator x Door panel	8.0	82	71 in.·lbf
UGGAGE COMPARTMENT DOOR	_	_	_
Luggage compartment door x body	5.5	56	49 in.·lbf
Luggage compartment door x luggage compartment door hinge	8.0	82	71 in.·lbf