

HOW TO PROCEED WITH TROUBLESHOOTING

The hand-held tester can be used in steps 4, 6, 8 and 9.

1 VEHICLE BROUGHT TO WORKSHOP

NEXT


2 CUSTOMER PROBLEM ANALYSIS (SEE PAGE 05-1451)

NEXT


3 WARNING LIGHT CHECK (SEE PAGE 05-1456)

NEXT

4 DTCs CHECK (Present and Past DTCs) (SEE PAGE 05-1464)



DTCs ARE OUTPUT (INCLUDING NORMAL SYSTEM CODE): Go to step 5



DTCs ARE NOT OUTPUT: PROBLEM SYMPTOMS TABLE (SEE PAGE 05-1477)

5 DTCs CHART (SEE PAGE 05-1478)

NEXT

6 CIRCUIT INSPECTION (SEE PAGE 05-1483 TO 05-1773)

NEXT


7 REPAIR

NEXT


8 CLEAR DTCs (Present and Past DTCs) (SEE PAGE 05-1464)

NEXT

9 DTCs CHECK (Present and Past DTCs) (SEE PAGE 05-1464)



DTCs ARE NOT OUTPUT: Go to step 10



DTCs ARE OUTPUT: Go to step 5

10	SYMPTOM SIMULATION (SEE PAGE 01-22)
----	--

WARNING LIGHT REMAINS OFF: Go to step 11

WARNING LIGHT IS ON: Go to step 5

11	CONFIRMATION TEST
----	-------------------

NEXT

END