
CIRCUIT IN STOP LIGHT SWITCH	PEN CIRCUIT IN STOP LIGHT SWITCH IRCUIT	C1249/49	DTC
------------------------------	---	----------	-----

CIRCUIT DESCRIPTION

	DTC No. DTC Detecting Condition ECU terminal IG1 voltage is 9.5 to 18.5 V and ABS is in non-operation, the open circuit of stop light switch circuit continues for 0.3 sec. or more.		Trouble Area
			Stop light switch circuit

WIRING DIAGRAM



INSPECTION PROCEDURE

1 | CHECK[\$TOP[LAMP[\$WITCH[OPERATION

(a) Check[]hat[]he[]stop[]ight[]ights[]up[]when[]brake[]pedal[]s[]depressed[]and[]urns[]off[]when[]he[]brake[]pedal is[]eleased.

OK

Go[to[step[3

NG


2 | CHECK[\$TOP[LAMP[\$WITCH[CIRCUIT

NGĎ

 $\begin{array}{ll} \textbf{REPAIR} \square \textbf{OR} \square \textbf{REPLACE} \square \textbf{STOP} \square \textbf{LAMP} \square \textbf{SWITCH} \\ \textbf{CIRCUIT} \end{array}$

OK

3 | CHECK[\$KID[CONTROL[ECU]TERMINAL[YOLTAGE(STP]TERMINAL]



- (a) Remove[the[skid[control[ECU[with[connectors[still[connected.
- (b) Measure voltage between rminal STP of skid control ECU and body fround when brake bedal special special.

OK:

Brake[pedal[is]depressed: 10 – 14 V Brake[pedal[is]released:[0][V

ОК

CHECK_AND_REPLACE_SKID_CONTROL_ECU ASSY

NG

4∏

CHECK[HARNESS[AND[CONNECTOR(STOP[LIGHT[\$WITCH - [\$KID[CONTROL ECU[ASSY)(See[page[01-31)]

NG∐

OK

PROCEED_TO_NEXT_CIRCUIT_INSPECTION_\$HOWN_ON_PROBLEM_\$YMPTOMS_TABLE (See_page_05-463)