# ABNORMAL[NOISE]OCCURS

## **INSPECTION PROCEDURE**

### 1 CHECK SPEAKERS

(a) ☐ Check The [\$peaker [unit [installation [condition.]

(1) Check[that[each[speaker[is[securely[installed.

Standard: The problem does not recur.

#### HINT:

The radio revention function reduce reduced r

Noise[Conditions	Noise[\$ource
Depressing@he@cceleratorpedalmakes@hemoise@buder.@however,@hemoisestops@mmediately@when@he@engine@s@stopped.	Alternator
Noise[occurs[while]the]A/C[or[heater[is]in[operation.	Blower@notor
Noise@an@e@eard@uring@udden@cceleration@n@an@inpaved@oad,@r@fterthe@gnition@witch@s@urned@N.	Fuel[pump
Noise@an@e@heard@when@hermorn@s@ressed@and@eleased,@r@eld@down continuously.	Horn
Slight@oise@an@e@eard@hile@he@ngine@uns,@ut@tops@hen@he@ngine@sstopped.	Ignition
Noise@an@e@heard@vhen@he@urn@signal@links.	Flasher
Noise@an@eeTheard@while@he@vindow@vasher@s@n@peration.	Washer
Noise@an@e@heard@while@he@ngine@s@unning@and@ontinues@after@t@sstopped.	Water[iemperature[sensor
Noise@an@e@heard@while@he@wiper@system@s@n@peration.	Wiper
Noise@an@e@heard@when@heake@pedal@s@depressed.	Stop[light[switch
Others	Static[electricity

#### HINT:

- First confirm that the foreign hoise cannot be heard. Failure to do so will kely result n misdiagnosis of the source of the noise.
- If more than one source exists, noise should be removed from the loudest to quietest.

NG REINSTALL SPEAKER PROPERLY

OK

PROCEED\_TO\_NEXT\_CIRCUIT\_INSPECTION\_\$HOWN[IN\_PROBLEM\_\$YMPTOMS\_TABLE (SEE\_PAGE\_05-46)