

# TORQUE SPECIFICATION

## 1AZ-FE

Part Tightened	N·m	kgf·cm	ft·lbf
Delivery pipe x Cylinder head	20	204	15
Fuel tank vent tube set plate x Fuel tank	3.5	36	31 in.·lbf
Fuel main tube support x Fuel tank assy	5.4	55	48 in.·lbf
Fuel tank assy x Body	39	400	29
Fuel tank protector lower center x Fuel tank assy	5.4	55	48 in.·lbf
Parking brake cable assy No. 3 x Body	5.4	55	48 in.·lbf
Parking brake cable assy No. 2 x Body	5.4	55	48 in.·lbf

## 2AZ-FE

Part Tightened	N·m	kgf·cm	ft·lbf
Delivery pipe x Cylinder head	20	204	15
Fuel tank vent tube set plate x Fuel tank	3.5	36	31 in.·lbf
Fuel main tube support x Fuel tank assy	5.4	55	48 in.·lbf
Fuel tank assy x Body	39	400	29
Fuel tank protector lower center x Fuel tank assy	5.4	55	48 in.·lbf
Parking brake cable assy No. 3 x Body	5.4	55	48 in.·lbf
Parking brake cable assy No. 2 x Body	5.4	55	48 in.·lbf

## 1MZ-FE

Part Tightened	N·m	kgf·cm	ft·lbf
Delivery pipe x Cylinder head	10	102	7
Pulsation damper x Delivery pipe	33	336	24
Fuel pipe x Delivery pipe	33	336	24
Fuel pipe x Intake manifold	20	199	14
Front suspension brace sub-assy upper center x Body	80	816	59
Fuel tank vent tube set plate x Fuel tank	3.5	36	31 in.·lbf
Fuel main tube support x Fuel tank	5.4	55	48 in.·lbf
Fuel tank x Body	39	400	29
Fuel tank protector lower center x Fuel tank	5.4	55	48 in.·lbf
Parking brake cable assy No.2 x Body	5.4	55	48 in.·lbf
Parking brake cable assy No.3 x Body	5.4	55	48 in.·lbf