

FUEL

SERVICE DATA

030EN-04

2AZ-FE:

Fuel pressure		304 to 343 kPa (3.1 to 3.5 kgf/cm ² , 44 to 50 psi)
Fuel pressure		147 kPa (1.5 kgf/cm ² , 21 psi) or more
Fuel injector Resistance	at 20°C (68°F)	13.4 to 14.2Ω
Injection volume		76 to 91 cm ³ (4.6 to 5.5 cu in.) per 15 seconds
Difference between each cylinder		15 cm ³ (0.9 cu in.) or less
Fuel leakage		1 drop or less per 12 minutes
Fuel pump Resistance	at 20°C (68°F)	0.2 to 3.0 Ω

1MZ-FE/3MZ-FE:

Fuel pressure		304 to 343 kPa (3.1 to 3.5 kgf/cm ² , 44 to 50 psi)
Fuel pressure		147 kPa (1.5 kgf/cm ² , 21 psi) or more
Fuel injector Resistance	at 20°C (68°F)	13.4 to 14.2Ω
Injection volume		60 to 73 cm ³ (3.7 to 4.5 cu in.) per 15 seconds
Difference between each cylinder		13 cm ³ (0.8 cu in.) or less
Fuel leakage		1 drop or less per 12 minutes
Fuel pump Resistance	at 20°C (68°F)	0.2 to 3.0 Ω