Conditionals

Victor Eijkhout, Susan Lindsey

Fall 2019



Conditionals



Conditionals

Single line conditional: if (test) statement

```
The full if-statement is:

if ( something ) then
  !! something_doing
else
  !! otherwise_else
end if
```

The 'else' part is optional; you can nest conditionals.



Comparison and logical operators

Operator	old style	meaning	example
==	.eq.	equals	x==y-1
/=	.ne.	not equals	x*x*!=5
>	.gt.	greater	y>x-1
>=	.ge.	greater or equal	sqrt(y)>=7
<	.lt.	less than	
<=	.le.	less equal	
	.andor.	and, or	x<1 .and. x>0
	.not.	not	.not.(x>1 .and. x<2
	.eqv.	equiv	$(x \wedge y) \vee (\neg x \wedge \neg y)$
	.neqv.	not equiv	$(x \wedge \neg y) \vee (\neg x \wedge y)$



Select statement

Test single values or ranges, integers or characters:

```
Select Case (i)
Case (:-1)
   print *,"Negative"
Case (5)
   print *,"Five!"
Case (0)
   print *,"Zero."
Case (1:4,6:) ! can not have (1:)
   print *,"Positive"
end Select
```

Compiler does checking on overlapping cases!



Exercise 1

Read in an integer. If it's a multiple of three print 'Fizz!'; if it's a multiple of five print 'Buzz'!. It it is a multiple of both three and five print 'Fizzbuzz!'. Otherwise print nothing. (Note: your program should display at most one output.)



Optional exercise 2

Read in three grades: Algebra, Biology, Chemistry, each on a scale $1 \cdots 10$. Compute the average grade, with the conditions:

- Algebra is always included.
- Biology is only included if it increases the average.
- Chemistry is only included if it is 6 or more.

