

Objects and classes

Kevin Schmidt, Susan Lindsey, Charlie Dey

Spring 2019

Classes

Definition of object

An object is an entity that you can request to do certain things. These actions are the *methods* and to make these possible the object probably stores data, the *members*.

When designing an object, first ask yourself: 'what functionality should this support'.

The structure of an object is given in a *class definition*.

Object functionality

Small illustration: vector objects.

Code:

```
Vector v(1.,2.);  
cout << "vector has length "  
      << v.length() << endl;  
v.scaleby(2.);  
cout << "vector has length "  
      << v.length() << endl;
```

Output

[object] functionality:

```
vector has length 2.23607  
vector has length 4.47214
```

Note the 'dot' notation; in a `struct` we use it for the data members; in an object we (also) use it for methods.

Exercise 1

Thought exercise:

What data does the object need to store to do this?

Is there more than one possibility?

Constructor

Use a *constructor*: function with same name as the class.
Typically used to initialize data members.

```
class Vector {  
private:  
    double x,y;  
public:  
    Vector( double x,double y )  
        : x(x),y(y) {};
```

The syntax `x(x)` copies the argument to the data member.

Member default values

Class members can have default values, just like ordinary variables:

```
class Point {  
private:  
    float x=3., y=.14;  
private:  
    // et cetera  
}
```

Each object will have its members initialized to these values.

Member initialization in the constructor

```
class Vector {  
private:  
    double x,y;  
public:  
    Vector( double userx,double usery ) {  
        x = userx; y = usery;  
    }  
}
```


Methods

Class methods

We used methods `length` and `scaleby`. These are defined inside the class:

```
void scaleby( double a ) {  
    x *= a; y *= a; }  
double length() {  
    return sqrt(x*x + y*y); };  
};
```

- They look like ordinary functions,
- except that they can use the data members of the class, for instance `x`;
- Methods can only be used on an object:

```
Vector vec(5,12);  
double s = vec.length();
```

Exercise 2

Make class `Point` with a constructor

```
Point( float xcoordinate, float ycoordinate );
```

Write the following methods:

- `distance_to_origin` returns a float.
- `printout` uses `cout` to display the point.
- `angle` computes the angle of vector (x,y) with the x -axis.

Methods that alter the object

Code:

```
class Vector {  
    /* ... */  
    void scaleby( double a ) {  
        vx *= a; vy *= a; };  
    /* ... */  
};  
  
/* ... */  
Vector p1(1.,2.);  
cout << "p1 has length "  
      << p1.length() << endl;  
p1.scaleby(2.);  
cout << "p1 has length "  
      << p1.length() << endl;
```

Output

[geom] pointscaleby:

```
p1 has length 2.23607  
p1 has length 4.47214
```

Methods that create a new object

Code:

```
class Vector {  
    /* ... */  
    Vector scale( double a ) {  
        return Vector( vx*a, vy*a );  
    }  
    /* ... */  
};  
  
/* ... */  
cout << "p1 has length "  
      << p1.length() << endl;  
Vector p2 = p1.scale(2.);  
cout << "p2 has length "  
      << p2.length() << endl;
```

Output

[geom] pointscale:

p1 has length 2.23607
p2 has length 4.47214

Default constructor

```
Vector v1(1.,2.), v2;  
cout << "v1 has length " << v1.length() << endl;  
v2 = v1.scale(2.);  
cout << "v2 has length " << v2.length() << endl;
```

gives (g++; different for intel):

```
pointdefault.cxx: In function 'int main()':  
pointdefault.cxx:32:21: error: no matching function for call to  
      'Vector::Vector()'  
      Vector v1(1.,2.), v2;
```

The problem is with v2. How is it created? We need to define two constructors:

```
Vector() {};  
Vector( double x, double y ) {  
    vx = x; vy = y;  
};
```

Exercise 3

Extend the `Point` class of the previous exercise with a method: `distance` that computes the distance between this point and another: if `p,q` are `Point` objects,

`p.distance(q)`

computes the distance between them.

Hint: remember the 'dot' notation for members.

Exercise 4

Write a method `halfway_point` that, given two `Point` objects `p,q`, construct the `Point` halfway, that is, $(p + q)/2$.

You can write this function directly, or you could write functions `Add` and `Scale` and combine these.

Access to internals

Constructor

Use a *constructor*: function with same name as the class.
Typically used to initialize data members.

```
class Vector {  
private:  
    double x,y;  
public:  
    Vector( double x,double y )  
        : x(x),y(y) {};
```

The syntax `x(x)` copies the argument to the data member.

Example of accessor functions

Getting and setting of members values is done through accessor functions:

```
class Vector {
private: // recommended!
    double vx,vy;
public:
    Vector( double x,double y ) {
        vx = x; vy = y;
    };

    double y() { return vy; };
    void setx( double newx ) {
        vx = newx; };
    void sety( double newy ) {
        vy = newy; };
}; // end of class definition

public:
    double x() { return vx; };
    Vector p1(1.,2.);
```

Usage:

```
p1.setx(3.12);
/* ILLEGAL: p1.x() = 5; */
cout << "P1's x=" << p1.x() << endl;
```

Use accessor functions!

```
class PositiveNumber { /* ... */ }  
class Point {  
private:  
    // data members  
public:  
    Point( float x,float y ) { /* ... */ };  
    Point( PositiveNumber r,float theta ) { /* ... */ };  
    float get_x() { /* ... */ };  
    float get_y() { /* ... */ };  
    float get_r() { /* ... */ };  
    float get_theta() { /* ... */ };  
};
```

Functionality is independent of implementation.

Exercise 5

Make a class `LinearFunction` with a constructor:

```
LinearFunction( Point input_p1,Point input_p2 );
```

and a function

```
float evaluate_at( float x );
```

which you can use as:

```
LinearFunction line(p1,p2);  
cout << "Value at 4.0: " << line.evaluate_at(4.0) << endl;
```

Exercise 6

Make a class `LinearFunction` with two constructors:

```
LinearFunction( Point input_p2 );  
LinearFunction( Point input_p1, Point input_p2 );
```

where the first stands for a line through the origin.
Implement again the `evaluate` function so that

```
LinearFunction line(p1,p2);  
cout << "Value at 4.0: " << line.evaluate_at(4.0) << endl;
```

Classes for abstract objects

Objects can model fairly abstract things:

Code:

```
class stream {  
private:  
    int last_result{0};  
public:  
    int next() {  
        return last_result++; }  
};  
  
int main() {  
    stream ints;  
    cout << "Next: "  
        << ints.next() << endl;  
    cout << "Next: "  
        << ints.next() << endl;  
    cout << "Next: "  
        << ints.next() << endl;  
}
```

Output

[object] stream:

```
Next: 0  
Next: 1  
Next: 2
```

Project Exercise 7

Write a class `primegenerator` that contains

- members `how_many_primes_found` and `last_number_tested`,
- a method `nextprime`;
- Also write a function `isprime` that does not need to be in the class.

Your main program should look as follows:

```
cin >> nprimes;
primegenerator sequence;
while (sequence.number_of_primes_found() < nprimes) {
    int number = sequence.nextprime();
    cout << "Number " << number << " is prime" << endl;
}
```


Project Exercise 8

The *Goldbach conjecture* says that every even number, from 4 on, is the sum of two primes $p + q$. Write a program to test this for the even numbers up to a bound that you read in.

This is a great exercise for a top-down approach! Make an outer loop over the even numbers e . In each iteration, make a `primegenerator` object to generate p values. For each p test whether $e - p$ is prime.

For each even number e then print e, p, q , for instance:

The number 10 is 3+7

If multiple possibilities exist, only print the first one you find.

Turn it in!

- If you have compiled your program, do:
`sdstestgold yourprogram.cc`
where 'yourprogram.cc' stands for the name of your source file.
- Is it reporting that your program is correct? If so, do:
`sdstestgold -s yourprogram.cc`
where the `-s` flag stands for 'submit'.
- If you don't manage to get your code working correctly, you can submit as incomplete with
`sdstestgold -i yourprogram.cc`

More about constructors

Copy constructor

- Several default copy constructors are defined
- They copy an object:
 - simple data, including pointers
 - included objects recursively.
- You can redefine them as needed, for instance for deep copy.

```
class has_int {  
private:  
    int mine{1};  
public:  
    has_int(int v) {  
        cout << "set: " << v <<  
        endl;  
        mine = v; };  
    has_int( has_int &h ) {  
        auto v = h.mine;  
        cout << "copy: " << v <<  
        endl;  
        mine = v; };  
    void printme() { cout  
        << "I have: " << mine <<  
        endl; };  
};
```

Copy constructor in action

Code:

```
has_int an_int(5);  
has_int other_int(an_int);  
an_int.printme();  
other_int.printme();
```

Output

[object] copyscalar:

```
set: 5  
copy: 5  
I have: 5  
I have: 5
```

Copying is recursive

Class with a vector:

```
class has_vector {  
private:  
    vector<int> myvector;  
public:  
    has_vector(int v) { myvector.push_back(v); };  
    void set(int v) { myvector.at(0) = v; };  
    void printme() { cout  
        << "I have: " << myvector.at(0) << endl; };  
};
```

Copying is recursive, so the copy has its own vector:

Code:

```
has_vector a_vector(5);  
has_vector other_vector(a_vector);  
a_vector.set(3);  
a_vector.printme();  
other_vector.printme();
```

Output

[object] copyvector:

```
I have: 3  
I have: 5
```

Destructor

- Every class `myclass` has a *destructor* `~myclass` defined by default.
- The default destructor does nothing:

```
~myclass() {};
```

- A destructor is called when the object goes out of scope.
Great way to prevent memory leaks: dynamic data can be released in the destructor. Also: closing files.

Destructor example

Destructor called implicitly:

Code:

```
class SomeObject {
public:
    SomeObject() {
        cout << "calling the constructor"
              << endl;
    };
    ~SomeObject() {
        cout << "calling the destructor"
              << endl;
    };
};

/* ... */
cout << "Before the nested scope"
     << endl;
{
    SomeObject obj;
    cout << "Inside the nested scope"
         << endl;
```

Output

[object] destructor:

```
make[2]: ./destructor: No such file or directory
make[2]: *** [run_destructor] Error 1
```


Other object stuff

Class prototypes

Header file:

```
class something {  
public:  
    double somedo(vector);  
};
```

Implementation file:

```
double something::somedo(vector v) {  
    .... something with v ....  
};
```