LAB 5 :

Aim: To Implement of Data Insertion, View Creation, and Multi-Table Join Operations in SQL

Q1. Insert new player Michale Clark with player ID 300311 in the table player .

SELECT *FROM player where PlayerID = 300311;

```
MySQL  localhost:3306 ssl  anannya_match  SQL > select*from player where PlayerID = 300311;
+----------+---------+-------+---------+-------+--------+-------+
| PlayerID | LName   | FName | Country | Yborn | Bplace | FTest |
+----------+---------+-------+---------+-------+--------+-------+
|   300311 | Michale | Clark | NULL    |  NULL | NULL   |  NULL |
+----------+---------+-------+---------+-------+--------+-------+
```

Q2. Insert new player Sam from India , Ahmedabad with player ID 406317 in the table player.

INSERT INTO Player (PlayerID, FName, Country, Bplace)
VALUES(406317, ‘Sam’,‘India’, ‘Ahmedabad’);
SELECT*
FROM Player
WHERE PlayerID = 406317;

```
MySQL  localhost:3306 ssl  anannya_match  SQL > select * from player where PlayerID=406317 ;
+----------+--------+-------+---------+-------+-----------+-------+
| PlayerID | LName  | FName | Country | Yborn | Bplace    | FTest |
+----------+--------+-------+---------+-------+-----------+-------+
|   406317 | Kapoor | Sam   | India   |  1975 | Ahemdabad |  1994 |
+----------+--------+-------+---------+-------+-----------+-------+
1 row in set (0.0006 sec)
```

Q3. Creating View for Batsman.

```
CREATE VIEW Batsman (PID,FName,LName,Country,MID,Score)
AS SELECT PlayerID,FName,LName,Country,MatchID,NRuns
FROM Player,Batting
WHERE PlayerID=PID;
select * from Batsman;
```

```
MySQL localhost:3306 ssl anannya_match SQL > select * from Batsman;

+-------+-----------+-------------+-----------+------+-------+
| PID   | FName     | LName       | Country   | MID  | Score |
+-------+-----------+-------------+-----------+------+-------+
| 23001 | Yuvraj    | Singh       | India     | 2755 |     0 |
| 25001 | MS        | Dhoni       | India     | 2755 |    71 |
| 91001 | Sanath    | Jayasuriya  | Sri Lanka | 2755 |    60 |
| 94002 | Chaminda  | Vaas        | Sri Lanka | 2755 |    17 |
| 92002 | Muthiah   | Murlitharan | Sri Lanka | 2755 |     1 |
| 89001 | Sachin    | Tendulkar   | India     | 2689 |    91 |
| 23001 | Yuvraj    | Singh       | India     | 2689 |    38 |
| 25001 | MS        | Dhoni       | India     | 2689 |    36 |
| 99002 | Adam      | Gilchrist   | Australia | 2689 |     2 |
| 95001 | Ricky     | Ponting     | Australia | 2689 |     1 |
| 24001 | Andrew    | Symonds     | Australia | 2689 |    42 |
| 99001 | Breet     | Lee         | Australia | 2689 |     7 |
| 27001 | Praveen   | Kumar       | India     | 2689 |     7 |
| 27001 | Praveen   | Kumar       | India     | 2755 |     2 |
| 98002 | Harbhajan | Singh       | India     | 2689 |     3 |
| 98002 | Harbhajan | Singh       | India     | 2755 |     2 |
+-------+-----------+-------------+-----------+------+-------+
```

Q4. Creating a View for Bowling.

```
CREATE VIEW Bowling2689 (PID,FName,LName,Country,NOvers,NWickets)
 AS SELECT PlayerID,FName,LName,Country,NOvers,NWickets
 FROM Player,Bowling
 WHERE PlayerID=PID
 AND MatchID=2689;


select * from Bowling2689;
```

```
MySQL  localhost:3306 ssl  anannya_match  SQL > select * from Bowling26
89;
+-------+----------+---------+----------+--------+----------+
| PID   | FName    | LName   | Country  | NOvers | NWickets |
+-------+----------+---------+----------+--------+----------+
| 99001 | Breet    | Lee     | Australia|     10 |        1 |
| 24001 | Andrew   | Symonds | Australia|      3 |        1 |
| 23001 | Yuvraj   | Singh   | India    |      3 |        0 |
| 98002 | Harbhajan| Singh   | India    |     10 |        1 |
+-------+----------+---------+----------+--------+----------+
```

Q5. Find the name of all players who have scored 60 or more runs.

```
SELECT FName, LName
FROM Batting2689
WHERE Runs >= 60;
```

```
MySQL  localhost:3306 ssl  anannya_match  SQL > select * from Bowling26
89;
+-------+----------+---------+----------+--------+----------+
| PID   | FName    | LName   | Country  | NOvers | NWickets |
+-------+----------+---------+----------+--------+----------+
| 99001 | Breet    | Lee     | Australia|     10 |        1 |
| 24001 | Andrew   | Symonds | Australia|      3 |        1 |
| 23001 | Yuvraj   | Singh   | India    |      3 |        0 |
| 98002 | Harbhajan| Singh   | India    |     10 |        1 |
+-------+----------+---------+----------+--------+----------+
```

Q6. Find the names of bowlers that have not taken any wickets in ODI matches 2689 .

```
SELECT P.FName, P.LName
FROM Player P
JOIN Bowling B ON P.PlayerID = B.PlayerID
WHERE B.MatchID = 2689
AND B.NWickets = 0;
```

```
MySQL  localhost:3306 ssl  anannya_match  SQL > SELECT P.FName, P.LName
                                              -> FROM Player P
                                              -> JOIN Bowling B ON P.PlayerID = B.PI
                                              -> WHERE B.MatchID = 2689
                                              ->   AND B.Nwickets = 0;
+--------+-------+
| FName  | LName |
+--------+-------+
| Yuvraj | Singh |
+--------+-------+
```

Q7. Define a view NPlayer for obtaining the names of the countries & number of players from each country.

```
CREATE VIEW NPlayer AS
SELECT Country, COUNT(*) AS NumberOfPlayers
FROM Player
GROUP BY Country;
```

```
MySQL  localhost:3306 ssl  anannya_match  SQL > SELECT * FROM NPlayer;
+--------------+-----------------+
| Country      | NumberOfPlayers |
+--------------+-----------------+
| India        |              10 |
| Australia    |               5 |
| West Indies  |               1 |
| Sri Lanka    |               3 |
| Pakistan     |               2 |
| Zimbabwe     |               1 |
| South Africa |               4 |
| New Zealand  |               2 |
| England      |               1 |
| NULL         |               1 |
| Country      |               1 |
+--------------+-----------------+
```