Experiment 4

Aim: To Implement of Data Insertion, View Creation, and Multi-Table Join Operations in SQL

Q1. Insert new player Michale Clark with player ID 300311 in the table player .

```
MySQL  localhost:3306 ssl  anannya_match  SQL > select*from player where PlayerID = 300311;
+----------+---------+-------+---------+-------+--------+-------+
| PlayerID | LName   | FName | Country | Yborn | Bplace | FTest |
+----------+---------+-------+---------+-------+--------+-------+
|   300311 | Michale | Clark | NULL    |  NULL | NULL   |  NULL |
+----------+---------+-------+---------+-------+--------+-------+
```

Q2. Insert new player Sam from India , Ahmedabad with player ID 406317 in the table player.

```
11 rows in set (0.0034 sec)
MySQL  localhost:3306 ssl  anannya_match  SQL > INSERT INTO Player (PlayerID, FName, Country, Bplace)
                                             -> VALUES (406317, 'Sam', 'India', 'Ahemdabad');
ERROR: 1062 (23000): Duplicate entry '406317' for key 'player.PRIMARY'
MySQL  localhost:3306 ssl  anannya_match  SQL > INSERT INTO Player (PlayerID, FName, Country, Bplace)
                                             -> VALUES (406319, 'Sam', 'India', 'Ahemdabad');
Query OK, 1 row affected (0.0092 sec)
MySQL  localhost:3306 ssl  anannya_match  SQL > SELECT *
                                             -> FROM Player
                                             -> WHERE PlayerID = 406319;
+----------+-------+-------+---------+-------+-----------+-------+
| PlayerID | LName | FName | Country | Yborn | Bplace    | FTest |
+----------+-------+-------+---------+-------+-----------+-------+
|   406319 | NULL  | Sam   | India   |  NULL | Ahemdabad |  NULL |
+----------+-------+-------+---------+-------+-----------+-------+
```

Q3. Creating View for Batsman.

```
CREATE VIEW Batsman (PID,FName,LName,Country,MID,Score)
 AS SELECT PlayerID,FName,LName,Country,MatchID,NRuns
 FROM Player,Batting
 WHERE PlayerID=PID;

select * from Batsman;
```

```
MySQL  localhost:3306 ssl  anannya_match  SQL > select * from Batsman;

+-------+----------+------------+----------+------+-------+
| PID   | FName    | LName      | Country  | MID  | Score |
+-------+----------+------------+----------+------+-------+
| 23001 | Yuvraj   | Singh      | India    | 2755 |     0 |
| 25001 | MS       | Dhoni      | India    | 2755 |    71 |
| 91001 | Sanath   | Jayasuriya | Sri Lanka| 2755 |    60 |
| 94002 | Chaminda | Vaas       | Sri Lanka| 2755 |    17 |
| 92002 | Muthiah  | Murlitharan| Sri Lanka| 2755 |     1 |
| 89001 | Sachin   | Tendulkar  | India    | 2689 |    91 |
| 23001 | Yuvraj   | Singh      | India    | 2689 |    38 |
| 25001 | MS       | Dhoni      | India    | 2689 |    36 |
| 99002 | Adam     | Gilchrist  | Australia| 2689 |     2 |
| 95001 | Ricky    | Ponting    | Australia| 2689 |     1 |
| 24001 | Andrew   | Symonds    | Australia| 2689 |    42 |
| 99001 | Breet    | Lee        | Australia| 2689 |     7 |
| 27001 | Praveen  | Kumar      | India    | 2689 |     7 |
| 27001 | Praveen  | Kumar      | India    | 2755 |     2 |
| 98002 | Harbhajan| Singh      | India    | 2689 |     3 |
| 98002 | Harbhajan| Singh      | India    | 2755 |     2 |
+-------+----------+------------+----------+------+-------+
```

Q4. Creating a View for Bowling.

```
CREATE VIEW Bowling2689 (PID,FName,LName,Country,NOvers,NWickets)
 AS SELECT PlayerID,FName,LName,Country,NOvers,NWickets
 FROM Player,Bowling
 WHERE PlayerID=PID
 AND MatchID=2689;
```

```
select * from Bowling2689;
```

```
MySQL  localhost:3306 ssl  anannya_match  SQL > select * from Bowling26
89;
+-------+----------+--------+----------+--------+----------+
| PID   | FName    | LName  | Country  | NOvers | NWickets |
+-------+----------+--------+----------+--------+----------+
| 99001 | Breet    | Lee    | Australia|     10 |        1 |
| 24001 | Andrew   | Symonds| Australia|      3 |        1 |
| 23001 | Yuvraj   | Singh  | India    |      3 |        0 |
| 98002 | Harbhajan| Singh  | India    |     10 |        1 |
+-------+----------+--------+----------+--------+----------+
```

Q5. Find the name of all players who have scored 60 or more runs.

```
MySQL  localhost:3306 ssl  anannya_match  SQL > select * from Bowling26
89;
+-------+----------+---------+-----------+--------+----------+
| PID   | FName    | LName   | Country   | NOvers | NWickets |
+-------+----------+---------+-----------+--------+----------+
| 99001 | Breet    | Lee     | Australia |     10 |        1 |
| 24001 | Andrew   | Symonds | Australia |      3 |        1 |
| 23001 | Yuvraj   | Singh   | India     |      3 |        0 |
| 98002 | Harbhajan | Singh  | India     |     10 |        1 |
+-------+----------+---------+-----------+--------+----------+
```

Q6. Find the names of bowlers that have not taken any wickets in ODI matches 2689 .

```
MySQL  localhost:3306 ssl  anannya_match  SQL > SELECT P.FName, P.LName

                                          -> FROM Player P
                                          -> JOIN Bowling B ON P.PlayerID = B.PI
                                          -> WHERE B.MatchID = 2689
                                          ->   AND B.Nwickets = 0;

+--------+-------+
| FName  | LName |
+--------+-------+
| Yuvraj | Singh |
+--------+-------+
```

Q7. Define a view NPlayer for obtaining the names of the countries & number of players from each country.

```
MySQL  localhost:3306 ssl  anannya_match  SQL > SELECT * FROM NPlayer;
+--------------+-----------------+
| Country      | NumberOfPlayers |
+--------------+-----------------+
| India        |              10 |
| Australia    |               5 |
| West Indies  |               1 |
| Sri Lanka    |               3 |
| Pakistan     |               2 |
| Zimbabwe     |               1 |
| South Africa |               4 |
| New Zealand  |               2 |
| England      |               1 |
| NULL         |               1 |
| Country      |               1 |
+--------------+-----------------+
```