- Phys. 1989, 20, 250-271. (b) de Maine, P. A. D.; de Maine, M. M. Computer Aids for Chemists. Anal. Chim. Acta (in press)
- (2) Szekely, P. Separating the User Interface from the Functionality of Application Programs; Report CMU-CS-88-101; Computer Science Department, Carnegie Mellon University: Pittsburgh, PA, 1988; 208
- (3) Savage, R. E.; Habinek, J. K. A Multilevel Menu-Driven User Interface: Design and Evaluation Through Simulation. In Human Factors in Computer Systems; Thomas, J. C., and Schneider, M. L., Eds.; ABLEX: Norwood, NJ, 1984; pp 165-186.
- Nickerson, R. S. Why Interactive Computer Systems are Sometimes Not Used by People Who Might Benefit From Them. Int. J. Man-Mach. Stud. 1981, 15, 469-483.
- (5) Gaines, B. R.; Shaw, M. L. G. Dialog Engineering. In Designing for Human-Computer Communications; Sime, M. E., and Coombs, M. J.,
- Eds.; Academic Pres: London, 1983; pp 1-20.

 (6) Ehrich, R. W. DMS—A System for Defining and Managing Human— Computer Dialogues. In Analysis, Design and Evaluation of Man-Machine Systems; Johannsen, G., and Rijnsdorp, J. E., Eds.; Pergamon
- Press: Oxford, U.K., 1983; pp 327-334.

 (7) Sime, M. E.; Coombs, M. J. In Designing for Human-Computer Communications; Sime, M. E., and Coombs, M. J., Eds.; Academic
- Press: London, 1983; pp 1-20.
 Williges, R. C.; Williges, B. H. Human-Computer Dialogue Design Considerations. In Analysis, Design and Evaluation of Man-Machine Systems; Johannsen, G., and Rijnsdorp, J. E., Eds.; Pergamon Press:
- Oxford, U.K., 1983; pp 239-246.

 (9) Foley, J. D.; Van Dam, A. Fundamentals of Interactive Computer Graphics; Addison-Wesley: Reading, MA, 1982; pp 55-56, 217-243.

 (10) Barnard, P. J.; Hammond, N. V.; Morton, J.; Long, J. B. Consistency
- and Compatibility in Human-Computer Dialogue. Int. J. Man-Mach. Stud. 1981, 15, 87-134.
- (11) Gaines, B. R. The Technology of Interaction—Dialogue Programming Rules. Int. J. Man-Mach. Stud. 1981, 14, 133-140.
- (12) Shneiderman, B. Human Factors Experiments in Designing Interactive
- Systems. Computer 1979, 12(12), 9-19.

 (13) Hansen, W. J. User Engineering Principles for Interactive Systems. In Interactive Programming Environments; Barstow, D. R., Shrobe, H. E., and Sandewall, E., Eds.; McGraw-Hill: New York, 1984; pp
- (14) Draper, S. W.; Norman, D. A. Software Engineering for User Inter-
- faces. IEEE Trans. Software Eng. 1985, SE-11, 252-258.

 (15) Smith, D. C.; Irby, C.; et al. Designing the Star User Interface. In Integrated Interactive Computing Systems; Proceedings of the European Conference on Integrated Interactive Computing Systems, Stresa, Italy, Sept 1-3, 1982; Degano, P., and Sandewall, E., Eds.; Amsterdam,
- North-Holland Publishing: 1982; pp 297-313.

 (16) Thimbleby, H. Dialogue Determination. Int. J. Man-Mach. Stud. 1980, 13, 295-304.

- (17) Marcus, A. Corporate Identity for Iconic Interface Design: The Graphic Design Perspective. IEEE Comput. Graphics Appl. 1984, **4**(12), 24–32
- (18) Hatvany, J. H., Guedj, R. A. Man-Machine Interactions in Computer-Aided Design Systems. In Analysis, Design and Evaluation of Man-Machine Systems; Johannsen, G., and Rijnsdorp, J. E., Eds.; Pergamon Press: Oxford, U.K., 1983, pp 231-237.
- (19) Smith, H. Human Computer Communication. In Human Interactions with Computers; Smith, H. T., and Green, T. R. G., Eds.; Academic Press: London, 1980, pp 5-38
- (20) Mozeico, H. A Human/Computer Interface to Accommodate User
- Learning Stages. Commun. ACM 1982, 25, 100-104.
 (21) Hayes, P.; Ball, E.; Reddy, R. Breaking the Man-Machine Communication Barrier. Computer 1981, 14(3), 19-30.
- (22) Shneiderman, B. Response Time and Display Rates in Human Performance with Computers. Comput. Surv. 1984, 16, 265-285
- (23) Lieberman, H. Designing Interactive Systems from the User's Viewpoint. In Integrated Interactive Computing Systems; Proceedings of the European Conference on Integrated Interactive Computing Systems, Stresa, Italy, Sept 1-3, 1982; Degano, P., and Sandewall, E., Eds.;
 North-Holland Publishing: Amsterdam, 1982; pp 45-59.
 Ledgard, H.; Singer, A.; Whiteside, J. Directions in Human Factors for Interactive Systems. In Lecture Notes in Computer Science; Goos,
- G., and Hartmanis, J., Eds.; Springer-Verlag: New York, 1981; pp 146-162.
- (25) Miller, L. A.; Thomas, J. C., Jr. Behavioral Issues in the Use of Interactive Systems. In Lecture Notes in Computer Science; Springer-Verlag: New York, 1976; Vol. 49, pp 193-215.
- (26) (a) de Maine, P. A. D. Automatic Deductive Systems for Chemistry. Anal. Chim. Acta/CTO 1981, 133, 685-698. (b) de Maine, P. A. D. Systems Manual for the CRAMS System; Automatic Systems for the Physical Sciences, Report 6; Computer Science and Engineering De-
- partment, Auburn University: Auburn, AL, 1980; 125 pp.

 (27) Cartee, B. C.; Head, D. M.; de Maine, P. A. D.; De Maine, M. M.

 CURFIT Interface System Manual; Automatic Systems for the Physical Sciences, Report 9; Computer Science and Engineering De-
- partment, Auburn University: Auburn, AL, 1986; 243 pp.

 (28) de Maine, P. A. D. Operation and Logic Manual for the CURFIT System; Automatic Systems for the Physical Sciences, Report 2; Computer Science and Engineering Department, Auburn University: Au-
- burn, AL, 1985; 241 pp.

 (29) Wojtyna, M. S.; de Maine, P. A. D. User's Manual for the FRANS Interactive User-Friendly Interface; Automatic Systems for the Physical Sciences, Report 15; Computer Science and Engineering Department,
- Auburn University: Auburn, AL, 1988; 9 pp.

 (30) de Maine, P. A. D. Operation Manual for the CRAMS System; Automatic Systems for the Physical Sciences, Report 5; Computer Science Tomatic Systems (1988) and 1989. Department, The Pennsylvania State University: University Park, PA, 1980; 194 pp.

Use of Small Computers for Large Computations: Enumeration of Polyhex Hydrocarbons

J. V. KNOP, W. R. MÜLLER, K. SZYMANSKI, and N. TRINAJSTIĆ*,

Computer Centre, The Heinrich Heine University, 4000 Düsseldorf, Federal Republic of Germany

Received October 27, 1989

The enumeration of polyhex hydrocarbons with up to 16 hexagons is reported. These results are now for the first time available.

Recently in this journal Tošić and Kovačević¹ reported generation and enumeration of unbranched catacondensed benzenoids with up to h = 20 (h is the number of hexagons in the benzenoid hydrocarbon). There have also been other papers in this journal on enumeration of benzenoid hydrocarbons.²⁻⁴ However, all these papers (and others in the literature⁵) are incomplete in the sense that they did not give the total numbers of benzenoid hydrocarbons for $h \ge 13$. The reason is that the enumeration of benzenoid hydrocarbons is a difficult combinatorial problem.⁶ It is also a computationally involved problem.5,7

[‡]Permanent address: The Rugjer Boškovič Institute, P.O. Box 1016, 41001 Zagreb, Croatia, Yugoslavia.

Since we have successfully developed a very powerful algorithm for enumeration of hexagonal structures,8 we wish to supplement the above studies with counts of polyhex hydrocarbons with up to h = 16. Polyhex hydrocarbons are graph theoretically represented by polyhexes. Polyhexes are hexagonal systems that may be obtained by any combination of regular hexagons such that two hexagons have exactly one common edge or are disjoint. Benzenoid hydrocarbons represent a subset of polyhex hydrocarbons 10 and are graph theoretically depicted by benzenoid graphs. 9 Benzenoid graphs are those polyhexes that are 1-factorable structures. 11 A 1-factorable polyhex corresponds to a polyhex hydrocarbon with Kekulé structure(s).12 Most of the papers reporting the enumeration of hexagonal structures did not distinguish be-

Table I. Enumeration of Polyhexes with up to h = 16

	planar	planar polyhexes with holes						
	polyhexes	single	ingle multiple		CPU time			
h	without holes	hole	holes	days	h	min	S	
1	1						0.44	
2	1						0.44	
3	3						0.44	
4	7						0.44	
5	22						0.60	
6	81						1.26	
7	331						4.67	
8	1 435	1					20.87	
9	6 505	5				1	40.13	
10	30 086	43				8	12.90	
11	141 229	283				40	52.17	
12	669 584	1 954			3	24	1.80	
13	3 198 256	12363	1		17	4	32.50	
14	15 367 577	76 283	11	3	14	4	24.76	
15	74 207 910	453 946	149	18	3	13	34.70	
16	359 863 778	2 641 506	1618	91	7	24	33.69	

tween the terms polyhex and benzenoid.

Our algorithm for enumeration of polyhexes is based on the DAST (the dualist angle-restricted spanning tree) code.¹³ This code is founded on the graph-theoretical concept of the weighted spanning tree of dualist. 14 A computer program for enumerating polyhex hydrocarbons using our algorithm is detailed elsewhere.⁸ Counts of planar polyhex hydrocarbons with and without holes with up to h = 16 are given in Table I. In the table we also give CPU time needed to complete computation for each h. For example, the required CPU time for the enumeration of polyhexes with 16 hexagons was 91 days, 7 h, 24 min, and 33.69 s.

Computations have been carried out on the Siemens PCD3D (20 MHz, 386-AT). We deliberately did not use our supercomputer to show that these types of combinatorial computations can be completed on the personal computer, if one is willing to spend some time to design carefully an efficient computational algorithm and if one can spare a PC for continuous computations over a long period of time.

ACKNOWLEDGMENT

This work was supported in part by the German-Yugoslav Scientific Cooperation Program. Financial support from the Internationales Büro, Kernforschungsanlage-Jülich, and from the Croatian Science Fund is gratefully acknowledged. We are thankful to reviewers for their critical but helpful com-

REFERENCES AND NOTES

- (1) Tošić, R.; Kovačević, M. Generating and Counting Unbranched Catacondensed Benzenoids. J. Chem. Inf. Comput. Sci. 1988, 28, 29-31.
- (2) Brunvoll, J.; Cyvin, B. N.; Cyvin, S. Enumeration and Classification of Coronoid Hydrocarbons. J. Chem. Inf. Comput. Sci. 1987, 27,
- (3) Brunvoll, J.; Cyvin, B. N.; Cyvin, S. Enumeration and Classification of Benzenoid Hydrocarbons. 2. Symmetry and Regular Benzenoids. J. Chem. Inf. Comput. Sci. 1987, 27, 171-177. Cyvin, S.; Brunvoll, J.; Cyvin, B. N. Distribution of K, the Number of
- Kekulé Structures, in Benzenoid Hydrocarbons: Normal Benzenoids with K to 110. J. Chem. Inf. Comput. Sci. 1989, 29, 74-90.
- (5) Cioslowski, J. Computer Enumeration of Polyhexes Using the Compact
- Naming Approach. J. Comput. Chem. 1987, 8, 906-915.
 (6) Harary, F.; Palmer, E. M. Graphical Enumeration; Academic: New York, 1973.
- (7) Balasubramanian, K.; Kauffman, J. J.; Koski, W. S.; Balaban, A. T. Graph Theoretical Characterization and Computer Generation of Certain Carcinogenic Benzenoid Hydrocarbons and Identification of Bay Regions. J. Comput. Chem. 1980, 1, 149-157
- (8) Müller, W. R.; Szymanski, K.; Knop, J. V.; Nikolić, S.; Trinajstić, N. On the Enumeration and Generation of Polyhex Hydrocarbons. J. Comput. Chem. (in press)
- Trinajstić, N. Chemical Graph Theory; CRC: Boca Raton, FL, 1983; Vol. 1, Chapter 3.
- (10) Trinajstić, N. On the Classification of Polyhex Hydrocarbons. J. Math. Chem. (in press).
- (11) Harary, F. Graph Theory, Addison-Wesley: Reading, MA, 1971; second printing.
- Knop, J. V.; Müller, W. R.; Szymanski, K.; Trinajstić, N. On the Enumeration of 2-Factors of Polyhexes. J. Comput. Chem. 1986, 7,
- (13) Knop, J. V.; Müller, W. R.; Szymanski, K.; Nikolić, S.; Trinajstić, N. Computer-oriented Molecular Codes. In Computational Chemical Graph Theory; Rouvray, D. H., Ed.; Nova: New York, 1990; pp 9-32.
 (14) Nikolić, S.; Trinajstić, N.; Knop, J. V.; Müller, W. R.; Szymanski, K.
- On the Concept of the Weighted Spanning Tree of Dualist. J. Math. Chem. (in press).

Molecular Topological Index

WOLFGANG R. MÜLLER, KLAUS SZYMANSKI, JAN V. KNOP, and NENAD TRINAJSTIĆ*,

Computer Centre, The Heinrich Heine University, 4000 Düsseldorf, Federal Republic of Germany

Received November 13, 1989

The molecular topological index (MTI) has been systematically tested for counterexamples (two or more nonisomorphic structures with the same MTI number). The analysis was carried out for alkane trees with up to 16 atoms. The search for counterexamples was positive: The first pair of alkane trees with identical MTI numbers was found in the octane family. The more disturbing finding was that two nonisomorphic alkane trees of different sizes may also possess the same MTI value. An attempt to redefine the MTI in terms of only the distance matrix and the valency matrix was abortive.

Schultz¹ has recently introduced in this journal a novel topological (or, more correctly, graph-theoretical) descriptor for characterization of alkanes by an integer. This descriptor was named by its originator the molecular topological index (MTI). The MTI appears to be an attractive graph-theoretical descriptor that is easy to compute and has structural significance. The important questions, Are the MTI numbers unique?, and, if the answer is positive, What are the smallest graphs for which MTI is not unique?, however, were not considered by Schultz. He only stated that the MTI is a highly discriminative descriptor. In this paper we will try to answer these questions.

The MTI is based on the adjacency $(N \times N)$ matrix A, the distance $(N \times N)$ matrix D, and the valency $(1 \times N)$ matrix v of an alkane. The sum of the elements e_i (i = 1, 2, ..., N)

Permanent address: The Rugjer Bošković Institute, P. O. Box 1016, 41001 Zagreb, Croatia, Yugoslavia