

Affiliation Index

- Air Products & Chemicals, Inc.,
2,90,170,270,298,372
AlliedSignal Environmental Catalysts, 94
AlliedSignal Research & Technology, 39
Brigham Young University, 74
Catalytica, Inc., 405
Cornell University, 140
Dipartimento di Chimica Industriale
e dei Materiali, 22,233
Ellison Consultants, 190
Engelhard Corporation, 215
Enichem ANIC, 233
Ford Motor Company, 53,66
Geo-Centers, Inc., 316
Government Industrial Research Institute
of Osaka, 420
Intech Inc., 190,205
Leiden University, 114
Lyondell Petrochemical Company, 273
Massachusetts Institute of Technology, 7,375
New Zealand Institute for Industrial Research
and Development, 301
Research Triangle Institute, 224
Rohm and Haas Company, 331,340
Siemens AG, 172
Università di Milano, 353
University of Akron, 157
University of Florida, 331,340
University of New Mexico, 39
University of Pittsburgh, 224
University of Tokyo, 114
University of Twente, 250
Utrecht University, 393
W.R. Grace and Company—Conn., 286

Subject Index

A

- Acidity of catalyst, sulfate effect, 266
Adhesion in three-way catalyst
ceramic support vs. Fermi level, 151,153
charge transfer, 150*t*,152*f*
experimental description, 141
Fermi level for N_2O_2 adsorption, 153,154*f*
Fermi level for NO adsorption, 151,153,154*f*
Fermi level variation, 151*t*,152
geometry, 141–146,148
interactions affecting adhesive
properties, 147,149–150
models, 146–148*f*
Adsorbents, synthetic carbonaceous, 332
Adsorption–desorption characteristics of
catalysts, sulfate effect, 262–264*f*
Air, role as oxidant in catalytic bromine
recovery from HBr waste, 417
Air–fuel ratio of exhaust, palladium
catalyst aging effect, 105–109*f*
Air inlet temperature, transient response
effect for monolithic oxidation
catalyst, 326*f*–329
 $\gamma\text{-Al}_2\text{O}_3$, use as support for NO and
 N_2O_2 adsorption on metal catalysts, 146
Aliphatic hydrocarbons, low-temperature
deep oxidation, 331–339
Alkaline earths, cocation effect in
catalytic decomposition of NO using
copper ion exchanged ZSM-5 zeolites,
8–20
Alternative fuels, examples, 270
Alumina
adhesion of Rh, Pd, and Pt, 140–154
diffuse reflectance IR experiments, 395–397
 γ -Alumina, catalyst for Claus reaction and
COS hydrolysis, 394
Aromatic hydrocarbons, low-temperature
deep oxidation, 331–339
Atmospheric sulfur
cycle, 372,373*f*
removal, 372,374
Au– $\gamma\text{-Al}_2\text{O}_3$, role in NO reduction by
hydrocarbon in oxidizing atmosphere, 61
Automobile exhaust, NO_x removal methods,
53–54
Automotive emission control catalysts,
function, 90
Automotive three-way catalyst, advantages
for purification of automotive exhaust
gas, 114

B

- Barium-promoted copper chromite oxide, low-temperature combustion of volatile organic compounds using ozone, 354–368
- Brocat, use in bromine recovery from HBr waste, 408–418
- Bromination of organic compounds applications, 405
- production of HBr, 405,406*t*
- Bromine recovery from HBr waste, catalytic, *See* Catalytic bromine recovery from HBr waste
- Butane conversion, low-temperature deep oxidation, 336,338*t*
- Butene, isomerization process, 275–285
- Byproducts, production, 372,374*t*

C

- C₃H₆ reduction of NO
 - Arrhenius plot for Cu–ZSM-5, 55,56*f*
 - C₃H₆ concentration effect over Cu–Al₂O₃, 58,59*f*
 - experimental procedure, 54–55
 - flow rate vs. activity over Cu–ZSM-5, 55,57*f*
 - initial reactant concentration rate, 55,58*t*
 - NO concentration effect over Cu–Al₂O₃, 58,60*f*
 - O₂ content effect over Cu–Al₂O₃, 58*t*,59*f*
 - O₂ content effect over Pd–ZSM-5, 58,62*f*
 - previous studies, 54
 - reactions, 61,63–64
 - temperature effect
 - Au–γ-Al₂O₃, 61,62*f*
 - Cu–Al₂O₃, 55,57*f*,58
 - Cu–ZSM-5, 55,56*f*
 - Pd–ZSM-5, 58,60*f*
- Carbon filter, limitations, 316
- Carbon molecular sieves, 332
- Carbonaceous adsorbents, synthetic, 332
- Catalysis, number of applications to solve environmental problems, 372
- Catalyst(s)
 - categories, 341
 - low-temperature oxidation of ethene, 301–313
 - monolithic oxidation, process condition effect of transient response, 316–329

Catalyst(s)—*Continued*

- role in fuel production, 270–271
- sulfate effect on adsorption–desorption characteristics, 262–264*f*
- sulfate treatment effect on surface area, 266
- Catalyst(s) for cleanup of NH₃, NO_x, and CO from nuclear waste processing facility
- Cu–ZSM-5 effect on CO and NH₃ conversion, 76–78
- Cu–ZSM-5 + Pt–Al₂O₃ effect on conversion, 84,85*t*,87*f*
- experimental procedure, 75–76
- NH₃–NO ratio effect on NH₃ and CO conversions, 78–81*f*
- NO_x reduction by NH₃ on metal ion exchanged ZSM-5 vs. that of previous studies, 85–87
- Pt–Al₂O₃ effect on CO conversion, 76,77*f*
- Pt–Al₂O₃ effect on NH₃ conversion, 78,82–84
- requirements, 74
- Catalyst performance
 - sulfate effect, 250–251
 - surface acidity effect, 250
- Catalyst technologies, NO_x removal in power plant applications, 215–223
- Catalytic bromine recovery from HBr waste air as oxidant, 417
- analytical procedure, 411
- catalyst activity test procedure, 409
- catalyst preparation, 408–409
- commercial requirements, 408
- contaminant studies, 413–415*f*
- flow rate effects, 416–417
- HBr concentration effects, 417
- HBr feed streams, 411
- HBr oxidation catalyst(s), 407*t*,412–414*f*
- heat management, 407–408
- interest, 406
- laboratory testing unit, 409,410*f*
- methods, 406*t*,407
- pilot unit design, 410*f*–412
- process condition effects, 416*t*–417
- Catalytic combustion
 - control of volatile organic compounds, 298
 - elimination of volatile organic compounds, 353

- Catalytic combustion of natural gas for
 NO_x control using $\text{La}_{1-x}\text{Sr}_x\text{CoO}_3$ catalysts
 catalyst preparation, 225
 catalytic methane combustion, 226–232
 CO vs. methane effect on NO reduction,
 229,230f
 experimental description, 224–225
 gas-phase combustion and catalytic
 combustion, 226,227f
 NO decomposition vs. catalyst, 228f,229
 reaction systems, 225,227f
 regulations for NO_x emissions, 224
 strontium effect, 229–232
 temperature-programmed oxygen evolution
 procedure, 226
 profiles for catalysts, 231t,232
 temperature-programmed reduction
 procedure, 225–226
 profiles for catalysts, 229–231t
 temperature vs. CO emission,
 226,228f,229
 temperature vs. methane conversion,
 226,228f
 temperature vs. NO_x formation,
 226,228f,229
- Catalytic converters for diesel engine
 exhaust control, need, 91
- Catalytic decomposition of nitric oxide
 over promoted copper ion exchanged
 ZSM-5 zeolites
 activity–exchange level relationship, 7–8
 advantage, 7
 catalyst characterization, 9,11t
 catalyst synthesis, 8–9,11t
 contact time vs. catalyst activity,
 17,19,20f
 conversion measurement procedure, 9–10
 experimental description, 8
 kinetics, 15–18f
 kinetics study procedure, 9–10
 NO decomposition in O_2 -containing gases
 vs. catalyst, 13–16f
 NO decomposition without O_2 vs.
 catalyst, 10,12f–14f
 previous studies, 8
 rare earth metal cation modified
 catalysts, 17,18f
 temperature effect, 14f–16f
- Catalytic decomposition of NO, use for NO_x
 removal, 4
- Catalytic emission control systems for
 power plants
 commercial experience, 222t,223
 competing reactions, 216,217f
 composite catalyst features, 216,217f,t
 rate-limiting reactions, 216
 reactions catalyzed, 216,217t
 selective catalytic reduction of NO_x ,
 216,218
 temperature-determined operation,
 218–222t
- Catalytic filter for chemical warfare
 agent removal, requirements, 317
- Catalytic reduction of NO, role of
 hydrocarbon oxidation, 53–64
- Ce–Rh– SiO_2 catalyst, NO–CO reaction
 effect, 157–166
- CeO_2 catalyst, SO_2 reduction to S, 378,381f
- $\text{CeO}_2(\text{La})$ catalyst, SO_2 reduction to S,
 383,385f
- Ceria catalysts, SO_2 reduction to S,
 375–391
- Cerium
 promoter in three-way catalysts, 157–158
 role in NO–CO reaction, 158–166
- Challenge concentration, transient
 response effect for monolithic
 oxidation catalyst, 324–326f
- Chemical warfare agents
 catalytic filter, requirements, 317
 removal from streams, complexity, 317
 removal systems, 316
- Chemical waste, reduction efforts, 372
- Chlorinated hydrocarbons, deep oxidation,
 340–351
- Claus process
 γ -alumina as catalyst, 394
 description and problems, 393
- Closed-loop control of automotive emissions,
 palladium-only catalysts, 94–111
- CO, catalysts for cleanup from nuclear
 waste processing facility, 74–87
- CO conversion
 Cu–ZSM-5 effect, 76,77f
 Cu–ZSM-5 + Pt– Al_2O_3 effect, 84,85t,87f
 Pt– Al_2O_3 effect, 76,77f
- CO oxidation, role of supported gold
 catalysts, 421–423f
- CO_2 hydrogenation, role of supported gold
 catalysts, 426t

- Contemporaneous SO_2 and NO removal from flue gas using regenerable copper-on-alumina sorbent-catalyst advantages, 233,249
 behavior during simultaneous removal, 238–239,241f
 copper distribution map within alumina pellet, 236,237f
 copper-on-alumina system, 234,236
 design requirements, 233–234
 experimental procedure, 236,238
 kinetics of SO_2 oxidation-sorption, 240,242–246
 pellet size effect, 246,247f
 porosity of support effect, 246,247f
 process layout, 234,235f
 scanning electron micrograph of sample, 236,237f
 SO_2 capture mechanism, 239–241f
 SO_2 sorption, breakthrough time, 246,248f
 textural properties of alumina supports, 236t
- Conversion, definition, 277
- Copper chromite oxide, barium-promoted, low-temperature combustion of volatile organic compounds using ozone, 354–368
- Copper-exchanged zeolite activity on NO conversion
 activity, 28–30
 comparison to that of Cu-loaded oxides, 36–37
 copper effect, 35t
 copper species effect, 30–33f
 experimental procedure, 24
 NO concentration effect, 28–30
 O_2 effect, 32–36
 sample preparation, 23–24
 temperature effect, 32,34f
- Copper-exchanged ZSM-5 zeolite
 reasons for interest, 66
 X-ray photoelectron study, 67–72
- Copper ion exchanged zeolite molecular sieve, use for NO_x removal, 4
- Copper ion exchanged ZSM-5 zeolites, catalytic decomposition of NO, 7–20
- Copper-loaded oxide reactivity on NO conversion
 catalyst pretreatment effect, 24,26t
 comparison to that of Cu-exchanged zeolites, 36–37
- Copper-loaded oxide reactivity on NO conversion—*Continued*
 experimental procedure, 24
 NO reactivity 24–26t
 O_2 effect, 26–28,35–36
 O_2 vs. selectivity to N_2 , 24–26
 sample preparation, 23
 temperature effect, 28,29f
- Copper-on-alumina sorbent-catalyst, contemporaneous SO_2 and NO removal from flue gas, 233–249
- COS conversion
 γ -alumina as catalyst, problems, 394
 hydrolysis to H_2S , 393
- COS hydrolysis on titania catalyst, *See* Hydrolysis of COS on titania catalysts
- CS_2 conversion, hydrolysis to H_2S , 393
- $\text{Cu}-\gamma\text{-Al}_2\text{O}_3$, role in NO reduction by hydrocarbon in oxidizing atmosphere, 55,57–60
- $\text{Cu}-\text{ZSM}-5$
 CO conversion effect, 76,77f
 NH_3 conversion effect, 76–78
 NO decomposition, 22–33
 NO reduction by hydrocarbon in oxidizing atmosphere, 55–57f
- $\text{Cu}-\text{ZSM}-5$ deactivation
 amorphous film formation in aged material, 45,47f–49f
 crystallinity of fresh catalyst, 45–47f
 CuO formation vs. aging, 42,43f
 experimental procedure, 39,40
 halo formation from amorphous material vs. aging, 42,44,46f
 intensity of reflections vs. aging severity, 44t,45,48
 micropore volume vs. deactivation severity, 42,43f,48
 performance of catalyst after treatment vs. temperature, 40–42
 performance of fresh catalyst, 40,41f
 role of sintering, 39
 sintering processes, 48,51
- $\text{Cu}-\text{ZSM}-5 + \text{Pt}-\text{Al}_2\text{O}_3$, CO and NH_3 conversion effect, 84,85t,87f
- $\text{CuO}-\text{Al}_2\text{O}_3$ and $\text{CuO}-\text{SiO}_2$, use for NO decomposition, 23
- Cupric sintering, role in $\text{Cu}-\text{ZSM}-5$ deactivation, 39–51

D

Deactivation of Cu-ZSM-5, *See* Cu-ZSM-5 deactivation

Deep oxidation of chlorinated hydrocarbons
activation energy, 346,347f
carbon support, structural parameters, 341t
catalyst characterization, 346,348–351
catalytic combustion reactivity, 342–344t
experimental procedure, 341–342
pore structure effect, 343
previous studies, 341
reactivity vs. hydrocarbon, 343–346
reactivity vs. hydrogen, 346,347f
reactivity vs. temperature, 346,347f

Desulfurization of combustion exhaust
gases, expense, 375

Diesel engine exhaust
catalytic posttreatment methods, 250
control using catalytic converters, 91
legislative requirements for emission, 250

Diffuse reflectance IR experiments

alumina, 395–397

titania, 397–400f

Doped CeO₂ catalyst, SO₂ reduction to S,
378–384

E

Emission control, mobile engine, 90–91

Emission standards, development in
Germany, 173,175f

Environmental legislation, impact on fuel
industry, 286

Environmental problems, application of
supported gold catalysts, 420–426

Ethene, requirements of low-temperature
oxidation catalyst for removal, 301

F

Flue gas, contemporaneous SO₂ and NO
removal using regenerable copper-on-
alumina sorbent–catalyst, 233–249

Foreign experience, SCR NO_x controls,
190–202

Formic acid, site-blocking agent for COS
hydrolysis, 399,401

Fuel industry, impact of environmental
legislation, 286

Future fuels, examples and production
methods, 270–271

G

Gasoline olefins, 273–275

Gasoline sulfur content
reaction kinetics for sulfur reduction,
286–295

reduction methods, 286–287

regulations, 296

Gasoline sulfur reduction

comparison to conventional technology,
293,294f

development, 293

reduction of gasoline-range sulfur
compounds, 293t–295

German experience with selective catalytic
reduction NO_x controls

high-dust configurations, 196–199

regulations, 196

tail end configurations, 199–200

transfer of technology to operating
conditions, 196

Germany, power plant capacity, 172,173t

Gold, catalytic activity, 420

Gold catalysts, supported, *See* Supported gold
catalyst application to environmental
problems

Granular activated carbon, use for control
of volatile organic compounds, 331–332

H

H₂ oxidation, role of supported gold
catalysts, 421–422

Halogenated hydrocarbons

advantages as solvents, 340

deep oxidation using catalysts, 341–351

disposal methods, 340–341

HBr

bromine recovery, 406–408

production from bromination of organic
compounds, 405,406t

recycling process, 406

Heterogeneous catalysts, control of volatile
organic compounds, 298–299

Hexane conversion, low-temperature deep
oxidation, 334,336t,337f

High-dust applications, SCR technology, 191–193

High-dust configuration

flue gas desulfurization effect, 210

German utility applications, 210,211*t*

location, 205,206*f*

problems, 207–209

High-sulfur coal service, U.S. application of SCR technology, 200–202

Highly selective olefin skeletal

isomerization process

advantages, 285

bench-scale reactor, 275–277

butene isomerization, 279,281*f*

catalyst performance, improvement, 279*t*,280*f*

catalyst screening, 275,277

commercial testing, 277,278*f*

development, 275

isobutylene yield vs. run time, 279,280*f*

operating conditions, 277

pentene isomerization, 279,282*f*,283*t*

process development unit, 276*f*,277

process flow diagram for butene and pentene isomerization, 283–285

saturates conversion in butene

isomerization, 279,281*f*

selectivity vs. run time, 279,280*f*

Hydrocarbon(s)

chlorinated, deep oxidation, 340–351

halogenated, *See* Halogenated

hydrocarbons

low-temperature deep oxidation, 331–339

NO_x removal, 4

Hydrocarbon combustion, role of supported

gold catalysts, 422,424*f*

Hydrocarbon oxidation, role in catalytic

reduction of NO, 53–64

Hydrofluoric acid, safety issue, 271

Hydrolysis of COS on titania catalysts

activity test of sulfated titania catalyst, 401–403

diffuse reflectance IR experiments

alumina, 395–397

titania, 397–400*f*

experimental procedure, 394–395

site-blocking agents, 399,401

sulfate formation, 400*f*,401

temperature-programmed reaction of sulfates with H₂S, 402*f*,403

I

Impregnated CeO₂(La) catalyst, SO₂ reduction to S, 388,391*f*

In situ infrared spectroscopy of NO–CO reaction on Rh–SiO₂ and Ce–Rh–SiO₂ experimental procedure, 158

reaction on Ce–Rh–SiO₂, 160–162*f*

reaction on prereduced and preoxidized Rh–SiO₂, 158–160

steady-state isotropic transient study, 160,163–166*f*

Isomerization process, highly selective olefin skeletal isomerization, *See* Highly selective olefin skeletal isomerization process

J

Japanese experience with selective

catalytic reduction NO_x controls ammonia injection system design, 194

base material design, 194–195

catalyst improvement, 194

commercial operation, 191

fuel additives, 194

NO_x reduction, significant factors, 190–191

product development trade-offs, 193,197*f*

reactions governing process, 190

removal efficiency, 193–194

SCR location configurations, 191,192*f*

soot and ammonium bisulfate deposit control, 195

start-up and shut-down of plants, 195

system features, 193

Takehara Station Unit 1, 195

K

Kinetics of gasoline sulfur compounds for sulfur reduction, *See* Reaction kinetics of gasoline sulfur compounds for sulfur reduction

L

La_{1-x}Sr_xCoO₃ catalysts, role in NO_x control by catalytic combustion of natural gas, 224–232

- Lead poisoning, palladium-only catalysts
for closed-loop control, 103,104f
- Lean-burn engines
emission control, 90
need for catalyst other
than three-way catalyst, 53
- Low-dust applications, SCR technology,
191–193
- Low-dust configuration, location, 205,206f
- Low-temperature catalytic combustion of
volatile organic compounds using ozone
applications, 368
catalysts, physicochemical characteristics,
356*t*,357
concentration vs. catalyst, 358,359f
concentration vs. temperature, 358,359f
experimental procedure, 354,357–358
laboratory plant, 357
micropollutant analysis 367–368
physicochemical analytical procedure, 357
pure catalyst vs. mixture, 363,364f
temperature vs. ozone concentration,
358,360–362f
temperature vs. volatile organic compound
concentration in air, 354,355f
volatile organic compounds, properties,
354,356*t*,357
X-ray photoelectron spectra vs. heat
treatment, 363,365–367
- Low-temperature deep oxidation of
aliphatic and aromatic hydrocarbons
advantages, 339
butane conversion, 336,338*t*
carbon supports, hydrophobicity, pore
volume, and properties, 334–335f
experimental procedure, 332–333
hexane conversion, 334,336*t*,337f
toluene conversion, 336,338*t*
- Low-temperature oxidation catalyst,
applications and examples, 301–302
- Low-temperature oxidation catalyst for
ethene removal
additional cation vs. reactivity, 313
bulk Pt concentration vs.
reactivity, 313
catalyst preparation and pretreatment
procedure, 304
catalyst testing method, 304,306f
experimental condition effect on
activity, 305,307–309*t*
- Low-temperature oxidation catalyst for
ethene removal—*Continued*
experimental description, 303
mini-reactor system for catalyst testing,
304,306f
nomenclature of ion-exchanged zeolite
samples, 303
palladium on alumina, 305,310f
PdCaNaY(L), 305,310–311f
platinum on asbestos, 305,308f
previous studies, 303
PtCaNaY(L), 305,311–313
reaction on reactor surfaces, 305,306f
requirements, 301
water vapor vs. reactivity, 312f,313
zeolites
analytical procedure, 303
ion-exchange procedure, 303
structure vs. reactivity, 313
- Low-temperature selective catalytic
reduction NO_x control
catalysts, 212–213
designs, 210,212–213
economic considerations for
configuration choice, 205,207
high-dust configurations, 207–209
operating information, 210
U.S. applications, 213
- M
- Metal–alumina surfaces, nitric oxide
reactions, 140–154
- Metal oxides
deep oxidation of chlorinated
hydrocarbons on synthetic
carbonaceous adsorbents, 340–351
oxidation catalysts, 302
- Methanol, production methods, 270
- Methyl *tert*-butyl ether, production, 270–271
- Mobile engine emission control
catalyst requirements, 90
catalytic converters for diesel engine
exhaust control, 91
lean-burn engine, 90
- Monolithic oxidation catalyst, process
condition effect of transient
response, 316–329
- Motor fuels, production methods, 271

N

Natural gas

catalytic combustion for NO_x control, 224–232

emission regulations, 224

industrial combustion systems, 224

NH₃, catalysts for cleanup from nuclear waste processing facility, 74–87

NH₃ conversion

Cu–ZSM-5 effect, 76–78

Cu–ZSM-5 + Pt–Al₂O₃ effect, 84,85*t*,87*f*

Pt–Al₂O₃ effect, 78,82–84

NH₃–NO ratio, NH₃ and CO conversion effect, 78–81*f*

Nitric oxide

catalytic decomposition over promoted copper ion exchanged ZSM-5 zeolites, 7–20

standards for automotive industry, 140

Nitrosyl reduction, mechanism, 140

NO

chemical transformations, 2,3*f*

contemporaneous removal with SO₂ from flue gas using regenerable copper-on-alumina sorbent–catalyst, 233–249

production, 2

NO and N₂O₂ adsorption on bare and supported metal catalysts

adhesion, 147,149–150

adhesion energies, 150*t*,151

ceramic support vs. Fermi level, 151,153

charge transfer, 150*t*,152*f*

Fermi level for N₂O₂ adsorption, 153,154*f*

Fermi level for NO adsorption, 151,153,154*f*

Fermi level variation, 151*t*,152

geometry, 141–146,148

models, 146–148*f*

NO–CO reaction, Rh–SiO₂ and Ce–Rh–SiO₂ catalyst effects on reaction, 157–166

NO conversion

O₂ effect on reaction mechanism, 35–36

O₂ effect on reactivity of Cu-based zeolites and oxides, 22–37

NO decomposition, need for catalyst, 22

NO oxidation, sulfate effect on Pt–ZrO₂ catalysts, 250–266

NO reduction

hydrocarbon oxidation, 53–64

mechanism study, 66–67

NO reduction in three-way catalyst

adhesion, 147,149–150

adhesion energies, 150*t*,151

charge transfer, 150*t*,152*f*

dinitrosyl species as reaction intermediates, 140–141

experimental description, 141

Fermi levels, 151*t*–154*f*

geometry, 141–146,148

models, 146–148*f*

NO reduction with hydrogen over Pt,

Rh, and Pt–Rh alloy surfaces

comparative studies, 129–135

experimental procedure, 115–116

mechanistic studies using Pt_{0.25}–Rh_{0.25}(100)

single-crystal surface as model catalyst, 120–121

NO + H₂ and NO + NH₃ reactions

10-mbar range, 126–129

10^{–6}–10^{–8}-mbar range, 123–126

reactions, 114–115

silica-supported catalysts, 116–120

silica-supported catalysts vs.

single-crystal surfaces, 135–138

spectroscopic data, 121–123

NO₂, source of health and

environmental problems, 2

NO_x

catalysts for cleanup from nuclear waste processing facility, 74–87

composition, 2

environmental removal, commercial

approaches, 2

selective catalytic reduction, 216,218

NO_x abatement, SCR catalysts, 172–188

NO_x control

catalytic combustion of natural gas, 224–232

foreign experience with selective catalytic reduction, 190–202

low-temperature SCR, 205–213

NO_x emissions

causes, 215

power plants, control methods, 170–171

removal methods, 233

NO_x reduction, role of supported gold catalysts, 422,426*t*,427

NO_x removal

automobile exhaust, methods, 53–54

catalytic decomposition of NO, 4

- NO_x removal—*Continued*
power plant applications, catalyst technologies, 215–223
reduction with hydrocarbons, 4
selective catalytic reduction, 2
- Noble metals, role in automotive emission control catalysts, 94,95f
- Nonvolatile organic compounds, regulation of emissions, 331
- Nuclear waste processing, NO_x and CO pollutants, 74
- O
- O_2 , role in Cu-based zeolite and oxide reactivity in NO conversion, 22–37
- O_2 emissions, removal methods, 233
- Olefin(s) in gasoline
future regulations, 273
ozone formation, 273,274f
reduction methods, 275
vapor pressure, 273,274f
- Olefin skeletal isomerization process, highly selective, *See* Highly selective olefin skeletal isomerization process
- Organic compounds, volatile, *See* Volatile organic compounds
- Oxidation catalyst, monolithic, process condition effect of transient response, 316–329
- Oxidation of hydrocarbons, role in catalytic reduction of NO, 53–64
- Oxidation of NO and SO_2 , 250–266
- Oxygen, COS hydrolytic effect, 401–403
- Oxygenates
gasoline blending, demand, 273
reformulated fuels, 270
- Ozone, use as oxidant in low-temperature catalytic combustion of volatile organic compounds, 354–368
- P
- Palladium
adhesion to alumina, 140–154
automotive emission control catalysts, 94,95f
- Palladium-only catalysts for closed-loop control
amount of noble metal used, 110,111f
- Palladium-only catalysts for closed-loop control—*Continued*
comparison of 50% Pt–Rh reduction, 96,97t,99f
development, 96
durability at stoichiometry after severe engine aging, 94,95f
exhaust air:fuel ratio effect on aging, 105–109f
lead poisoning, 103,104f
manifold mounted converter advantages, 106,109f–111f
performance characteristics, 97–111
problems, 94,96
rich NO_x performance, 103
 SO_2 poisoning, 103,105t
thermal durability performance, 97–102
- PdCaNaY(L), catalyst for low-temperature oxidation of ethene, 305,310–311f
- Pd–ZSM-5, role in NO reduction by hydrocarbon in oxidizing atmosphere, 58,60f,62f
- Pentene, isomerization process, 275–285
- Perovskite catalysts, role in NO_x control by catalytic combustion of natural gas, 224–232
- Plate-type catalytic converters
activity profile with high As_2O_3 content, 182,183f
applications, 187–188f
arrangement, 178,179f
catalyst activity and SO_2 conversion rate vs. V_2O_5 content, 182,183f
development, 173,177
dust deposition vs. geometric and fluid dynamic parameters, 178,180f
erosion resistance, 178,180f
operating results, 182,185–186f
selection according to operating conditions, 177t
selection criteria, 178,182,183f
- Platinum
adhesion to alumina, 140–154
catalyst, NO reduction effect, 114–138
role in automotive emission control catalysts, 94,95f
surface, sulfate effect, 263
- Power plant(s), catalytic emission control systems, 215–223

- Power plant capacity of Germany
 emission standards, development, 173,175*f*
 emissions from typical hard coal fired
 plant, 172,174*f*
 NO_x removal measures, 173,175*f*
 power sources, 172,173*f*
 Power plant emissions, control methods,
 170–171
 Process condition effect on transient response
 of monolithic oxidation catalyst
 air inlet temperature, 326*f*–329
 catalyst preparation 318–319
 challenge concentration, 324–326*f*
 equipment, 319–321
 experimental procedure, 317–318,321
 step change in concentration, 321–323
 Pt–Al₂O₃
 CO conversion effect, 76,77*f*
 NH₃ conversion effect, 78–84
 Pt–Rh alloy surfaces, NO reduction effect,
 114–138
 Pt–ZrO₂, sulfation by aging, 265–266
 Pt–ZrO₂ catalysts
 properties of aged catalysts, 266
 sulfate effect on NO and SO₂ oxidation,
 250–266
 PtCaNaY(L), catalyst for low-temperature
 oxidation of ethene, 305,311–313
 Pyridine, site-blocking agent for COS
 hydrolysis, 399,401
- R**
- Reaction kinetics of gasoline sulfur
 compounds for sulfur reduction
 catalytic cracking products of
 thiophene, 288–290*f*
 cracking rate determination, 289,291
 cracking reactions pathways, 291,292*f*
 experimental procedure, 287–288
 feedstock properties, 288,289*t*
 hydrogen transfer rate effect, 290*f*–292*f*
 sulfur compound cracking rates relative to
 that of hexadecane, 290*f*–293
 sulfur technology, developing, 293*t*–295
 Reactivity of Cu-based zeolites and oxides
 in NO conversion, O₂ effect, 22–37
 Reduction of NO, catalytic, role of
 hydrocarbon oxidation, 53–64
- Reduction with hydrocarbons, use for NO_x
 removal, 4
 Reformulated gasoline, requirement of
 Clean Air Act Amendment, 270
 Rh catalyst
 NO reduction effect, 114–138
 performance improvement, 157
 Rh–SiO₂ catalyst, NO–CO reaction effect,
 157–166
 Rhodium
 adhesion to alumina, 140–154
 automotive emission control
 catalysts, 94,95*f*,140
 Rich NO_x performance, palladium-only
 catalysts for closed-loop control, 103
- S**
- Selective catalytic reduction (SCR)
 catalyst properties, 215
 catalytic converters for NO_x control
 activity profile(s)
 catalysts, 182,184*f*
 high As₂O₃ content, 182,183*f*
 poisoning resistant catalysts, 182,184*f*
 application(s), 187–188*f*
 application to U.S. high-sulfur coal
 service, 200,201*t*,203
 arrangement, 178,179*f*
 blockage frequency vs. converter type,
 182,185*f*
 catalyst activity and SO₂ conversion
 rate vs. V₂O₅ content, 182,183*f*
 description, 173,176*f*
 development of plate-type
 converters,173,177
 dust deposition vs. geometric and fluid
 dynamic parameters, 178,180*f*
 erosion resistance, 178,180*f*,186*f*
 German experience, 196–200
 Japanese experience, 190–195,197
 operating results, 182,184–186*f*
 selection according to operating
 conditions, 177*t*
 selection criteria, 178,182,183*f*
 types, 178,181*f*
 description, 216,218
 location configurations, 191–193

Selective catalytic reduction (SCR)—

Continued

operating environment and process constraints, 215

NO_x removal, 2

Selective catalytic reduction reactor,

location configurations, 205,206f

Selectivity, definition, 277

Selectivity factor, definition, 255

Semivolatile organic compounds, emission control methods, 331–332

Sintering, cupric, role in Cu–ZSM-5 deactivation, 39–51

SO₂, contemporaneous removal with NO from flue gas using regenerable copper-on-alumina sorbent–catalyst, 233–249

SO₂ oxidation, sulfate effect on Pt–ZrO₂ catalysts, 250–266

SO₂ poisoning, palladium-only catalysts for closed-loop control, 103,105t

SO_x emissions from power plants, control methods, 170–171

Stack gas emissions from power plants, catalytic control methods, 170–171

Stadtwerke Duesseldorf, low-temperature SCR design, 210,212

Strontium, role in NO_x control by catalytic combustion of natural gas, 224–232

Sulfate(s)

formation during COS hydrolysis, 400f,401
temperature-programmed reaction with H₂S, 402f,403

Sulfate effect on Pt–ZrO₂ catalysts for NO and SO₂ oxidation

activity measurement procedure, 251,252t
adsorption–desorption characteristics of catalysts, 262–264f

aging tests, 255,256f

catalyst acidity, 266

catalyst preparation, 251t

experimental description, 250–251

Fourier-transform IR spectra, 257,261f,262

NO conversion with and without SO₂, 252,253f,255

properties of aged Pt–ZrO₂ catalysts, 266

Pt–ZrO₂ sulfation by aging, 265–266

reduction of surface sulfate, 265

selectivity, 255,256f

Sulfate effect on Pt–ZrO₂ catalysts for NO and SO₂ oxidation—*Continued*

SO₂ conversion with and without NO, 252,254f,255

surface Pt, 263

temperature-programmed desorption procedure, 252

temperature-programmed desorption vs. pretreatment, 255,257–259f

temperature-programmed reduction vs.

fresh and used samples, 257,259–260f

treatment effect on catalyst surface area, 266

Sulfate surface, reduction, 265

Sulfated titania catalyst, activity test, 401–403

Sulfur compounds, gasoline, *See* Gasoline
sulfur content

Sulfur dioxide reduction to elemental sulfur methods, 375–376

redox reaction mechanism, 376–377

water in feed gas effect, 376

Sulfur dioxide reduction to elemental sulfur over ceria catalysts

apparatus, 377

association enthalpy and conductivity

for solid solutions of dopants, 379,381t

catalyst preparation, 378,380t

CeO₂ catalyst, 378,381f

CeO₂(La) catalyst, 384,385f

dopant vs. activity, 379,382f

doped CeO₂ catalysts, 378–384

experimental procedure, 377

impregnated CeO₂(La) catalyst, 388,391f

light-off behavior, 379,382,384f

mechanisms, 388–390

water vapor effect, 384,386–388

Y₂O₃ dopant content vs. activity, 379,380t,382f

Sulfur reduction, catalytic mechanisms, and reaction kinetics, 286–295

Sulfuric acid, safety issue, 271

Supported gold catalyst application to environmental problems

characterization of catalysts, 421t

CO oxidation, 421–423f

CO₂ hydrogenation, 426t

experimental procedure, 420–421

H₂ oxidation, 421–422

hydrocarbon combustion, 422,424f

NO_x reduction, 422,426t,427

trimethylamine combustion, 422,425f

Supported noble metals, use as oxidation catalysts, 302
Surface acidity, catalyst performance effect, 250–251
Surface platinum, sulfate effect, 263
Surface sulfate, reduction, 265
Synthetic carbonaceous adsorbent(s), 332
Synthetic carbonaceous adsorbent supported metal oxides for deep oxidation of chlorinated hydrocarbons
activation energy, 346,347*f*
carbon support, structural parameters, 341*t*
catalyst characterization, 346,348–351
catalytic combustion reactivity, 342–344*t*
experimental procedure, 341–342
pore structure effect, 343
previous studies, 341
reactivity vs. hydrocarbon, 343–346
reactivity vs. hydrogen, 346,347*f*
reactivity vs. temperature, 346,347*f*
Synthetic carbonaceous adsorbent supported transition metal oxides for low-temperature deep oxidation of aliphatic and aromatic hydrocarbons
advantages, 339
butane conversion, 336,338*t*
carbon supports
hydrophobicity, 334,335*f*
pore volume, 334*t*,335*f*
properties, 334*t*
experimental procedure, 332–333
hexane conversion, 334,336*t*,337*f*
toluene conversion, 336,338*t*

T

Tail end configuration
advantages, 209–210
German utility applications, 210,211*t*
location 205,206*f*
problems, 209
Tail gas applications, SCR technology, 191–193
Temperature
NO_x selective catalytic reduction
catalyst effect, 215–223
role in catalytic decomposition of NO over promoted copper ion exchanged ZSM-5 zeolites, 8–20

Thermal combustion, control of volatile organic compounds, 298
Thermal durability performance, palladium-only catalysts for closed-loop control, 97–102
Thermal oxidation, control of volatile organic compounds, 331–332
Titania
catalyst for COS hydrolysis, 394–403
diffuse reflectance IR experiments, 397–400*f*
Toluene conversion, low-temperature deep oxidation, 336,338*t*
Transient response
oxidation catalysts, automotive applications, 317
process conditions for monolithic oxidation catalyst, 316–329
Transition metal(s), cocation effect in catalytic decomposition of NO using copper ion exchanged ZSM-5 zeolites, 8–20
Transition metal oxides, low-temperature deep oxidation of aliphatic and aromatic hydrocarbons using synthetic carbonaceous adsorbents, 331–339
Trimethylamine combustion, role of supported gold catalysts, 422,425*f*
Turnover frequency
CO₂ formation, definition, 163
definition, 15

U

United States high-sulfur coal service, application of SCR technology, 200–202

V

Volatile organic compounds
advantages of catalytic combustion for elimination, 353–354
control using heterogeneous catalysts, 298–299
elimination methods, 353
emission control methods, 331–332
future research needs, 300

Volatile organic compounds—*Continued*
low-temperature catalytic combustion,
354–368
recovery methods, 353
regulations, 298,331
source of pollution, 353

W

Water, SO₂ reduction to S effect, 376
Water vapor, SO₂ reduction to S,
384,386–388

X

X-ray photoelectron spectroscopy
Cu–ZSM-5 zeolite
analytical system, 67–68
Cu core level spectra vs. reactor
treatment, 68–71
Cu core level spectra vs. reductive
treatments, 71,72*f*

X-ray photoelectron spectroscopy—
Continued
Cu–ZSM-5 zeolite—*Continued*
experimental description, 67
previous studies, 67
treatments, 68,69*t*
zeolite studies, 67

Y

Yield, definition, 277

Z

Zeolite(s), advantages as supports for
oxidation catalysts, 302
Zeolite degradation, role in Cu–ZSM-5
deactivation, 39–51
ZSM-5 zeolites, copper ion exchanged,
catalytic decomposition of NO, 7–20

Production: Charlotte McNaughton
Indexing: Deborah H. Steiner
Acquisition: Rhonda Bitterli
Cover design: Bob Sargent

Printed and bound by Maple Press, York, PA

In Environmental Catalysis; Armor, John N.;
ACS Symposium Series; American Chemical Society: Washington, DC, 1994.