

Affiliation Index

- Boehringer Mannheim Corporation, 47
 City University of New York, 124,169
 Colorado State University, 158
 Delft University of Technology, 34
 Eli Lilly and Company, 84
 Firestone Building Products Company, 2
 Georgetown University, 252
 Kumamoto University School
 of Medicine, 194
 Kyushu University, 238
 National Institute of Bioscience and
 Human Technology, 41
 National Tsing Hua University, 276
 Naval Research Laboratory, 252,264
 Polytechnic University, 124,169
 Purdue University, 47
 Technische Universität München, 34,110
 Tianjin Medical College, 96
 Tokyo Medical and Dental
 University, 194
 Tufts University, 21
 University of British Columbia, 211
 University of Cincinnati, 137
 University of Hacettepe, 71,222
 University of Manchester, 71
 University of Neuchâtel, 298
 University of North Carolina at
 Chapel Hill, 149
 University of Texas at Austin, 34,
 180,307

Subject Index

A

- Affinity chromatography, polystyrene-
 based particles, 227
 Albumin adsorption, nondegradable
 polystyrene-based particles, 227–229
 Amperometric biosensors
 drawbacks, 110–111
 reagentless enzyme electrode
 development, 111–112,113f
 Amperometric enzyme electrodes for
 glucose determination, sandwich-type,
 See Sandwich-type amperometric
 enzyme electrodes for glucose
 determination
 Amperometric glucose-sensing electrodes
 with modified enzymes
 enzyme electrode systems, 42–43
 experimental description, 41–42
 flow injection measurement of glucose
 for lipid-modified enzyme electrode,
 44,45f,46t
 Purdue University, 47
 Technische Universität München, 34,110
 Tianjin Medical College, 96
 Tokyo Medical and Dental
 University, 194
 Tufts University, 21
 University of British Columbia, 211
 University of Cincinnati, 137
 University of Hacettepe, 71,222
 University of Manchester, 71
 University of Neuchâtel, 298
 University of North Carolina at
 Chapel Hill, 149
 University of Texas at Austin, 34,
 180,307
 Amperometric glucose-sensing electrodes
 with modified enzymes—*Continued*
 glucose response
 lipid-modified enzyme electrode,
 44,45f
 polyethylene glycol-modified enzyme
 electrode, 43,45f
 lipid-modified enzyme properties, 44
 polyethylene glycol-modified enzyme
 properties, 43
 Amperometric glucose electrodes based
 on glucose oxidase, chemical or
 electrochemical steps, 124–125
 Amperometric glucose sensors
 glucose oxidase and nonphysiological
 redox mediators, electron-transfer
 mechanism, 169–170
 poly(etheramine–quinone)s as electron
 transfer relay systems, 124–135
 viologen derivative containing
 polysiloxane as electron-transfer
 mediator, 169–178

Amperometric peroxidase-based H_2O_2 sensors

examples, 180–183*t*

reactions, 180–184

Anionic species, flow injection analysis

with automated dual working electrode potentiostat, 137–147

Antibodies to hepatitis B surface antigen, use for thin-layer flow-through enzyme immunosensor, 96–106

Apparent Michaelis–Menten constants

poly(etheramine–quinone)s as electron transfer relay systems in amperometric glucose sensors, 132,134–135*f*

viologen derivative containing polysiloxane as electron-transfer mediator in amperometric glucose sensors, 175,177*f*,178*t*

Artificial endocrine pancreas,

2-methacryloyloxyethylphosphorylcholine copolymers for implantable glucose sensor, 204–209

Automated dual working electrode potentiostat, design, 140,142–143*f*

B

Biochemical sensors, miniaturization, 298

Biocompatibility

importance for biomedical materials, 194

perfluorosulfonic acid polymer

membranes for biosensor applications in vitro investigations, 214–220 in vivo investigations, 212–214 requirements, 211

Biocompatible polymers, molecular design, 194–195,196*t*

Biodegradable monosize polycyanoacrylate particles

applications, 230

degradation, 230–232*f*

optical micrographs, 230,231*f*

preparation, 230

Biodegradable poly(lactic acid) microspheres

applications, 232

molecular weight vs. drug release rate, 233–234

preparation, 232–233

scanning electron micrographs, 233*f*

Biomedical applications, modified

poly(vinyl chloride) membranes for microfabricated ion-selective electrode arrays, 149–156

Biomimetic sensors, use of semi-synthetic macromolecular conjugates, 238–250

Biosensor(s)

redox polymers, 18–19

ultrathin film composite membranes

advantages, 164,166

approach, 158

calibration curve for glucose, 162*f*,163

chemical selectivity of films, 463 concepts, 158–159

device fabrication procedure, 161

film defects, 163

glucose effect on cyclic voltammogram, 159,160*f*

O_2 concentration vs. sensor response, 164,165*f*

prototype, 159,160*f*

response characteristics of prototype, 161–162

response time, 164,165*f*

size-based selectivity of films, 163

Biosensor applications, biocompatibility of perfluorosulfonic acid polymer membranes, 211–220

Bis(2,2'-bipyridine)- N,N' -dichloroosmium electrodes, electrical communication with glucose oxidase, 307–316

Blood compatibility, 2-methacryloyloxyethylphosphorylcholine copolymers, 202,204–209

Blood compatibility tests, sandwich-type amperometric enzyme electrodes for glucose determination, 75,81–82

C

Calcium ion sensor, use of semisynthetic macromolecular conjugates, 241–244

Cationic radical polymerization, steps, 138

Chemical sensors, technological evolution, 71

Composite membranes, ultrathin film, biosensor design, 158–166

Conducting polymer(s)

- applications, 137–138
- development, 137
- functionalized, covalent binding of enzymes, 112,114–117

Conducting polymer films, electrochemically grown, enzyme entrapment, 115,118–121*f*

Conjugates, semisynthetic macromolecular, *See* Semisynthetic macromolecular conjugates for biomimetic sensors

Constant potential measurement, poly(etheramine–quinone)s as electron transfer relay systems in amperometric glucose sensors, 129,132–134*f*

Controlled release from liposomes of long-chain polymerizable diacetylenic phosphocholine and short-chain saturated phospholipid

- experimental description, 265–266, 271–272
- lipid ratio vs. particle size and morphology, 267–268,269*f*,273
- liposome formation method vs. polymerization, 267
- liposome preparation procedure, 266
- permeability of unpolymerized and polymerized liposomes, 268,270*f*,272–273
- polymerization procedure, 266
- previous studies, 265
- release study procedure, 267
- size and morphology of liposomes, 266
- sonication time vs. polymerization, 267
- spacer lipid effect, 272
- structures, 266,269*f*

Controlled release from liposomes of long-chain polymerizable diacetylenic phosphocholine and short-chain saturated phospholipid—*Continued*

- Triton X–100 vs. release from polymerized liposomes, 268,271*f*

Controlled-release properties of stabilized liposomes, interest, 264

Current measurements, conductivity and intrinsic property determination, 50–51

Cyclic voltammetry, viologen derivative containing polysiloxane as electron transfer mediator in amperometric glucose sensors, 171,173*f*,174*t*

Cyclic voltammetry measurement, poly(etheramine–quinone)s as electron transfer relay systems in amperometric glucose sensors, 129,130*f*,131*f*,*t*

D

Dahms–Ruff relationship, equation, 51

Degradable polymers, fiber-optic sensors, 21–33

Deoxyribonucleic acid (DNA) binding drug sensor, use of semisynthetic macromolecular conjugates, 245–250

Diabetes treatment, importance of continuous blood glucose level readings, 84

Diagnostic enzymes

- mechanism of thermal stability, 15,17*f*
- properties, 13,15,16*t*

Diagnostic imaging, polystyrene-based radiopharmaceuticals, 224–225

Diagnostic polymers and coatings

- advantages, 2
- applications, 17–18
- biosensors, 18–19
- constructions, 6–8*f*
- history of dry chemistry, 3
- matrix binders, 9,11*t*
- molded dry chemistry, 13,15,16*t*,17*f*
- nonaqueous coatings, 10,12–13,14*f*
- reactions, 4,6,7*f*

Diagnostic polymers and coatings—

Continued

waterborne coatings, 9–10,11f

Differentially permeable outer membrane

material for implantable glucose sensor

advantages, 93–94

diffusion study procedure, 88

fabrication, 86f

in vitro characterization of

performance, 89

molecular weight determination

procedure, 88

polymer biocompatibility enhancement

procedure, 88–89

results, 93–94

polymer synthesis

procedure, 87–88

results, 92–93

relative diffusion coefficients, 92–93,94f

water pickup determination

procedure, 88

Dry chemistry

background, 3–4

constructions, 6–8f

diabetes considerations, 6,9

history, 3

Dry chemistry diagnostic test kits

list, 4,5t

reactions, 4,6,7f

Durability, glucose oxidase immobiliza-

tion on polyethylene film using

plasma-induced graft copolymerization

process, 293,295f

Dye-attached polystyrene-based particles,

albumin adsorption, 229f

E

Electrical communication between

glucose oxidase and electrodes based

on poly(vinylimidazole) complex of

bis(2,2'-bipyridine)-*N,N'*-

dichloroosmium

cyclic voltammetry, 307

Electrical communication between

glucose oxidase and electrodes based

on poly(vinylimidazole) complex of

bis(2,2'-bipyridine)-*N,N'*-dichloroosmium—*Continued*

electrochemical experimental

procedure, 309

electrodes, 308–309,310f

enzyme loading dependence,

313,315–316f

experimental materials and objective,

308

glucose response, 309,311f

ionic strength dependence, 313,314f

oxygen competition, 309,312f

pH dependence, 313,314f

polymer preparation, 308,310

problem, 307

thickness dependence, 313,315f

Electrical connection of peroxidase redox

centers, hydrogen peroxide electrodes,

180–191

Electrochemical aided adsorption

membrane deposition

enzyme immobilization, 301,303–305

procedure, 300

Electrochemical detection, advantages,

180

Electrochemical microbiosensors, rapid

blood chemistry determinations, 47

Electrochemical systems for glucose

determination, electron-transfer

shuttle for electron transport, 47–48

Electrochemically grown conducting

polymer films, enzyme entrapment,

115,118–121f

Electrode(s), amperometric glucose

sensing, *See* Amperometric glucose-

sensing electrodes with modified

enzymes

Electrode potentiostat, automated dual

working, design, 140,142–143f

Electrodeposition technique for glucose

oxidase immobilization for implantable

glucose sensor

advantages, 94–95

- Electrodeposition technique for glucose oxidase immobilization for implantable glucose sensor—*Continued*
- biomolecule codeposition procedure, 87
- concept, 84–85
- development, 85
- enzyme deposition
- procedure, 86–87
- results, 89–92
- Electron-relaying polymer network, three dimensional, hydrogen peroxide electrodes, 180–191
- Electron-transfer mediator, viologen derivative containing polysiloxane in amperometric glucose sensors, 169–178
- Electron-transfer relay systems in amperometric glucose sensors, poly(etheramine–quinone)s, 124–135
- Electron-transport rates in enzyme electrode for glucose
- cyclic voltammetry at planar electrodes, 60,61f,62t
- electrochemical measurement
- procedure, 53
- electrode fabrication, 52
- enzyme concentration vs. diffusion constant, 65
- experimental description, 48,50–52
- factors controlling sensor response, 67–69
- film configuration and homogeneity, 53–55,56f,57t
- film fabrication, 52–53
- limiting current measurements, 58–60
- Os concentration vs. electron diffusion rate, 63,65
- Os site surface coverage determination, 55,56f,58
- polymer–enzyme complex, 65
- potential errors, 66–67
- previous studies, 48,50
- rate constant calculation, 60,63
- reaction mechanism, 67
- reaction sequence, 48
- sensor response at maximal rates, 63,64f
- Electron-transport rates in enzyme electrode for glucose—*Continued*
- system heterogeneity effect, 65–66
- system optimization, 69
- Enzyme(s)
- advantages of modification, 41
- covalent binding by functionalized conducting polymers, 112,114–117
- entrapment within electrochemically grown conducting polymer films, 115,118–121f
- role in dry chemistry, 4
- Enzyme-based sensors, technological evolution, 71
- Enzyme electrodes for glucose
- electron-transport rates, 47–69
- sandwich-type amperometric, *See* Sandwich-type amperometric enzyme electrodes for glucose determination
- Enzyme immobilization
- polymerizable phospholipid assemblies
- advantages, 260,262
- binding constants, 253
- concept, 253
- enzyme assay procedure, 258
- enzyme immobilized vesicle
- preparation procedure, 256,258
- experimental materials, 254,256
- lipid contamination, 258
- miscibility behavior
- determination, 256
- results, 258–260
- phospholipid synthesis procedure, 256–257
- polymerization effect, 260,261f
- protocol, 254–255
- steps, 253–254
- structure of phospholipids, 253,254f
- thermal behavior determination
- procedure, 256
- spatially controlled on-wafer and on-chip, use of photochemical and electrochemical techniques, 298–305
- Enzyme immunoassay, function, 96–98

Enzyme immunosensor, thin-layer flow-through, *See* Thin-layer flow-through enzyme immunosensor based on polycaprolactam net

F

Fiber-optic sensors based on degradable polymers
microparticle structure, 24,25*f*
microsphere preparation procedure, 24–26
microsphere size vs. preparation conditions, 26,27*f*
molecular weight of polymer vs. release rate, 26,28*f*
release pattern, 24
sensor configuration, 26,27*f*
sensor design, 26,28–33
substantiated-release polymers, 22–24
substance enclosure, 24

Flow-injection analysis of anionic species with electrode potentiostat using poly(3-methylthiophene)-modified electrode
automated dual working electrode potentiostat design, 140,142–143*f*
electrochemical cells, 139
electrochemical techniques, 139
electrodes, 139
experimental materials, 138–139
hardware design, 140–141,144*f*,145
objectives, 138
potentiostat design and manufacture approach, 138
preliminary experiments, 145–147
schematic representation, 140,141*f*
software design, 145

Functionalized conducting polymers, covalent binding of enzymes, 112,114–117

G

Glucose, electron-transport rates in enzyme electrode, 47–69

Glucose determination, sandwich-type amperometric enzyme electrodes, 71–82

Glucose oxidase

electrical communication with bis(2,2'-bipyridine)-*N,N'*-dichloroosmium electrodes, 307–315
immobilization using electrodeposition, 84

Glucose oxidase immobilization on polyethylene film using plasma-induced graft copolymerization process apparatus, 277
durability, 293,295*f*
electron spectroscopy for chemical analysis of substrate polymer preparation, 280–285*f*
enzyme activity assay procedure, 280
enzyme immobilization, 281,286–288*f*
experimental materials, 277
maximum reaction velocity, 281,289,290*f*
Michaelis constant, 281,289,290*f*,*t*
pH stability, 293,294*f*
stability measurement procedure, 280
storage stability, 293,296*f*
substrate polymer preparation, 277–280
thermal stability, 289,291*f*,292*f*,*t*

Glucose-sensing electrodes, amperometric, *See* Amperometric glucose-sensing electrodes with modified enzymes

Glucose sensor, implantable, *See* Implantable glucose sensor

H

Hepatitis B surface antigen antibodies, use for thin-layer flow-through enzyme immunosensor, 96–106

Home monitoring, history, 3

Hydrogen peroxide electrodes based on electrical connection of peroxidase redox centers
construction, 184,186*f*

Hydrogen peroxide electrodes based on electrical connection of peroxidase redox centers—*Continued*
electrostatic interaction of polymer and enzyme, 188,191*f*
 H_2O_2 detection based on three-dimensional redox epoxy networks, 185–187*f*
isoelectric focusing procedure, 184–185
operation, 184
peroxidase sensor response, 185,188–191*f*

I

Immobilization
enzymes, polymerizable phospholipid assemblies, 252–262
glucose oxidation, use of plasma-induced graft copolymerization process on polyethylene film, 276–296
Immunoassay, function, 96
Implantable biosensors for long-term in vivo clinical monitoring, development, 211
Implantable glucose sensor
advantages, 84
description, 84–85
development, 85–95
2-methacryloyloxyethylphosphorylcholine copolymers, 204–209
Interdigitated arrays, conductivity and intrinsic property determination, 50–51
Ion-channel sensors, concept, 238

L

Linearity tests, sandwich-type
amperometric enzyme electrodes for glucose determination, 74–75,77–80

Liposomes
long-chain phosphocholine and short-chain phospholipid, controlled release, 264–273
stabilization methods, 264–265
Long-chain polymerizable diacetylenic phosphocholine, controlled release from liposomes, 264–273

M

Macromolecular conjugates, semisynthetic, *See* Semisynthetic macromolecular conjugates for biomimetic sensors
Maximum reaction velocity, glucose oxidase immobilization on polyethylene film using plasma-induced graft copolymerization process, 281,289,290*f*
Mediator-modified enzymes, entrapment within conducting polymer films, 118,121*f*
2-Methacryloyloxyethylphosphorylcholine, structure, 195,197*f*
2-Methacryloyloxyethylphosphorylcholine copolymers
application for implantable glucose sensor of artificial endocrine pancreas, 204–209
blood compatibility, 195,197–203
mechanism of blood compatibility on surface, 202,204,205*f*
solubility, 195
Michaelis constant, glucose oxidase immobilization on polyethylene film using plasma-induced graft copolymerization process, 281,289,290*f,t*
Microcapsules, definition, 24
Microfabricated ion-selective electrode arrays in biomedical applications, stability characterization of modified poly(vinyl chloride) membranes, 149–156

Microparticles, definition, 24
Microspheres, definition, 24
Modified enzymes, use in amperometric glucose-sensing electrodes, 41–46
Modified poly(vinyl chloride) membrane stability for microfabricated ion-selective electrode arrays in biomedical applications
buffer solution preparation, 151
cell internal resistance determination procedure, 151
current vs. time transient measurement procedure, 151
decomposition, 152–155
dissolved ionophore and lipophilic salt additive determination procedure, 151–152
electromotive force measurement procedure, 151
experimental description, 150–151
membrane(s) and membrane solution preparation, 151
membrane characteristics vs. time, 152,153f
planar ion-selective electrode fabrication on Kapton wafers, 151
time constant determination, 155–156
Molecular design of biocompatible polymers, categories, 194–195,196t
Monosize polycyanoacrylate particles, biodegradable, *See* Biodegradable monosize polycyanoacrylate particles
Monosize polymeric particles, applications, 222
Myocardial ischemia symptoms, 149
time course of ischemic events, 149

N

Nafion polymer membranes, *See* Perfluorosulfonic acid polymer membranes
Nanoparticles, definition, 24

Nonaqueous coatings, chemistry, 10,12–13,14f
Nondegradable polystyrene-based particles
albumin adsorption, 227–229
phagocytosis, 225–227
preparation, 223–224
surface modification, 224
use
affinity chromatography, 227
diagnostic imaging, 224–225
Nonenzymatic urea sensor, use of semisynthetic macromolecular conjugates, 244–245,246f

P

Perfluorosulfonic acid polymer membranes
applications, 212
development, 212
in vitro biocompatibility investigations, 214–220
in vivo biocompatibility investigations, 212–214
structure, 212
Peroxidase enzymes
electrical connection of redox centers to hydrogen peroxide electrodes, 180–191
 H_2O_2 reduction catalysis, 180
pH stability, glucose oxidase immobilization on polyethylene film using plasma-induced graft copolymerization process, 293,294f
Phagocytosis, nondegradable polystyrene-based particles, 225–227
Phospholipid(s), potential for microstructure formation, 252
Phospholipid assemblies, polymerizable, enzyme immobilization, 252–262
Photolithographic membrane deposition enzyme immobilization, 301,302f
procedure, 300

- Plasma deposition polymerization, surface chemical modification of polymeric materials, 276
- Plasma-induced graft copolymerization technique
glucose oxidase immobilization on polyethylene film, 276–296
studies, 276
- Plasma treatment, surface chemical modification of polymeric materials, 276
- Polyallylamine, role in wired quinoprotein glucose dehydrogenase electrode stability enhancement, 34–39
- Polycaprolactam net, thin-layer flow-through enzyme immunosensor, 96–106
- Poly(etheramine–quinone)s as electron transfer relay systems in amperometric glucose sensors
apparent Michaelis–Menten constants, 132, 134–135*f*
constant potential measurement, 129, 132–134*f*
cyclic voltammetry measurement, 129, 130*f*, 131*f*, *t*
electrochemical measurement procedure, 128–129
electrode construction procedure, 128
experimental description, 126
polymer synthesis procedure, 126–128
- Polyethylene film, glucose oxidase immobilization using plasma-induced graft copolymerization process, 276–296
- Poly(lactic acid) microspheres, biodegradable, *See* Biodegradable poly(lactic acid) microspheres
- Polymer(s)
applications in medical field, 2
degradable, fiber-optic sensors, 21–23
- Polymer–enzyme hydrogel films, schematic representation, 48, 49*f*
- Polymeric redox mediators, applications, 307
- Polymerizable phospholipid(s), applications, 252–253
- Polymerizable phospholipid assemblies, enzyme immobilization, 252–262
- Poly(3-methylthiophene)
doping–undoping mechanism, 138
use as electrochemical detector for anionic species, 138, 139*f*
- Poly(3-methylthiophene)-modified electrode, flow injection analysis of anionic species, 137–147
- Polysiloxane
quinone group containing, structures, 125–126, 127*f*
viologen derivative containing, *See* Viologen derivative containing polysiloxane as electron transfer mediator in amperometric glucose sensors
- Polystyrene-based particles
affinity chromatography, 227
albumin adsorption, 227–229
nondegradable, *See* Nondegradable polystyrene-based particles
phagocytosis, 225–227
- Polystyrene-based radiopharmaceuticals, diagnostic imaging, 224–225
- Poly(vinylimidazole) complex of bis(2,2′-bipyridine)-*N,N*′-dichloroosmium electrodes, electrical communication with glucose oxidase, 307–316
- Pyrrole-modified glucose oxidase and pyrrole, copolymerization, 115, 118–120*f*
- Q
- Quinoprotein dehydrogenase electrode, wired, *See* Wired quinoprotein dehydrogenase electrode
- R
- Reagent delivery systems
active, 21
passive, 22

Reagentless amperometric enzyme electrodes
 development possibilities, 111–112, 113f
 enzyme entrapment within electrochemically grown conducting polymer films, 115, 118–121f
 functionalized conducting polymers for covalent binding of enzymes, 112, 114–117
 future work, 122
 Redox polymers, biosensors, 18–19
 Relative diffusion coefficients, calculation, 92–93

S

Sandwich-type amperometric enzyme electrodes
 glucose determination
 blood compatibility test
 procedure, 75
 results, 81–82
 chemical coating procedure, 73–74
 electrode, 72, 73f
 electrode description, 75–76
 enzyme layer preparation, 74
 experimental description, 72
 glow discharge treatment procedure, 72, 73f
 inner membrane preparation, 74
 linearity test
 procedure, 74–75
 results, 77–80
 outer membrane preparation, 72–74
 selectivity test
 procedure, 74
 results, 76–77
 layers, 71–72
 Selectivity tests, sandwich-type
 amperometric enzyme electrodes for
 glucose determination, 74, 76–77
 Self-testing, history, 3
 Semisynthetic macromolecular conjugates
 for biomimetic sensors
 calcium ion sensor, 241–244

Semisynthetic macromolecular conjugates
 for biomimetic sensors—*Continued*
 DNA-binding drug sensor, 245–250
 DNA-immobilized electrode
 preparation, 240
 electrochemical measurement
 procedure, 240
 experimental description, 239
 Fourier transform IR measurement
 procedure, 240–241
 nonenzymatic urea sensor, 244–245, 246f
 polypeptide-immobilized electrode
 preparation, 239–240
 schematic representation, 239f
 Sensors
 biomimetic, use of semisynthetic
 macromolecular conjugates, 238–250
 continuity requirement, 21
 reversibility, 21
 Short-chain saturated phospholipid,
 liposomes of long-chain phosphocholine and short-chain phospholipid,
 controlled release, 264–273
 Signal transduction in living cell
 surface, mechanisms, 238
 Solid-phase chemistry, *See* Dry
 chemistry
 Spatially controlled on-wafer and on-chip
 immobilization using photochemical
 and electrochemical techniques
 apparatus, 299–300
 electrochemical aided adsorption
 membrane deposition procedure,
 300–301
 electrochemical measurement
 procedure, 301
 electrochemically aided adsorption,
 301, 303–305
 experimental description, 298–299
 photolithographic deposition, 301, 302f
 photolithographic membrane deposition
 procedure, 300
 previous studies, 298–299
 transducers, 300, 302f
 Spherical polymeric particles,
 polymerization techniques, 223

Stability

- modified poly(vinyl chloride)
 - membranes for microfabricated ion-selective electrode arrays in biomedical applications, 149–156
- wired quinoprotein glucose dehydrogenase electrode
 - current dependence on glucose concentration, 36–37
 - experimental procedure, 34–36
- isoelectric focusing electrophoresis, 37–38
- polyallylamine effect, 39*t*
- properties, 39*t*
- time dependence of currents, 38–39

Stationary potential measurements,

- viologen derivative containing polysiloxane as electron-transfer mediator in amperometric glucose sensors, 174*f*, 175–177*f*

Storage stability, glucose oxidase

- immobilization on polyethylene film using plasma-induced graft copolymerization process, 293, 296*f*

Surface chemical modification of

- polymeric materials, plasma treatment and plasma deposition polymerization, 276

Surface modification, nondegradable

- polystyrene-based particles, 224

Sustained-release polymers, use for

- sensor construction, 22–24

Synthetic phospholipids, potential for

- microstructure formation, 252

T

Thermal stability, glucose oxidase

- immobilization on polyethylene film using plasma-induced graft copolymerization process, 289, 291*f*, 292*f*, *t*

Thin-layer flow-through enzyme

- immunosensor based on polycaprolactam net
 - antibody attachment to net, 100
 - antibody concentration vs. sensor response, 101, 103*f*
 - apparatus, 98, 102*f*
 - enzyme immunosensor and assay procedure, 99–100
 - experimental materials, 98–99
 - feasibility of immunosensor construction
 - for antigen determination, 104, 106*f*
 - flow rate vs. sensor response, 101, 103*f*
 - incubation time vs. sensor response, 100–101
 - nonspecific binding elimination, 101, 104, 105*f*
 - O-methylation of net, 100
 - pH vs. sensor response, 101, 102*f*
 - sensor calibration curve, 104, 106*f*
- Three-dimensional electron relaying
 - polymer network, hydrogen peroxide electrodes, 180–191

U

Ultrathin film composite membranes,

- biosensor design, 158–166

Urea sensor, nonenzymatic, use of

- semisynthetic macromolecular conjugates, 244–245, 246*f*

V

Viologen derivative containing

- polysiloxane as electron-transfer mediator in amperometric glucose sensors
 - apparent Michaelis–Menten constants, 175, 177*f*, 178*t*
 - cyclic voltammetry, 171, 173*f*, 174*t*
 - electrochemical methods, 171

Viologen derivative containing
 polysiloxane as electron-transfer
 mediator in amperometric glucose
 sensors—*Continued*
electrode construction, 171
experimental description, 170
polymer synthesis procedure, 170–172
stationary potential measurements,
 174*f*, 175–177*f*

W

Water pickup, determination, 88
Waterborne coatings, chemistry, 9–10, 11*f*
Wire, definition, 307
Wired quinoprotein dehydrogenase
 electrode
 advantages, 34
 stability enhancement, 34–39

Production: Meg Marshall
Indexing: Deborah H. Steiner
Acquisition: Rhonda Bitterli
Cover design: Michele Telschow

Printed and bound by Maple Press, York, PA