AIP Journal of Applied Physics

Erratum: Radial conduction effects in the pulse method of measuring thermal diffusivity

A. B. Donaldson

Citation: Journal of Applied Physics **48**, 849 (1977); doi: 10.1063/1.324304
View online: http://dx.doi.org/10.1063/1.324304
View Table of Contents: http://scitation.aip.org/content/aip/journal/jap/48/2?ver=pdfcov
Published by the AIP Publishing

ERRATA

Erratum: Radial conduction effects in the pulse method of measuring thermal diffusivity [J. Appl. Phys. 43, 4226 (1972)]

A. B. Donaldson

Sandia Laboratories, Albuquerque, New Mexico 87115

PACS numbers: 99.10.+g, 66.70.+f

Table I contains incorrect values and should be replaced by the following:

TABLE I. Values of dimensionless half-time as a function of H_1 and H_2 for various σ.

H_1	H_2/H_1^a	$\tau_{1/2}(\sigma=\infty)$	$\tau_{1/2}(\sigma=10)$	$\tau_{1/2}(\sigma=5)$	$\tau_{1/2}(\sigma=1)$	$\tau_{1/2}(\sigma=0.5)$	$\tau_{1/2}(\sigma=0.1)$
0.000	Finite	0.13878	0.13878	0.13867	0.09880	0.08100	0.07311
0.050	0.000	0.13548	0.13548	0.13547	0.09829	0.08068	0.07284
0.050	0.500	0.13417	0.13417	0.13416	0.09804	0.08053	0.07272
0.050	1.000	0.13298	0.13298	0.13298	0.09779	0.08037	0.07259
0.100	0.000	0.13305	0.13305	0.13305	0.09780	0.08037	0.07259
0.100	0.500	0.13087	0.13087	0.13087	0.09731	0.08007	0.07234
0.100	1.000	0.12895	0.12895	0.12895	0.09684	0.07977	0.07209
0.500	0.000	0.12113	0.12113	0.12113	0.09446	0.07822	0.07080
0.500	0.500	0.11518	0.11518	0.11518	0.09240	0.07689	0.06970
0.500	1.000	0.11080	0.11080	0.11080	0.09065	0.07574	0.06873
1.000	0.000	0.11276	0.11276	0.11276	0.09127	0.07609	0.06901
1.000	0.500	0.10455	0.10455	0.10455	0.08781	0.07381	0.06710
1.000	1.000	0.09929	0.09929	0.09929	0.08518	0.07203	0.06558
5.000	0.000	0.09112	0.09112	0.09112	0.07988	0.06793	0.06189
5.000	0.500	0.07729	0.07729	0.07729	0.07140	0.06205	0.05689
5.000	1.000	0.07221	0.07221	0.07221	0.06767	0.05925	0.05442
10.000	0.000	0.08396	0.08396	0.08396	0.07513	0.06423	0.05455
10.000	0.500	0.06768	0.06768	0.06768	0.06409	0.05644	0.05177
10.000	1.000	0.06358	0.06358	0.06358	0.06078	0.05380	0.04908

[a] Values of $H_2 \leq H_1$ are taken since for similar surface and surroundings the heat loss is proportional to $\overline{T}^3$, and $T_2 \leq T_1$.

Erratum: On the generalized theory of normal mode excitation in electromagnetic and polarized medium waveguides by external sources [J. Appl. Phys. 46, 1707 (1975)]

A. A. Barybin

California Institute of Technology, Pasadena, California 91109

PACS numbers: 01.85.+s, 84.40.Sr, 72.30.+q, 72.50.+b

Formulas (78) and (79) must be written

$$\int_{S_1} F_{1\vec{n}}^{(b)}\, dS = \frac{\partial}{\partial z}\int_{S_1} (\mathbf{e}_z \cdot \mathbf{G}_{1\tilde{n}})\, dS + \oint_{L_s} (\mathbf{n}_s^+ \cdot \mathbf{G}_{1\vec{n}}^-)\, dl, \qquad (78)$$

$$\int_{S_2} F_{1\vec{n}}^{(b)}\, dS = \frac{\partial}{\partial z}\int_{S_2} (\mathbf{e}_z \cdot \mathbf{G}_{1\vec{n}})\, dS + \oint_{L_s} (\mathbf{n}_s^- \cdot \mathbf{G}_{1\tilde{n}}^+)\, dl. \qquad (79)$$

In the subsequent formulas (80), (91), (96), (97), (101), (104), (107), (121), and (125) signs before the contour integrals as $\int_{L_s}(\ldots)\, dl$ must be replaced by opposite ones.

