

THIRD-ORDER NONLINEAR OPTICAL COEFFICIENTS OF LiIO₃

Masakatsu Okada

Citation: [Applied Physics Letters](#) **18**, 451 (1971); doi: 10.1063/1.1653490

View online: <http://dx.doi.org/10.1063/1.1653490>

View Table of Contents: <http://scitation.aip.org/content/aip/journal/apl/18/10?ver=pdfcov>

Published by the [AIP Publishing](#)

Articles you may be interested in

[Third-order nonlinear optical properties of As₂S₃ chalcogenide glass](#)

J. Appl. Phys. **74**, 3683 (1993); 10.1063/1.354511

[DETERMINATION OF THE SECOND-HARMONIC-GENERATION COEFFICIENT AND THE LINEAR ELECTRO-OPTIC COEFFICIENT IN LiIO₃ THROUGH OBLIQUE RAMAN PHONON MEASUREMENTS](#)

Appl. Phys. Lett. **18**, 499 (1971); 10.1063/1.1653512

[Optical Properties of LiIO₃ in the Far Infrared](#)

J. Appl. Phys. **41**, 3928 (1970); 10.1063/1.1658390

[Optical Nonlinearities in LiIO₃](#)

J. Appl. Phys. **40**, 5201 (1969); 10.1063/1.1657376

[LARGE NONLINEAR OPTICAL COEFFICIENT AND PHASE MATCHED SECOND HARMONIC GENERATION IN LiIO₃](#)

Appl. Phys. Lett. **14**, 154 (1969); 10.1063/1.1652754

A promotional banner for Applied Physics Reviews. On the left is a thumbnail image of the journal cover, which shows a diagram of a layered structure. The main part of the banner has a blue background with a bright light source on the right. The text 'NEW Special Topic Sections' is written in large white letters. Below this, 'NOW ONLINE' is written in yellow, followed by 'Lithium Niobate Properties and Applications: Reviews of Emerging Trends' in white. The AIP Applied Physics Reviews logo is in the bottom right corner.

NEW Special Topic Sections

NOW ONLINE
Lithium Niobate Properties and Applications:
Reviews of Emerging Trends

AIP Applied Physics Reviews

THIRD-ORDER NONLINEAR OPTICAL COEFFICIENTS OF LiIO_3

Masakatsu Okada

Broadcasting Science Research Laboratories of NHK (Japan Broadcasting Corporation)

1-10-11, Kinuta, Setagaya, Tokyo, 157, Japan

(Received 9 February 1971)

The third-order nonlinear optical coefficients of LiIO_3 have been measured by third harmonic generation. It has been found that the third-order nonlinear optical coefficient c_{35} is large. The coefficient c_{12} has a finite value, which shows that Kleinman's symmetry relations are not strictly valid in LiIO_3 .

Since LiIO_3 was found to show a large optical nonlinearity,^{1,2} it is used for the phased-matched second harmonic generation, optical mixing, and parametric oscillation. Moreover, LiIO_3 has been pointed out¹ to be appropriate for a check on the Kleinman's symmetry relations³ on nonlinear optical coefficients. We have shown⁴ that the Kleinman's relations are not perfectly valid in the second-order nonlinear optical coefficients of LiIO_3 . In this letter we report that the third-order nonlinear optical coefficients have large values and do not satisfy the Kleinman's relations.

Third-order nonlinear optical coefficients c_{ij} have been measured through the third harmonic generation using a repetitively *Q*-switched Nd:YAG laser, which radiates an output with a peak power of 2 MW and a pulse width of 22 nsec at 1.064μ .

LiIO_3 belongs to the point group 6. Nonlinear coefficients are given as

$$\begin{array}{cccccccccc} c_{11} & c_{12} & 0 & c_{14} & 0 & c_{16} & 0 & c_{11}/3 & c_{12}/3 & 0 \\ -c_{12} & c_{11} & 0 & c_{16} & 0 & -c_{14} & 0 & -c_{13}/3 & c_{11}/3 & 0 \\ 0 & 0 & c_{33} & 0 & c_{35} & 0 & c_{35} & 0 & 0 & 0 \end{array}$$

If the Kleinman's relations are applied, coefficients c_{12} and c_{14} vanish and c_{35} is equal to c_{16} .⁵

Third-order nonlinear phase-matchable processes are classified into three types,⁵ that is, (I) $o+o+o \rightarrow e$, (II) $o+o+e \rightarrow e$, and (III) $o+e+e \rightarrow e$ (o and e refer to the ordinary and extraordinary waves, respectively). In LiIO_3 the third-order nonlinear polarizations for each type of process are written as

$$\begin{aligned} P(3\omega; o+o+o \rightarrow e) &= c_{12} \cos \theta [E^o(\omega)]^3 \\ P(3\omega; o+o+e \rightarrow e) &= (c_{11} \cos^2 \theta / 3 + c_{35} \sin^2 \theta) \\ &\quad \times [E^o(\omega)]^2 E^e(\omega), \\ P(3\omega; o+e+e \rightarrow e) &= (c_{12} \cos^3 \theta / 3 + c_{14} \cos \theta \sin^2 \theta) \\ &\quad \times E^o(\omega) [E^e(\omega)]^2, \end{aligned}$$

where θ is the phase-matching angle, and $E^o(\omega)$ and $E^e(\omega)$ are amplitudes of ordinary and extraordinary components of fundamental wave, respectively. However, if the Kleinman's relations are applied, the type I and III processes are forbidden, while the polarization in the type II process is unchanged.

Phase-matching angles for each process have been calculated by using refractive indices $n_1^o = 1.860$, $n_1^e = 1.719$, $n_3^o = 1.982$, and $n_3^e = 1.815$. In the type

I process the phase-matching angle is $57^\circ 02'$ and in the type III process it does not exist. The phase-matching angle for the type II process is near 90° , but only several symmetrical sideband structures have been observed around 90° , as shown in Fig. 1, in the experiment of angular variation since the perfect phase-matching angle is not within 90° .

Two pieces of crystal have been prepared for the type I and II processes to satisfy the condition of nearly normal incidence in the phase-matched state. Cross sections of crystals are large compared with the beam diameter of 2 mm, and lengths are 4.56 and 290 mm for the type I and II processes, respectively. The optical transmission of a crystal with a thickness of 4.56 mm has been measured from 0.28 to 1.5μ for the two polarizations, $E \parallel c$ and $E \perp c$, and shown to be sufficiently transparent at 0.355μ as shown in Fig. 2.

For the type I process, which is forbidden by the Kleinman's relations, a sharp central peak with a width of about $10'$ has been observed in the experiment of dependence of the third harmonic power on the angular variation around the phase-matching angle, which has been measured to be $57^\circ 46'$. Moreover, in order to ascertain the process to be the third order, the dependence of third harmonic intensity on the polarization of fundamental wave has been measured by rotating the direction of polarization of fundamental wave. The third harmonic power is expected to be proportional to $\cos^6 \phi$ in the type I process, where ϕ is the rotating angle of the direction of polarization of the incoming fundamental wave from that of the ordinary wave. The experimental result has been consistent with the prediction.

Experiments have been performed for the type II




FIG. 1. Dependence of third harmonic intensity on the angular variation of crystal near the phase-matching angle in the type II process.




FIG. 2. Optical transmission characteristics of LiIO_3 from 0.28 to 1.5 μ .

process in the same way as for the type I process. The dependence of third harmonic power on the polarization of fundamental wave, which is proportional to $\cos^4\phi \sin^2\phi$, had a good agreement with the experimental results. In the angular dependence of the third harmonic power, several sidebands have been observed around 90° . From the ratios of peak values of successive sidebands, the first measured sideband in Fig. 1 is estimated to correspond to the 5th or 6th one in the regular phase-matching characteristics.

Nonlinear coefficients of LiIO_3 have been calculated by comparing with those of KDP and ADP.⁶ The third harmonic generation in KDP and ADP have been done through the type I process. KDP and ADP crystals with length of 11 mm and cross section of 4×5 mm have been prepared so that the condition of normal incidence might be satisfied when the azimuthal angle was chosen as 22.5° in the phase-matched state. An expression for the dependence of the third harmonic power S_3 on the crystal length l and the effective nonlinear optical coefficients⁷ c_{eff} has been derived by modifying the procedure for

the second harmonic generation.⁷ In the case of small diffraction and double refraction, S_3 is given as

$$S_3 = 96S_1^3 \left(\frac{128\pi^2\omega^2 c_{\text{eff}}^2}{c^4 n_1^3 n_3} \right) \frac{l^2}{w_0^4},$$

where S_1 is the laser intensity, w_0 the radius of the beam waist, and $c_{\text{eff}} = (c_{11} - 3c_{18}) \cos\theta \sin(4 \times 22.5^\circ)/4$ for KDP and ADP, $c_{\text{eff}} = c_{12} \cos\theta$, and $c_{\text{eff}} = (c_{11} \cos^2\theta + c_{35} \sin^2\theta)$ for the type I and II processes of LiIO_3 , respectively. By using data for refractive indices and phase-matching angles, the third-order nonlinear coefficients are estimated as follows:

$$(c_{11} - 3c_{18})^{\text{KDP}} = 2.1(c_{11} - 3c_{18})^{\text{ADP}},$$

$$c_{12}^{\text{LiIO}_3} = 12(c_{11} - 3c_{18})^{\text{ADP}},$$

$$c_{35}^{\text{LiIO}_3} = 300 \sim 400(c_{11} - 3c_{18})^{\text{ADP}}.$$

It is concluded that LiIO_3 shows a large third-order nonlinear optical coefficient c_{35} , and may be useful in the third-order nonlinear optical processes. Moreover, it is noted that c_{12} is a few percent of c_{35} , and thus the Kleinman's symmetry relations are not strictly valid in LiIO_3 .

The author thanks Dr. S. Ieiri for helpful discussions and T. Umezawa for supplying LiIO_3 crystals.

¹G. Nath and S. Haussühl, Appl. Phys. Letters 14, 154 (1969).

²F. R. Nash, J. G. Bergman, G. D. Boyd, and E. H. Turner, J. Appl. Phys. 40, 520 (1969).

³D. A. Kleinman, Phys. Rev. 126, 1977 (1962).

⁴M. Okada and S. Ieiri, Phys. Letters (to be published).

⁵J. E. Midwinter and J. Warner, Brit. J. Appl. Phys. 16, 1667 (1965).

⁶C. C. Wang and E. L. Baardsen, Appl. Phys. Letters 15, 396 (1969).

⁷G. D. Boyd and D. A. Kleinman, J. Appl. Phys. 39, 3597 (1968).

VISUAL OBSERVATION OF SUBMILLIMETER WAVE LASER BEAMS

F. Keilmann

Max-Planck-Institut fuer Plasmaphysik, 8046 Garching, Germany

and

K. F. Renk

Physik Department der Technischen Universität, Muenchen, Germany

(Received 15 March 1971)

The operation of a thermal image converter for infrared and submillimeter wave laser radiation is reported. An energy density of 0.004 J/cm^2 is sufficient for full contrast, independent of wavelength. Photographs taken with HCN laser radiation are shown.

For the detection of submillimeter laser radiation, only pointlike detectors have been used, e.g., a Golay cell integrating over a small area of, say, 0.1 cm^2 . It is, however, desirable to develop a simple means of visualizing two-dimensional intensity patterns for many applications, where a scanning type of image synthesis¹ seems inadequate or too complicated.

Our approach is based on a thermal effect, as first demonstrated for detecting near-ir radiation by Hansen *et al.*²: Through absorption in a thin film, a temperature image is formed which can be reversibly read out by using the optical properties of a layer of cholesteric liquid crystals. This material shows a sharply peaked back-scattering spectrum if illuminated with white light; the wavelength