See discussions, stats, and author profiles for this publication at: https://www.researchgate.net/publication/248746299

Combustion Synthesis of Nanometric Powders of LaPO 4 and Sr-Substituted LaPO 4

ARTICLE in CHEMISTRY OF MATERIALS · AUGUST 2005	
Impact Factor: 8.35 · DOI: 10.1021/cm047945q	
CITATIONS	READS
55	63

3 AUTHORS, INCLUDING:



M.T. Colomer

Spanish National Research Council

92 PUBLICATIONS **1,155** CITATIONS

SEE PROFILE

1

2

5

6

7

8

9 10

13

14

15 16

17

18

19

20

21

22

23

24

25

26

27

28

29

30

31

32

33

USER: vkb69

Combustion Synthesis of Nanometric Powders of LaPO₄ and Sr-Substituted LaPO₄

S. Gallini, J. R. Jurado, and M. T. Colomer*

Instituto de Cerámica y Vidrio, CSIC, C/Kelsen nº 5, Campus de la Universidad Autónoma, 28049 Madrid, Spain

Received November 24, 2004. Revised Manuscript Received March 22, 2005

 $La_{(1-\gamma)}Sr_{(\gamma)}PO_4$ materials are very stable at high temperature and water vapor partial pressure and they show protonic conductivity; thus, they could be used as electrolytes in HTPFCs (high-temperature protonic fuel cells), hydrogen sensors, and hydrogen separation technology. This work describes the combustion synthesis of $La_{(1-x)}Sr_{(x)}PO_4$ powders (x = 0, 0.025, 0.05) from mixtures of $La(NO_3)_3$ ·6H₂O and $Sr(NO_3)_2$ as cation precursors, (NH₄)₂HPO₄ as anion precursor, and urea as fuel. The characterization of the asprepared combustion products showed that the combustion synthesis provides a straightforward method for the achievement of solid solutions of these materials as nanometric powders. Furthermore, dilatometric studies reveal that dense ceramics can be obtained at low sintering temperature (1300 °C), in air, from the synthesized nanometric powders.

Introduction

Rare-earth phosphates present a high luminescence quantum efficiency and unusual magnetic behavior and, therefore, they find applications in special glasses, laser technology, ^{1,2} compact fluorescent lamps, and plasma display panels.3 Phosphates glasses and ceramics are also used in biological implants and glass metal joining. LaPO₄ has also been found to be a good oxide interphase material, with a good chemical compatibility with alumina at high temperatures (up to at least 1700 °C).⁵⁻⁷ Moreover, (La-) monazite crystals, naturally occurring minerals, are known to have survived 109 years of weathering; for this reason they are considered as host material for long-term storage of radioactive wastes.⁸

In recent years, the interest in LaPO₄ has also focused on its possible application as a high-temperature protonic conductor (HTPC)9-14 when a small percentage of La is substituted by Sr or Ca. HTPCs are materials in which the

conductivity is mainly protonic at temperatures higher than 600 °C. Proton conductivity is the main mechanism in many and diverse processes such as photosynthesis in plants and the production of electricity in electrochemical devices. The interest of the scientific community in Sr:LaPO₄ as a proton conductor derives from its high stability at high temperature and high water vapor partial pressure, as mentioned above, a requisite condition for materials applied to high-temperature electrochemical devices.

41

42

48

The authors have demonstrated in a previous article¹⁴ that Sr:LaPO₄ prepared by combustion synthesis and sintered at 1300 °C is predominantly a protonic conductor below 700 °C in wet oxygen. In addition, the grain boundary resistance is negligible at 400 °C and higher temperatures and, thus, could be a good candidate as an electrolyte in HTPFCs.

In relation to the preparation of LaPO₄, Chen and Mah¹⁵ prepared this material through four different chemical routes. These authors concluded that the two best routes were the direct reaction between La₂O₃ and H₃PO₄ because of the absence of byproducts, and the reaction between the same phosphoric acid with lanthanum hydroxide, although no attempts of doping were made in these cases. According to Lucas et al., 16 the wet synthesis of rare-earth phosphates by the precipitation method from a rare-earth chloride solution and H₃PO₄ or (NH₄)₂HPO₄ always leads to the formation of precipitates crystallized in the hexagonal structure of rhabdophane $RePO_4 \cdot nH_2O$ (Re = La, Ce, or Y). Furthermore, H₃PO₄ adsorbed at the surface of the particles is always present in the precipitates. From these results a unit chemical formula can be proposed as RePO₄·nH₂O· $(H_3PO_4)x$ with $n \approx 0.5$ for La. The removal of H_3PO_4 is only possible using a high-temperature calcination treatment at 1400 °C in order to achieve its decomposition. Gallini et al. 17 synthesized $La_{(1-x)}Sr_xPO_4$ powders through coprecipi-

^{*} To whom correspondence should be addressed. E-mail: tcolomer@icv.csic.es.

⁽¹⁾ Danielmeyer, H. G.; Weber, H. P. J. Quantum Electron. 1972, 8, 805.

⁽²⁾ Albrand, K. R.; Attig, R.; Fenner, J.; Jesser, J. P.; Moot, D. Mater. Res. Bull. 1974, 9, 129.

⁽³⁾ Rao, R. P.; Devine, D. J. J. Luminescence 2000, 87-89, 1260.

⁽⁴⁾ Ohgaki, M.; Kizuki, T.; Katsura, M.; Yamashita, K. J. Biomed. Mater. Res. 2001, 57, 366.

⁽⁵⁾ Morgan, P. E. D.; Marshall, D. B. Mater. Sci. Eng. A 1993, 162, 15.

⁽⁶⁾ Morgan, P. E. D.; Marshall, D. B. J. Am. Ceram. Soc. 1995, 78, 1553.

⁽⁷⁾ Morgan, P. E. D.; Marshall, D. B.; Housley, R. M. Mater. Sci. Eng. A 1995, 195, 215.

⁽⁸⁾ Boatner, L. A.; Beall, G. W.; Abraham, M. M.; Finch, C. B.; Floran, R. J.; Huray, P. G.; Rappaz, M. The management of Alphacontaminated wastes; International Atomic Energy Agency, IAEA-SM-264/73: Vienne, Austria, 1980.

⁽⁹⁾ Norby, T.; Christiansen, N. Solid State Ionics 1995, 77, 240. Amezawa, K.; Kjelstrup, S.; Norby, T.; Ito, Y. J. Electrochem. Soc. 1998, 145,

⁽¹⁰⁾ Abe, Y.; Hosono, H.; Akita, O.; Hench, L. L. J. Electrochem. Soc. **1994**, 141, 6.

⁽¹¹⁾ Mellander, B.-E.; Zhu, B.; Solid State Ionics 1993, 61, 105.

⁽¹²⁾ Tyholdt, F.; Horst, J. A.; Jørgensen, S.; Østvold, T.; Norby, T. Surf. Interface Anal. 2000, 30, 95.

⁽¹³⁾ Iwahara, H. Solid State Ionics 1995, 77, 289.

⁽¹⁴⁾ Gallini, S.; Hansel, M.; Norby, T.; Colomer, M. T.; Jurado, J. R. Solid State Ionics 2003, 162-163, 167.

⁽¹⁵⁾ Chen, P.; Mah, T. J. Mater. Sci. 1997, 32, 3863.

⁽¹⁶⁾ Lucas, S.; Champion, E.; Bregiroux, D.; Bernache-Assollant, D.; Audubert, F. J. Solid State Chem. 2004, 177, 1302.

B Chem. Mater. Gallini et al.

tation using La(NO₃)₃•6H₂O, Sr(NO₃)₂, and (NH₄)₂HPO₄ as precursors. Monazite phase (monoclinic LaPO₄) is directly achieved after drying at 105 °C; however, by TEM analysis the rhabdophane phase (needle-shape crystals) is detected, which can be due to a possible hydration of the monazite phase. By that synthesis method, NH₄NO₃ and HNO₃ acid are obtained as byproduct being totally eliminated after calcination at 800 °C. An experiment performed by Arul Dhas et al. 18 describes the preparation of crystalline lanthanum phosphate powder by flash combustion. This is a complex synthesis method that even requires the preparation of the fuel. The preparation method that is described in the present work shows several advantages if compared to the preparation described by those authors:18 it is more simple (one step); there is no need to synthesize the fuel and no explosion takes place. Fujishiro et al. 19 prepared LaPO₄ particles using the hydrothermal reaction of a La(edta)chelate precursor and phosphate ions. Although monodispersed spherical and spindle-like monazite-type LaPO₄ particles are formed by the hydrothermal reaction at 150 °C, a low relative density (91.6%) after sintering at 1400 °C is attained. Ruigang et al.20 prepared a mixture of both rhabdophane and monazite-type LaPO₄ powders using a direct liquid-solid reaction of lanthanum oxide and phosphoric acid. Pure monazite-type LaPO₄ was obtained by calcining the precursor powders at a temperature higher than 600 °C. The sintering temperature in that work is 1600 °C, much higher than the one required to sinter the $La_{(1-x)}Sr_{(x)}PO_4$ powders in the present work.

68

69 70

71 72

73

74

75

76

77

78

79

80

81

82

83

84

85

86

87

88

89

90

91

92

93

94

95

96

97

98

99

100

101

102

103

104

105

106

107

108

109

110

111

112

113

As is well-known in ceramic materials science, the synthesis route plays a key role in the final properties of the ceramics. For this reason, it is necessary to test new preparation methods and to analyze the effect on the powder characteristics, microstructure of the materials, and, therefore, on the physical, chemical, and electrochemical behavior.

In recent years, combustion synthesis as a preparative process to produce homogeneous very fine crystalline, unagglomerated, multicomponent oxide ceramic powders without the intermediate decomposition and/or calcining steps has attracted a good deal of attention. The combustion synthesis technique consists of bringing a saturated aqueous solution composed of the desired metal salts and of a suitable organic fuel to the boiling temperature, until the mixture ignites and a self-sustaining and rather fast combustion reaction takes off, resulting in a dry, usually crystalline fine powder. While redox reactions are exothermic in nature and

119

120

121

123

124

125

126

127

128

129

130

134

135

136

137

139

140

141

142

143

146

147

148

149

152

153

154

158

159

160

161

162

165

166

167

168

often lead to explosion if not controlled, the combustion of

metal nitrates-urea mixtures usually occurs as a self-

In this work we aim to define a protocol in order to obtain pure and nanometric powders of $La_{1-x}Sr_{1-x}PO_4$ (where x = 0, 0.025, 0.05) by means of the combustion synthesis using urea as fuel. To sinter $La_{1-x}Sr_xPO_4$ and to use it as a protonic conductor is very important to obtain dense, gastight, and pure materials since impurities could diminish their ionic mobility.

Experiments

The combustion synthesis was performed using the following powder precursors (analytical grade): La(NO₃)₃•6 H₂O, Sr(NO₃)₂ and (NH₄)₂HPO₄ purchased from Panreac Química S.A, Barcelona, Spain. As mentioned above, urea was used as a fuel (analytical grade purchased from Aldrich, Germany). The precursors and the fuel were previously mixed in a wide-mouth vitreous silica basin employing a glass bar until a viscous liquid uniform mixture was formed. The basin was then placed on a hot plate and heated to 100 °C for 10 min before the final treatment at 300 °C for 1 h. The reaction takes place in a few minutes, leaving a white foam in the basin. The powder obtained by crushing the foam is white and fine and was easily sieved through a 100 μ m sieve. The powders were calcined in air at three different temperatures 200, 400, and 800 °C for 12 h, applying a heating rate of 5 °C/min. The final treatments were calcination at 800 °C/12 h in air in order to increase the powder crystallinity and attrition-milling in ethanol for 3 h using 1 mm diameter zirconia balls (purchased from Tosoh, Japan). A final sieve through 100 μ m before compaction was performed. The nitrogen content of the powders at each calcination temperature was determined with a LECO TC-436 nitrogen analyzer, employing the gas fusion method.²⁷ Chemical analysis of the carbon content of the powders at each calcination temperature was performed using a LECO analyzer, CS-200 model. Differential thermal and thermogravimetric analysis (DTA/TG) in air of the as-prepared powder was carried out on a NETZSCH STA-409 Thermoanalyzer, utilizing alumina as the reference material, in the temperature range of 20-1350 °C with a heating rate of 3 °C/min. Phase identification was performed by X-ray diffraction on a Siemens powder diffractometer D-5000, operating at 50 kV and 30 mA, using Cu Kα radiation and a Ni-filter in the range of $2\theta = 10-80^{\circ}$. The scanning step was 0.05°, the time/step 1.5 s, and the rotation speed 30 rpm. X-ray patterns were collected on the as-prepared powders and at the three calcination temperatures mentioned above. A longer term and wider range scan was employed to obtain the cell parameters: $2\theta = 10$ - 110° , time/step = 20 s, using Si as an internal standard. These data allowed us to calculate the cell parameters (software 'Unitcell'). Crystallite sizes were calculated by X-ray line-broadening analysis using the Scherrer equation.²⁸ The average agglomerate size was measured by means of a particle-size laser analyzer provided by Malvern Instruments, model Mastersizer. BET specific surface area of the powders was determined using a Monosorb Analyzer MS-13 QuantaChrome. Infrared absorption spectra in the 400-4000 cm⁻¹ frequency range were obtained employing a Perkin-Elmer FT-IR spectrometer 1760X on cold-pressed pellets composed of 0.01 g of the prepared powders and 0.3 g of KBr. Particle morphology was observed by scanning electron microscopy and

propagating and nonexplosive exothermic reaction. The large amounts of gases formed can result in the appearance of a flame, which can reach temperatures on excess of 1000 °C. In this work we aim to define a protocol in order to obtain pure and nanometric powders of $La_{1-x}Sr_{1-x}PO_4$ (where $x = 0.0027 \cdot 0.007$) and $C_{1-x}C_{1-x$

⁽¹⁷⁾ Gallini, S.; Jurado, J. R.; Colomer, M. T. Accepted for publication in J. Eur. Ceram. Soc.

⁽¹⁸⁾ Arul Dhas, N.; Patil, K. C. J. Alloys Compd. 1993, 202, 137.

⁽¹⁹⁾ Fujishiro, Y.; Ito, H.; Sato, T.; Okuwaki, A. J. Alloys Compd. 1997, 252, 103.

⁽²⁰⁾ Ruigang, W.; Wei, P.; Jian, C.; Minghao, F.; Zhenzh, C.; Yongming, L. Mater. Chem. Phys. 2003, 79, 30.

⁽²¹⁾ Manoharan, S. S.; Patil, K. P. J. Am. Ceram. Soc. 1992, 75, 1012.

⁽²²⁾ Ravindranathan, P.; Komarnemi, S.; Roy, R. J. Mater. Sci. 1993, 12, 369.

⁽²³⁾ Zhang, Y.; Strangle, G. C. J. Mater. Res. 1994, 9, 1997.

⁽²⁴⁾ Muthuraman, M.; Arul Das, N.; Patil, K. C. *J. Math. Synth. Process* **1996**, 4–2, 115.

⁽²⁵⁾ Fumo, D. A.; Morelli, M. R.; Segadães, A. M. Mater. Res. Bull. 1996, 31, 1243.

⁽²⁶⁾ Colomer, M. T.; Fumo, D. A.; Jurado, J. R.; Segadães, A. M. J. Mater. Chem. 1999, 9, 2505.

⁽²⁷⁾ Thomas, A.; Muller, G. J. Eur. Ceram. Soc. 1991, 8, 163.

⁽²⁸⁾ Klug, K. D.; Alexander, L. E. X-ray diffraction procedures; Wiley: New York, 1974; pp 618–708.

173

174

175 176

177

178

179 180

181

182

183

184

185

186

187

188

189

190

191

192

193

194

195

196

197

198

199

200

201

202

203

204

205

206

207

208

209

210

211

212

213

214

215

216

217

218

219

220

221

222

223

224

225

Combustion Synthesis of LaPO₄ and Sr-Substituted LaPO₄

Chem. Mater. C

226

228

230

232

233

234

235

236

237

239

241

243

245

246

247

248

250

252

254

256

257

258

260

261

262

263

265

chemically analyzed by energy dispersive X-ray spectroscopy (SEM-EDS) on both Zeiss DSM 950 and Hitachi S-4700 microscopes. Crystallite size and morphology of the as-prepared powders were also estimated by transmission electron microscopy and chemically analyzed by energy dispersive X-ray spectroscopy (TEM-EDS), using a JEM-2000FX microscope. The shrinkage behavior study was performed using a high-temperature dilatometer (Adamel Lhomargy, DI-24 model) at a heating rate of 2 °C/min up to 1500 °C, on uniaxially and isostatically pressed (200 MPa) disks of 2-3 mm thick and 6 mm in diameter of previously calcined powder at 800 °C/12 h.

Results and Discussion

Combustion Reactions. To prepare $La_{(1-x)}Sr_{(x)}PO_4$, where x = 0, 0.025, and 0.050, by the combustion route, using urea as fuel, crystalline La(NO₃)₃·6H₂O can be used as a La source (total valencies -15), $Sr(NO_3)_2$ as a Sr source (total valencies -10), and (NH₄)₂HPO₄ as a PO₄³⁻ source (total valencies +4). Urea, CO(NH₂)₂ (total valencies +6), was used as fuel, as mentioned above. For most purposes urea is the most convenient fuel to be used: it is readily available commercially, it is inexpensive, and it generates the highest temperature, although fuel-rich mixtures might produce prematurely sintered particle agglomerates. It is important to avoid a presintering effect during the combustion reaction which may produce large and hard agglomerates difficult to deagglomerate, disabling the densification of the prepared powders. For this reason, an adequate quantity of urea must be employed in the reaction mixture.

Direct use of the propellant chemistry criterion, with the metal precursor and the PO₄3- anion in a 1:1 molar ratio (LaPO₄ case), to determine the urea needed to balance the total oxidizing and reducing valencies in the mixture of oxidizers and fuels, leads to

$$(-15) + 4 + 6n = 0$$

where -15 is the total valence of La(NO₃)₃•6H₂O, +4 is the total valence of $(NH_4)_2HPO_4$, and + 6 corresponds to the total valency of CO(NH₂)₂, as mentioned above. The equation gives n = 1.83, which means that 1.83 moles of urea are required for each mole of La(NO₃)₃•6H₂O or $(NH_4)_2HPO_4$.

Standard thermodynamic properties of the compounds which might be involved in the combustion process are reported in Table 1.^{29,30} The combustion reactions are described in Table 2 together with the ΔH° found in the literature. ^{29,30} Furthermore, the combustion reaction of urea, described by eq R1 in Table 2, is exothermic and should provide the energy (heat) needed for the synthesis reaction. Besides, if one takes into account that the reaction takes place in an acid environment (pH \approx 2), the protonation of urea, described as (R2) in Table 2, is very likely to occur. The individual decomposition reactions of the precursor nitrates, leading to the corresponding oxides ((R6) and (R7), respectively), are also listed in Table 2 and the decomposition of $(NH_4)_2HPO_4$ to H_3PO_4 is described by eq (R8). The rest of

Table 1. Standard Thermodynamic Properties of the Compounds Which Might Be Involved in the Combustion Process

compound	$\Delta H_{\rm f}^{\circ}$ [kJ mol ⁻¹]	C_p° [J mol ⁻¹ K ⁻¹]
LaPO ₄	-1949	100.950
$(NH_4)_2HPO_4$	-1566.9	188.0
$Sr(NO_3)_2$	-978.2	149.9
$La(NO_3)_3 \cdot 6H_2O$	-3060.7	-
$CO(NH_2)_2$	-318.8	89.04
H_3PO_4	-1284.4	106.1
SrO	-592.04	45.4
La_2O_3	-1793.7	108.68
NH_4NO_3	-365.65	139.12
NH_3	-45.898	35.652
CO_2	-393.133	$43.22 + 0.01145T^a$
H_2O	-241.587	$30.10 + 0.01505T^a$
N_2	0	$27.17 + 0.00418T^a$
O_2	0	$24.74 + 0.01505T^{a,b}$

^a T is the absolute temperature. ^b Calculated from discrete values.

the equations in Table 2 represent other reactions which also might take place during the combustion synthesis. For instance, (R9), (R10), and (R11) equations describe the possible reaction of each precursor with urea.

By X-ray diffraction a single phase was identified as LaPO₄ for the as-prepared powder with x = 0 (Figure 2). This result suggests that the overall reaction can be described as (R19) equation (Table 2), where Sr(NO₃)₂ is included as a precursor.

The fact that the combustion process is not complete, in the sense that no flame is produced, can be due to the low enthalpy of the reaction, i.e., the energy released is not enough to produce a complete combustion. The possible protonation of urea, described as (R2) in Table 2, could be another reason to explain the lack of a flame since the available unprotonated urea in the combustion reaction media might be less than the required amount. Furthermore, as is well-known, urea suffers a thermal decomposition which involves the formation of different compounds (see reactions (R3), (R4), and (R5) in Table 2).31 This thermal decomposition provokes a depletion of fuel in the reagent mixture. As a consequence, the direct reaction between urea and the rest of the reagents is forced to happen according to a modified stoichiometry. 31,32 In the experiments described in this work, a stoichiometric amount of urea and an excess of 25 mole % were used in order to clarify the reason an incomplete combustion process takes place.

A further depletion of urea could take place if part of each precursor of the initial mixture reacts with urea; a lesser amount of the fuel will be free for the total reaction. However, it has to be outlined that the addition of an excess of 25 mole % urea to the stoichiometric amount does not change the result of the reaction in any sense. This could indicate that the low enthalpy of the reaction is the main reason to explain the absence of a flame and that the urea depletion has no significant effect in this system.

Powder Characterization. Nitrogen analysis was performed on the combustion product and on the powders calcined at 400 and 800 °C for 12 h. The nitrogen content was 3.1 wt % in the as-prepared powders, 1.0 wt % in the powders calcined at 400 °C, and no nitrogen was detected in the powders calcined at 800 °C. These data could indicate

⁽²⁹⁾ CRC Handbook of Chemistry and Physics, 84th ed.; Lide, D. R., Ed.; CRC Press: Boca Raton, FL, 2003-2004.

⁽³⁰⁾ Thiriet, C.; Konings, R. J. M.; Javorský, P.; Magnani, N.; Wastin, F. J. Chem. Thermodyn. 2005, 37, 131.

⁽³¹⁾ Biamino, S.; Badini, C. J. Eur. Ceram. Soc. 2004, 24, 3021.

⁽³²⁾ Podsiadlo, S. Thermochim. Acta 1995, 256 (2), 375.

D Chem. Mater. Gallini et al.

Table 2. Equations Describing the Reactions That Might Be Involved in the Combustion Process

reaction		ΔH° (25 °C) [kJ mol ⁻¹]
R1	$CO(NH_2)_{2 (c)} + 1.5O_{2 (g)} \Rightarrow CO_{2 (g)} + 2H_2O_{(g)} + N_{2 (g)}$	-557.5
R2	$CO(NH_2)_2$ (c) $+ H_3O^+$ (c) $\rightarrow CO(NH_2)(NH_3)^+$ (c) $+ H_2O$ (g)	
R3	$CO(NH_2)_{2,(c)} \rightarrow NH_{3,(e)} + HCNO$	
R4	$CO(NH_2)_2$ (c) $+ HCNO \rightarrow H_2NCONHCONH_2$	
R5	$\text{HCNO} + \overset{\frown}{\text{H}_2}\text{O}_{(g)} \Rightarrow \text{CO}_{2(g)} + \text{NH}_{3(g)}$	
R6	$La(NO_3)_3 \cdot 6H_2O_{(c)} \rightarrow 0.5La_2O_{3(c)} + 6H_2O_{(g)} + 1.5N_{2(g)} + 3.75O_{2(g)}$	715.2
R7	$Sr(NO_3)_{2(c)} \rightarrow SrO_{(c)} + N_{2(g)} + 2.5O_{2(g)}$	386.2
R8	$(NH_4)_2HPO_4$ (c) $+ 3/4O_2$ (g) $\Rightarrow H_3PO_4$ (c) $+ 1/2N_2$ (g) $+ 3/2H_2O$ (g) $+ NH_3$ (g)	125.8
R9	$2[La(NO_3)_3 \cdot 6H_2O]_{(c)} + CO(NH_2)_2 \cdot (c) \rightarrow 5La_2O_3 \cdot (c) + CO_2 \cdot (g) + 14H_2O \cdot (g) + 4N_2 \cdot (g) + 6O_2(g)$	
R10	$Sr(NO_3)_2$ (c) + $CO(NH_2)_2$ (c) \Rightarrow SrO (c) + CO_2 (g) + $2H_2O$ (g) + $2N_2$ (g) + O_2 (g)	
R11	$(NH_4)_2HPO_4$ (c) $+CO(NH_2)_2$ (c) $+O_2$ (g) $\rightarrow H_3PO_4$ (c) $+CO_2$ (g) $+5H_2O$ (g) $+2N_2$ (g)	
R12	$2\text{La}_2\text{O}_3\ (c) + 3\text{H}_3\text{PO}_4\ (c) \Rightarrow 3\text{La}_2\text{PO}_4\ (c) + La(OH)_3\ (c) + 3\text{H}_2\text{O}\ (g)$	
R13	$2NH_4^+ + 2NO_3^- \rightarrow 2NH_4NO_3$ (c)	
R14	$(1-s)La_2O_{3(c)} + 2H_3PO_{4(c)} + (2s)SrO_{(c)} + (2s)O_2 \Rightarrow 2La_{(1-s)}PO_4$: $Sr_{s(c)} + La_{(1-s)}PO_4$: $Sr_{s'}xH_2O_{(c)} + 3H_2O_{(g)}$	
R15	$SrO_{(c)} + CO_{2(g)} \Rightarrow SrCO_{3(c)}$	
R16	$(1-s)La(NO_3)_3 \cdot 6H_2O_{(c)} + (s)SrO_{(c)} + H_3PO_{4(c)} \Rightarrow 2La_{(1-s)}PO_4: Sr_{s(c)} + La_{(1-s)}PO_4: Sr_{s'}xH_2O_{(c)} + \frac{3}{2}(5-4s)H_2O_{(g)} + \frac{3}{2}(1-s)N_2_{(g)} + (15-16s)/4O_{2(g)}$	
R17	$(1-s)\text{La}_2\text{O}_{3 \text{ (c)}} + (2s)\text{Sr}(\text{NO}_{3)2 \text{ (c)}} + 2\text{H}_3\text{PO}_{4 \text{ (c)}} \Rightarrow 2\text{La}_{(1-s)}\text{PO}_4: \text{ Sr}_{s \text{ (c)}} + \text{La}_{(1-s)}\text{PO}_4: \text{ Sr}_{s \text{ (c)}} \cdot x\text{H}_2\text{O} + (2s)\text{N}_{2 \text{ (g)}} + 3\text{H}_2\text{O}_{(g)} + \frac{3}{2}(1+s)\text{O}_{2 \text{ (g)}}$	
R18	$(1-s)\text{La}(\text{NO}_3)_3 \cdot \text{GH}_2\text{O (c)} + (s)\text{SrO (c)} + \text{H}_3\text{PO}_4 \cdot \text{(c)} \Rightarrow 2\text{La}_{(1-s)}\text{PO}_4: \text{Sr}_s \cdot \text{(c)} + \text{La}_{(1-s)}\text{PO}_4: \text{Sr}_s \cdot \text{xH}_2\text{O (c)} + \frac{3}{2}(5-4s)\text{H}_2\text{O (g)} + \frac{3}{2}(1-s)\text{N}_2 \cdot \text{(g)} + (15-16s)/4\text{O}_2 \cdot \text{(g)}$	
R19	$ (1-s) \text{La}(\text{NO}_3)_3 \cdot 6\text{H}_2\text{O (c)} + (s) \text{Sr}(\text{NO}_3)_2 \cdot (c) + \text{CO}(\text{NH}_2)_2 \cdot (c) + \text{H}_3\text{PO}_4 \cdot (c) \\ \Rightarrow \text{La}_{(1-s)}\text{PO}_4 : \text{Sr}_s \cdot (c) + \text{La}_{(1-s)}\text{PO}_4 : \text{Sr}_s \cdot x\text{H}_2\text{O (c)} + ((19-12s)/2)\text{H}_2\text{O (g)} + ((4-s)/2)\text{N}_2 + ((15-16s)/4) + \text{CO}_2 \cdot (g) + ((9-6s)/4)\text{O}_2 \cdot (g) $	

a(c) = crystalline, (g) = gas, (l) = liquid.




Figure 1. DTA/TG of LaPO $_4$ combustion product.

268

269

270

271

272

273

274

275

276

277

278

279

280

281

282

283

284

285

286

287

288

289

that the compounds containing nitrogen (NH₄NO₃, NH₃, unreacted nitrate used as precursors, etc.) are retrieved in the as-prepared powders. The carbon content analysis confirms the presence of C in the as-prepared powders (1.0 wt %); however, no carbon is detected in the powders calcined at 800 °C.

TGA data of LaPO₄ as-prepared powder (Figure 1) showed a large weight loss (~68.0 wt %) between room temperature and 1100 °C. The weight loss could indicate among other phenomena that during the combustion reaction the generated byproducts, such as H₂O, NH₄NO₃, NH₃, etc., have not been completely eliminated. In fact, two endothermic peaks, the first one centered at 120 °C and the second (as a shoulder) at 250 °C (A and B, respectively), are detected in the DTA pattern. The endothermic peak centered at \sim 120 °C can be attributed to the loss of physisorbed water, and can be also assigned to the orthorhombic to tetragonal (55 °C) and tetragonal to cubic (130 °C) phase transitions, and melting (170 °C) of NH₄NO₃. ^{33,34} This endothermic peak is accompanied by a weight loss of ~25 wt%. The second endothermic peak centered at 250 °C (shoulder of the peak centered at 120 °C) could correspond to both the progressive

dehydration of the rhabdophane phase and to the decomposition of NH₄NO₃^{33,34} (272 °C) and is accompanied also by a loss of weight of about 5%. The rhabdophane-structured materials can be dehydrated by heating at ~200 °C40 and the references therein. The water in this type of crystal is zeolitic water present in its channel-type structure and the dehydration temperature depends on the synthesis method employed. 15,16,19,35-44 As is well-known, the urea undergoes a first decomposition step in the temperature range 154-263 °C; this process happens with a large weight loss, sharp endothermic effect, and vigorous gas emission. Thus, the possible unreacted urea could contribute according to the literature data,³¹ to both the weight loss in the TGA and the endothermic process in the DTA in the above mentioned range of temperature. A 17% weight loss and a sharp endothermic peak centered at ~325 °C (C) can be attributed to NO₂ emission. This intermediate compound in the combustion reactions gives rise to the N₂ and O₂ gases.³¹ It must be taken into account that in this work the combustion reactions have been written in their final form, with no indication of the intermediate products. Furthermore, different

291

293

295

297

299

301

303

⁽³³⁾ Hussain, G.; Rees, G. J. Propellants, Explosives, Pyrotechnics 1990, 15, 43.

⁽³⁴⁾ Hussain, G.; Rees, G. J. Fuel 1995, 74, 273.

⁽³⁵⁾ Buissette, V.; Moreau, M.; Gacoin, T.; Boilot, J-P.; Chane-Ching, J-Y.; Le Mercier, T. Chem. Mater. 2004, 16, 3767.

⁽³⁶⁾ Glorieux, B.; Matecki, M.; Fayon, F.; Coutures, J. P.; Palau, S.; Douy, A.; Peraudeay, G. J. Nucl. Mater. 2004, 326, 156.

⁽³⁷⁾ Onoda, H.; Nariai, H.; Maki, H.; Motooka, I. Mater. Chem. Phys. 2002, 73, 19.

⁽³⁸⁾ Nishihama, S.; Hirai, T.; Komasawa, I. J. Mater. Chem. 2002, 12, 1053.

⁽³⁹⁾ Boakye, E.; Hay, R. S.; Petry, M. D. J. Am. Ceram. Soc. 1999, 82,

⁽⁴⁰⁾ Jonasson, R. G.; Vance, E. R. *Thermochem. Acta* **1986**, *108*, 65.

⁽⁴¹⁾ Hikichi, Y.; Hukuo, K.; Shiokawa, J. Bull. Chem. Soc. Jpn. 1978, 51, 3645.

⁽⁴²⁾ Guo, Y.; Woznicki, P.; Barkatt, A.; Saad, E. E.; Talmy, I. G. J. Mater. Res. 1996, 11, 3, 639.

⁽⁴³⁾ Terra, O.; Clavier, N.; Dacheux, N.; Podor, R. New J. Chem. 2003, 27, 957.

⁽⁴⁴⁾ Rajesh, K.; Sivakumar, B.; Krishna Pillai, B.; Mukundan, P.; Warrier, K. G. K.; Nair, V. R. Mater. Lett. 2004, 58, 1687.

BATCH: cm5c37

311 312

313

314

315

316

317

318

319

320

321

322

323

324

325

326

327

328

329

330

331

332

333

334

335

336

337

338

339

340

341

342

343

344

345

346

347

348

349

350

358

363

364

370

377

381




Figure 2. XRD data of LaPO₄ combustion product and the same powder calcined at three different temperatures.

temperature values in the range of 375 to 900 °C are given for the rhabdophane-type LaPO₄ (hexagonal) to monazitetype LaPO₄ (monoclinic) phase transition, according to the revised literature. 15,16,19,35-44 In this study, the endothermic peak at \sim 500 °C (D) can be assigned to this transformation. A broad exothermic peak from 500 °C and centered at \sim 900 °C (E) is observed and could correspond to the crystallization of the monazite phase and to the decomposition of organic material. Similar DTA/TG and nitrogen and carbon analysis results are obtained for the Sr-doped compositions.

X-ray analysis data are shown in Figure 2. The data of the as-prepared powder and the one calcined at 200 °C, a temperature below the one reached during the combustion, present low crystallinity; i.e., the peaks are very broad, indicating a small crystal domain. According to the literature, 45 lanthanide orthophosphates exist in five polymorphic forms: rhabdophane, weinschenkite, monazite, xenotime, and orthorhombic symmetries. The X-ray pattern of the asprepared and dried powders correspond to the rhabdophanetype LaPO₄•nH₂O (PDF file 46-1439). At 200 °C, the crystallinity increases although the peaks are still very broad. At 400 °C, the X-ray pattern corresponds to the monazitetype LaPO₄ (PDF file 32-0493). The monazite crystallinity is improved through a calcination at 800 °C/12 h. As mentioned earlier, by DTA/TG, further crystallization of the monazite phase is developed from 500 to 1100 °C (exothermic peak).

X-ray data of Sr-subtituted LaPO₄ powders were also collected, and no significant variation was found compared to pure LaPO₄ powder X-ray data. It can be explained by considering that the monazite structure appears to be an especially accommodating structure since it can accept ions with variable charges and variable ionic radii.⁴⁶ In this case, the effective ionic radii of Sr²⁺ and La³⁺ ions are 1.26 Å $(Sr^{2+}, coordination number = 8)$ and 1.18 Å (La³⁺, coordination number = 8), respectively.⁴⁷ The "softness" of the monazite structure may explain the complex chemical composition of natural monazites. The analysis of longer term scans using the "unitcell" software to calculate the cell parameters gave results that confirmed this behavior. From



⁽⁴⁶⁾ Montel, J.-M.; Devidal, J.-L.; Avignant, D. Chem. Geol. 2002, 191,




Figure 3. FT-IR spectra of LaPO₄ as-prepared powder and calcined at two different temperatures, 400 and 800 °C.

the X-ray diffraction patterns of LaPO₄ powders calcined at 800 °C for 12 h, the lattice parameters (monoclinic structure) were calculated and found to be in good agreement with the published data, 35,43,46,48 namely, $a = 0.6847 \pm 0.0003$ nm, b $= 0.7079 \pm 0.0003$ nm, $c = 0.6510 \pm 0.0003$ nm, $\beta =$ $103.32 \pm 0.09^{\circ}$, and volume = $0.3071 \pm 0.0005 \text{ nm}^3$. The lattice parameters and the lattice volume of $La_{(1-x)}Sr_xPO_4$ with x = 0.025 and 0.05 did not show any significant variation with respect to pure LaPO₄.

XRD data were also used to calculate the average crystallite size of the powder calcined at 800 °C: ~60 nm. This value seems to be confirmed by the TEM analysis (Figure 7). As can be seen, the crystallite size is uniform and is in the 50-100 nm range.

Figure 3 indicates the transmittance bands of the asprepared LaPO₄ powder and the same powder after calcination at 400 and 800 °C/12 h. The band at 1620 cm $^{-1}$ on the FTIR spectrum of the as-prepared powder can be assigned to the hydration water of the hexagonal LaPO₄•nH₂O. ¹⁶ This band completely disappears at 400 °C. This fact indicates that the rhabdophane phase is not present in the powder at that temperature in accordance with the XRD data. The other bands present on the FTIR spectrum of the as-prepared powder are assigned to the phosphate groups. Four bands located at 541, 564, 579 and 617 cm⁻¹, were clearly observed in the v region of vibration of PO₄ groups. ^{49,50} The presence of these four bands is characteristic of the vibrations of phosphate groups in the monoclinic structure of monazitetype LaPO₄. For the rhabdophane phase the bands in the v_4 region are only three (541, 579 and 617 cm⁻¹). ¹⁶ This fact indicates that the as-prepared powder is a mixture of both rhabdophane and monazite phases, although the XRD does not reveal the presence of the monazite phases, although the XRD does not reveal the presence of the monazite phase.

⁽⁴⁷⁾ Shannon, R. D. Acta Crystallogr. 1976, A32, 751.

⁽⁴⁸⁾ Ni, R. C. L.; Hugues, J. M.; Mariano, A. N. Am. Mineral. 1995, 80, 21.

⁽⁴⁹⁾ Farmer, V. C. The infrared spectra of minerals; Farmer, V. C., Ed.; Mineralogic Society: London, 1974.

Mullica, D. F.; Milligan, W. O.; Grossie, D. W.; Boatner, L. A. Inorg. Chim. Acta 1984, 95, 231. Pretsch, E., Clerc, T., Seibl, J., Simon, W. Tablas para la Elucidación Estructural de Compuestos Orgánicos por Métodos Espectroscópicos, Vol. I, Alhambra, Madrid, 1988.

BATCH: cm5c37 USER: vkb69 DIV: @xyv04/data1/CLS_pj/GRP_cm/JOB_i13/DIV_cm047945q DATE: May 24, 2005

F Chem. Mater. Gallini et al.

At low frequencies, the five characteristic bands (v_3 region: 1093, 1060, 1024, 993 and 954 cm⁻¹) of rare-earth phosphates in the monoclinic structure of monazite-type LaPO₄, resulting from the distortion of the tetrahedral phosphate groups in the 9-fold coordinated La atoms, can be clearly observed for the calcined powder at 800 °C. The resolution of the vibration bands of phosphate in the domain 990-110 cm⁻¹ (v_3 region) of the FTIR spectra is increased when increases the calcination temperature indicating a higher crystallization of the monoclinic phase. Several extra bands are present in the noncalcined powders data and are not present in the powders calcined at 800 °C. IR analysis of the precursors were performed in order to understand the presence of these extra bands. For instance, two bands can be observed in the as-prepared powder spectrum at 1375 and 1470 cm⁻¹ that can be associated with both the NO₃⁻ group of the residual unreacted nitrate precursors and from the NH₄-NO₃ formed during the combustion reaction. The experimental IR spectrum of La(NO₃)₃•6H₂O shows one band centered at 1385 cm⁻¹ and another one at 1468 cm⁻¹; both values match the IR frequencies of the extra bands. In fact, both wavelengths are characteristics of the N-O bond in the NO₃⁻ group in nitrates. The band at 1468 cm⁻¹ could also be assigned to N-H vibrations (1400-1460 cm⁻¹) resulting from the presence of ammonium residues 16 or/and the presence of the biuret (H₂NCONHCONH₂), decomposition product of the urea. Another band detected in the asprepared powders is centered at 1780 cm⁻¹ and could be assigned to the N=O bond of the nitrates (unreacted precursors) and from the NH₄NO₃ formed. At 1720 cm⁻¹ appears a band that can be associated with the carbonyl group of the unreacted urea or/and the biuret.⁵⁰ This band disappears at 400 °C. All these extra bands do not appear in the powders calcined at 800 °C for 12 h. In fact, the carbon content analysis confirms the presence of this element in the noncalcined powders in the amount of 1.0 wt %, as mentioned above, and no presence of carbon is detected for the calcined powders at 800 °C. The bands centered at 1620 and 3500 cm⁻¹ can be due to the hydration water (O-H bond) of the rhabdophane phase in the as-prepared powders, as mentioned above, and also to the water adsorbed on the KBr pellet used to perform the IR analysis in the as-prepared and calcined powders. The broad band centered at 3500 cm⁻¹ can overlap another one at 3120 cm⁻¹ that can be due to the N-H vibration resulting from the presence of ammonium or/and biuret residues⁵⁰ present in both the as-prepared and calcined at 400 °C powders, being the band less intense in the latter case. The doped samples show the same bands at every calcination temperature.

385

386

387

388

389

390

391

392

393 394

395

396

397

398

399

400

401

402

403

404

405

406

407

408

409

410

411

412

413

414

415

416

417

418

419

420

421

422

423

424

425

426

427

428

429

430

431

432

433

434

435

436

437

438

439

440

441

442

443

The agglomerate average size was studied through a laser analyzer. The data of both the as-prepared and the calcined LaPO₄ powder are represented in Figure 4. In all cases, the agglomerate size corresponds to a bimodal distribution. The size range of the as-prepared powder is $0.07-250~\mu m$. There are clearly two peaks in the distribution, one centered at $0.25~\mu m$ and the second one at $40~\mu m$. Three differences can be observed in the distribution of the calcined powder at 400~ °C with respect to the as-prepared powder: the first one is that the peak at $0.25~\mu m$ has a lower intensity, the second is




Figure 4. Particle size distribution analysis of LaPO₄ as-prepared powder compared to powder calcined at two different temperatures, 400 and 800 °C, and attrition-milled.

that the peak at 40 μ m has a higher intensity than that of the as-prepared powders, and the third one is that the maximum is slightly shifted to a higher value (70 μ m) when the powder is calcined. This behavior indicates that the average agglomerate size is increased, a normal phenomenum in polycrystalline materials when they are calcined. To reduce the agglomerate size and to obtain a better sintering behavior, the powders were attrition-milled for 3 h after the final calcination at 800 °C. After the attrition-milling, the agglomerate size distribution is significantly changed: the particle diameter range is $0.15-40 \mu m$ and two peaks in the size distribution are still present but they are at different positions of the ones found in the calcined unmilled powders. The new peak positions are at 1 and 20 μ m the latter has a very low density and it is clear that the agglomerate size is drastically reduced by about 2 orders of magnitude. Moreover, the agglomerates size was not affected by 2.5% or 5% substitution of Sr in $La_{(1-x)}Sr_{(x)}PO_4$ powders. Attrition-milling for more than 3 h was applied on the powders and no significant differences in either the agglomerates size or their distribution were found.

SEM micrographs presented in Figure 5 confirm the size range of the agglomerates given by the laser analyzer. Picture 5 (a) shows the as-prepared powder with large agglomerates (some of them larger than 50 μ m), picture 5(b) shows a detail of the agglomerates, while the picture on the right side, (5c), corresponds to the calcined at 800 °C and attrition-milled powder where a drastic reduction of the agglomerate size can be observed. Furthermore, the specific surface area of the latter was found to be 7.0 m²/g, a higher value than that of the unmilled powders. Similar results are observed in the doped powders.

In Figure 6 agglomerates of nanometric crystals of the asprepared powders can be observed by TEM. The powder exhibits two different morphologies: in some areas needle-like crystals, characteristics of the rhabdophane phase, ¹⁷ and in another areas rounded crystals, corresponding to the monazite phase. ¹⁷ The electron diffraction of the agglomerates indicates that they are polycrystalline, but the diffraction is not well-defined; in fact, the crystallite size is very small, less than 10 nm. The same technique was used to characterize the powder calcined at 800 °C/12 h. Figure 7 shows round-shaped crystals of LaPO₄ powders of a size that varies in the range 40–80 nm. During the heat treatment, the crystals with a needlelike morphology (rhabdophane phase) begin

457

460

461

462

463

464

466

467

468

469

470

474

475

476


479

481

483

484

485







Figure 5. SEM micrographs of as-prepared LaPO₄ powder (a) detail of the agglomerates (b) and the same powder calcined at 800 °C and attrition-milled (c).



 $\begin{tabular}{ll} \textbf{Figure 6.} & TEM & micrograph & and & electron & diffraction & pattern & of the as-prepared & and & dried & LaPO_4 & powder. \\ \end{tabular}$

489

490

491

492

493

494

495

496

497

498

499

500

501

502

503

504

to change their morphology to an equiaxial shape, characteristic of the monazite phase, due to their transformation. At 800 °C of calcination temperature, only equiaxial crystals are detected by TEM, corresponding to the monazite phase, as mentioned above (Figure 7). Electron diffraction indicates a good crystallinity, being the crystallite size about 10 times bigger than that in the noncalcined powder.

The last step in the preparation protocol is the attrition-milling for 3 h, as mentioned above. Figure 8 shows how milling affects the size of the agglomerates of nanometric crystals (TEM micrograph). Less agglomerate powder is attained after milling. The crystals are round-shaped as mentioned above, which is an adequate characteristic in order to pack each other and to obtain a good sinterability. The doped samples show the same crystal size and morphology than that of the undoped samples. TEM-EDX analysis indicates




Figure 7. TEM micrograph and a selected area electron diffraction pattern of the LaPO $_4$ powder calcined at 800 °C/12 h.




Figure 8. TEM micrograph of LaPO₄ powder calcined at 800 °C/12 h and attrition-milled.




Figure 9. Dilatometric curves, shrinkage vs temperature and shrinkage rate vs temperature of a green pellet of $La_{0.95}Sr_{0.05}PO_4$.

the presence of La, Sr, and P elements in the stoichometric proportions in both as-prepared and calcined powders.

Dilatometric Studies. From the dilatometric curve (Figure 9) of 5% substituted Sr:LaPO₄ it can be concluded that the starting densification temperature is ~850 °C and when the temperature increases a large shrinkage (16.5% of the total length) was detected from that temperature up to 1300 °C. The maximum shrinkage rate was achieved at 1030 °C. It is important to outline that the densification behavior is affected by the substitution of La³⁺ by Sr²⁺. In the case of pure LaPO₄, the sintering process is not complete at 1500 °C. However, for the doped samples, the sintering process is complete at ~1300 °C. Thus, Sr²⁺ ions enhanced the densification process, as is expected, since Sr²⁺ generates oxygen vacancies when replaced with La3+ ions in the lattice,⁹ allowing the sintering temperature to decrease. Therefore, the absence of a flame during the combustion could enhance the densification of the ceramic compacts

BATCH: cm5c37 USER: vkb69 DIV: @xyv04/data1/CLS_pj/GRP_cm/JOB_i13/DIV_cm047945q DATE: May 24, 2005

H Chem. Mater. PAGE EST: 7.3 Gallini et al.

because the high temperature, reached when a flame is produced during the reaction, might provoke premature sintered agglomerates. In addition, for the scale-up industrial production, this synthesis method provides a very rapid and efficient technique for nanometric powders of $La_{1-x}(Sr)_xPO_4$ compared to other methods.

Conclusions

This work shows that the valency molar proportions of reactants proposed by the propellant chemistry can be conveniently used to produce nanometric $\text{La}_{(1-x)}\text{Sr}_{(x)}\text{PO}_4$ powders at low temperature. XRD data reveal that the doping with Sr does not affect the volume of the LaPO₄ lattice. It has been demonstrated that the homogeneous powders are adequate to obtain dense materials after calcination at 800 °C/12 h and attrition-milling for 3 h. The sintering temper-

ature could be as low as 1300 °C. Unlike other methods, combustion synthesis offers the advantage of simplicity of the experimental setup, a surprisingly short time to obtain the final product and savings in external energy consumption. The fact that the combustion process is not complete in this case can be an advantage because it could enhance the densification, which is required for the use of these materials as electrolytes in fuel cells.

Acknowledgment. The authors are grateful to the European RTN project "Investigation of high temperature solid proton conductors of relevance to fuel processing and energy conversion applications" (Contract Number: HPRN-CT-2000-00042) and the Spanish Project MAT2001-1489-CO2-02 for funding. CM0479450