Packed Bed Reactor Technology for Chemical-Looping Combustion

ARTICLE *in* INDUSTRIAL & ENGINEERING CHEMISTRY RESEARCH · JANUARY 2007

Impact Factor: 2.59 · DOI: 10.1021/ie061178i

2 AUTHORS, INCLUDING:

M. Van Sint Annaland
Technische Universiteit Eindhoven
273 PUBLICATIONS **5,714** CITATIONS

2nd Workshop

International Oxy-Combustion Research Network

Hilton Garden Inn
Windsor, CT, USA

25th and 26th January 2007

Hosted by:
Alstom Power Inc.

PRESENTATION - 18

Packed Bed Reactor Technology for Chemical-Looping Combustion

by:

Sander Noorman
University of Twente, The Netherlands

Packed Bed Reactor Technology for Chemical-Looping Combustion

S. Noorman, M. van Sint Annaland, J.A.M. Kuipers (UT)
N.A.M. ten Asbroek, P.H.M. Feron (TNO)

2nd IEAGHG Oxyfuel Combustion Workshop
25th and 26th of January 2007, Windsor, USA

Chemical-looping Combustion



I: $4\ Me + 2\ O_2 \rightarrow 4\ MeO\ (\Delta H < 0)$

II: $4\ MeO + CH_4 \rightarrow 4\ Me + CO_2 + 2\ H_2O\ (\Delta H > 0)$

- Power production with inherent CO_2 separation
- Direct contact between air and fuel is avoided

2

Introduction

- Chemical-looping Combustion:
  - Potential for very high CO_2 capture efficiency
  - No energy penalty for separation
  - No NO_x formation
  - Direct implementation in power plants is challenging



- Important research themes:
  - Oxygen carrier (MeO = NiO, Fe_2O_3, Mn_3O_4, CuO)
  - Implementation in power plant
  - Reactor concepts

Oxidizing and reducing conditions must be imposed alternately

3

Reactor Concepts

Recirculation or stationary solids?



- Disadvantage of fluidization:
  - Recirculation of particles
  - Difficult gas-solid separation (formation of fines)
- Packed bed (membrane-assisted) CLC:
  - Stationary solids
  - Periodic switching of gas streams
  - Dynamically operated parallel reactors (gas switching system)
  - Natural gas → combined cycle!

4

Packed Bed CLC

- Packed bed CLC (UT):



- Packed bed membrane-assisted CLC (TNO):



- Process demands:
  - Constant high-temperature air stream
  - High overall and CO_2 capture efficiency
  - Continuous operation
  - Extreme conditions (T_{out} = 1300-1500 K, p = 20-30 bar)

5

Project Goal

- Evaluation of the feasibility of packed bed CLC as an alternative power production technology:
  - Can CLC be carried out using packed bed (membrane-assisted) technology?
  - How can packed bed CLC with an optimal overall energy efficiency be realized?
  - How does packed bed CLC perform, compared to fluidized bed CLC and other CO_2 capture processes?
- This presentation:
  - Modeling and experimental work on packed bed CLC.

6

Packed Bed CLC: Oxidation



- Oxidation cycle:
  - Calculation of axial temperature and concentration profiles.
  - Particle behavior is described using a two-zone model



7

Packed Bed CLC: Oxidation



- Oxidation cycle:
  - Temperature evolution



- 'No' influence of reaction kinetics or flow rate
- An air stream of high, constant temperature is produced → gas turbine

8

Oxygen Carrier Properties

- Analytical approximation:
  - Infinitely high reaction rate
  - No influence of conduction

$$\Delta T = \frac{(-\Delta H_R)}{\frac{C_{p,s} M_{act}}{w_{act}} \xi - \frac{C_{p,g} M_{O_2}}{w_{g,O_2}^{in}}}$$

- Temperature increase can be tuned:
  - Active content
  - Support material
  - Oxygen concentration



9

Packed Bed CLC: Reduction



- Reduction cycle:
  - Efficient use of fuel
  - High CO_2 capture efficiency
  - Selectivity to CO_2 and H_2O
  - Incomplete regeneration of part of the bed



10

Packed Bed CLC: Operation

- Operation over multiple cycles:





➢ Fluidization between oxidation and reduction cycles is necessary to level off temperature profiles.

Modeling Packed Bed CLC



→ Cyclic steady state is obtained after only a few oxidation/reduction cycles.

Experimental Validation







13

Experimental Validation

Model description



Experimental results



Oxidation reaction: (t = 0, 6, 12, 18, 24, 30 s)
(CuO/Cu, w_{act} ≈ 0.1)

	Model	Exp.	
ΔT_{max} [K]	195	199	➨
w_2 [cm/s]	1.53	1.58	➨
w_1 [cm/s]	0.13	0.15	➨

Improvements:

- Correct implementation of heat losses in the model
- Coupling of particle model and reactor model

14

Implementation

- Implementation in power plant:
  - Combined cycle to maximize overall energy efficiency
- Process design:
  - Pressure drop
  - Number of reactors
  - Reactor sizing
  - Heat integration, etc.
- Important features:
  - Compact design
  - Suitable for part-load operation



15

Conclusions

- Packed bed (membrane-assisted) CLC is an interesting alternative power production technology:
- Process operation:
  - Oxidation cycle: generation of high temperature air stream
  - Reduction cycle: combining efficient use of fuel and high CO_2 capture efficiency
- Implementation in power plant:
  - Combined cycle
- Future work:
  - Experimental validation of packed bed CLC
  - Process design and efficiency calculations

16