



---

# OData Common Schema Definition Language (CSDL) XML Representation Version 4.02

Committee Specification Draft 01

14 July 2023

## This stage:

<https://docs.oasis-open.org/odata/odata-csdl-json/v4.02/csd01/odata-csdl-xml-v4.02-csd01.md>  
(Authoritative)

<https://docs.oasis-open.org/odata/odata-csdl-json/v4.02/csd01/odata-csdl-xml-v4.02-csd01.html>

<https://docs.oasis-open.org/odata/odata-csdl-json/v4.02/csd01/odata-csdl-xml-v4.02-csd01.pdf>

## Previous stage:

N/A

## Latest stage:

<https://docs.oasis-open.org/odata/odata-csdl-json/v4.02/odata-csdl-json-v4.02.md> (Authoritative)

<https://docs.oasis-open.org/odata/odata-csdl-json/v4.02/odata-csdl-json-v4.02.html>

<https://docs.oasis-open.org/odata/odata-csdl-json/v4.02/odata-csdl-json-v4.02.pdf>

## Technical Committee:

[OASIS Open Data Protocol \(OData\) TC](#)

## Chairs:

Ralf Handl ([ralf.handl@sap.com](mailto:ralf.handl@sap.com)), [SAP SE](#)

Michael Pizzo ([mikep@microsoft.com](mailto:mikep@microsoft.com)), [Microsoft](#)

## Editors:

Ralf Handl ([ralf.handl@sap.com](mailto:ralf.handl@sap.com)), [SAP SE](#)

Michael Pizzo ([mikep@microsoft.com](mailto:mikep@microsoft.com)), [Microsoft](#)

Heiko Theißen ([heiko.theissen@sap.com](mailto:heiko.theissen@sap.com)), [SAP SE](#)

## Additional artifacts:

This prose specification is one component of a Work Product that also includes:

- XML schemas: *OData EDMX XML Schema and OData EDM XML Schema*. Latest stage: <https://docs.oasis-open.org/odata/odata-cSDL-xml/v4.01/os/schemas/>

## Related work:

This specification replaces or supersedes:

- *OData Common Schema Definition Language (CSDL) JSON Representation Version 4.01*. Edited by Michael Pizzo, Ralf Handl, and Martin Zurmuehl. OASIS Standard. Latest stage: <https://docs.oasis-open.org/odata/odata-cSDL-json/v4.01/odata-cSDL-json-v4.01.html>.

This specification is related to:

- *OData Version 4.02*. Edited by Michael Pizzo, Ralf Handl, and Heiko Theißen. A multi-part Work Product that includes:
  - *OData Version 4.02 Part 1: Protocol*. Latest stage: <https://docs.oasis-open.org/odata/odata/v4.02/odata-v4.02-part1-protocol.html>
  - *OData Version 4.02 Part 2: URL Conventions*. Latest stage: <https://docs.oasis-open.org/odata/odata/v4.02/odata-v4.02-part2-url-conventions.html>
  - *ABNF components: OData ABNF Construction Rules Version 4.01 and OData ABNF Test Cases*. <https://docs.oasis-open.org/odata/odata/v4.01/os/abnf/>
- *OData Vocabularies Version 4.0*. Edited by Michael Pizzo, Ralf Handl, and Ram Jeyaraman. Latest stage: <https://docs.oasis-open.org/odata/odata-vocabularies/v4.0/odata-vocabularies-v4.0.html>
- *OData Common Schema Definition Language (CSDL) JSON Representation Version 4.01*. Edited by Michael Pizzo, Ralf Handl, and Martin Zurmuehl. Latest stage: <https://docs.oasis-open.org/odata/odata-cSDL-json/v4.01/odata-cSDL-json-v4.01.html>
- *OData JSON Format Version 4.01*. Edited by Ralf Handl, Mike Pizzo, and Mark Biamonte. Latest stage: <https://docs.oasis-open.org/odata/odata-json-format/v4.01/odata-json-format-v4.01.html>

## Abstract:

OData services are described by an Entity Model (EDM). The Common Schema Definition Language (CSDL) defines specific representations of the entity data model exposed by an OData service, using XML, JSON, and other formats. This document (OData CSDL JSON Representation) specifically defines the JSON representation of CSDL.

## Status:

This document was last revised or approved by the OASIS Open Data Protocol (OData) TC on the above date. The level of approval is also listed above. Check the "Latest stage" location noted above for possible later revisions of this document. Any other numbered Versions and other technical work produced by the Technical Committee (TC) are listed at [https://www.oasis-open.org/committees/tc\\_home.php?wg\\_abbrev=odata#technical](https://www.oasis-open.org/committees/tc_home.php?wg_abbrev=odata#technical).

TC members should send comments on this specification to the TC's email list. Others should send comments to the TC's public comment list, after subscribing to it by following the instructions at the "[Send A Comment](#)" button on the TC's web page at <https://www.oasis-open.org/committees/odata/>.

This specification is provided under the [RF on RAND Terms Mode](#) of the [OASIS IPR Policy](#), the mode chosen when the Technical Committee was established. For information on whether any patents have been disclosed that may be essential to implementing this specification, and any offers of patent licensing terms, please refer to the Intellectual Property Rights section of the TC's web page (<https://www.oasis-open.org/committees/odata/ipr.php>).

Note that any machine-readable content ([Computer Language Definitions](#)) declared Normative for this Work Product is provided in separate plain text files. In the event of a discrepancy between any such plain text file and display content in the Work Product's prose narrative document(s), the content in the separate plain text file prevails.

### Key words:

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in BCP 14 [\[RFC2119\]](#) and [\[RFC8174\]](#) when, and only when, they appear in all capitals, as shown here.

### Citation format:

When referencing this specification the following citation format should be used:

#### [OData-CSDL-JSON-v4.02]

*OData Common Schema Definition Language (CSDL) JSON Representation Version 4.02*. Edited by Ralf Handl, Michael Pizzo, and Heiko Theißen. 14 July 2023. OASIS Committee Specification Draft 01. <https://docs.oasis-open.org/odata/odata-csdl-json/v4.02/csd01/odata-csdl-xml-v4.02-csd01.html>. Latest stage: <https://docs.oasis-open.org/odata/odata-csdl-json/v4.02/odata-csdl-json-v4.02.html>.

### Notices

Copyright © OASIS Open 2023. All Rights Reserved.

Distributed under the terms of the OASIS [IPR Policy](#).

The name "OASIS" is a trademark of [OASIS](#), the owner and developer of this specification, and should be used only to refer to the organization and its official outputs.

For complete copyright information please see the full Notices section in an Appendix below.

# Table of Contents

## [1 Introduction](#)

### [1.1 Changes from earlier Versions](#)

### [1.2 Glossary](#)

#### [1.2.1 Definitions of terms](#)

#### [1.2.2 Acronyms and abbreviations](#)

#### [1.2.3 Document conventions](#)

## [\[2 XML Representation\]](#)

### [2.1 Requesting the XML Representation](#)

### [\[2.2 XML Namespaces\]](#)

#### [2.2.1 Namespace EDMX](#)

#### [2.2.2 Namespace EDM](#)

### [\[2.3 XML Schema Definitions\]](#)

### [\[2.4 XML Document Order\]](#)

## [3 Entity Model](#)

### [3.1 Nominal Types](#)

### [3.2 Structured Types](#)

### [3.3 Primitive Types](#)

### [3.4 Built-In Abstract Types](#)

### [3.5 Built-In Types for defining Vocabulary Terms](#)

### [3.6 Annotations](#)

## [4 CSDL XML Document](#)

### [4.1 Reference](#)

### [4.2 Included Schema](#)

### [4.3 Included Annotations](#)

## [5 Schema](#)

### [5.1 Alias](#)

### [5.2 Annotations with External Targeting](#)

## [A References](#)

### [A.1 Normative References](#)

### [A.2 Informative References](#)

## [B Table of XML Elements and Attributes](#)

## [C Acknowledgments](#)

### [C.1 Special Thanks](#)

### [C.2 Participants](#)

## [D Revision History](#)

## [E Notices](#)

# 1 Introduction

OData services are described in terms of an [Entity Model](#). The Common Schema Definition Language (CSDL) defines a representation of the entity model exposed by an OData service using the JavaScript Object Notation (JSON), see [\[RFC8259\]](#).

This format is based on the OpenUI5 OData V4 Metadata JSON Format, see [\[OpenUI5\]](#), with some extensions and modifications made necessary to fully cover OData CSDL Version 4.01.

## 1.1 Changes from earlier Versions

## 1.2 Glossary

### 1.2.1 Definitions of terms

### 1.2.2 Acronyms and abbreviations

### 1.2.3 Document conventions

Keywords defined by this specification use `this monospaced font`.

Some sections of this specification are illustrated with non-normative examples.

*Example 1: text describing an example uses this paragraph style*

Non-normative examples use this paragraph style.

All examples in this document are non-normative and informative only. Examples labeled with  $\triangle$  contain advanced concepts or make use of keywords that are defined only later in the text, they can be skipped at first reading.

Representation-specific text is indented and marked with vertical lines.

### Representation-Specific Headline

Normative representation-specific text

All other text is normative unless otherwise labeled.

*Here is a customized command line which will generate HTML from this markdown file (named odata-csdl-xml-v4.02-csd01.md). Line breaks are added for readability only:*

```
pandoc -f gfm+tex_math_dollars+fenced_divs
-t html
-o odata-csdl-xml-v4.02-csd01.html
-c styles/markdown-styles-v1.7.3b.css
-c styles/odata.css
-s
--mathjax
--eol=lf
--wrap=none
--metadata pagetitle="OData Common Schema Definition Language (CSDL) XML"
```

This uses pandoc 3.1.2 from <https://github.com/jgm/pandoc/releases/tag/3.1.2>.

## [2 XML Representation]

OData CSDL XML is a full representation of the OData Common Schema Definition Language in the Extensible Markup Language (XML) 1.1 (Second Edition) [XML-1.1] with further building blocks from the W3C XML Schema Definition Language (XSD) 1.1 as described in [XML-Schema-1] and [XML-Schema-2].

It is an alternative to the CSDL JSON representation defined in [OData-CSDLJSON] and neither adds nor removes features.

### 2.1 Requesting the XML Representation

The OData CSDL XML representation can be requested using the `$format` query option in the request URL with the media type `application/xml`, optionally followed by media type parameters, or the case-insensitive abbreviation `xml` which MUST NOT be followed by media type parameters.

Alternatively, this representation can be requested using the `Accept` header with the media type `application/xml`, optionally followed by media type parameters.

If specified, `$format` overrides any value specified in the `Accept` header.

The response MUST contain the `Content-Type` header with a value of `application/xml`, optionally followed by media type parameters.

This specification does not define additional parameters for the media type `application/xml`.

### [2.2 XML Namespaces]

In addition to the default XML namespace, the elements and attributes used to describe the entity model of an OData service are defined in one of the following namespaces.

#### 2.2.1 Namespace EDMX

Elements and attributes associated with the top-level wrapper that contains the CSDL used to define the entity model for an OData Service are qualified with the Entity Data Model for Data Services Packaging namespace:

- `http://docs.oasis-open.org/odata/ns/edmx`

Prior versions of OData used the following namespace for EDMX:

- EDMX version 1.0: `http://schemas.microsoft.com/ado/2007/06/edmx`

They are non-normative for this specification.

In this specification the namespace prefix `edmx` is used to represent the Entity Data Model for Data Services Packaging namespace, however the prefix name is not prescriptive.

## 2.2.2 Namespace EDM

Elements and attributes that define the entity model exposed by the OData Service are qualified with the Entity Data Model namespace:

- <http://docs.oasis-open.org/odata/ns/edm>

Prior versions of CSDL used the following namespaces for EDM:

- CSDL version 1.0: <http://schemas.microsoft.com/ado/2006/04/edm>
- CSDL version 1.1: <http://schemas.microsoft.com/ado/2007/05/edm>
- CSDL version 1.2: <http://schemas.microsoft.com/ado/2008/01/edm>
- CSDL version 2.0: <http://schemas.microsoft.com/ado/2008/09/edm>
- CSDL version 3.0: <http://schemas.microsoft.com/ado/2009/11/edm>

They are non-normative for this specification.

In this specification the namespace prefix `edm` is used to represent the Entity Data Model namespace, however the prefix name is not prescriptive.

## [2.3 XML Schema Definitions]

This specification contains normative XML schemas for the EDMX and EDM namespaces; see [\[OData-EDMX\]](#) and [\[OData-EDM\]](#)

These XML schemas only define the shape of a well-formed CSDL XML document and are not descriptive enough to define what a correct CSDL XML document **MUST** be in every imaginable use case. This specification document defines additional rules that correct CSDL XML documents **MUST** fulfill. In case of doubt on what makes a CSDL XML document correct the rules defined in this specification document take precedence.

## [2.4 XML Document Order]

Client libraries **MUST** retain the document order of XML elements for CSDL XML documents because for some elements the order of child elements is significant. This includes, but is not limited to, [members of enumeration types](#) and items within a [collection expression](#).

OData does not impose any ordering constraints on XML attributes within XML elements.

## 3 Entity Model

An OData service exposes a single entity model. This model may be distributed over several [schemas](#), and these schemas may be distributed over several documents.

A service is defined by a single CSDL document which can be accessed by sending a **GET** request to `<serviceRoot>/$metadata`. This document is called the metadata document. It **MAY** [reference](#) other CSDL documents.

The metadata document contains a single [entity container](#) that defines the resources exposed by this service. This entity container **MAY** [extend](#) an entity container defined in a [referenced document](#).

The *model* of the service consists of all CSDL constructs used in its entity containers.

The *scope* of a CSDL document is the document itself and all schemas [included](#) from directly [referenced documents](#). All entity types, complex types and other named model elements *in scope* (that is, defined in the document itself or a schema of a directly referenced document) can be accessed from a referencing document by their qualified names. This includes the [built-in primitive](#) and [abstract types](#).

Referencing another document may alter the model defined by the referencing document. For instance, if a referenced document defines an entity type derived from an entity type in the referencing document, then an [entity set](#) of the service defined by the referencing document may return entities of the derived type. This is identical to the behavior if the derived type had been defined directly in the referencing document.

Note: referencing documents is not recursive. Only named model elements defined in directly referenced documents can be used within the schema. However, those elements may in turn include or reference model elements defined in schemas referenced by their defining schema.

### [3.1 Nominal Types](#)

A nominal type has a name that MUST be a [simple identifier](#). Nominal types are referenced using their [qualified name](#). The qualified type name MUST be unique within a model as it facilitates references to the element from other parts of the model.

Names are case-sensitive, but service authors SHOULD NOT choose names that differ only in case.

### [3.2 Structured Types](#)

Structured types are composed of other model elements. Structured types are common in entity models as the means of representing entities and structured properties in an OData service. [Entity types](#) and [complex types](#) are both structured types.

Structured Types are composed of zero or more [structural properties](#) and [navigation properties](#).

[Open entity types](#) and [open complex types](#) allow properties to be added dynamically to instances of the open type.

### [3.3 Primitive Types](#)

Structured types are composed of other structured types and primitive types. OData defines the following primitive types:

| Type        | Meaning                |
|-------------|------------------------|
| Edm.Binary  | Binary data            |
| Edm.Boolean | Binary-valued logic    |
| Edm.Byte    | Unsigned 8-bit integer |



| Type                         | Meaning  |
|------------------------------|--|
| Edm.Date                     | Date without a time-zone offset                                |
| Edm.DateTimeOffset           | Date and time with a time-zone offset, no leap seconds         |
| Edm.Decimal                  | Numeric values with decimal representation                     |
| Edm.Double                   | IEEE 754 binary64 floating-point number (15-17 decimal digits) |
| Edm.Duration                 | Signed duration in days, hours, minutes, and (sub)seconds      |
| Edm.Guid                     | 16-byte (128-bit) unique identifier                            |
| Edm.Int16                    | Signed 16-bit integer  |
| Edm.Int32                    | Signed 32-bit integer  |
| Edm.Int64                    | Signed 64-bit integer  |
| Edm.SByte                    | Signed 8-bit integer   |
| Edm.Single                   | IEEE 754 binary32 floating-point number (6-9 decimal digits)   |
| Edm.Stream                   | Binary data stream   |
| Edm.String                   | Sequence of characters   |
| Edm.TimeOfDay                | Clock time 00:00-23:59:59.999999999999                         |
| Edm.Geography                | Abstract base type for all Geography types                     |
| Edm.GeographyPoint           | A point in a round-earth coordinate system                     |
| Edm.GeographyLineString      | Line string in a round-earth coordinate system                 |
| Edm.GeographyPolygon         | Polygon in a round-earth coordinate system                     |
| Edm.GeographyMultiPoint      | Collection of points in a round-earth coordinate system        |
| Edm.GeographyMultiLineString | Collection of line strings in a round-earth coordinate system  |
| Edm.GeographyMultiPolygon    | Collection of polygons in a round-earth coordinate system      |
| Edm.GeographyCollection      | Collection of arbitrary Geography values                       |
| Edm.Geometry                 | Abstract base type for all Geometry types                      |
| Edm.GeometryPoint            | Point in a flat-earth coordinate system                        |

| Type                        | Meaning  |
|-----------------------------|--|
| Edm.GeometryLineString      | Line string in a flat-earth coordinate system                |
| Edm.GeometryPolygon         | Polygon in a flat-earth coordinate system                    |
| Edm.GeometryMultiPoint      | Collection of points in a flat-earth coordinate system       |
| Edm.GeometryMultiLineString | Collection of line strings in a flat-earth coordinate system |
| Edm.GeometryMultiPolygon    | Collection of polygons in a flat-earth coordinate system     |
| Edm.GeometryCollection      | Collection of arbitrary Geometry values                      |

Edm.Date and Edm.DateTimeOffset follow [\[XML-Schema-2\]](#) and use the proleptic Gregorian calendar, allowing the year 0000 (equivalent to 1 BCE) and negative years (year -0001 being equivalent to 2 BCE etc.). The supported date range is service-specific and typically depends on the underlying persistency layer, e.g. SQL only supports years 0001 to 9999.

Edm.Decimal with a [Scale](#) value of floating, Edm.Double, and Edm.Single allow the special numeric values -INF, INF, and NaN.

Edm.Stream is a primitive type that can be used as a property of an [entity type](#) or [complex type](#), the underlying type for a [type definition](#), or the binding parameter or return type of an [action](#) or [function](#). Edm.Stream, or a type definition whose underlying type is Edm.Stream, cannot be used in collections or for non-binding parameters to functions or actions.

Some of these types allow [facets](#), defined in section "[Type Facets](#)".

See rule primitiveLiteral in [\[OData-ABNF\]](#) for the representation of primitive type values in URLs and [\[OData-JSON\]](#) for the representation in requests and responses.

### 3.4 Built-In Abstract Types

The following built-in abstract types can be used within a model:

- Edm.PrimitiveType
- Edm.ComplexType
- Edm.EntityType
- Edm.Untyped

Conceptually, these are the abstract base types for primitive types (including type definitions and enumeration types), complex types, entity types, or any type or collection of types, respectively, and can be used anywhere a corresponding concrete type can be used, except:

- Edm.EntityType
  - cannot be used as the type of a singleton in an entity container because it doesn't define a structure, which defeats the purpose of a singleton.

- cannot be used as the type of an entity set because all entities in an entity set must have the same key fields to uniquely identify them within the set.
- cannot be the base type of an entity type or complex type.
- `Edm.ComplexType`
  - cannot be the base type of an entity type or complex type.
- `Edm.PrimitiveType`
  - cannot be used as the type of a key property of an entity type or as the underlying type of an enumeration type.
  - cannot be used as the underlying type of a type definition in a CSDL document with a version of 4.0.
  - can be used as the underlying type of a type definition in a CSDL document with a version of 4.01 or greater.
- `Edm.Untyped`
  - cannot be returned in a payload with an `odata-Version` header of 4.0. Services should treat untyped properties as dynamic properties in 4.0 payloads.
  - cannot be used as the type of a key property of an entity type.
  - cannot be the base type of an entity type or complex type.
  - cannot be used as the underlying type of a type definition or enumeration type.
- `Collection(Edm.PrimitiveType)`
  - cannot be used as the type of a property or term.
  - cannot be used as the type of a parameter or the return type of an action or function.
- `Collection(Edm.Untyped)`
  - cannot be returned in a payload with an `odata-Version` header of 4.0. Services should treat untyped properties as dynamic properties in 4.0 payloads.

### [3.5 Built-In Types for defining Vocabulary Terms](#)

[Vocabulary terms](#) can, in addition, use

- `Edm.AnnotationPath`
- `Edm.PropertyPath`
- `Edm.NavigationPropertyPath`
- `Edm.AnyPropertyPath` (`Edm.PropertyPath` Or `Edm.NavigationPropertyPath`)
- `Edm.ModelElementPath` (any model element, including `Edm.AnnotationPath`, `Edm.NavigationPropertyPath`, and `Edm.PropertyPath`)

as the type of a primitive term, or the type of a property of a complex type (recursively) that is exclusively used as the type of a term. See section "[Path Expressions](#)" for details.

### [3.6 Annotations](#)

Many parts of the model can be decorated with additional information using [annotations](#). Annotations are identified by their term name and an optional qualifier that allows applying the same term multiple times to the same model element.

A model element **MUST NOT** specify more than one annotation for a given combination of term and qualifier.

## 4 CSDL XML Document

::: {.varxml .rep}

### Element `edm:Edmx`

The `edm:Edmx` element is the root element of a CSDL XML document. It MUST contain the `Version` attribute and it MUST contain exactly one `edm:DataServices` element.

It MAY contain [`edm:Reference`](#) elements to reference other CSDL documents.

### Attribute `Version`

The `Version` attribute specifies the OData protocol version of the service. For OData 4.0 responses the value of this attribute MUST be 4.0. For OData 4.01 responses the value of this attribute MUST be 4.01. Services MUST return an OData 4.0 response if the request was made with an `OData-MaxVersion` header with a value of 4.0.

### Element `edm:DataServices`

The `edm:DataServices` element MUST contain one or more [`edm:Schema`](#) elements which define the schemas exposed by the OData service. :::

Example 2:

```
<edm:Edmx xmlns:edm="http://docs.oasis-open.org/odata/ns/edm"
  Version="4.01">
  <edm:DataServices>
    ...
  </edm:DataServices>
</edm:Edmx>
```

## 4.1 Reference

A reference to an external CSDL document allows to bring part of the referenced document's content into the scope of the referencing document.

A reference MUST specify a URI that uniquely identifies the referenced document, so two references MUST NOT specify the same URI. The URI SHOULD be a URL that locates the referenced document. If the URI is not dereferencable it SHOULD identify a well-known schema. The URI MAY be absolute or relative URI; relative URLs are relative to the URL of the document containing the reference, or relative to a base URL specified in a format-specific way.

A reference MAY be annotated.

The [`Core.SchemaVersion`](#) annotation, defined in [\[OData-VocCore\]](#), MAY be used to indicate a particular version of the referenced document. If the [`Core.SchemaVersion`](#) annotation is present, the `$schemaversion` system query option, defined [\[OData-Protocol\]](#), SHOULD be used when retrieving the referenced schema document.

## Element `edm:Reference`

The `edm:Reference` element specifies external CSDL documents referenced by the referencing document. The child elements [`edm:Include`](#) and [`edm:IncludeAnnotations`](#) specify which parts of the referenced document are available for use in the referencing document.

The `edm:Reference` element MUST contain the `Uri` attribute, and it MUST contain at least one [`edm:Include`](#) or [`edm:IncludeAnnotations`](#) child element.

It MAY contain [`edm:Annotation`](#) elements.

## Attribute `Uri`

The value of `Uri` is an absolute or relative URI; relative URIs are relative to the `xml:base` attribute, see [\[XML-Base\]](#).

*Example 3: references to other CSDL documents*

```
<?xml version="1.0" encoding="UTF-8" standalone="yes"?>
<edm:Edmx xmlns:edm="http://docs.oasis-open.org/odata/ns/edm"
  Version="4.0">
  <edm:Reference Uri="http://vocabs.odata.org/capabilities/v1">
    ...
  </edm:Reference>
  <edm:Reference Uri="http://vocabs.odata.org/core/v1">
    ...
  </edm:Reference>
  <edm:Reference Uri="http://example.org/display/v1">
    ...
  </edm:Reference>
  <edm:DataServices>...</edm:DataServices>
</edm:Edmx>
```

## 4.2 Included Schema

A reference MAY include zero or more schemas from the referenced document.

The included schemas are identified via their [namespace](#). The same namespace MUST NOT be included more than once, even if it is declared in more than one referenced document.

When including a schema, a [simple identifier](#) value MAY be specified as an alias for the schema that is used in qualified names instead of the namespace. For example, an alias of `display` might be assigned to the namespace `org.example.vocabularies.display`. An alias-qualified name is resolved to a fully qualified name by examining aliases for included schemas and schemas defined within the document.

If an included schema specifies an alias, the alias MAY be used instead of the namespace within qualified names to identify model elements of the included schema. An alias only provides a more convenient notation, allowing a short string to be substituted for a long

namespace. Every model element that can be identified via an alias-qualified name can alternatively be identified via its full namespace-qualified name.

Aliases are document-global, so all schemas defined within or included into a document **MUST** have different aliases, and aliases **MUST** differ from the namespaces of all schemas defined within or included into a document.

The alias **MUST NOT** be one of the reserved values `Edm`, `odata`, `System`, or `Transient`.

An alias is only valid within the document in which it is declared; a referencing document may define its own aliases for included schemas.

### **Element `edm:Include`**

The `edm:Include` element specifies a schema to include from the referenced CSDL document. It **MUST** provide the `Namespace` attribute and it **MAY** provide the `Alias` attribute.

It **MAY** contain [`edm:Annotation`](#) elements.

### **Attribute `Namespace`**

The value of `Namespace` is the namespace of a schema defined in the referenced CSDL document.

### **Attribute `Alias`**

The value of `Alias` is a [simple identifier](#) that can be used in qualified names instead of the namespace.

*Example 4: references to entity models containing definitions of vocabulary terms*

```
<?xml version="1.0" encoding="UTF-8" standalone="yes"?>
<edm:Edmx xmlns:edm="http://docs.oasis-open.org/odata/ns/edm"
  Version="4.0">
  <edm:Reference Uri="http://vocabs.odata.org/capabilities/v1">
    <edm:Include Namespace="Org.OData.Capabilities.V1" />
  </edm:Reference>
  <edm:Reference Uri="http://vocabs.odata.org/core/v1">
    <edm:Include Namespace="Org.OData.Core.V1" Alias="Core">
      <Annotation Term="Core.DefaultNamespace" />
    </edm:Include>
  </edm:Reference>
  <edm:Reference Uri="http://example.org/display/v1">
    <edm:Include Alias="UI" Namespace="org.example.display" />
  </edm:Reference>
  <edm:DataServices>...</edm:DataServices>
</edm:Edmx>
```

## **4.3 Included Annotations**

In addition to including whole schemas with all model constructs defined within that schema, annotations can be included with more flexibility.

Annotations are selectively included by specifying the [namespace](#) of the annotations' term. Consumers can opt not to inspect the referenced document if none of the term namespaces is of interest for the consumer.

In addition, the [qualifier](#) of annotations to be included MAY be specified. For instance, a service author might want to supply a different set of annotations for various device form factors. If a qualifier is specified, only those annotations from the specified term namespace with the specified qualifier (applied to a model element of the target namespace, if present) SHOULD be included. If no qualifier is specified, all annotations within the referenced document from the specified term namespace (taking into account the target namespace, if present) SHOULD be included.

The qualifier also provides consumers insight about what qualifiers are present in the referenced document. If the consumer is not interested in that particular qualifier, the consumer can opt not to inspect the referenced document.

In addition, the namespace of the annotations' [target](#) MAY be specified. If a target namespace is specified, only those annotations which apply a term from the specified term namespace to a model element of the target namespace (with the specified qualifier, if present) SHOULD be included. If no target namespace is specified, all annotations within the referenced document from the specified term namespace (taking into account the qualifier, if present) SHOULD be included.

The target namespace also provides consumers insight about what namespaces are present in the referenced document. If the consumer is not interested in that particular target namespace, the consumer can opt not to inspect the referenced document.

### **[Element edm:IncludeAnnotations](#)**

The `edm:IncludeAnnotations` element specifies the annotations to include from the referenced CSDL document. If no `edm:IncludeAnnotations` element is specified, a client MAY ignore all annotations in the referenced document that are not explicitly used in an [edm:Path](#) expression of the referencing document.

The `edm:IncludeAnnotations` element MUST provide the `TermNamespace` attribute, and it MAY provide the `Qualifier` and `TargetNamespace` attribute.

### **[Attribute TermNamespace](#)**

The value of `TermNamespace` is a namespace.

### **[Attribute Qualifier](#)**

The value of `Qualifier` is a [simple identifier](#).

### **[Attribute TargetNamespace](#)**

The value of `TargetNamespace` is a namespace.

*Example 5: reference documents that contain annotations*

```
<?xml version="1.0" encoding="UTF-8" standalone="yes"?>
<edm:Edmx xmlns:edm="http://docs.oasis-open.org/odata/ns/edm">
```



```

    Version="4.0">
  <edmx:Reference Uri="http://odata.org/ann/b">
    <edmx:IncludeAnnotations TermNamespace="org.example.validation" />
    <edmx:IncludeAnnotations TermNamespace="org.example.display"
      Qualifier="Tablet" />
    <edmx:IncludeAnnotations TermNamespace="org.example.hcm"
      TargetNamespace="com.example.Sales" />
    <edmx:IncludeAnnotations TermNamespace="org.example.hcm"
      Qualifier="Tablet"
      TargetNamespace="com.example.Person" />
  </edmx:Reference>
  <edmx:DataServices>...</edmx:DataServices>
</edmx:Edmx>

```

The following annotations from `http://odata.org/ann/b` are included:

- Annotations that use a term from the `org.example.validation` namespace, and
- Annotations that use a term from the `org.example.display` namespace and specify a `Tablet` qualifier and
- Annotations that apply a term from the `org.example.hcm` namespace to an element of the `com.example.Sales` namespace and
- Annotations that apply a term from the `org.example.hcm` namespace to an element of the `com.example.Person` namespace and specify a `Tablet` qualifier.

## 5 Schema

One or more schemas describe the entity model exposed by an OData service. The schema acts as a namespace for elements of the entity model such as entity types, complex types, enumerations and terms.

A schema is identified by a [namespace](#). Schema namespaces **MUST** be unique within the scope of a document and **SHOULD** be globally unique. A schema cannot span more than one document.

The schema's namespace is combined with the name of elements in the schema to create unique [qualified names](#), so identifiers that are used to name types **MUST** be unique within a namespace to prevent ambiguity.

Names are case-sensitive, but service authors **SHOULD NOT** choose names that differ only in case.

The namespace **MUST NOT** be one of the reserved values `Edm`, `odata`, `System`, or `Transient`.

### **[Element edm:Schema](#)**

The `edm:Schema` element defines a schema. It **MUST** contain the `Namespace` attribute and it **MAY** contain the `Alias` attribute.

It **MAY** contain elements [edm:Action](#), [edm:Annotations](#), [edm:Annotation](#), [edm:ComplexType](#), [edm:EntityContainer](#), [edm:EntityType](#), [edm:EnumType](#), [edm:Function](#), [edm:Term](#), or [edm:TypeDefinition](#).

### **[Attribute Namespace](#)**

The value of `Namespace` is the namespace of the schema

### 5.1 Alias

A schema **MAY** specify an alias which **MUST** be a [simple identifier](#).

If a schema specifies an alias, the alias **MAY** be used instead of the namespace within qualified names to identify model elements of that schema. An alias only provides a more convenient notation, allowing a short string to be substituted for a long namespace. Every model element that can be identified via an alias-qualified name can alternatively be identified via its full namespace-qualified name.

Aliases are document-global, so all schemas defined within or included into a document **MUST** have different aliases, and aliases **MUST** differ from the namespaces of all schemas defined within or included into a document. Aliases defined by a schema can be used throughout the containing document and are not restricted to the schema that defines them.

The alias **MUST NOT** be one of the reserved values `Edm`, `odata`, `System`, or `Transient`.

### **[Attribute Alias](#)**

The value of `Alias` is a [simple identifier](#).

Example 6: schema org.example with an alias and a description for the schema

```
<Schema Namespace="org.example" Alias="self">
  <Annotation Term="Core.Description" String="Example schema" />
  ...
</Schema>
```

## 5.2 Annotations with External Targeting

### Element `edm:Annotations`

The `edm:Annotations` element is used to apply a group of annotations to a single model element. It MUST contain the `Target` attribute and it MAY contain the `Qualifier` attribute.

It MUST contain at least one [edm:Annotation](#) element.

### Attribute `Target`

The value of `Target` is a path expression identifying the [annotation target](#). It MUST resolve to a model element in scope.

### Attribute `Qualifier`

The value of `Qualifier` is a [simple identifier](#).

Example 7: annotations should only be applied to tablet devices

```
<Annotations Target="org.example.Person" Qualifier="Tablet">
  <Annotation Term="Core.Description" String="Dummy" />
  ...
</Annotations>
```

## Appendix A. References

This appendix contains the normative and informative references that are used in this document.

While any hyperlinks included in this appendix were valid at the time of publication, OASIS cannot guarantee their long-term validity.

### A.1 Normative References

The following documents are referenced in such a way that some or all of their content constitutes requirements of this document.

#### **[OData-v4.02]**

- *OData Version 4.02*. Edited by Michael Pizzo, Ralf Handl, and Heiko Theißen. A multi-part Work Product that includes:
  - *OData Version 4.02 Part 1: Protocol*. Latest stage. <https://docs.oasis-open.org/odata/odata/v4.02/odata-v4.02-part1-protocol.html>
  - *OData Version 4.02 Part 2: URL Conventions*. Latest stage. <https://docs.oasis-open.org/odata/odata/v4.02/odata-v4.02-part2-url-conventions.html>

#### **[ECMAScript]**

*ECMAScript 2016 Language Specification, 7th Edition*. June 2016. Standard ECMA-262.  
<http://www.ecma-international.org/publications/standards/Ecma-262.htm>.

#### **[EPSG]**

*European Petroleum Survey Group (EPSG)*. [http://www.epsg.org/#####](http://www.epsg.org/) [RFC7493] Bray, T., Ed., "The I-JSON Message Format", RFC7493, March 2015.  
<https://tools.ietf.org/html/rfc7493.#####> [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, DOI 10.17487/RFC2119, March 1997.  
<http://www.rfc-editor.org/info/rfc2119>.

#### **[OData-ABNF]**

*OData ABNF Construction Rules Version 4.01*.  
See link in "[Additional artifacts](#)" section on cover page.

#### **[OData-CSDL-Schema]**

*OData CSDL JSON Schema*.  
See link in "[Related work](#)" section on cover page.

#### **[OData-CSDL-JSON]**

*OData Common Schema Definition Language (CSDL) JSON Representation Version 4.01*.  
See link in "[Related work](#)" section on cover page.

**[OData-CSDL-XML]**

*OData Common Schema Definition Language (CSDL) XML Representation Version 4.01.*

See link in "[Related work](#)" section on cover page.

**[OData-EDM]**

*OData EDM XML Schema.*

See link in "[Additional artifacts](#)" section on cover page.

**[OData-EDMX]**

*OData EDM XML Schema.*

See link in "[Additional artifacts](#)" section on cover page.

**[OData-JSON]**

*OData JSON Format Version 4.01.*

See link in "[Related work](#)" section on cover page.

**[OData-Protocol]**

*OData Version 4.01 Part 1: Protocol.*

See link in "[Related work](#)" section on cover page.

**[OData-URL]**

*OData Version 4.01 Part 2: URL Conventions.*

See link in "[Related work](#)" section on cover page.

**[OData-VocCore]**

*OData Vocabularies Version 4.0: Core Vocabulary.*

See link in "[Related work](#)" section on cover page.

**[OData-VocMeasures]**

*OData Vocabularies Version 4.0: Measures Vocabulary.*

See link in "[Related work](#)" section on cover page.

**[OData-VocValidation]**

*OData Vocabularies Version 4.0: Validation Vocabulary.*

See link in "[Related work](#)" section on cover page.##### [RFC6570] Gregorio, J., Fielding, R., Hadley, M., Nottingham, M., and D. Orchard, "URI Template", RFC 6570, March 2012.

<http://tools.ietf.org/html/rfc6570>.

**[RFC2119]**

Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, DOI 10.17487/RFC2119, March 1997.

<https://www.rfc-editor.org/info/rfc2119>.

**[RFC6570]**

Gregorio, J., Fielding, R., Hadley, M., Nottingham, M., and D. Orchard, "URI Template", RFC 6570, March 2012.

<http://tools.ietf.org/html/rfc6570>.

**[RFC8174]**

Leiba, B., "Ambiguity of Uppercase vs Lowercase in RFC 2119 Key Words", BCP 14, RFC 8174, DOI 10.17487/RFC8174, May 2017.

<http://www.rfc-editor.org/info/rfc8174>.

**[RFC8259]**

Bray, T., Ed., "The JavaScript Object Notation (JSON) Data Interchange Format", RFC 8259, December 2017.

<http://tools.ietf.org/html/rfc8259>.

**[XML-1.1]**

*Extensible Markup Language (XML) 1.1 (Second Edition)*. F. Yergeau, E. Maler, J. Cowan, T. Bray, C. M. Sperberg-McQueen, J. Paoli, Editors, W3C Recommendation, 16 August 2006.

<http://www.w3.org/TR/2006/REC-xml11-20060816>. Latest version available at <http://www.w3.org/TR/xml11/>.

**[XML-Base]**

*XML Base (Second Edition)*. J. Marsh, R. Tobin, Editors, W3C Recommendation, 28 January 2009.

<http://www.w3.org/TR/2009/REC-xmlbase-20090128/>. Latest version available at <http://www.w3.org/TR/xmlbase/>.

**[XML-Schema-1]**

*W3C XML Schema Definition Language (XSD) 1.1 Part 1: Structures*. D. Beech, M. Maloney, C. M. Sperberg-McQueen, H. S. Thompson, S. Gao, N. Mendelsohn, Editors, W3C Recommendation, 5 April 2012.

<http://www.w3.org/TR/2012/REC-xmlschema11-1-20120405/>. Latest version available at <http://www.w3.org/TR/xmlschema11-1/>.

**[XML-Schema-2]**

*W3C XML Schema Definition Language (XSD) 1.1 Part 2: Datatypes*. D. Peterson, S. Gao, C. M. Sperberg-McQueen, H. S. Thompson, P. V. Biron, A. Malhotra, Editors, W3C Recommendation, 5 April 2012.

<http://www.w3.org/TR/2012/REC-xmlschema11-2-20120405/>. Latest version available at <http://www.w3.org/TR/xmlschema11-2/>.

**A.2 Informative References****[OpenUI5]**

*OpenUI5 Version 1.40.10 - OData V4 Metadata JSON Format*.

<https://openui5.hana.ondemand.com/1.40.10/#docs/guide/87aac894a40640f89920d7b2a414499b.html>.

## Appendix B. Table of XML Elements and Attributes

Element `edm:Edmx`

Attribute `Version`

Element `edm:DataServices`

Element `edm:Reference`

Attribute `Uri`

Element `edm:Include`

Attribute `Namespace`

Attribute `Alias`

Element `edm:IncludeAnnotations`

Attribute `TermNamespace`

Attribute `Qualifier`

Attribute `TargetNamespace`

Element `edm:Schema`

Attribute `Namespace`

Attribute `Alias`

Element `edm:Annotations`

Attribute `Target`

Attribute `Qualifier`

## Appendix C. Acknowledgments

Note: A Work Product approved by the TC must include a list of people who participated in the development of the Work Product. This is generally done by collecting the list of names in this appendix. This list shall be initially compiled by the Chair, and any Member of the TC may add or remove their names from the list by request. Remove this note before submitting for publication.

### C.1 Special Thanks

Substantial contributions to this document from the following individuals are gratefully acknowledged:

Participant Name, Affiliation or "Individual Member"

### C.2 Participants

The following individuals have participated in the creation of this specification and are gratefully acknowledged:

#### **OpenC2 TC Members:**

| First Name | Last Name  | Company            |
|------------|------------|--------------------|
| Philippe   | Alman      | Something Networks |
| Alex       | Amirnovman | Company B          |
| Kris       | Anderman   | Mini Micro         |
| Darren     | Anstman    | Big Networks       |



## Appendix D. Revision History

| Revision           | Date       | Editor      | Changes Made          |
|--------------------|------------|-------------|-----------------------|
| specname-v1.0-wd01 | yyyy-mm-dd | Editor Name | Initial working draft |

## Appendix E. Notices

Copyright © OASIS Open 2023. All Rights Reserved.

All capitalized terms in the following text have the meanings assigned to them in the OASIS Intellectual Property Rights Policy (the "OASIS IPR Policy"). The full [Policy](#) may be found at the OASIS website.

This document and translations of it may be copied and furnished to others, and derivative works that comment on or otherwise explain it or assist in its implementation may be prepared, copied, published, and distributed, in whole or in part, without restriction of any kind, provided that the above copyright notice and this section are included on all such copies and derivative works. However, this document itself may not be modified in any way, including by removing the copyright notice or references to OASIS, except as needed for the purpose of developing any document or deliverable produced by an OASIS Technical Committee (in which case the rules applicable to copyrights, as set forth in the OASIS IPR Policy, must be followed) or as required to translate it into languages other than English.

The limited permissions granted above are perpetual and will not be revoked by OASIS or its successors or assigns.

This document and the information contained herein is provided on an "AS IS" basis and OASIS DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE INFORMATION HEREIN WILL NOT INFRINGE ANY OWNERSHIP RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

As stated in the OASIS IPR Policy, the following three paragraphs in brackets apply to OASIS Standards Final Deliverable documents (Committee Specification, OASIS Standard, or Approved Errata).

[OASIS requests that any OASIS Party or any other party that believes it has patent claims that would necessarily be infringed by implementations of this OASIS Standards Final Deliverable, to notify OASIS TC Administrator and provide an indication of its willingness to grant patent licenses to such patent claims in a manner consistent with the IPR Mode of the OASIS Technical Committee that produced this deliverable.]

[OASIS invites any party to contact the OASIS TC Administrator if it is aware of a claim of ownership of any patent claims that would necessarily be infringed by implementations of this OASIS Standards Final Deliverable by a patent holder that is not willing to provide a license to such patent claims in a manner consistent with the IPR Mode of the OASIS Technical Committee that produced this OASIS Standards Final Deliverable. OASIS may include such claims on its website, but disclaims any obligation to do so.]

[OASIS takes no position regarding the validity or scope of any intellectual property or other rights that might be claimed to pertain to the implementation or use of the technology described in this OASIS Standards Final Deliverable or the extent to which any license under such rights might or might not be available; neither does it represent that it has made any effort to identify any such rights. Information on OASIS' procedures with respect to rights in any document or deliverable produced by

an OASIS Technical Committee can be found on the OASIS website. Copies of claims of rights made available for publication and any assurances of licenses to be made available, or the result of an attempt made to obtain a general license or permission for the use of such proprietary rights by implementers or users of this OASIS Standards Final Deliverable, can be obtained from the OASIS TC Administrator. OASIS makes no representation that any information or list of intellectual property rights will at any time be complete, or that any claims in such list are, in fact, Essential Claims.]

The name "OASIS" is a trademark of [OASIS](https://www.oasis-open.org/), the owner and developer of this specification, and should be used only to refer to the organization and its official outputs. OASIS welcomes reference to, and implementation and use of, specifications, while reserving the right to enforce its marks against misleading uses. Please see <https://www.oasis-open.org/policies-guidelines/trademark/> for above guidance.