


Chapter 7: Synchronization Examples





Chapter 7: Synchronization Examples

- Explain the bounded-buffer, readers-writers, and dining philosophers synchronization problems.
- Describe the tools used by Linux and Windows to solve synchronization problems.
- Illustrate how POSIX and Java can be used to solve process synchronization problems.





Classical Problems of Synchronization

- Classical problems used to test newly-proposed synchronization schemes
 - Bounded-Buffer Problem
 - Readers and Writers Problem
 - Dining-Philosophers Problem





Bounded-Buffer Problem

- n buffers, each can hold one item
- Semaphore **mutex** initialized to the value 1
- Semaphore **full** initialized to the value 0
- Semaphore **empty** initialized to the value n





Bounded Buffer Problem (Cont.)

- The structure of the producer process

```
while (true) {  
    ...  
    /* produce an item in next_produced */  
    ...  
    wait(empty);  
    wait(mutex);  
    ...  
    /* add next produced to the buffer */  
    ...  
    signal(mutex);  
    signal(full);  
}
```





Bounded Buffer Problem (Cont.)

- The structure of the consumer process

```
while (true) {  
    wait(full);  
    wait(mutex);  
    ...  
    /* remove an item from buffer to next_consumed */  
    ...  
    signal(mutex);  
    signal(empty);  
    ...  
    /* consume the item in next consumed */  
    ...  
}
```





Readers-Writers Problem

- A data set is shared among a number of concurrent processes
 - **Readers** – only read the data set; they do ***not*** perform any updates
 - **Writers** – can both read and write
- Problem – allow multiple readers to read at the same time
 - Only one single writer can access the shared data at the same time
- Several variations of how readers and writers are considered – all involve some form of priorities
- Shared Data
 - Data set
 - Semaphore **rw_mutex** initialized to 1
 - Semaphore **mutex** initialized to 1
 - Integer **read_count** initialized to 0





Readers-Writers Problem (Cont.)

- The structure of a writer process

```
while (true) {  
    wait(rw_mutex);  
  
    ...  
    /* writing is performed */  
    ...  
    signal(rw_mutex);  
}
```





Readers-Writers Problem (Cont.)

- The structure of a reader process

```
while (true){
    wait(mutex);
    read_count++;
    if (read_count == 1)
        wait(rw_mutex);
    signal(mutex);

    ...
    /* reading is performed */
    ...

    wait(mutex);
    read_count--;
    if (read_count == 0)
        signal(rw_mutex);
    signal(mutex);
}
```






Readers-Writers Problem Variations

- **First** variation – no reader kept waiting unless writer has permission to use shared object
- **Second** variation – once writer is ready, it performs the write ASAP
- Both may have starvation leading to even more variations
- Problem is solved on some systems by kernel providing reader-writer locks





Dining-Philosophers Problem



- Philosophers spend their lives alternating thinking and eating
- Don't interact with their neighbors, occasionally try to pick up 2 chopsticks (one at a time) to eat from bowl
 - Need both to eat, then release both when done
- In the case of 5 philosophers
 - Shared data
 - ▶ Bowl of rice (data set)
 - ▶ Semaphore **chopstick** [5] initialized to 1





Dining-Philosophers Problem Algorithm

- Semaphore Solution
- The structure of Philosopher *i*:

```
while (true){  
    wait (chopstick[i] );  
    wait (chopstick[ (i + 1) % 5] );  
  
    /* eat for awhile */  
  
    signal (chopstick[i] );  
    signal (chopstick[ (i + 1) % 5] );  
  
    /* think for awhile */  
  
}
```

- What is the problem with this algorithm?





Monitor Solution to Dining Philosophers

```
monitor DiningPhilosophers
{
    enum { THINKING, HUNGRY, EATING} state [5] ;
    condition self [5];

    void pickup (int i) {
        state[i] = HUNGRY;
        test(i);
        if (state[i] != EATING) self[i].wait;
    }

    void putdown (int i) {
        state[i] = THINKING;
        // test left and right neighbors
        test((i + 4) % 5);
        test((i + 1) % 5);
    }
}
```





Solution to Dining Philosophers (Cont.)

```
void test (int i) {
    if ((state[(i + 4) % 5] != EATING) &&
        (state[i] == HUNGRY) &&
        (state[(i + 1) % 5] != EATING) ) {
        state[i] = EATING ;
        self[i].signal () ;
    }
}

initialization_code() {
    for (int i = 0; i < 5; i++)
        state[i] = THINKING;
}
}
```





Solution to Dining Philosophers (Cont.)

- Each philosopher i invokes the operations `pickup()` and `putdown()` in the following sequence:

```
DiningPhilosophers.pickup(i) ;
```

```
/** EAT **/
```

```
DiningPhilosophers.putdown(i) ;
```

- No deadlock, but starvation is possible

