



Darktrace Connector — Credential Provisioning Guide

Version 0.1.0, 2026-08-31

Table of Contents

Overview.....	1
What kind of account to create.....	1
Permissions to grant	1
Generating the credential.....	1
Mapping values into Crogl.....	2
Verifying the setup.....	2

Overview

The draft Crogl Darktrace connector requires a Darktrace appliance host and one Darktrace API token pair: a public token and a private token. Darktrace requires a per-request HMAC-SHA1 signature in addition to the token pair. This guide is based only on the supplied Darktrace API documentation and has not been verified against a live customer console. A Darktrace administrator or local Threat Visualizer administrator should perform the vendor-side steps.

IMPORTANT

The connector remains **draft** because no Darktrace test environment is available. Crogl main now provides the server-side **darktrace_hmac** request-signing provider, and this connector declares it. Do not mark the connector field-tested until a signed request succeeds against a real instance.

What kind of account to create

Darktrace's documented per-user token flow uses a local user created in Threat Visualizer. API tokens are not available to users created through LDAP or SAML SSO. A global token can instead be created by a user who can modify the Threat Visualizer System Config page, but per-user tokens are preferred because their permissions are restricted to those of the associated user.

Permissions to grant

For a per-user token:

1. In Threat Visualizer, open **Main Menu > Admin > Permissions Admin**.
2. Select the **Created Accounts** tab.
3. Locate the intended local user and choose the edit (pen) control.
4. On the **Flags** step, enable **API Access** and save.
5. Grant only the Darktrace UI permissions needed for the read-only API surfaces that will be used. The supplied documentation lists endpoint-specific requirements; for example, **/modelbreaches** requires **Unrestricted Devices** and one of **Visualizer**, **Darktrace / IDENTITY Console**, **View Models**, or **Edit Models**.

Verify the exact permission names against the customer's Darktrace version. Do not grant write permissions for a read-only connector.

Generating the credential

1. Sign in as the local API-enabled user.
2. Open **Account Settings** from the main menu.
3. Locate **API Access** and select **New**.
4. Record the displayed public and private token values in an approved secret store. The private token is not displayed again.

- Record the appliance hostname or IP address separately. Do not include `https://` or an API path in the host value.

If using a global token instead, a user with access to System Config can open **Settings**, locate the **API Token** section, choose **New**, and securely record both displayed values. The supplied documentation recommends per-user tokens rather than global tokens when least privilege is required.

Mapping values into Crogl

||=== || Crogl field | Where it came from | Notes

|| `host` || The Darktrace appliance hostname or IP address || Enter the host only; omit the scheme and path. Use the optional TLS checkbox only when the appliance certificate requires it and the exception is approved.

|| `public_token` || The public value from the Darktrace API token pair || Treat it as a secret and do not place it in chat, tickets, or source files.

|| `private_token` || The private value displayed when the token pair was created || Treat it as a high-sensitivity secret. It cannot be recovered from Darktrace after the creation screen is closed.

|| `skip_tls_verification` || A deployment decision, not a Darktrace credential || Leave disabled unless the appliance uses a self-signed or otherwise untrusted certificate and the exception is approved. ||===

Verifying the setup

Crogl main now provides the server-side signing integration. After creating the connector, run a small read-only request such as `GET /status?fast=true&includechildren=false` or a narrow `/modelbreaches` query. A real Darktrace test environment is still required before changing the connector status.

A valid Darktrace request must include:

- `D-API-Token` containing the public token.
- `D-API-Date` containing a UTC date accepted by Darktrace and within 30 minutes of the instance system time.
- `D-API-Signature` containing the HMAC-SHA1 value calculated from the exact endpoint path and query, a newline, the public token, another newline, and the same date.

The host must not be included in the signed string. If query parameters are changed, the signature must be regenerated.

- HTTP 200:** the request was accepted; an empty result may still be a valid successful query.
- Authentication/signature rejection:** verify the public/private pair, exact path and query, matching date value, UTC clock, and the 30-minute clock tolerance.

- **Permission failure:** the token authenticated but its associated Darktrace user lacks the permission required by the endpoint.
- **TLS failure:** verify the host and certificate. Do not disable verification as a general workaround.
- **HTTP 400:** correct malformed or unsupported parameters; do not retry unchanged.

Do not use the credential examples printed in vendor documentation. They are examples only and must never be entered into Crogl.