week 8 lab

Pass

From the output of the show interfaces trunk command in the previous step, what is the current native VLAN for the S1 F0/5 trunk interface?

- the native vlan was vlan 1

The following message should display after a brief period of time:

```
02:16:28: %CDP-4-NATIVE_VLAN_MISMATCH: Native VLAN mismatch discovered on
FastEthernet0/5 (99), with S2 FastEthernet0/5 (1).
```

What does the message mean?

- The native VLAN does not match at both ends on the trunk, this has happened because S2 is still using native vlan 1 where as S1 is using VLAN99

What appened to the message?

- setting S2's native vlan to VLAN99

What is the MAC address of the R1 G0/0/1 interface?

- 706e.6d2a.9eal

On S1, issue the show port-security

- What is the Security Violation Count?
  - 1
- What is the status of the F0/5 port?
  - Secure-up
- What is the Last Source Address and VLAN?
  - 0000.0000.0000:0

From the R1 CLI, ping PC-A. Was the ping successful? Explain.

- No, the port on S1 has been put into err disabled state as the mac address specified is not present.

From R1, try to ping the PC-A again at 192.168.1.10. Was the ping successful? Explain.

- No, the port is still in the err disabled state and needs to be manualy enabled.

Credit

Which command is used to verify that a port is protected?

```
show interfaces [interface-id] switchport
```

Which command is used to de-activate the PVLAN Edge feature?

```
int [interface-id]
no switchport protected
```