DLS Lab annual seminar

Octavio Villarreal

March 16, 2017

Istituto Italiano di Tecnologia

Outline

1. Introduction

2. Master thesis: "Dynamic control of 3D directional drilling systems using state estimation"

3. Research proposal: "Locomotion control of HyQ using max-plus algebra linear systems"

Introduction

About me

Octavio Antonio Villarreal Magaña

- MSc. Mechanical Engineering, track Control Engineering (TUDelft, The Netherlands)

- BSc. Mechatronic Engineering (UNAM, Mexico)

- Research interests:
  - Control Methods for Robotics
  - Robust Control

Master thesis: ”Dynamic control of 3D directional drilling systems using state estimation”

Dynamic control of 3D directional drilling systems

- Challenging dynamic system
- Interesting robustness problem (not addressed here)
- Collaboration between researchers of TU Delft, TU Eindhoven and the University of Minnesota

Applications of directional drilling





- Extract oil, mineral and thermal energy resources
- Reach targets that need complex geometries such as:
  - Under a city or an ecosystem
  - Far from the drill rig
  - Relief for hazardous situations

General description of the system



Rotary Steerable System (RSS)



BHA: Bottom hole assembly

Context and challenges



[Sugiura 2009]

- State-of-practice: constant RSS force (open loop)
- Negative effects: kinking, rippling and spiraling
- Consequences of negative effects: reduced penetration rate and accuracy

Research goal

Develop a control strategy for a 3D directional drilling system, that allows to drill boreholes with complex geometries, while avoiding undesired behaviors.

Mathematical model charateristics

- Function of borehole length (ξ)
- Model form: nonlinearly coupled delay differential equations (delays: drillstring should fit in already drilled borehole)
- States: borehole inclination (Θ) and azimuth (Φ) at the bit
- Inputs: RSS actuator forces (Γ_Θ and Γ_Φ)
- No access to measurements of the states (output equations y_Θ and y_Φ)



Available measurements



Control objectives

- Track a desired reference trajectory corresponding to a complex borehole geometry
- The response of the system should have favorable transient behavior (avoid kinking, rippling and spiraling)
- Rely only on local measurements

Output-feedback strategy



- Focus of the research: Implement observer-based control strategy

- Challenges
  - Nonlinear coupling between states while $\Theta \neq \check{\Theta}$
  - Controller and observer gain design

$e_i := i_r - i \qquad \delta_i := i - \check{i}_i \qquad \text{for } i = \Theta, \Phi$

Controller synthesis

- Define isolated systems e_Θ, δ_Θ, e_Φ and δ_Φ
- Synthesize controller and observer gains for each isolated system separately
- Favorable transient performance



Controller synthesis

- Infinite number of poles in delay systems (no pole-placement)
- Spectral approach [Michiels and Niculescu 2007]
- Optimize location of right-most pole over K_i (state-feedback gains) and L_i (observer-feedback gains)



Simulation results





Research proposal: ”Locomotion control of HyQ using max-plus algebra linear systems”

Motivation

- Provide versatility to the types of gaits that the robot can perform
- Have a unified and systematic way to generate motions of the legs according to the scenario
- Can be applied to other legged systems

General picture



General picture



Supervisory controller

Main goal

Decide **geometrical** and **time** gait parameters, based on sensory data, to overcome the scenario that the robot is facing.



Geometrical parameters

- Not necessarily the same for all four legs
- Examples of trajectory parameters:
  - Oscillator shape parameters [Barasuol et.al. 2013]
  - Control points of a Bézier (spline) curve [Hyun et.al. 2014]





Supervisory controller (continue)

Time parameters:

- Duty factor D_f
- Step frequency S_f
- Gait parameterization G (e.g., $G_{trot} = \{1, 4\} \prec \{2, 3\}$)
- Time difference vector Δ







Main goal

Using the **time**-related gait parameters provided by the supervisory controller, generate the times that each leg has to touch or leave the ground.



Max-plus gait scheduler (continue)



$$G_{trot} = \{1, 4\} \prec \{2, 3\}$$
$$D_f = 0.58$$
$$S_f = 0.42$$
$$\Delta = [0.2, 0.2]$$

k	$g_1(k)$	$g_2(k)$	$g_3(k)$	$g_4(k)$	$l_1(k)$	$l_2(k)$	$l_3(k)$	$l_4(k)$
0	0	0	0	0	0	0	0	0
1	2.4	3.6	3.6	2.4,	1.4	2.6	2.6	1.4
2	4.8	6	6	4.8	3.8	5	5	3.8
3	7.2	8.4	8.4	7.2	6.2	7.4	7.4	6.2
4	9.6	10.8	10.8	9.6	8.6	9.8	9.8	8.6
5	12	13.2	13.2	12	11	12.2	12.2	11

Max-plus gait scheduler (continue)

- Systematic coordinated gait generation
- Total cycle time analysis (max-plus linear systems theory)
- Coupling time analysis ("settling time")
- Not computationally expensive

Main goal

Making use of the **touchdown** and **lift-off** times of the max-plus gait scheduler, provide a reference trajectory for each of the legs.



Simulation

Change of parameters every 20 seconds



Thank you. Questions or comments?



Group members:

- Claudio Semini
- Alex Oleg Posatskiy
- Yannick Berdou
- Yifu Gao
- Michele Focchi
- Victor Barasuol
- Romeo Orsolino
- Andreea Radulescu
- Carlos Mastalli
- Marco Camurri
- Marco Frigerio
- Roy Featherstone
- Josephus Driessen
- Antonios Gkikakis
- Roodra P. Singh B.