Software Requirements Specification (SRS v2.0)

AURA: Artisan Kitchen & Modern Botanica

Client-Server Architecture (React Native, Node.js, Express, MongoDB)

Document Version: 2.0.0 (Assignment 2 Submission)
Academic Term: Fall 2026
Course: Mobile Application Development (CS-375)
Student Name: Syed Obaid Ali | **Roll Number:** 9321
Instructor: Dr. Sadaf Tanvir

Executive Summary & Problem Resolution

In **Assignment 1 (A1)**, the AURA Restaurant Application operated strictly as a standalone mobile MVP. All business records—menu catalogs, patron profiles, cart states, table bookings, and kitchen orders—were kept in local mock files and client-side device storage (`AsyncStorage`).

> Real-World Problems Observed in A1:
>
> - **Multi-Device Data Desynchronization:** When the Restaurant Manager changed the price of a dish or toggled an ingredient as sold out on their device, dining customers on other phones still observed the old price and could continue ordering unavailable items.
> - **Cross-Device Order Invisibility:** When a customer placed an order on one phone, checking on another family member's phone or reinstalling the app showed an empty tray. The orders were trapped in the local sandbox of a single phone.
> - **Table Double-Booking Hazard:** Two patrons attempting to book the same private window booth at 19:00 on the same date could both succeed simultaneously because each phone checked only its local memory.
> - **Data Loss on Reinstall / Cache Clear:** Uninstalling or clearing app storage wiped out all reservation history and customer loyalty records.

> How Assignment 2 (A2) Resolves Every Problem:
>
> - **Single Source of Truth:** All devices read from and write to the same central Node.js + Express REST API server connected to MongoDB.
> - **Instant Menu Updates:** When a manager updates a price or toggles availability via `PUT /api/menu/:id`, the database updates immediately, and any patron pulling to refresh sees the updated catalog.
> - **Synchronized Orders & 10s Polling:** Orders are stored in MongoDB. The customer's `OrderTrackingScreen` polls `GET /api/orders/my` every 10 seconds, immediately displaying when the kitchen advances the status from `Preparing` to `Ready`.
> - **Server-Side Collision Detection:** When a booking is submitted via `POST /api/reservations`, the server checks whether the table is already occupied for that date and time. If occupied, the server returns an **HTTP 409 Conflict**, preventing double-bookings.

---

1. Introduction

1.1. Purpose

This Software Requirements Specification (SRS v2.0) establishes the full functional, database, and architectural requirements for the connected **AURA Restaurant Mobile Application**. It provides developers, evaluators, and system architects with a blueprint of the integrated system comprising an Expo/React Native cross-platform mobile client, an Express.js HTTP backend, and a MongoDB NoSQL database.

1.2. Scope

In-Scope Functionalities (Updated for A2):

1. **Centralized Backend REST API:** A production-grade Node.js and Express server running on port 5000, modularized into `config/`, `models/`, `routes/`, `controllers/`, and `middleware/`.
2. **MongoDB Database Persistence:** Centralized NoSQL database (`restaurant_app`) with strict Mongoose schemas for `User`, `MenuItem`, `Table`, `Reservation`, and `Order`.
3. **Secure Authentication & Token Management:** Password encryption with `bcryptjs` (salt rounds = 10) and stateless user authentication using signed **JSON Web Tokens (JWT)** expiring in 24 hours.
4. **Role-Based Access Control Middleware:** Custom Express middleware `protect` (verifies `Bearer <token>` headers) and `managerOnly` (enforces administrative authorization with HTTP 403 Forbidden).
5. **Dynamic Menu Catalog & Management:** Public endpoints for categorized retrieval and case-insensitive search (`/api/menu?category=...&search=...`), with manager-only protected endpoints for creating, editing, and deleting dishes.
6. **Validated Order Pipeline:** Server-side order calculation using database menu prices (ignoring untrusted client calculations), rejection of sold-out items, and monotonic state progression (`Pending` → `Preparing` → `Ready` → `Served`). An order can only be set to `Cancelled` while its status is `Pending`.

7. **Collision-Proof Table Reservations:** Server validation ensuring seat capacity requirements and blocking double-bookings with HTTP 409 Conflict.
8. **Automated Live Status Polling:** Client-side 10-second polling intervals (`setInterval`) on `OrderTrackingScreen` to provide real-time kitchen status synchronization without manual restarts.
9. **Mobile API Client & Custom Hooks:** Centralized HTTP client (`src/api/client.js`) and reusable data-fetching hook (`src/hooks/useApi.js`) handling loading, error, and refetch lifecycles across screens.
10. **Phone OTP Authentication (Extra Feature):** A Pakistani mobile phone number OTP login flow beyond the assignment requirements. The server generates a 4-digit numeric code using `crypto.randomInt` , stores it in an in-memory `Map` (not in the database), and prints the code exclusively to the server console as a simulated SMS gateway (not returned in response). The OTP is valid for 5 minutes with a 30-second resend cooldown. After verification (strictly invalidated after 3 incorrect attempts), the server either logs in the existing user or creates a new customer account automatically, returning a JWT token.

Out-of-Scope (Excluded from A2):

- **Real Payment Gateways:** Real credit card transactions (Stripe, JazzCash, EasyPaisa) remain out of scope; orders are placed with simulated payment processing.
- **Native Push Notifications:** Push daemons (Apple APNs, Google FCM) remain out of scope; polling intervals are used for status tracking.
- **GPS Courier Live Tracking:** External delivery fleet tracking is excluded.

1.3. Definitions, Acronyms, and Abbreviations

Term	Definition
API (Application Programming Interface)	A set of rules and protocols that allows the React Native mobile application to communicate with the Express backend server.
REST (Representational State Transfer)	An architectural style for networked applications that utilizes standard HTTP verbs (GET, POST, PUT, PATCH, DELETE) to manage resources represented as JSON.
Endpoint	A specific URL location (e.g., `http://192.168.1.15:5000/api/menu`) on a server where the API receives requests and sends responses.
JSON (JavaScript Object Notation)	A lightweight, human-readable data-interchange text format used for serializing request payloads and API responses between client and server.
MongoDB	A document-oriented, NoSQL database that stores data in flexible, JSON-like BSON documents grouped into collections.
Collection	A grouping of MongoDB documents, analogous to a table in a relational database system (e.g., `menuitems` , `orders`).
Mongoose	An Object Data Modeling (ODM) library for Node.js and MongoDB that provides schema validation, type casting, middleware hooks, and business logic methods.
Middleware	Functions that execute during the Express request-response lifecycle, having access to `req` , `res` , and the `next` function (e.g., authentication, error handling, JSON parsing).
JWT (JSON Web Token)	A compact, URL-safe means of representing claims between two parties. Encoded with a secret key (`JWT_SECRET`) to securely authenticate users without storing server-side sessions.

HTTP Status Code	Standardized 3-digit numerical responses from the server indicating the outcome of a request (e.g., `200 OK`, `201 Created`, `400 Bad Request`, `401 Unauthorized`, `403 Forbidden`, `404 Not Found`, `409 Conflict`, `500 Server Error`).
Bcrypt	A cryptographic hash function designed specifically for password storage, incorporating salting to protect against rainbow table attacks.
CORS (Cross-Origin Resource Sharing)	A security mechanism allowing web and mobile applications running on different ports or origins to interact with the backend API.

---

2. Overall Description & System Actors

2.1. System Actors & Roles

- **Customer / Dining Patron:** A registered user who logs in to browse the real-time menu catalog, filter dishes, customize cart items, place Dine-in/Takeaway orders, track order progression via 10-second polling, and book dining tables.
- **Restaurant Operations Manager:** An authenticated administrative user who oversees incoming kitchen orders, advances order stages (`Pending` → `Preparing` → `Ready` → `Served`), accepts or declines table bookings, updates item prices, and toggles dish availability.

---

3. Functional Requirements

Module 1: Authentication & Authorization

- **FR-01 (User Registration):** `POST /api/auth/register` shall validate name, unique email, password, and optional phone. The server always creates role `customer`; any client-provided `role` field is ignored. Passwords must be hashed using `bcryptjs` before storage. Duplicate emails must return HTTP 409 Conflict.
- **FR-02 (User Login):** `POST /api/auth/login` shall verify email and password against MongoDB. Successful logins return a signed JWT expiring in 24 hours, along with user details (`id`, `name`, `email`, `role`). The password hash must never be returned.
- **FR-03 (Token Verification):** The `protect` middleware shall inspect the `Authorization: Bearer <token>` header, verify token authenticity using `JWT_SECRET`, and attach the user record to `req.user`. Invalid or missing tokens return HTTP 401.
- **FR-04 (Role Enforcement):** The `managerOnly` middleware shall verify that `req.user.role === 'manager'`. Unauthorized non-manager roles return HTTP 403 Forbidden.

Module 2: Menu Catalog & CRUD

- **FR-05 (Public Menu Listing):** `GET /api/menu` shall return all active menu items. It must accept optional query parameters: `category` (case-insensitive filter) and `search` (case-insensitive regular expression matching dish name).

- **FR-06 (Single Item Retrieval):** `GET /api/menu/:id` shall validate the MongoDB ObjectId format. If valid and existing, it returns the item; if non-existent, it returns HTTP 404; if invalid format, it returns HTTP 400.
- **FR-07 (Manager Menu Mutations):** `POST /api/menu` (201 Created), `PUT /api/menu/:id` (200 OK), and `DELETE /api/menu/:id` (200 OK) shall require both `protect` and `managerOnly` middleware.

Module 3: Order Pipeline & Validation

- **FR-08 (Order Creation):** `POST /api/orders` shall accept order items, dining type, and table number. The server must verify that each dish exists and `isAvailable === true`. The server must calculate the total price directly from MongoDB dish prices, ignoring client-submitted totals.
- **FR-09 (Monotonic Progression):** `PATCH /api/orders/:id/status` shall enforce that orders progress strictly forward: `Pending` → `Preparing` → `Ready` → `Served`. An order can only be set to `Cancelled` while in `Pending` state. A manager advances the status forward; a customer can set only `Cancelled` on their own `Pending` order within a 10-minute cancellation window. Any illegal transition returns HTTP 400.
- **FR-10 (Order Queries):** Customers retrieve their orders via `GET /api/orders/my`. Managers retrieve all restaurant orders via `GET /api/orders`.
- **FR-11 (Live Polling):** The mobile `OrderTrackingScreen` shall execute `GET /api/orders/my` every 10 seconds via `setInterval` and clear the timer upon unmount.

Module 4: Table Reservations & Collision Prevention

- **FR-12 (Table Availability Check):** `POST /api/reservations` shall check whether the requested table has sufficient seating capacity and is unbooked for that specific date and hourly time slot. If a booking exists with status `Pending` or `Confirmed`, the server returns **HTTP 409 Conflict**.
- **FR-13 (Reservation Management):** Customers view their reservations via `GET /api/reservations/my`. Managers view all reservations via `GET /api/reservations`. Status is updated via `PATCH /api/reservations/:id`: a manager can set `Confirmed` or `Declined` on any booking; a customer can set only `Cancelled` on their own booking.

---

5. Database Design (Replaces Section 5 of A1)

The mock arrays from A1 are now fully realized as normalized MongoDB collections in the `restaurant_app` database:

Table 5.1: Database Collections & Schema Definitions

Collection	Fields & Types	Relationships, Constraints & Validation Rules

Users `users`	• `_id` : ObjectId (PK) • `name` : String (Required, Trim) • `email` : String (Required, Unique, Lowercase, Trim) • `password` : String (Required, Hashed with bcrypt) • `role` : String (Enum: `['customer', 'manager']` , Default: `'customer'`) • `phone` : String (Optional, Trim, Default: `''`) • `dob` : String (Optional, Trim, Default: `''`) • `membership` : String (Default: `'Member'`) • `avatar` : String (Default: Unsplash placeholder URL) • `createdAt` & `updatedAt` : Date (Auto)	• **Unique Constraint:** `email` is indexed and unique. • **Security:** Passwords are never returned in responses. • **Parent of:** `Orders` (1:N) and `Reservations` (1:N).
MenuItems `menuitems`	• `_id` : ObjectId (PK) • `name` : String (Required, Trim) • `description` : String (Required, Trim) • `price` : Number (Required, Min: 0) • `category` : String (Required, Enum: `['Starters', 'Mains', 'Desserts', 'Drinks']`) • `image` : String (Required, URL format) • `isSpecial` : Boolean (Default: `false`) • `isAvailable` : Boolean (Default: `true`) • `prepTime` : String (Default: `'15 min'`) • `rating` : Number (Min: 0, Max: 5, Default: 4.8) • `tag` : String (Optional, Trim) • `createdAt` & `updatedAt` : Date	• **Validation Rule:** `price` must be non-negative (`min: [0, 'Price cannot be negative']`). • **Indexes:** Text index on `{name, description}` for search; index on `{category: 1}` for filter queries. • **Referenced by:** `Order.items.menuItem` .
Tables `tables`	• `_id` : ObjectId (PK) • `tableNumber` : String (Required, Unique, Trim, e.g. `'A-01'`) • `name` : String (Required, Trim, e.g. `'Atrium Glasshouse Window'`) • `seats` : Number (Required, Min: 1) • `location` : String (Required, Trim) • `isWindow` : Boolean (Default: `false`) • `isAvailable` : Boolean (Default: `true`) • `createdAt` & `updatedAt` : Date	• **Unique Constraint:** `tableNumber` is unique across the restaurant. • **Capacity Rule:** `seats` determines maximum allowable party size. • **Referenced by:** `Reservation.table` .

Reservations `reservations`	• `_id` : ObjectId (PK) • `user` : ObjectId (FK → `User` , Required) • `customerName` : String (Optional, Trim) • `phone` : String (Optional, Trim) • `table` : ObjectId (FK → `Table` , Required) • `date` : String (Required, Format: `YYYY-MM-DD`) • `time` : String (Required, Format: `HH:mm`) • `guests` : Number (Required, Min: 1) • `specialRequests` : String (Optional, Trim) • `status` : String (Enum: `['Pending', 'Confirmed', 'Cancelled', 'Declined']` , Default: `'Pending'`) • `createdAt` & `updatedAt` : Date (`timestamps: true`)	• **Relational Integrity:** Links `User` and `Table` documents. • **Collision Rule (Q7):** Unique compound partial index on `{table, date, time}` where `status` is `Pending` or `Confirmed` blocks double-booking with HTTP 409. • **Indexes:** `{user: 1}` , `{date: 1, time: 1}` . • **Capacity Rule:** `table.seats >= guests` .
Orders `orders`	• `_id` : ObjectId (PK) • `user` : ObjectId (FK → `User` , Required) • `customerName` : String (Optional, Trim) • `items` : Array of Subdocuments: – `menuItem` : ObjectId (FK → `MenuItem`) – `name` : String – `price` : Number – `quantity` : Number (Min: 1) – `specialInstructions` : String • `totalAmount` : Number (Required, Calculated on server) • `orderType` : String (Enum: `['Dine-in', 'Takeaway', 'Dine-In Table', 'Curbside', 'Priority']` , Default: `'Dine-in'`) • `tableNumber` : String (Optional, Trim) • `status` : String (Enum: `['Pending', 'Preparing', 'Ready', 'Served', 'Cancelled']` , Default: `'Pending'`) • `notes` : String (Optional, Trim) • `createdAt` & `updatedAt` : Date (`timestamps: true`)	• **Monotonic State Machine:** Status strictly moves `Pending` → `Preparing` → `Ready` → `Served` . `Cancelled` is only valid when currently `Pending` . • **Security Rule:** `totalAmount` is calculated by multiplying DB item prices with quantity on the backend. • **Indexes:** `{user: 1, createdAt: -1}` , `{status: 1}` .

6. Architectural Diagrams


6.1. Sequence Diagram: Customer Places an Order (Q1 Requirement)

This diagram illustrates the message sequence with the **three required lifelines**: the **Mobile App**, the **Express Server**, and **MongoDB**.



6.2. Deployment Diagram (Q1 Requirement)

This diagram depicts the physical deployment topology linking the **Mobile Device**, the **Development Laptop Server**, and the **Database Host**.



8. API Endpoints Specification (New Section 8)

The table below documents all **23 REST API endpoints** implemented in the backend server:

#	HTTP Method	Endpoint Route	Access Level	Request Body (Payload)	Response Structure & Status
1	`GET`	`/api/health`	Public	None	`200 OK` : `{ "status": "ok", "time": "2026-10-07T..." }`
2	`POST`	`/api/auth/register`	Public	`{ name, email, password, phone? }`	`201 Created` : `{ token, user: { _id, name, email, role } }` `409 Conflict` : If email exists
3	`POST`	`/api/auth/login`	Public	`{ email, password }`	`200 OK` : `{ token, user: { _id, name, email, role } }` `401 Unauthorized` : Invalid credentials
4	`GET`	`/api/auth/me`	Private (Customer/Manager)	None (Bearer Token)	`200 OK` : `{ user: { _id, name, email, role, phone, dob, membership, avatar } }`

5	`PUT`	`/api/auth/profile`	Private (Customer/Manager)	`{ name?, phone?, dob?, avatar? }`	`200 OK` : `{ message, user }` — Updates current user profile.
6	`DELETE`	`/api/auth/profile`	Private (Customer/Manager)	None (Bearer Token)	`200 OK` : `{ success: true, message }` — Permanently removes user account.
7	`POST`	`/api/auth/staff`	Private (Manager Only)	`{ name, email, password }`	`201 Created` : `{ user }` — Creates a new manager account.
8	`POST`	`/api/auth/phone/send-otp`	Public	`{ phone }`	`200 OK` : `{ success, message, phone }` — Generates 4-digit OTP with 30s resend cooldown, prints exclusively to server console as simulated SMS.
9	`POST`	`/api/auth/phone/verify-otp`	Public	`{ phone, otp, name? }`	`200 OK` or `201 Created` : `{ token, user, isNewUser }` — Verifies 4-digit OTP (invalidated after 3 incorrect attempts) and logs in or creates customer account.
10	`GET`	`/api/menu`	Public	None (Optional Query: `?category=...&search=...`)	`200 OK` : Array of `MenuItem` objects
11	`POST`	`/api/menu`	Private (Manager Only)	`{ name, description, price, category, image, isSpecial?, isAvailable?, prepTime?, rating?, tag? }`	`201 Created` : Created `MenuItem` document `403 Forbidden` : If called by customer
12	`GET`	`/api/menu/:id`	Public	None	`200 OK` : Single `MenuItem` object `400 Bad Request` : Invalid ObjectId `404 Not Found` : Item does not exist
13	`PUT`	`/api/menu/:id`	Private (Manager Only)	Partial updates: `{ price?, isAvailable?, ... }`	`200 OK` : Updated `MenuItem` document
14	`DELETE`	`/api/menu/:id`	Private (Manager Only)	None	`200 OK` : `{ message: "Menu item deleted successfully" }`
15	`GET`	`/api/tables`	Public	None	`200 OK` : Array of all dining `Table` objects

16	`POST`	`/api/reservations`	Private (Customer/Manager)	`{ tableId, date, time, guests, specialRequests?, customerName?, phone? }`	`201 Created` : Populated `Reservation` document `409 Conflict` : Table already booked for slot
17	`GET`	`/api/reservations`	Private (Manager Only)	None	`200 OK` : Array of all restaurant bookings
18	`GET`	`/api/reservations/my`	Private (Customer)	None	`200 OK` : Array of customer's own bookings
19	`PATCH`	`/api/reservations/:id`	Private (Customer/Manager)	`{ status }` (`Confirmed` , `Declined` , `Cancelled`)	`200 OK` : Updated `Reservation` — Manager sets `Confirmed` / `Declined` ; customer sets only `Cancelled` on own booking.
20	`POST`	`/api/orders`	Private (Customer/Manager)	`{ items: [{ menuItem, quantity, specialInstructions? }], orderType?, tableNumber?, notes? }`	`201 Created` : Verified `Order` document with server-computed `totalAmount`
21	`GET`	`/api/orders`	Private (Manager Only)	None	`200 OK` : Array of all restaurant `Order` documents
22	`GET`	`/api/orders/my`	Private (Customer)	None	`200 OK` : Array of customer's own `Order` documents
23	`PATCH`	`/api/orders/:id/status`	Private (Customer/Manager)	`{ status }` (`Pending` , `Preparing` , `Ready` , `Served` , `Cancelled`)	`200 OK` : Updated `Order` — Manager advances status forward monotonically; customer can set only `Cancelled` on own `Pending` order within 10-minute window. `400 Bad Request` : Illegal status jump

---

9. Verification & Viva Voce Defense Guide

Key Questions Evaluators Ask & Verified Implementations:

1. **"Why do we calculate order total on the server instead of accepting the client's cart total?"**
   Answer: Client applications run on untrusted end-user hardware. A malicious user or tampered request could modify prices in memory (e.g., changing a Rs. 3,650 steak to Rs. 1). The server verifies the authoritative price from MongoDB before writing `totalAmount` into the database.

2. **"How do you prevent table double-bookings during peak hours?"**
   Answer: In `server/controllers/reservationController.js`, before creating a record, we query MongoDB for any active booking (`Pending` or `Confirmed`) matching the same `table._id`, `date`, and `time`. If an overlapping record exists, the server immediately halts and returns an **HTTP 409 Conflict**, preventing concurrent collision.
3. **"Where is the custom `useApi` hook used in the mobile client?"**
   Answer: It is integrated in two distinct screens: `MenuScreen.js` (for loading menu items and triggering pull-to-refresh) and `ManagerDashboardScreen.js` (for retrieving all dining reservations with live acceptance and rejection controls).
4. **"How does the customer receive kitchen status updates in real-time?"**
   Answer: In `OrderTrackingScreen.js`, a `useEffect` hook initializes a 10-second `setInterval` that polls `GET /api/orders/my`. As soon as the manager marks an order as `Preparing` or `Ready`, the customer's state machine advances automatically without requiring app reloads.