Obelisk Proof Assistant — Reference Demonstration

Variant: Higher-Order Logic & Morse–Kelley Class Theory • Author: Georgy Dunaev • contact@obelisk.mozmail.com

1) Propositional logic

1.01) Axm. A01 (Weakening / Positive Implicative Axiom; K-Axiom; Russian: Утверждение следствия):

(α → (β → α))

Typing judgment: ((α : Bool) ∧ (β : Bool))

1.02) Axm. A02 (Distribution of Implication):

((α → (β → γ)) → ((α → β) → (α → γ)))

Typing judgment: ((α : Bool) ∧ ((β : Bool) ∧ (γ : Bool)))

1.03) Axm. A03 (Conjunction Elimination Left):

((α ∧ β) → α)

Typing judgment: ((α : Bool) ∧ (β : Bool))

1.04) Axm. A04 (Conjunction Elimination Right):

((α ∧ β) → β)

Typing judgment: ((α : Bool) ∧ (β : Bool))

1.05) Axm. A05 (Conjunction Introduction):

(α → (β → (α ∧ β)))

Typing judgment: ((α : Bool) ∧ (β : Bool))

1.06) Axm. A06 (Disjunction Introduction Left):

(α → (α ∨ β))

Typing judgment: ((α : Bool) ∧ (β : Bool))

1.07) Axm. A07 (Disjunction Introduction Right):

(β → (α ∨ β))

Typing judgment: ((α : Bool) ∧ (β : Bool))

1.08) Axm. A08 (Disjunction Elimination / Cases):

((α → γ) → ((β → γ) → ((α ∨ β) → γ)))

Typing judgment: ((α : Bool) ∧ ((β : Bool) ∧ (γ : Bool)))

1.09) Axm. A09 (Negation Elimination / Contradiction to Bottom):

((¬α) → (α → ⊥))

Typing judgment: (α : Bool)

1.10) Axm. A10 (Reductio Ad Absurdum / Negation Introduction):

((α → β) → ((α → ¬β) → ¬α))

Typing judgment: ((α : Bool) ∧ (β : Bool))

1.11) Axm. A11 (Ex Falso Quodlibet):

(⊥ → α)

Typing judgment: (α : Bool)

1.12) Axm. A12 (Law of Excluded Middle):

(α ∨ ¬α)

Typing judgment: (α : Bool)

1.13) Rule Modus Ponens (MP):

α, (α → β) ⊢ β

Typing judgment: ((α : Bool) ∧ (β : Bool))

2) Predicate logic

2.01) Axm. Discourse domain is non-empty:

∃(K : Class) ⊤

Typing judgment: (K : Class)

2.02) Rule Forall Instantiation (FI):

((∀(x : Class) φ) → φ[t/x])

Syntactic side condition: FFI(t, v_x, φ)

2.03) Rule Exists Instantiation (EI):

(φ[t/x] → ∃(x : Class) φ)

Syntactic side condition: FFI(t, v_x, φ)

2.04) Rule Forall Abstraction (FA / Bernays):

(ψ → φ) ⊢ (ψ → ∀(x : Class) φ)

Syntactic side condition: (NFV(v_x, ψ) ∧ NFV(v_x, Γ))

2.05) Rule Exists Abstraction (EA / Bernays):

(φ → ψ) ⊢ (∃(x : Class) (φ → ψ))

Syntactic side condition: (NFV(v_x, ψ) ∧ NFV(v_x, Γ))

2.06) Rule Generalisation (Gen):

φ ⊢ ∀(x : Class) φ

Syntactic side condition: NFV(v_x, Γ)

3) Set/class-theoretic foundations of mathematics

3.01) Axm. Class Comprehension Axiom:

∀(x : Class) ((x ∈ { y | φ(y) }) ⟷ (isSet(x) ∧ φ(x)))

Syntactic side condition: NFV(v_C, φ)

3.02) Axm. Extensionality Axiom:

∀(A, B : Class) ((∀(x : Class) ((x ∈ A) ⟷ (x ∈ B))) → (A = B))

Typing judgment: ((A : Class) ∧ ((B : Class) ∧ (x : Class)))

3.08) Axm. Subset-Sethood / Heredity Axiom (Subclasses of Sets are Sets):

∀(A, b : Class) ((isSet(b) ∧ (A ⊆ b)) → isSet(A))

Typing judgment: ((A : Class) ∧ (b : Class))

3.12) Axm. Regularity (Foundation / Cumulative □-Induction) Axiom:

((∀(X : Class) ((□(X) ⊆ X) → (V ⊆ X))) ∧ (∀(A : Class) ((A ≠ ∅) → ∃(x : Class) ((x ∈ A) ∧ ((x ∩ A) = ∅)))))

Typing judgment: ((X : Class) ∧ ((A : Class) ∧ (x : Class)))

3.13) Axm. Unordered Pair Definition & Pairing Axiom:

∀(a, b : Class) (({a, b} = { x | ((x = a) ∨ (x = b)) }) ∧ ((isSet(a) ∧ isSet(b)) → isSet({a, b})))

Typing judgment: ((a : Class) ∧ ((b : Class) ∧ (x : Class)))

3.14) Axm. Unary Union Definition & Union Axiom:

∀(a : Class) ((⋃ a = { x | ∃(y : Class) ((y ∈ a) ∧ (x ∈ y)) }) ∧ (isSet(a) → isSet(⋃ a)))

Typing judgment: ((a : Class) ∧ ((x : Class) ∧ (y : Class)))

3.22) Def. IF-THEN-ELSE-FI (Class conditional with NFV side condition and context turnstile):

W, Γ ⊢ (⟦IF ψ THEN A ELSE B FI⟧ = { v | ((ψ ∧ (v ∈ A)) ∨ (¬ψ ∧ (v ∈ B))) })

Syntactic side condition: (NFV(v_v, ψ) ∧ NFV(v_v, Γ))

3.23) Def. simple_if (metalevel conditional over Type_Expression):

∀(T_e : Type_Expression), (simple_if(⟦T_e⟧) : (Bool → (⟦T_e⟧ → (⟦T_e⟧ → ⟦T_e⟧))))

∀(T_e : Type_Expression), ∀(t₁ : ⟦T_e⟧) ∀(t₂ : ⟦T_e⟧) ((simple_if(⟦T_e⟧, true, t₁, t₂) = t₁) ∧ (simple_if(⟦T_e⟧, false, t₁, t₂) = t₂))

Typing judgment: ((T_e : Type_Expression) ∧ ((t₁ : ⟦T_e⟧) ∧ (t₂ : ⟦T_e⟧)))

3.24) Def. if_dep (dependent conditional over Bool → Type_Expression):

∀(T_e : (Bool → Type_Expression)), (if_dep : Π(b : Bool), ⟦T_e(true)⟧ → (⟦T_e(false)⟧ → ⟦T_e(b)⟧))

∀(T_e : (Bool → Type_Expression)), ∀(b : Bool) ∀(t₁ : ⟦T_e(true)⟧) ∀(t₂ : ⟦T_e(false)⟧) ((if_dep(b, t₁, t₂) : ⟦T_e(b)⟧) ∧ ((if_dep(true, t₁, t₂) = t₁) ∧ (if_dep(false, t₁, t₂) = t₂)))

Typing judgment: ((T_e : (Bool → Type_Expression)) ∧ ((b : Bool) ∧ ((t₁ : ⟦T_e(true)⟧) ∧ (t₂ : ⟦T_e(false)⟧))))

3.32) Thm. Ordinal / Transitive-Class ∈-Induction (∈-Ind):

((∀(K, A : Class) ((Tr(K) ∧ ((K ∩ □(A)) ⊆ A)) → (K ⊆ A))) ∧ ((∀(x : Class) ((x ∈ On) → ((∀(y : Class) ((y ∈ x) → φ(y))) → φ(x)))) → ∀(x : Class) ((x ∈ On) → φ(x))))

Syntactic side condition: (Fresh(v_y, v_x) ∧ NFV(v_y, φ(x)))

3.33) Def. Power Class Definition (□(A)):

∀(A, x : Class) ((x ∈ □(A)) ⟷ (isSet(x) ∧ (x ⊆ A)))

Syntactic side condition: Fresh(v_x, v_A)

3.34) Axm. Power Set / Exponent Axiom (Power Class of a Set is a Set):

∀(a : Class) (isSet(a) → isSet(□(a)))

Typing judgment: (a : Class)

3.35) Def. Size Comparison Relation (A ≤ B / lesseq):

∀(A : Class) ∀(B : Class) ((A ≤ B) ⟷ ∃(f : Class) (((isClassFunction(f) ∧ (A ⊆ Dom(f))) ∧ (f[A] ⊆ B)) ∧ isInjective(f)))

Typing judgment: ((A : Class) ∧ ((B : Class) ∧ (f : Class)))

3.36) Def. Class Cardinality (|K|):

∀(K : Class) (|K| = (On ∩ ⋂({ a | ((a ∈ On) ∧ (K ≤ a)) })))

Typing judgment: ((K : Class) ∧ (a : Class))

3.37) Axm. Image / Replacement Axiom (isSet(F[a])):

∀(F, a : Class) ((isClassFunction(F) ∧ isSet(a)) → isSet(F[a]))

Typing judgment: ((F : Class) ∧ (a : Class))

3.38) Def. Strictly Smaller Size Relation (A ≺ B):

∀(A : Class) ∀(B : Class) ((A ≺ B) ⟷ ¬(B ≤ A))

Typing judgment: ((A : Class) ∧ (B : Class))

3.39) Axm. Limitation of Size Axiom ((X ∈ V) ⟷ (|X| ≺ |V|)):

∀(X : Class) ((X ∈ V) ⟷ (|X| ≺ |V|))

Typing judgment: (X : Class)

3.40) Def. Dunaev Tagged Ordered Pair:

∀(A, B : Class) ([A, B]_D = { z | ∃(a ∈ A) (z = {{{{a}}}, {∅}}) ∨ ∃(b ∈ B) (z = {{{{b}}}, {∅, {∅}}}) })

Typing judgment: ((A : Class) ∧ (B : Class))

3.41) Thm. First Projection of Dunaev Tagged Ordered Pair:

∀(A, B : Class) ({ a | ({{{{a}}}, {∅}} ∈ [A, B]_D) } = A)

Typing judgment: ((A : Class) ∧ (B : Class))

3.42) Thm. Second Projection of Dunaev Tagged Ordered Pair:

∀(A, B : Class) ({ b | ({{{{b}}}, {∅, {∅}}} ∈ [A, B]_D) } = B)

Typing judgment: ((A : Class) ∧ (B : Class))

3.45) Axm. Infinity Axiom:

∃(x : Class) (isSet(x) ∧ ((∅ ∈ x) ∧ ∀(y : Class) ((y ∈ x) → ((y ∪ {y}) ∈ x))))

Typing judgment: ((x : Class) ∧ (y : Class))

3.46) Axm. Global Choice Axiom:

∃(F : Class) (isClassFunction(F) ∧ ∀(x : Class) ((isSet(x) ∧ (x ≠ ∅)) → (F(x) ∈ x)))

Typing judgment: ((F : Class) ∧ (x : Class))

3.47) Def. Universal Class (V):

(V = { x | (x = x) })

Typing judgment: (V : Class)

3.53) Def. Transitive Class Predicate:

(Tr(A) ⟷ ∀(x : Class) ((x ∈ A) → (x ⊆ A)))

Typing judgment: ((A : Class) ∧ (x : Class))

3.66) Axm. Tarski's Axiom of Universes:

∀(x : Class) (isSet(x) → ∃(u : Class) ((isUniverse(u) ∧ (x ∈ u)) ∧ isSet(u)))

Typing judgment: ((x : Class) ∧ (u : Class))

3.67) Def. Semi-Singleton Class Predicate (semi_singleton):

(semi_singleton(s) ⟷ ∀(x : Class) ∀(y : Class) (((x ∈ s) ∧ (y ∈ s)) → (x = y)))

Typing judgment: ((s : Class) ∧ ((x : Class) ∧ (y : Class)))

3.68) Def. Semi-Singleton Subset Relation (s sss A):

∀(s : Class) ∀(A : Class) ((s sss A) ⟷ ((s ⊆ A) ∧ ∀(x : Class) ∀(y : Class) (((x ∈ s) ∧ (y ∈ s)) → (x = y))))

Typing judgment: ((s : Class) ∧ ((A : Class) ∧ ((x : Class) ∧ (y : Class))))

3.69) Thm. Theorem of Evaluation of a Family (F(x) = ⋃{ s | [x, s]_D ∈ F } and (Λx, t)(z) = t[z/x]):

∀(F : Class) ∀(x : Class) (isFamily(F) → (F(x) = ⋃({ s | ([x, s]_D ∈ F) })))

Typing judgment: ((F : Class) ∧ ((x : Class) ∧ ((z : Class) ∧ ((s : Class) ∧ ((t : Class.Expression) ∧ ((v_x : Variable) ∧ (v_s : Variable)))))))

Syntactic side condition: (FFI(z, v_x, (s sss t)) ∧ (Fresh(v_s, v_x) ∧ NFV(v_s, t)))

3.70) Def. Set-Theoretic Model of Dependent Sum (ΣB / Sigma Model):

∀(B : Class) ∀(x : Class) ∀(y : Class) (isFamily(B) → (((x ∈ Dom(B)) ∧ (y ∈ B(x))) ⟷ ([x, y]_D ∈ { s | ∃(a : Class) ∃(b : Class) ((s = [a, b]_D) ∧ ((a ∈ Dom(B)) ∧ (b ∈ B(a)))) })))

Typing judgment: ((B : Class) ∧ ((x : Class) ∧ ((y : Class) ∧ ((s : Class) ∧ ((a : Class) ∧ (b : Class))))))

3.71) Def. Set-Theoretic Model of Dependent Product (ΠB / Pi Predicate & Set-Section Models):

∀(B : Class) ∀(f : Class) ((isFamily(B) ∧ (isFamily(f) ∧ (Dom(f) = Dom(B)))) → ∀(x : Class) ((x ∈ Dom(B)) → (f(x) ∈ B(x))))

Typing judgment: ((B : Class) ∧ ((f : Class) ∧ (x : Class)))

4) Metalogical laws

4.01) Axm. Instantiation Axiom:

∀(T_e : Type_Expression), ∀(G : Ctx) ∀(φ : Fm) ∀(t : ⟦T_e⟧) ∀(v : Variable) ((W, G ⊢ (∀(v : ⟦T_e⟧) φ)) → (W, G ⊢ (let v = t in φ)))

Typing judgment: ((T_e : Type_Expression) ∧ ((t : ⟦T_e⟧) ∧ (v : Variable)))

4.02) Axm. Generalisation Axiom:

∀(T_e : Type_Expression), ∀(Γ : Ctx) ∀(φ : Fm) ∀(v : Variable) (¬(Enc(v) ∈ Ctx.FV(Γ)) → ((W, Γ ⊢ φ) → (W, Γ ⊢ ∀(v : ⟦T_e⟧) φ)))

Typing judgment: ((T_e : Type_Expression) ∧ ((Γ : Ctx) ∧ ((φ : Fm) ∧ (v : Variable))))

Syntactic side condition: NFV(v, Γ)

4.03) Rule CoNecessitation:

(F, [] ⊢ ‹F, Γ ⊢ φ›) ⊢ (F, Γ ⊢ φ)

Typing judgment: ((F : Theory) ∧ ((Γ : Ctx) ∧ (φ : Fm)))

4.04) Def. Quantifier Unique (!):

∀(φ : Fm) ((!(z : Class) φ) ⟷ ∀(x, y : Class) ((φ[x/z] ∧ φ[y/z]) → (x = y)))

Typing judgment: ((z : Variable) ∧ ((x : Variable) ∧ (y : Variable)))

4.05) Def. Quantifier Exists and Unique (∃!):

∀(φ : Fm) (T, [] ⊢ ((∃!(x : Class) φ) ⟷ ((∃(x : Class) φ) ∧ !(x : Class) φ)))

Typing judgment: ((x : Variable) ∧ (φ : Fm))

4.06) Axm. Class Comprehension Axiom (Metatheory):

∀(φ : Fm) ∀(x : Name) ∀(k : Class.Expr) (FFI(k, x, φ) → (T, [] ⊢ ((k ∈ { x | φ }) ⟷ (isSet(k) ∧ φ[k/x]))))

Syntactic side condition: FFI(k, x, φ)

4.07) Axm. Completeness / Reflection & Soundness of Full Theory F:

∀(φ : Fm) (((F, [] ⊢ φ) → ⟦φ⟧) ∧ (⟦φ⟧ → (F, [] ⊢ φ)))

Typing judgment: ((φ : Fm) ∧ (F : Theory))

4.08) Axm. Theory Inclusion (Model(T) ⊆ Model(F)):

∀(Γ : Ctx) ∀(φ : Fm) ((T, Γ ⊢ φ) → (F, Γ ⊢ φ))

Typing judgment: ((T : Theory) ∧ ((F : Theory) ∧ ((Γ : Ctx) ∧ (φ : Fm))))

4.09) Def. Syntactic Encoding Operator (Enc):

∀(T_e : Type_Expression), ∀(s : ⟦T_e⟧) (isSet(Enc(s)) ∧ (Enc(s) ∈ Emb(⟦T_e⟧)))

Typing judgment: ((T_e : Type_Expression) ∧ (s : ⟦T_e⟧))

4.10) Def. Syntactic Decoding & Roundtrip Law (Dec):

∀(T_e : Type_Expression), ∀(s : ⟦T_e⟧) ((Dec(Enc(s), Emb(⟦T_e⟧)) : ⟦T_e⟧) = (s : ⟦T_e⟧))

Typing judgment: ((T_e : Type_Expression) ∧ (s : ⟦T_e⟧))

4.11) Def. Dual Type Embedding Operator (Emb):

∀(X : Class) ((Emb(Class)(X) ⟷ ⊤) ∧ (Emb(Set)(X) ⟷ isSet(X)))

Typing judgment: (X : Class)

4.12) Def. Proof-Object Class Family (ProofsOf):

∀(s : Stmt) ∀(p : Prf) ((Enc(p) ∈ ProofsOf(Enc(s))) ⟷ CheckProof(p, s))

Typing judgment: ((s : Stmt) ∧ (p : Prf))

4.13) Def. Class of Provable Statements (Theorems):

∀(s : Stmt) ((Enc(s) ∈ Theorems) ⟷ (∃(p : Class) (p ∈ ProofsOf(Enc(s)))))

Typing judgment: ((s : Stmt) ∧ (p : Class))

5) Tactics and inference rules

5.01) Thm. Elementary Theorems:

((F, [(b ∈ X)] ⊢ ∃(X : Class) (b ∈ X)) ∧ (F, [(b ∈ X)] ⊢ isSet(b)))

Typing judgment: ((b : Class) ∧ (X : Class))

5.02) Rule Definition to Introduction Rule:

(F, [(b ∈ X)] ⊢ ∃(X : Class) (b ∈ X)) ⊢ (F, [(b ∈ X)] ⊢ isSet(b))

Typing judgment: ((b : Class) ∧ (X : Class))

5.03) Rule Deduction Rule Application:

(F, [] ⊢ ((b ∈ X) → isSet(b)))

Typing judgment: ((b : Class) ∧ (X : Class))

5.04) Thm. Tactics Proof Example:

F, [] ⊢ ((∃(Y : Class) ∀(x : Class) (x ∈ Y)) → ∀(x : Class) ∃(Y : Class) (x ∈ Y))

Typing judgment: ((x : Class) ∧ (Y : Class))

6) Incompleteness-related statements

6.01) Axm. Theories (Metalevel Stratification):

((Model(W) ⊆ Model(Q)) ∧ ((Model(Q) ⊆ Model(T)) ∧ (Model(T) ⊆ Model(F))))

Typing judgment: ((W : Theory) ∧ ((Q : Theory) ∧ ((T : Theory) ∧ (F : Theory))))

6.02) Thm. Löb's Theorem:

∀(φ : Fm) (Q, [] ⊢ ((T, [] ⊢ ((T, [] ⊢ φ) → φ)) → (T, [] ⊢ φ)))

Typing judgment: (φ : Fm)

6.03) Thm. Gödel's Second Incompleteness Theorem:

Q, [] ⊢ (¬(T, [] ⊢ ⊥) → ¬(T, [] ⊢ ¬(T, [] ⊢ ⊥)))

Typing judgment: ((T : Theory) ∧ (Q : Theory))

Appendix: NBG Formulas-as-Types Standard Library

30 closed proof terms compiled by NBGSurfaceCompiler in Poly/ML. A formula is a type; a proof program is a term inhabiting it. The Dunaev pair injectivity theorem is the class-correct replacement for Kuratowski pairing on proper classes.

Theorem	Formula (Type)	AST	Norm
empty_class_no_elements	(∀(z : Class) ((z ∈ { x | ⊥ }) → ⊥))	7	7
empty_class_is_subclass	(∀(X : Class) (∀(z : Class) ((z ∈ { x | ⊥ }) → (z ∈ X))))	8	8
universal_class_characterization	(∀(z : Class) (((z ∈ { x | ⊤ }) → isSet(z)) ∧ (isSet(z) → (z ∈ { x | ⊤ }))))	15	15
russell_class_is_not_a_set	(isSet({ x | ((x ∈ x) → ⊥) }) → ⊥)	19	32
binary_inter_comm	(∀(A : Class) (∀(B : Class) (∀(z : Class) (((z ∈ { x | ((x ∈ A) ∧ (x ∈ B)) }) → (z ∈ { x | ((x ∈ B) ∧ (x ∈ A)) })) ∧ ((z ∈ { x | ((x ∈ B) ∧ (x ∈ A)) }) → (z ∈ { x | ((x ∈ A) ∧ (x ∈ B)) })))))))	50	50
binary_union_comm	(∀(A : Class) (∀(B : Class) (∀(z : Class) (((z ∈ { x | ((x ∈ A) ∨ (x ∈ B)) }) → (z ∈ { x | ((x ∈ B) ∨ (x ∈ A)) })) ∧ ((z ∈ { x | ((x ∈ B) ∨ (x ∈ A)) }) → (z ∈ { x | ((x ∈ A) ∨ (x ∈ B)) })))))))	44	44
class_diff_subclass_left	(∀(A : Class) (∀(B : Class) (∀(z : Class) ((z ∈ { x | ((x ∈ A) ∧ ((x ∈ B) → ⊥)) }) → (z ∈ A)))))	10	10
class_eq_sym	(∀(X : Class) (∀(Y : Class) ((X = Y) → (Y = X))))	6	6
class_eq_trans	(∀(X : Class) (∀(Y : Class) (∀(Z : Class) (((X = Y) ∧ (Y = Z)) → (X = Z)))))	9	9
quantifier_swap	(∀(R : Class) ((∃(y : Set) (∀(x : Set) ([x, y]_D ∈ R))) → (∀(x : Set) (∃(y : Set) ([x, y]_D ∈ R)))))	8	8
dunaev_tagged_pair_projections	(∀(A : Class) (∀(B : Class) ((π₁([A, B]_D) = A) ∧ (π₂([A, B]_D) = B))))	3	3
cantor_diagonal_theorem	(∀(S : Class) (∀(R : Class) (∀(c : Class) ((c ∈ S) → ((∀(z : Class) (((z ∈ { x | ((x ∈ S) ∧ (([x, x]_D ∈ R) → ⊥)) }) → ([c, z]_D ∈ R)) ∧ (([c, z]_D ∈ R) → (z ∈ { x | ((x ∈ S) ∧ (([x, x]_D ∈ R) → ⊥)) }))))) → ⊥)))))	36	67
self_in_singleton	(∀(x : Class) (isSet(x) → (x ∈ { u | (u = x) })))	8	8
self_in_succ	(∀(x : Class) (isSet(x) → (x ∈ { u | ((u ∈ x) ∨ (u = x)) })))	9	9
class_sub_succ	(∀(x : Class) (∀(z : Class) ((z ∈ x) → (z ∈ { u | ((u ∈ x) ∨ (u = x)) }))))	12	12
dunaev_pair_injective	(∀(A : Class) (∀(B : Class) (∀(C : Class) (∀(E : Class) (([A, B]_D = [C, E]_D) → ((A = C) ∧ (B = E)))))))	26	26
dunaev_cartesian_elim	(∀(A : Class) (∀(B : Class) (∀(p : Class) ((p ∈ { q | (∃(u : Set) (∃(v : Set) (((u ∈ A) ∧ (v ∈ B)) ∧ (q = [u, v]_D)))) }) → (∃(u : Set) (∃(v : Set) (((u ∈ A) ∧ (v ∈ B)) ∧ (p = [u, v]_D))))))))	9	9
inter_sub_left	(∀(A : Class) (∀(B : Class) (∀(z : Class) ((z ∈ { u | ((u ∈ A) ∧ (u ∈ B)) }) → (z ∈ A)))))	10	10
inter_sub_right	(∀(A : Class) (∀(B : Class) (∀(z : Class) ((z ∈ { u | ((u ∈ A) ∧ (u ∈ B)) }) → (z ∈ B)))))	10	10
union_sub_left	(∀(A : Class) (∀(B : Class) (∀(z : Class) ((z ∈ A) → (z ∈ { u | ((u ∈ A) ∨ (u ∈ B)) })))))	13	13
semi_singleton_sub_elim	(∀(s : Class) (∀(A : Class) (∀(x : Class) (∀(y : Class) (((∀(u : Class) ((u ∈ s) → (u ∈ A))) ∧ (∀(u : Class) (∀(v : Class) (((u ∈ s) ∧ (v ∈ s)) → (u = v))))) → (((x ∈ s) ∧ (y ∈ s)) → ((x ∈ A) ∧ (x = y))))))))	19	19
family_fiber_char	(∀(A : Class) (∀(s : Class) ((s ∈ { u | (u ⊆ A) }) → (isSet(s) ∧ (s ⊆ A)))))	7	7
sigma_dependent_sum_intro	(∀(B : Class) (∀(x : Set) (∀(y : Set) ((isSet([x, y]_D) ∧ ((x ∈ Dom(B)) ∧ (y ∈ ValOf(B, x)))) → ([x, y]_D ∈ { p | (∃(a : Set) (∃(b : Set) (((a ∈ Dom(B)) ∧ (b ∈ ValOf(B, a))) ∧ (p = [a, b]_D)))) })))))	16	16
pi_dependent_product_elim	(∀(B : Class) (∀(f : Class) (∀(x : Class) (((∀(u : Class) ((u ∈ Dom(B)) → (ValOf(f, u) ∈ ValOf(B, u)))) ∧ (x ∈ Dom(B))) → (ValOf(f, x) ∈ ValOf(B, x))))))	10	10
union_sub_right	(∀(A : Class) (∀(B : Class) (∀(z : Class) ((z ∈ B) → (z ∈ { u | ((u ∈ A) ∨ (u ∈ B)) })))))	13	13
model_stratification_trans	(∀(W : Class) (∀(Q : Class) (∀(T : Class) (∀(F : Class) (((∀(z : Class) ((z ∈ Model(W)) → (z ∈ Model(Q)))) ∧ ((∀(z : Class) ((z ∈ Model(Q)) → (z ∈ Model(T)))) ∧ (∀(z : Class) ((z ∈ Model(T)) → (z ∈ Model(F)))))) → (∀(z : Class) ((z ∈ Model(W)) → (z ∈ Model(F))))))))))	22	22
if_dep_true_elim	(∀(A : Class) (∀(T1 : Class) (∀(T2 : Class) (∀(x : Class) (∀(z : Class) (((((x ∈ A) → (if_dep(x, A, ValOf(T1, x), ValOf(T2, x)) = ValOf(T1, x))) ∧ (((x ∈ A) → ⊥) → (if_dep(x, A, ValOf(T1, x), ValOf(T2, x)) = ValOf(T2, x)))) ∧ ((x ∈ A) ∧ (z ∈ if_dep(x, A, ValOf(T1, x), ValOf(T2, x))))) → (z ∈ ValOf(T1, x)))))))))	17	17
if_dep_false_elim	(∀(A : Class) (∀(T1 : Class) (∀(T2 : Class) (∀(x : Class) (∀(z : Class) (((((x ∈ A) → (if_dep(x, A, ValOf(T1, x), ValOf(T2, x)) = ValOf(T1, x))) ∧ (((x ∈ A) → ⊥) → (if_dep(x, A, ValOf(T1, x), ValOf(T2, x)) = ValOf(T2, x)))) ∧ (((x ∈ A) → ⊥) ∧ (z ∈ if_dep(x, A, ValOf(T1, x), ValOf(T2, x))))) → (z ∈ ValOf(T2, x)))))))))	17	17
inter_idempotent_elim	(∀(A : Class) (∀(z : Class) ((z ∈ { u | ((u ∈ A) ∧ (u ∈ A)) }) → (z ∈ A))))	9	9
singleton_membership_eq	(∀(a : Class) (∀(z : Class) ((z ∈ { u | (u = a) }) → (z = a))))	8	8

Reproduce locally: python3 obelisk_cli.py compile examples/nbg_verified_programs.nbg