Obelisk Proof Assistant — Reference Demonstration

Variant: Higher-Order Logic & Morse–Kelley Class Theory • Author: Georgy Dunaev • contact@obelisk.mozmail.com

1) Propositional logic

1.01) Axm. A01 (Weakening / Positive Implicative Axiom; K-Axiom; Russian: Утверждение следствия):
(α → (β → α))

1.02) Axm. A02 (Distribution of Implication):
((α → (β → γ)) → ((α → β) → (α → γ)))

1.03) Axm. A03 (Conjunction Elimination Left):
((α ∧ β) → α)

1.04) Axm. A04 (Conjunction Elimination Right):
((α ∧ β) → β)

1.05) Axm. A05 (Conjunction Introduction):
(α → (β → (α ∧ β)))

1.06) Axm. A06 (Disjunction Introduction Left):
(α → (α ∨ β))

1.07) Axm. A07 (Disjunction Introduction Right):
(β → (α ∨ β))

1.08) Axm. A08 (Disjunction Elimination / Cases):
((α → γ) → ((β → γ) → ((α ∨ β) → γ)))

1.09) Axm. A09 (Negation Introduction / Contradiction):
((¬α) → (α → ⊥))

1.10) Axm. A10 (Reductio Ad Absurdum):
((α → β) → ((α → ¬β) → ¬α))

1.11) Axm. A11 (Ex Falso Quodlibet):
(⊥ → α)

1.12) Axm. A12 (Law of Excluded Middle):
(α ∨ ¬α)

1.13) Rule Modus Ponens (MP):
α, (α → β) ⊢ β

2) Predicate logic

2.01) Axm. Discourse domain is non-empty:
∃(K : Class) ⊤

2.02) Rule Forall Instantiation (FI):
((∀(x : Class) φ) → φ[t/x])
Syntax side condition: FFI(t, v_x, φ)

2.03) Rule Exists Instantiation (EI):
(φ[t/x] → ∃(x : Class) φ)
Syntax side condition: FFI(t, v_x, φ)

2.04) Rule Forall Abstraction (FA / Bernays):
(ψ → φ) ⊢ (ψ → ∀(x : Class) φ)
Syntax side condition: (NFV(v_x, ψ) ∧ NFV(v_x, Γ))

2.05) Rule Exists Abstraction (EA / Bernays):
(φ → ψ) ⊢ (∃(x : Class) (φ → ψ))
Syntax side condition: (NFV(v_x, ψ) ∧ NFV(v_x, Γ))

2.06) Rule Generalisation (Gen):
φ ⊢ ∀(x : Class) φ
Syntax side condition: NFV(v_x, Γ)

3) Set/class-theoretic foundations of mathematics

3.01) Axm. Class Comprehension Axiom:

$\forall(x : \mathrm{Class})\ ((x \in \{\ y \mid \varphi(y)\ \}) \longleftrightarrow (\mathrm{isSet}(x) \wedge \varphi(x)))$

Syntax side condition: $\mathrm{NFV}(v_C, \varphi)$

3.02) Axm. Extensionality Axiom:

$\forall(A, B : \mathrm{Class})\ ((\forall(x : \mathrm{Class})\ ((x \in A) \longleftrightarrow (x \in B))) \rightarrow (A = B))$

3.08) Axm. Heredity Axiom (Subclasses of Sets are Sets):

$\forall(A, b : \mathrm{Class})\ ((\mathrm{isSet}(b) \wedge (A \subseteq b)) \rightarrow \mathrm{isSet}(A))$

3.12) Axm. Regularity (Foundation) Axiom:

$\forall(A : \mathrm{Class})\ ((A \neq \emptyset) \rightarrow \exists(x : \mathrm{Class})\ ((x \in A) \wedge ((x \cap A) = \emptyset)))$

3.13) Axm. Pairing Axiom:

$\forall(a, b : \mathrm{Class})\ ((\mathrm{isSet}(a) \wedge \mathrm{isSet}(b)) \rightarrow \mathrm{isSet}(\{a, b\}))$

3.14) Axm. Union Axiom:

$\forall(a : \mathrm{Class})\ (\mathrm{isSet}(a) \rightarrow \mathrm{isSet}(\bigcup a))$

3.22) Def. IF-THEN-ELSE-FI (Class conditional with NFV side condition and context turnstile):

$W, \Gamma \vdash (\llbracket \mathrm{IF}\ \psi\ \mathrm{THEN}\ A\ \mathrm{ELSE}\ B\ \mathrm{FI} \rrbracket = \{\ v \mid ((\psi \wedge (v \in A)) \vee (\neg\psi \wedge (v \in B)))\ \})$

Syntax side condition: $(\mathrm{NFV}(v_v, \psi) \wedge \mathrm{NFV}(v_v, \Gamma))$

3.23) Def. simple_if (metalevel conditional over Type_Expression):

$\forall(T_e : \mathrm{Type_Expression}),\ (\mathrm{simple_if}(\llbracket T_e \rrbracket) : (\mathrm{Bool} \rightarrow (\llbracket T_e \rrbracket \rightarrow (\llbracket T_e \rrbracket \rightarrow \llbracket T_e \rrbracket))))$

$\forall(T_e : \mathrm{Type_Expression}),\ \forall(t_1 : \llbracket T_e \rrbracket)\ \forall(t_2 : \llbracket T_e \rrbracket)\ ((\mathrm{simple_if}(\llbracket T_e \rrbracket, \mathrm{true}, t_1, t_2) = t_1) \wedge (\mathrm{simple_if}(\llbracket T_e \rrbracket, \mathrm{false}, t_1, t_2) = t_2))$

3.24) Def. if_dep (dependent conditional over Bool → Type_Expression):

$\forall(T_e : (\mathrm{Bool} \rightarrow \mathrm{Type_Expression})),\ (\mathrm{if_dep} : \Pi(b : \mathrm{Bool}),\ \llbracket T_e(\mathrm{true}) \rrbracket \rightarrow (\llbracket T_e(\mathrm{false}) \rrbracket \rightarrow \llbracket T_e(b) \rrbracket))$

$\forall(T_e : (\mathrm{Bool} \rightarrow \mathrm{Type_Expression})),\ \forall(b : \mathrm{Bool})\ \forall(t_1 : \llbracket T_e(\mathrm{true}) \rrbracket)\ \forall(t_2 : \llbracket T_e(\mathrm{false}) \rrbracket)\ ((\mathrm{if_dep}(b, t_1, t_2) : \llbracket T_e(b) \rrbracket) \wedge ((\mathrm{if_dep}(\mathrm{true}, t_1, t_2) = t_1) \wedge (\mathrm{if_dep}(\mathrm{false}, t_1, t_2) = t_2)))$

3.32) Thm. Ordinal Induction (∈-Ind):

$((\forall(x : \mathrm{Class})\ ((x \in \mathrm{On}) \rightarrow ((\forall(y : \mathrm{Class})\ ((y \in x) \rightarrow \varphi(y))) \rightarrow \varphi(x)))) \rightarrow \forall(x : \mathrm{Class})\ ((x \in \mathrm{On}) \rightarrow \varphi(x)))$

Syntax side condition: $(\mathrm{Fresh}(v_y, v_x) \wedge \mathrm{NFV}(v_y, \varphi(x)))$

3.33) Def. Power Class Definition (□(A)):

$\forall(A, x : \mathrm{Class})\ ((x \in \square(A)) \longleftrightarrow (\mathrm{isSet}(x) \wedge (x \subseteq A)))$

Syntax side condition: $\mathrm{Fresh}(v_x, v_A)$

3.34) Axm. Power Set / Exponent Axiom (Power Class of a Set is a Set):

$\forall(a : \mathrm{Class})\ (\mathrm{isSet}(a) \rightarrow \mathrm{isSet}(\square(a)))$

3.35) Def. Size Comparison Relation (A ≤ B / lesseq):

$\forall(A : \mathrm{Class})\ \forall(B : \mathrm{Class})\ ((A \preceq B) \longleftrightarrow \exists(f : \mathrm{Class})\ (((\mathrm{isClassFunction}(f) \wedge (A \subseteq \mathrm{Dom}(f))) \wedge (f[A] \subseteq B)) \wedge \mathrm{isInjective}(f)))$

3.36) Def. Class Cardinality (|K|):

$\forall(K : \mathrm{Class})\ (|K| = (\mathrm{On} \cap \bigcap(\{\ a \mid ((a \in \mathrm{On}) \wedge (K \preceq a))\ \})))$

3.37) Axm. Image / Replacement Axiom (isSet(F[a])):

$\forall(F, a : \mathrm{Class})\ ((\mathrm{isClassFunction}(F) \wedge \mathrm{isSet}(a)) \rightarrow \mathrm{isSet}(F[a]))$

3.38) Def. Strictly Smaller Size Relation (A ≺ B):

$\forall(A : \mathrm{Class})\ \forall(B : \mathrm{Class})\ ((A \prec B) \longleftrightarrow \neg(B \preceq A))$

3.39) Axm. Limitation of Size Axiom ((X ∈ V) ⟷ (|X| ≺ |V|)):

$\forall(X : \mathrm{Class})\ ((X \in V) \longleftrightarrow (|X| \prec |V|))$

3.40) Def. Dunaev Tagged Ordered Pair:

$\forall(A, B : \mathrm{Class})\ ([A, B]_D = \{\ z \mid \exists(a \in A)\ (z = \{\{\{\{a\}\}\}, \{\emptyset\}\})\ \vee\ \exists(b \in B)\ (z = \{\{\{\{b\}\}\}, \{\emptyset, \{\emptyset\}\}\})\ \})$

3.41) Thm. First Projection of Dunaev Tagged Ordered Pair:

$\forall(A, B : \mathrm{Class})\ (\{\ a \mid (\{\{\{\{a\}\}\}, \{\emptyset\}\} \in [A, B]_D)\ \} = A)$

3.42) Thm. Second Projection of Dunaev Tagged Ordered Pair:

$\forall(A, B : \mathrm{Class})\ (\{\ b \mid (\{\{\{\{b\}\}\}, \{\emptyset, \{\emptyset\}\}\} \in [A, B]_D)\ \} = B)$

3.45) Axm. Infinity Axiom:

$\exists(x : \mathrm{Class})\ (\mathrm{isSet}(x) \wedge ((\emptyset \in x) \wedge \forall(y : \mathrm{Class})\ ((y \in x) \rightarrow ((y \cup \{y\}) \in x))))$

3.46) Axm. Global Choice Axiom:

$\exists(F : \mathrm{Class})\ (\mathrm{isClassFunction}(F) \wedge \forall(x : \mathrm{Class})\ ((\mathrm{isSet}(x) \wedge (x \neq \emptyset)) \rightarrow (F(x) \in x)))$

3.47) Def. Universal Class (V):
(V = { x | (x = x) })

3.53) Def. Transitive Class Predicate:
(Tr(A) ⟷ ∀(x : Class) ((x ∈ A) → (x ⊆ A)))

3.66) Axm. Tarski's Axiom of Universes:
∀(x : Class) (isSet(x) → ∃(u : Class) ((isUniverse(u) ∧ (x ∈ u)) ∧ isSet(u)))

3.67) Def. Semi-Singleton Class Predicate (semi_singleton):
(semi_singleton(s) ⟷ ∀(x : Class) ∀(y : Class) (((x ∈ s) ∧ (y ∈ s)) → (x = y)))

3.68) Def. Semi-Singleton Subset Relation (s sss A):
∀(s : Class) ∀(A : Class) ((s sss A) ⟷ ((s ⊆ A) ∧ ∀(x : Class) ∀(y : Class) (((x ∈ s) ∧ (y ∈ s)) → (x = y))))

3.69) Thm. Theorem of Evaluation of a Family (F(x) = ⋃{ s | [x, s]_D ∈ F } and (Λx, t)(z) = t[z/x]):
∀(F : Class) ∀(x : Class) (isFamily(F) → (F(x) = ⋃({ s | ([x, s]_D ∈ F) })))
Syntax side condition: FFI(z, v_x, t)

3.70) Def. Set-Theoretic Model of Dependent Sum (ΣB / Sigma Model):
∀(B : Class) ∀(x : Class) ∀(y : Class) (isFamily(B) → (((x ∈ Dom(B)) ∧ (y ∈ B(x))) ⟷ ([x, y]_D ∈ { s | ∃(a : Class) ∃(b : Class) ((s = [a, b]_D) ∧ ((a ∈ Dom(B)) ∧ (b ∈ B(a)))) })))

3.71) Def. Set-Theoretic Model of Dependent Product (ΠB / Pi Predicate & Set-Section Models):
∀(B : Class) ∀(f : Class) ((isFamily(B) ∧ (isFamily(f) ∧ (Dom(f) = Dom(B)))) → ∀(x : Class) ((x ∈ Dom(B)) → (f(x) ∈ B(x))))

4) Metalogical laws

4.01) Axm. Instantiation Axiom:
∀(T_e : Type_Expression), ∀(G : Ctx) ∀(φ : Fm) ∀(t : ⟦T_e⟧) ∀(v : Variable) ((W, G ⊢ (∀(v : ⟦T_e⟧) φ)) → (W, G ⊢ (let v = t in φ)))

4.02) Axm. Generalisation Axiom:
∀(T_e : Type_Expression), ∀(Γ : Ctx) ∀(φ : Fm) ∀(v : Variable) (¬(Enc(v) ∈ Ctx.FV(Γ)) → ((W, Γ ⊢ φ) → (W, Γ ⊢ ∀(v : ⟦T_e⟧) φ)))
Syntax side condition: NFV(v, Γ)

4.03) Rule CoNecessitation:
(F, [] ⊢ ‹F, Γ ⊢ φ›) ⊢ (F, Γ ⊢ φ)

4.04) Def. Quantifier Unique (!):
∀(φ : Fm) ((!(z : Class) φ) ⟷ ∀(x, y : Class) ((φ[x/z] ∧ φ[y/z]) → (x = y)))

4.05) Def. Quantifier Exists and Unique (∃!):
∀(φ : Fm) (T, [] ⊢ ((∃!(x : Class) φ) ⟷ ((∃(x : Class) φ) ∧ !(x : Class) φ)))

4.06) Axm. Class Comprehension Axiom (Metatheory):
∀(φ : Fm) ∀(x : Name) ∀(k : Class.Expr) (FFI(k, x, φ) → (T, [] ⊢ ((k ∈ { x | φ }) ⟷ (isSet(k) ∧ φ[k/x]))))
Syntax side condition: FFI(k, x, φ)

4.07) Axm. Completeness / Reflection & Soundness of Full Theory F:
∀(φ : Fm) (((F, [] ⊢ φ) → ⟦φ⟧) ∧ (⟦φ⟧ → (F, [] ⊢ φ)))

4.08) Axm. Theory Inclusion (T ⊆ F):
∀(Γ : Ctx) ∀(φ : Fm) ((T, Γ ⊢ φ) → (F, Γ ⊢ φ))

4.09) Def. Syntactic Encoding Operator (Enc):
∀(T_e : Type_Expression), ∀(s : ⟦T_e⟧) (isSet(Enc(s)) ∧ (Enc(s) ∈ Emb(⟦T_e⟧)))

4.10) Def. Syntactic Decoding & Roundtrip Law (Dec):
∀(T_e : Type_Expression), ∀(s : ⟦T_e⟧) ((Dec(Enc(s), Emb(⟦T_e⟧)) : ⟦T_e⟧) = (s : ⟦T_e⟧))

4.11) Def. Dual Type Embedding Operator (Emb):
∀(X : Class) ((Emb(Class)(X) ⟷ ⊤) ∧ (Emb(Set)(X) ⟷ isSet(X)))

4.12) Def. Proof-Object Class Family (ProofsOf):
∀(s : Stmt) ∀(p : Prf) ((Enc(p) ∈ ProofsOf(Enc(s))) ⟷ CheckProof(p, s))

4.13) Def. Class of Provable Statements (Theorems):
∀(s : Stmt) ((Enc(s) ∈ Theorems) ⟷ (∃(p : Class) (p ∈ ProofsOf(Enc(s)))))

5) Tactics and inference rules

5.01) Thm. Elementary Theorems:

((F, [(b ∈ X)] ⊢ ∃(X : Class) (b ∈ X)) ∧ (F, [(b ∈ X)] ⊢ isSet(b)))

5.02) Rule Definition to Introduction Rule:

(F, [(b ∈ X)] ⊢ ∃(X : Class) (b ∈ X)) ⊢ (F, [(b ∈ X)] ⊢ isSet(b))

5.03) Rule Deduction Rule Application:

(F, [] ⊢ ((b ∈ X) → isSet(b)))

5.04) Thm. Tactics Proof Example:

F, [] ⊢ ((∃(Y : Class) ∀(x : Class) (x ∈ Y)) → ∀(x : Class) ∃(Y : Class) (x ∈ Y))

6) Incompleteness-related statements

6.01) Axm. Theories (Metalevel Stratification):

((Model(W) ⊆ Model(Q)) ∧ ((Model(Q) ⊆ Model(T)) ∧ (Model(T) ⊆ Model(F))))

6.02) Thm. Löb's Theorem:

∀(φ : Fm) (Q, [] ⊢ ((T, [] ⊢ ((T, [] ⊢ φ) → φ)) → (T, [] ⊢ φ)))

6.03) Thm. Gödel's Second Incompleteness Theorem:

Q, [] ⊢ (¬(T, [] ⊢ ⊥) → ¬(T, [] ⊢ ¬(T, [] ⊢ ⊥)))

Appendix: NBG Formulas-as-Types Standard Library

30 closed proof terms compiled by NBGSurfaceCompiler in Poly/ML. A formula is a type; a proof program is a term inhabiting it. The Dunaev pair injectivity theorem is the class-correct replacement for Kuratowski pairing on proper classes.

Theorem	Formula (Type)	AST	Norm
empty_class_no_elements	(∀(z : Class) ((z ∈ { x | ⊥ }) → ⊥))	7	7
empty_class_is_subclass	(∀(X : Class) (∀(z : Class) ((z ∈ { x | ⊥ }) → (z ∈ X))))	8	8
universal_class_characterization	(∀(z : Class) (((z ∈ { x | ⊤ }) → isSet(z)) ∧ (isSet(z) → (z ∈ { x | ⊤ }))))	15	15
russell_class_is_not_a_set	(isSet({ x | ((x ∈ x) → ⊥) }) → ⊥)	19	32
binary_inter_comm	(∀(A : Class) (∀(B : Class) (∀(z : Class) ((z ∈ { x | ((x ∈ A) ∧ (x ∈ B)) }) → (z ∈ { x | ((x ∈ B) ∧ (x ∈ A)) })))))	26	26
binary_union_comm	(∀(A : Class) (∀(B : Class) (∀(z : Class) ((z ∈ { x | ((x ∈ A) ∨ (x ∈ B)) }) → (z ∈ { x | ((x ∈ B) ∨ (x ∈ A)) })))))	23	23
class_diff_subclass_left	(∀(A : Class) (∀(B : Class) (∀(z : Class) ((z ∈ { x | ((x ∈ A) ∧ ((x ∈ B) → ⊥)) }) → (z ∈ A)))))	10	10
class_eq_sym	(∀(X : Class) (∀(Y : Class) ((X = Y) → (Y = X))))	6	6
class_eq_trans	(∀(X : Class) (∀(Y : Class) (∀(Z : Class) (((X = Y) ∧ (Y = Z)) → (X = Z)))))	9	9
quantifier_swap	(∀(R : Class) ((∃(y : Set) (∀(x : Set) ([x, y]_D ∈ R))) → (∀(x : Set) (∃(y : Set) ([x, y]_D ∈ R)))))	8	8
dunaev_tagged_pair_projections	(∀(A : Class) (∀(B : Class) ((π₁([A, B]_D) = A) ∧ (π₂([A, B]_D) = B))))	3	3
cantor_diagonal_theorem	(∀(S : Class) (∀(R : Class) (∀(c : Class) ((c ∈ S) → ((((c ∈ { x | ((x ∈ S) ∧ (([x, x]_D ∈ R) → ⊥)) }) → ([c, c]_D ∈ R)) ∧ (([c, c]_D ∈ R) → (c ∈ { x | ((x ∈ S) ∧ (([x, x]_D ∈ R) → ⊥)) }))) → ⊥)))))	34	62
self_in_singleton	(∀(x : Class) (isSet(x) → (x ∈ { u | (u = x) })))	8	8
self_in_succ	(∀(x : Class) (isSet(x) → (x ∈ { u | ((u ∈ x) ∨ (u = x)) })))	9	9
class_sub_succ	(∀(x : Class) (∀(z : Class) ((z ∈ x) → (z ∈ { u | ((u ∈ x) ∨ (u = x)) }))))	12	12
dunaev_pair_injective	(∀(A : Class) (∀(B : Class) (∀(C : Class) (∀(E : Class) (([A, B]_D = [C, E]_D) → ((A = C) ∧ (B = E)))))))	26	26
dunaev_cartesian_elim	(∀(A : Class) (∀(B : Class) (∀(p : Class) ((p ∈ { q | (∃(u : Set) (∃(v : Set) (((u ∈ A) ∧ (v ∈ B)) ∧ (q = [u, v]_D)))) }) → (∃(u : Set) (∃(v : Set) (((u ∈ A) ∧ (v ∈ B)) ∧ (p = [u, v]_D))))))))	9	9
inter_sub_left	(∀(A : Class) (∀(B : Class) (∀(z : Class) ((z ∈ { u | ((u ∈ A) ∧ (u ∈ B)) }) → (z ∈ A)))))	10	10
inter_sub_right	(∀(A : Class) (∀(B : Class) (∀(z : Class) ((z ∈ { u | ((u ∈ A) ∧ (u ∈ B)) }) → (z ∈ B)))))	10	10
union_sub_left	(∀(A : Class) (∀(B : Class) (∀(z : Class) ((z ∈ A) → (z ∈ { u | ((u ∈ A) ∨ (u ∈ B)) })))))	13	13
semi_singleton_sub_elim	(∀(s : Class) (∀(A : Class) (∀(x : Class) (∀(y : Class) (((∀(u : Class) ((u ∈ s) → (u ∈ A))) ∧ (∀(u : Class) (∀(v : Class) (((u ∈ s) ∧ (v ∈ s)) → (u = v))))) → (((x ∈ s) ∧ (y ∈ s)) → ((x ∈ A) ∧ (x = y))))))))	19	19
family_fiber_char	(∀(A : Class) (∀(s : Class) ((s ∈ { u | (u ⊆ A) }) → (isSet(s) ∧ (s ⊆ A)))))	7	7
sigma_dependent_sum_intro	(∀(B : Class) (∀(x : Set) (∀(y : Set) ((isSet([x, y]_D) ∧ ((x ∈ Dom(B)) ∧ (y ∈ ValOf(B, x)))) → ([x, y]_D ∈ { p | (∃(a : Set) (∃(b : Set) (((a ∈ Dom(B)) ∧ (b ∈ ValOf(B, a))) ∧ (p = [a, b]_D)))) })))))	16	16
pi_dependent_product_elim	(∀(B : Class) (∀(f : Class) (∀(x : Class) (((∀(u : Class) ((u ∈ Dom(B)) → (ValOf(f, u) ∈ ValOf(B, u)))) ∧ (x ∈ Dom(B))) → (ValOf(f, x) ∈ ValOf(B, x))))))	10	10
union_sub_right	(∀(A : Class) (∀(B : Class) (∀(z : Class) ((z ∈ B) → (z ∈ { u | ((u ∈ A) ∨ (u ∈ B)) })))))	13	13
model_stratification_trans	(∀(W : Class) (∀(Q : Class) (∀(T : Class) (∀(F : Class) (((∀(z : Class) ((z ∈ Model(W)) → (z ∈ Model(Q)))) ∧ ((∀(z : Class) ((z ∈ Model(Q)) → (z ∈ Model(T)))) ∧ (∀(z : Class) ((z ∈ Model(T)) → (z ∈ Model(F)))))) → (∀(z : Class) ((z ∈ Model(W)) → (z ∈ Model(F))))))))	22	22
if_dep_true_elim	(∀(A : Class) (∀(T1 : Class) (∀(T2 : Class) (∀(x : Class) (∀(z : Class) (((((x ∈ A) → (if_dep(x, A, ValOf(T1, x), ValOf(T2, x)) = ValOf(T1, x))) ∧ (((x ∈ A) → ⊥) → (if_dep(x, A, ValOf(T1, x), ValOf(T2, x)) = ValOf(T2, x)))) ∧ ((x ∈ A) ∧ (z ∈ if_dep(x, A, ValOf(T1, x), ValOf(T2, x))))) → (z ∈ ValOf(T1, x))))))))	17	17
if_dep_false_elim	(∀(A : Class) (∀(T1 : Class) (∀(T2 : Class) (∀(x : Class) (∀(z : Class) (((((x ∈ A) → (if_dep(x, A, ValOf(T1, x), ValOf(T2, x)) = ValOf(T1, x))) ∧ (((x ∈ A) → ⊥) → (if_dep(x, A, ValOf(T1, x), ValOf(T2, x)) = ValOf(T2, x)))) ∧ (((x ∈ A) → ⊥) ∧ (z ∈ if_dep(x, A, ValOf(T1, x), ValOf(T2, x))))) → (z ∈ ValOf(T2, x))))))))	17	17
inter_idempotent_elim	(∀(A : Class) (∀(z : Class) ((z ∈ { u | ((u ∈ A) ∧ (u ∈ A)) }) → (z ∈ A))))	9	9
singleton_membership_eq	(∀(a : Class) (∀(z : Class) ((z ∈ { u | (u = a) }) → (z = a))))	8	8

Reproduce locally: python3 obelisk_cli.py compile examples/nbg_verified_programs.nbg