PA & CO - logo for debossing

What the artwork can hold, and at what size.


The smallest feature depends only on the size

At 50 mm the thinnest stroke is 0.25 mm and the tightest gap, between the O and the bar under it, is 0.88 mm. Making the strokes heavier does not help on its own: every 0.1 mm added to a stroke is 0.1 mm taken from the gap beside it, because both edges move. The two meet in the middle, so the best this logo can do is half of what the stroke and the gap add up to, which scales to one millimetre for every 88 mm of width:

50.0 mm wide	smallest feature 0.56 mm	
60.0 mm wide	smallest feature 0.68 mm	
70.0 mm wide	smallest feature 0.79 mm	
80.0 mm wide	smallest feature 0.90 mm	
88.7 mm wide	smallest feature 1.00 mm	<- 1.00 mm needs 88.7 mm
100.0 mm wide	smallest feature 1.13 mm	


The O and the bar, at 4x

as supplied




stroke 0.25 mm, gap 0.88 mm

90 mm file



stroke 1.02 mm, gap 1.02 mm

50 mm file



stroke 0.57 mm, gap 0.57 mm

The two files

	90 mm	**50 mm**
Thinnest stroke	1.02 mm	0.57 mm
O-to-bar gap	1.02 mm	0.57 mm
Next tightest gap, C to O	2.21 mm	1.23 mm
Shapes / counters	6 / 12	6 / 12
Drawing changed?	nothing moved	nothing moved

Which to use

If the minimum is 1 mm, the logo must run at 88.7 mm or wider. The 90 mm file does that with nothing moved: every stroke 1.02 mm, every gap 1.02 mm or more.

The 50 mm file is the most this logo can give at that size, 0.57 mm. Use it only if the producer confirms they hold 0.57 mm; otherwise work to the width in the table.

In both, the O is joined to the bar by a stem of the bar's own weight, so they deboss as one piece. The slivers at the diamond's inner facets and the crook of the ampersand still taper below these figures; they are wedges, they measure the same as supplied, and they round off.