PA & CO - logo for debossing

Every stroke raised to 1 mm, and the O-to-bar junction kept open.


The two constraints

The thinnest stroke in the artwork is 0.26 mm. Raising it to 1 mm adds 0.37 mm to every edge.

The bar sits 0.88 mm below the bowl of the O. That gap is already under 1 mm, and bolding takes 0.75 mm out of it, leaving 0.13 mm, which fills in and reads as a blob. The gap cannot reach 1 mm at 50 mm by any amount of bolding, because it does not start there. Either the bar moves down, or the logo runs bigger. Both are drawn below.


The junction, at 4x

as supplied




gap 0.88 mm

A: bar moved down 0.95 mm



gap 1.03 mm

B: at 90 mm, nothing moved



gap 1.04 mm

Two files, pick one

	A - 50 mm wide	**B - 90 mm wide**
Thinnest stroke	1.03 mm	1.00 mm
Heaviest stroke	2.83 mm	4.20 mm
Thick-to-thin contrast	2.7 : 1	4.2 : 1
as supplied	7.9 : 1	7.9 : 1
O-to-bar gap	1.03 mm	1.04 mm
Shapes / counters	6 / 12	6 / 12
Drawing changed?	bar lowered 0.95 mm	nothing moved
Overall size	50.0 x 35.6 mm	90.0 x 61.9 mm

Which to use

B is the better drawing. Nothing is moved, and it keeps far more of the thick-to-thin contrast the logo is built on. Use it wherever the logo can run at 90 mm.

A is for 50 mm. It holds 1 mm everywhere, but the bar sits 0.95 mm lower to keep the junction open, and taking a 0.26 mm hairline to 1 mm at this size flattens the contrast.

Both keep the O joined to the bar, so each debosses as a single piece.

Three places still taper below 1 mm: the two slivers where the diamond's inner facets meet its point, and the crook of the ampersand. These are wedges that narrow to nothing, not channels, they measure the same in the artwork as supplied, and they will simply round off a little.

If the supplier can hold finer than 1 mm, both files can be redrawn lighter, which costs less of the contrast and, for A, moves the bar less.