Project 2: Bookmark

1. JS Console Error 2.	Solution : Project settings -> API keys
2. Email not confirmed	Solution : Project Setting -> Authentication -> disable email confirm
3. Testing bug 	Solution : Claude fixed it. Logic problem.

Console errors (image 1):

```
⊗ ▶ POST                                    supabaseService.js:24
  https://bookmgr.supabase.co/auth/v1/token?grant_type=password
  net::ERR_NAME_NOT_RESOLVED

⊗ ▶ TypeError: Failed to fetch                    installHook.js:1
      at Object.signIn (supabaseService.js:24:49)
      at handleAuth (bookmark-manager.jsx:135:44)
    Show ignore-listed frames

⊗ ▶ Auth error: AuthRetryableFetchError: Failed to fetch    installHook.js:1
      at async Object.signIn (supabaseService.js:24:29)
      at async handleAuth (bookmark-manager.jsx:135:26)
    Show ignore-listed frames

  ▶  [cmd] [i] to turn on code suggestions. Don't show again  NEW
```

Testing bug (image 2):

Found a bug : If I have 2 folders, named work and tech and 4 bookmark entries. 2 each in work & tech. When I look at tech and then go back to 'All Bookmarks' view, it shows 0 entries

What Was the Bug?

The Problem:

When you clicked on "All Bookmarks" folder, it was being treated as a regular folder and trying to filter bookmarks by its UUID instead of showing ALL bookmarks.

Flow of the bug:

1. Database creates "All Bookmarks" folder with UUID (e.g., `abc-123-def`)
2. User clicks "All Bookmarks" → `selectedFolder` = `abc-123-def`
3. Filter logic: `if (selectedFolder !== 'all')` → TRUE (because it's a UUID, not 'all')
4. Tries to filter: `bookmarks.filter(b => b.folder_id === 'abc-123-def')`
5. **But bookmarks are in 'work' and 'tech' folders, not in the default folder!**
6. Result: 0 bookmarks shown ❌

Why This Happened (image 3):

The Supabase version uses real database UUIDs for folder IDs, but the initial code assumed "All Bookmarks" would always have the ID `'all'` (like the localStorage version). When the default folder was created in the database, it got a UUID, breaking the assumption.

The fix makes it work for both:

- String ID `'all'` (localStorage)
- UUID with `is_default: true` flag (Supabase)