

OBI Data Modelling Prototype

James A. Overton james@overton.ca

2013-06-17

This is a prototype of the “value specification” approach to modelling data in OBI/IAO. It is based on discussing during the Philly2013 workshop and on the mailing list, but it does not (yet) reflect a consensus.

I used the new OBI build tool to convert this document into OWL and test it. See: <http://obi.svn.sourceforge.net/viewvc/obi/trunk/src/tools/build/>

Motivation

OBI’s scope is biomedical investigations, and it must be able to describe the data generated in investigations. Some of the oldest terms in OBI and IAO were designed to describe measurement. More recently, we have recognized the need to describe predictions, simulations, and setting information. Superficially these are very similar to each other. “20g” could occur as:

1. a measurement of the mass of a particular mouse
2. a predicted mass of some future mouse after a treatment
3. an output of a simulation of mouse growth
4. a rule for selecting mice of a certain mass

Despite the superficial similarity, 1-4 are *about* very different things (if they’re about anything at all):

1. a particular quality of a particular mouse at a particular time – something that clearly existed
2. a calculated value that does not correspond to any existing particular quality, but may be compared with a particular quality of a particular mouse in the future if the treatment is carried out
3. a calculated value, perhaps about what the mass of mice in general would be like under certain conditions
4. a directive, perhaps about part of a particular plan (now) to select mice in the future

OBI is a realist ontology, where we try to build consensus by being as precise as we can be about what is going on in the world. *Aboutness* is our primary way of distinguishing information content entities, and so we need to be clear in distinguishing measurements from predictions and settings, etc. This pushes our modelling toward greater complexity.

But we also want our modelling to be as simple as possible. We would like to *factor out* the similarities between 1-4, in order to reuse as much of our modelling as possible, and in order to reduce the number of asserted hierarchies we're dealing with.

In the proposal laid out here we distinguish the *structure* from the *content* of an information content entity. We assert a new hierarchy under "information structural entity" that contains "value specifications" such as the "20g" structure, which are not clearly *about* anything. Under "information content entity" we include entities that are clearly about things (in different ways), such a measurement data.

The proposal is designed to add just enough complexity to allow us to model measurements, predictions, and simulations in a similar way, by factoring out the shared structure of a "value specification".

Here are some notes on previous discussions:

- [Bjoern's summary and proposal](#)
- [ICBO 2012 working session](#)
- [Christian's summary and proposal](#)
- [Philippe and Alejandra's modelling tests](#)

Upper Ontology

For clarity, we start from scratch rather than importing an existing ontology. Wherever possible, terms here have the same ID as in their source ontologies.

These are BFO classes and relations that we will need. NOTE: I don't include "dependent continuant", because it's not in BFO2 Graz and doesn't serve a purpose here.

```
Class: obo:BFO_0000001
Annotations: rdfs:label "entity"

Class: obo:BFO_0000002
Annotations: rdfs:label "continuant"
SubClassOf: 'entity'

Class: obo:BFO_0000031
```

```

    Annotations: rdfs:label "generically dependent continuant"
    SubClassOf: 'continuant'

Class: obo:BF0_0000020
    Annotations: rdfs:label "specifically dependent continuant"
    SubClassOf: 'continuant'

Class: obo:BF0_0000004
    Annotations: rdfs:label "independent continuant"
    SubClassOf: 'continuant'

Class: obo:BF0_0000019
    Annotations: rdfs:label "quality"
    SubClassOf: 'specifically dependent continuant'

ObjectProperty: obo:BF0_0000086
    Annotations: rdfs:label "has quality"

Class: obo:BF0_0000003
    Annotations: rdfs:label "occurrent"
    SubClassOf: 'entity'

Class: obo:BF0_0000015
    Annotations: rdfs:label "process"
    SubClassOf: 'occurrent'

ObjectProperty: obo:BF0_0000057
    Annotations: rdfs:label "participates in"

```

Running Example

Our running example will involve measurements of a particular mouse named “Mickey” as part of a fictional investigation. Here we describe two universals and two particulars:

```

Class: obo:PATO_0000125
    Annotations: rdfs:label "mass"
    SubClassOf: 'quality'

Individual: mickey
    Annotations: rdfs:label "Mickey",
                 rdfs:comment "Mickey is a mouse."
    Facts: 'has quality' 'mass of Mickey'

```

```
Individual: mickey-mass
Types: 'mass'
Annotations: rdfs:label "mass of Mickey"
```

NOTE: In a previous draft of this document we used the determinable/determinate distinction to sub-class ‘mass’. This made the modelling more complicated. Since a BFO OWL representation of determinable/determinate classes have not yet been discussed in detail, we decided to remove them from the current prototype.

- Barry’s slides: <http://ontology.buffalo.edu/bfo/2013/BFO-2-Smith.ppt>
- Bare BFO2 issue: <https://code.google.com/p/bfo/issues/detail?id=42>

NOTE: I also haven’t tried modelling time in this prototype.

We’ll focus first on scalar measurements of Mickey’s mass. In later versions of this document we’ll consider some other cases.

Information Entities

Under “generically dependent continuant” we distinguish between information content entities (ICEs) that are *about* something, and information entities that are purely structural (ISEs) and not about anything. This is a new distinction put forward by Alan based on ongoing discussions with Barry and Werner.

```
ObjectProperty: obo:IAO_0000136
Annotations: rdfs:label "is about"
```

```
Class: obo:IAO_0000030
Annotations: rdfs:label "information content entity"
SubClassOf: 'generically dependent continuant'
SubClassOf: 'is about' some 'entity'
```

```
Class: information-structural-entity
Annotations: rdfs:label "information structural entity"
SubClassOf: 'generically dependent continuant'
```

In order to connect ISEs to ICEs we define a new relation. The label is just temporary.

```
ObjectProperty: has-information-structure
Annotations: rdfs:label "has information structure"
Domain: 'information content entity'
Range: 'information structural entity'
```

Units of Measurement

Under ISE we include “unit labels” to connect to the Units of Measurement Ontology, and we have an ObjectProperty and a DataProperty to use with them:

```
Class: obo:IAO_0000003
  Annotations: rdfs:label "unit label",
               rdfs:comment "was 'measurement unit label'"
  SubClassOf: 'information structural entity'

ObjectProperty: obo:IAO_0000039
  Annotations: rdfs:label "has unit label",
               rdfs:comment "was 'has measurement unit label'"
```

In OBI we have been modelling specific measurement units as OWL individuals. For our purposes we’ll just need the SI unit “gram”.

```
Class: obo:UO_0000002
  Annotations: rdfs:label "mass unit label"
  SubClassOf: 'unit label'

Individual: obo:UO_0000021
  Types: 'mass unit label'
  Annotations: rdfs:label "gram"
```

Value Specifications

Also under ISE we have “value specification”. The most important of these is “scalar value specification”, which is the pair of a number and a unit.

```
Class: obo:IAO_0000601
  Annotations: rdfs:label "value specification"
  SubClassOf: 'information structural entity'

DataProperty: obo:IAO_0000004
  Annotations: rdfs:label "has value",
               rdfs:comment "was 'has measurement value'"
  Range: xsd:float
```

TODO: explain this relation

```
ObjectProperty: obo:IAO_0000605
  Annotations: rdfs:label "specifies value of"
  SubPropertyOf: 'is about'
```

Given the “unit label” asserted hierarchy, we can create a hierarchy of *defined classes* as needed:

```
Class: obo:IAO_0000602
  Annotations: rdfs:label "scalar value specification"
  EquivalentTo: 'value specification' and
    'has unit label' some 'unit label'

Class: scalar-mass-value-specification
  Annotations: rdfs:label "scalar mass value specification"
  EquivalentTo: 'value specification' and
    'has unit label' some 'mass unit label'
```

Here is an example of a particular scalar mass value specification, “20g”:

```
Individual: mass-20g-structure
  Types: 'value specification'
  Annotations: rdfs:label "mass 20g structure"
  Facts: 'has unit label' 'gram',
    'has value' "20"
```

Notice that we only assert that this is a ‘value specification’, and not that it is specifically a ‘scalar mass value specification’. The reasoner will classify it correctly:

```
Fact: mass 20g structure is a scalar mass value specification
Query: 'scalar mass value specification'
Individuals: include 'mass 20g structure'
```

Measurement Data

Our primary goal is to model measurement data well. We assert this class in OBI:

```
Class: obo:IAO_0000109
  Annotations: rdfs:label "measurement datum",
    rdfs:comment "We will also model the following:
      is_specified_output_of some
        ('data transformation' or prediction or 'information acquisition')"
```

Given the asserted hierarchy of value specifications, we can create a *defined hierarchy* of measurement classes.

```

Class: value-measurement-datum
  Annotations: rdfs:label "value measurement datum"
  EquivalentTo: 'measurement datum' and
    'has information structure' some 'value specification'

Class: scalar-measurement-datum
  Annotations: rdfs:label "scalar measurement datum"
  EquivalentTo: 'measurement datum' and
    'has information structure' some 'scalar value specification'

Class: scalar-mass-measurement-datum
  Annotations: rdfs:label "scalar mass measurement datum"
  EquivalentTo: 'measurement datum' and
    ('has information structure' some 'scalar mass value specification') and
    ('specifies value of' some 'mass')

```

We define an instance of a measurement datum about Mickey’s mass by linking the information structural entity “20g” (using ‘has information structure’) to the particular mass quality being measured (using ‘specifies value of’):

```

Individual: mass-20g-measurement
  Types: 'measurement datum'
  Annotations: rdfs:label "scalar measurement of mass of Mickey"
  Facts: 'has information structure' 'mass 20g structure',
    'specifies value of' 'mass of Mickey'

```

We just assert that this is a ‘measurement datum’, but the reasoner classifies it correctly as a ‘scalar mass measurement datum’ and a ‘mass measurement datum’:

```

Fact: mass measurement of Mickey is a scalar mass measurement datum
Query: 'scalar mass measurement datum'
Individuals: include 'scalar measurement of mass of Mickey'

```

Queries

Modelling the data correctly is important, but we also need to query the data and get useful answers. First of all, we can query for all mass measurements:

```

Fact: mass measurement of Mickey is a mass measurement datum
Query: 'measurement datum' and ('specifies value of' some 'mass')
Individuals: include 'scalar measurement of mass of Mickey'
Subclasses: include 'scalar mass measurement datum'

```

We can create this defined class to capture all mass measurements:

```
Class: mass-measurement-datum
  Annotations: rdfs:label "mass measurement datum"
  EquivalentTo: 'measurement datum' and
    'specifies value of' some 'mass'

Fact: mass measurement of Mickey is a 'mass measurement datum'
Query: 'mass measurement datum'
Individuals: include 'scalar measurement of mass of Mickey'
Subclasses: include 'scalar mass measurement datum'
```

Using SPARQL we can get the subject, value, and units for mass measurements:

```
FACT get subject, value, and units for mass of Mickey measurement
PREFIX obo: <http://purl.obolibrary.org/obo/>
PREFIX : <http://purl.obolibrary.org/obo/obi/test.owl#>
SELECT ?subject ?value ?unit
WHERE {
  ?mass rdf:type obo:PATO_0000125 . # PATO mass
  ?subject obo:BFO_0000086 ?mass_instance . # BFO has quality
  ?measurement rdf:type obo:IAO_0000109 . # IAO measurement datum
  ?measurement obo:IAO_0000605 ?mass_instance . # IAO specifies value of
  ?measurement :has-information-structure ?spec .
  ?spec obo:IAO_0000039 ?unit . # IAO has unit label
  ?spec obo:IAO_0000004 ?value . # IAO has value
}
INCLUDE 'Mickey' "20" 'gram'
```

This query looks fairly complicated. However the only *added* complexity from using “value specification” is the ‘has information structure’ link:

```
?measurement :has-information-structure ?spec .
```

TODO: Add a Turtle example. Because Turtle has a nicer syntax for specifying anonymous entities, I expect it to look cleaner than have OWL individuals for the measurement datum and the value specification.

Measurement Processes

When modelling measurements, it’s also important to be able to trace which processes produced which results. We’ll extend the current model to include an assay that measures Mickey.


```

Class: obo:OBI_0000011
  Annotations: rdfs:label "planned process"
  SubClassOf: 'process'

Class: obo:OBI_0000070
  Annotations: rdfs:label "assay"
  SubClassOf: 'planned process'

ObjectProperty: obo:OBI_0000293
  Annotations: rdfs:label "has specified input"
  SubPropertyOf: 'participates in'

ObjectProperty: obo:OBI_0000299
  Annotations: rdfs:label "has specified output"
  SubPropertyOf: 'participates in'

Individual: assay-of-mass-of-mickey
  Types: 'assay'
  Annotations: rdfs:label "assay of mass of Mickey"
  Facts: 'has specified input' 'Mickey',
        'has specified output' 'scalar measurement of mass of Mickey'

```

Now we extend the query above to include the assay that generated the measurement datum.

```

FACT get the assay that measured the mass of Mickey
PREFIX obo: <http://purl.obolibrary.org/obo/>
PREFIX : <http://purl.obolibrary.org/obo/obi/test.owl#>
SELECT ?assay ?subject ?value ?unit
WHERE {
  ?mass rdf:type obo:PATO_0000125 . # PATO mass
  ?subject obo:BFO_0000086 ?mass_instance . # BFO has quality
  ?measurement rdf:type obo:IAO_0000109 . # IAO measurement datum
  ?measurement obo:IAO_0000605 ?mass_instance . # IAO specifies value of
  ?measurement :has-information-structure ?spec .
  ?spec obo:IAO_0000039 ?unit . # IAO has unit label
  ?spec obo:IAO_0000004 ?value . # IAO has value
  ?assay obo:OBI_0000299 ?measurement . # OBI has specified output
}
INCLUDE 'assay of mass of Mickey' 'Mickey' "20" 'gram'

```

We can query forward from Mickey to the results about him:

```

FACT get the results of assays with Mickey as input
PREFIX obo: <http://purl.obolibrary.org/obo/>

```

```

PREFIX : <http://purl.obolibrary.org/obo/obi/test.owl#>
SELECT ?value ?unit
WHERE {
  ?assay obo:OBI_0000293 :mickey . # OBI has specified input
  ?assay obo:OBI_0000299 ?measurement . # OBI has specified output
  ?measurement :has-information-structure ?spec .
  ?spec obo:IAO_0000039 ?unit . # IAO has unit label
  ?spec obo:IAO_0000004 ?value . # IAO has value
}
INCLUDE "20" 'gram'

```

We can query backward from a given measurement datum to the assay and its input:

```

FACT get the input of the assay that generated a particular measurement
PREFIX obo: <http://purl.obolibrary.org/obo/>
PREFIX : <http://purl.obolibrary.org/obo/obi/test.owl#>
SELECT ?assay ?input
WHERE {
  ?assay obo:OBI_0000299 :mass-20g-measurement . # OBI has specified output
  ?assay obo:OBI_0000293 ?input . # OBI has specified input
}
INCLUDE 'assay of mass of Mickey' 'Mickey'

```

If a value specification is unique, then we can query back from it to the assay and inputs:

```

FACT get the input of the assay that generated a particular value specification
PREFIX obo: <http://purl.obolibrary.org/obo/>
PREFIX : <http://purl.obolibrary.org/obo/obi/test.owl#>
SELECT ?assay ?input
WHERE {
  ?measurement :has-information-structure :mass-20g-structure .
  ?assay obo:OBI_0000299 ?measurement . # OBI has specified output
  ?assay obo:OBI_0000293 ?input . # OBI has specified input
}
INCLUDE 'assay of mass of Mickey' 'Mickey'

```

However, we might want to reuse the same value specification for all our “20g” measurements, in which case this query will not return a unique assay and input.

Other Cases

TODO: Provide examples of categorical measurements and unstructured measurements.

TODO: Provide examples of settings.