

Infinite Width, NTK, and Feature Learning

Student Meeting 1

Shreyas Kalvankar

October 2, 2025

TU Delft

Agenda

Goal of this talk

- Introduce the infinite-width lens, NTK, and the lazy training regime via a simple one-layer example.
- Situate these ideas within related work: baseline results at infinite width and viewpoints that go beyond linearization.

What I would like from you

- Conceptual clarifications and critiques of how I'm connecting the papers.
- Suggestions for key references I might be missing.
- Pointers to alternative frameworks worth comparing (mean-field, functional-analytic, optimization bias).

Why theory?

- Larger models keep improving, but we don't fully know *why*.

Why theory?

- Larger models keep improving, but we don't fully know *why*.
- **A solvable starting point:** infinite width gives a clean baseline; modern models are large-but-finite, deep, and do feature learning.

Why theory?

- Larger models keep improving, but we don't fully know *why*.
- **A solvable starting point:** infinite width gives a clean baseline; modern models are large-but-finite, deep, and do feature learning.
- **What can theory help in:** explanations of convergence/generalization, signals for when features move, and guidance on design choices (init, learning rate, normalization).

- **Infinite width:** clean, analyzable baseline; randomness averages to a deterministic kernel.

- **Infinite width:** clean, analyzable baseline; randomness averages to a deterministic kernel.
- **NTK:** first-order (linear) view of training; clear convergence intuition via a fixed kernel.

- **Infinite width:** clean, analyzable baseline; randomness averages to a deterministic kernel.
- **NTK:** first-order (linear) view of training; clear convergence intuition via a fixed kernel.
- **Beyond the linear NTK picture:** when does it stop being accurate?
 - Does the *kernel* change during training?

- **Infinite width:** clean, analyzable baseline; randomness averages to a deterministic kernel.
- **NTK:** first-order (linear) view of training; clear convergence intuition via a fixed kernel.
- **Beyond the linear NTK picture:** when does it stop being accurate?
 - Does the *kernel* change during training?
 - Do the model's internal features move?

- **Infinite width:** clean, analyzable baseline; randomness averages to a deterministic kernel.
- **NTK:** first-order (linear) view of training; clear convergence intuition via a fixed kernel.
- **Beyond the linear NTK picture:** when does it stop being accurate?
 - Does the *kernel* change during training?
 - Do the model's internal features move?
 - Do training curves deviate from the NTK baseline prediction?

- **Infinite width:** clean, analyzable baseline; randomness averages to a deterministic kernel.
- **NTK:** first-order (linear) view of training; clear convergence intuition via a fixed kernel.
- **Beyond the linear NTK picture:** when does it stop being accurate?
 - Does the *kernel* change during training?
 - Do the model's internal features move?
 - Do training curves deviate from the NTK baseline prediction?
 - Possible causes: higher-order effects, useful parameter re-organization that push the model out of the lazy regime.

Supervised learning: data $\{(\mathbf{x}_i, y_i)\}_{i=1}^n$, $\mathbf{x}_i \in \mathbb{R}^d$, $y_i \in \mathbb{R}$.

Supervised learning: data $\{(\mathbf{x}_i, y_i)\}_{i=1}^n$, $\mathbf{x}_i \in \mathbb{R}^d$, $y_i \in \mathbb{R}$.

Neural network $f : \mathbb{R}^d \times \Theta \rightarrow \mathbb{R}$ with parameters $\boldsymbol{\theta} \in \Theta \subset \mathbb{R}^p$.

Supervised learning: data $\{(\mathbf{x}_i, y_i)\}_{i=1}^n$, $\mathbf{x}_i \in \mathbb{R}^d$, $y_i \in \mathbb{R}$.

Neural network $f : \mathbb{R}^d \times \Theta \rightarrow \mathbb{R}$ with parameters $\boldsymbol{\theta} \in \Theta \subset \mathbb{R}^p$.

Trained by (continuous-time) gradient flow on squared loss:

$$L(\boldsymbol{\theta}) = \frac{1}{2} \sum_{i=1}^n (f(\mathbf{x}_i; \boldsymbol{\theta}) - y_i)^2,$$

Supervised learning: data $\{(\mathbf{x}_i, y_i)\}_{i=1}^n$, $\mathbf{x}_i \in \mathbb{R}^d$, $y_i \in \mathbb{R}$.

Neural network $f : \mathbb{R}^d \times \Theta \rightarrow \mathbb{R}$ with parameters $\boldsymbol{\theta} \in \Theta \subset \mathbb{R}^p$.

Trained by (continuous-time) gradient flow on squared loss:

$$L(\boldsymbol{\theta}) = \frac{1}{2} \sum_{i=1}^n (f(\mathbf{x}_i; \boldsymbol{\theta}) - y_i)^2, \quad \frac{d}{dt} \boldsymbol{\theta}_t = -\nabla_{\boldsymbol{\theta}} L(\boldsymbol{\theta}_t).$$

Linearization at Initialization

First-order Taylor around θ_0 :

$$f(\mathbf{x}; \boldsymbol{\theta}) \approx f(\mathbf{x}; \boldsymbol{\theta}_0) + \underbrace{\nabla_{\boldsymbol{\theta}} f(\mathbf{x}; \boldsymbol{\theta}_0)^\top}_{:= \boldsymbol{\phi}(\mathbf{x})^\top} (\boldsymbol{\theta} - \boldsymbol{\theta}_0).$$

Linearization at Initialization

First-order Taylor around θ_0 :

$$f(\mathbf{x}; \theta) \approx f(\mathbf{x}; \theta_0) + \underbrace{\nabla_{\theta} f(\mathbf{x}; \theta_0)^{\top}}_{:= \phi(\mathbf{x})^{\top}} (\theta - \theta_0).$$

This induces the **Neural Tangent Kernel (NTK)** at θ_0 :

$$K(\mathbf{x}, \mathbf{x}') = \phi(\mathbf{x})^{\top} \phi(\mathbf{x}') = \nabla_{\theta} f(\mathbf{x}; \theta_0)^{\top} \nabla_{\theta} f(\mathbf{x}'; \theta_0).$$

Ref: (Jacot et al., 2018)

Illustrative Model (One Hidden Layer, No Biases)

Consider a m -width neural network

$$f(\mathbf{x}) = \frac{1}{\sqrt{m}} \sum_{r=1}^m a_r \sigma(\mathbf{w}_r^\top \mathbf{x}),$$

Illustrative Model (One Hidden Layer, No Biases)

Consider a m -width neural network

$$f(\mathbf{x}) = \frac{1}{\sqrt{m}} \sum_{r=1}^m a_r \sigma(\mathbf{w}_r^\top \mathbf{x}), \quad a_r \sim \mathcal{N}(0, \sigma_a^2), \quad \mathbf{w}_r \sim \mathcal{N}\left(0, \frac{\sigma_w^2}{d} I\right).$$

Illustrative Model (One Hidden Layer, No Biases)

Consider a m -width neural network

$$f(\mathbf{x}) = \frac{1}{\sqrt{m}} \sum_{r=1}^m a_r \sigma(\mathbf{w}_r^\top \mathbf{x}), \quad a_r \sim \mathcal{N}(0, \sigma_a^2), \quad \mathbf{w}_r \sim \mathcal{N}\left(0, \frac{\sigma_w^2}{d} I\right).$$

Gradients:

$$\nabla_{a_r} f(\mathbf{x}) = \frac{1}{\sqrt{m}} \sigma(\mathbf{w}_r^\top \mathbf{x}),$$

Illustrative Model (One Hidden Layer, No Biases)

Consider a m -width neural network

$$f(\mathbf{x}) = \frac{1}{\sqrt{m}} \sum_{r=1}^m a_r \sigma(\mathbf{w}_r^\top \mathbf{x}), \quad a_r \sim \mathcal{N}(0, \sigma_a^2), \quad \mathbf{w}_r \sim \mathcal{N}\left(0, \frac{\sigma_w^2}{d} I\right).$$

Gradients:

$$\nabla_{a_r} f(\mathbf{x}) = \frac{1}{\sqrt{m}} \sigma(\mathbf{w}_r^\top \mathbf{x}), \quad \nabla_{\mathbf{w}_r} f(\mathbf{x}) = \frac{1}{\sqrt{m}} a_r \sigma'(\mathbf{w}_r^\top \mathbf{x}) \mathbf{x}.$$

Illustrative Model (One Hidden Layer, No Biases)

Consider a m -width neural network

$$f(\mathbf{x}) = \frac{1}{\sqrt{m}} \sum_{r=1}^m a_r \sigma(\mathbf{w}_r^\top \mathbf{x}), \quad a_r \sim \mathcal{N}(0, \sigma_a^2), \quad \mathbf{w}_r \sim \mathcal{N}\left(0, \frac{\sigma_w^2}{d} I\right).$$

Gradients:

$$\nabla_{a_r} f(\mathbf{x}) = \frac{1}{\sqrt{m}} \sigma(\mathbf{w}_r^\top \mathbf{x}), \quad \nabla_{\mathbf{w}_r} f(\mathbf{x}) = \frac{1}{\sqrt{m}} a_r \sigma'(\mathbf{w}_r^\top \mathbf{x}) \mathbf{x}.$$

Finite-width NTK:

$$K_m(\mathbf{x}, \mathbf{x}') = \frac{1}{m} \sum_{r=1}^m \sigma(\mathbf{w}_r^\top \mathbf{x}) \sigma(\mathbf{w}_r^\top \mathbf{x}') + \frac{1}{m} \sum_{r=1}^m a_r^2 \sigma'(\mathbf{w}_r^\top \mathbf{x}) \sigma'(\mathbf{w}_r^\top \mathbf{x}') \mathbf{x}^\top \mathbf{x}'.$$

Infinite-Width NTK

The two sums are empirical averages of i.i.d. terms. Since a_r and w_r are independent with finite moments, the (strong) law of large numbers gives, almost surely, as width $m \rightarrow \infty$:

Infinite-Width NTK

The two sums are empirical averages of i.i.d. terms. Since a_r and w_r are independent with finite moments, the (strong) law of large numbers gives, almost surely, as width $m \rightarrow \infty$:

$$\frac{1}{m} \sum_{r=1}^m \sigma(w_r^\top x) \sigma(w_r^\top x') \longrightarrow \mathbb{E}_w [\sigma(w^\top x) \sigma(w^\top x')],$$

Infinite-Width NTK

The two sums are empirical averages of i.i.d. terms. Since a_r and w_r are independent with finite moments, the (strong) law of large numbers gives, almost surely, as width $m \rightarrow \infty$:

$$\frac{1}{m} \sum_{r=1}^m \sigma(w_r^\top x) \sigma(w_r^\top x') \longrightarrow \mathbb{E}_w [\sigma(w^\top x) \sigma(w^\top x')],$$

$$\frac{1}{m} \sum_{r=1}^m a_r^2 \sigma'(w_r^\top x) \sigma'(w_r^\top x') \longrightarrow \sigma_a^2 \mathbb{E}_w [\sigma'(w^\top x) \sigma'(w^\top x')].$$

Infinite-Width NTK

The two sums are empirical averages of i.i.d. terms. Since a_r and w_r are independent with finite moments, the (strong) law of large numbers gives, almost surely, as width $m \rightarrow \infty$:

$$\frac{1}{m} \sum_{r=1}^m \sigma(w_r^\top x) \sigma(w_r^\top x') \longrightarrow \mathbb{E}_w [\sigma(w^\top x) \sigma(w^\top x')],$$

$$\frac{1}{m} \sum_{r=1}^m a_r^2 \sigma'(w_r^\top x) \sigma'(w_r^\top x') \longrightarrow \sigma_a^2 \mathbb{E}_w [\sigma'(w^\top x) \sigma'(w^\top x')].$$

Thus, in the infinite-width limit, the empirical NTK converges almost surely to a deterministic kernel

$$K_\infty(\mathbf{x}, \mathbf{x}') = \mathbb{E}_{\mathbf{w}} [\sigma(\mathbf{w}^\top \mathbf{x}) \sigma(\mathbf{w}^\top \mathbf{x}')] + \sigma_a^2 \mathbf{x}^\top \mathbf{x}' \mathbb{E}_{\mathbf{w}} [\sigma'(\mathbf{w}^\top \mathbf{x}) \sigma'(\mathbf{w}^\top \mathbf{x}')].$$

Infinite-Width NTK

The two sums are empirical averages of i.i.d. terms. Since a_r and w_r are independent with finite moments, the (strong) law of large numbers gives, almost surely, as width $m \rightarrow \infty$:

$$\frac{1}{m} \sum_{r=1}^m \sigma(w_r^\top x) \sigma(w_r^\top x') \longrightarrow \mathbb{E}_w [\sigma(w^\top x) \sigma(w^\top x')],$$

$$\frac{1}{m} \sum_{r=1}^m a_r^2 \sigma'(w_r^\top x) \sigma'(w_r^\top x') \longrightarrow \sigma_a^2 \mathbb{E}_w [\sigma'(w^\top x) \sigma'(w^\top x')].$$

Thus, in the infinite-width limit, the empirical NTK converges almost surely to a deterministic kernel

$$K_\infty(\mathbf{x}, \mathbf{x}') = \mathbb{E}_{\mathbf{w}} [\sigma(\mathbf{w}^\top \mathbf{x}) \sigma(\mathbf{w}^\top \mathbf{x}')] + \sigma_a^2 \mathbf{x}^\top \mathbf{x}' \mathbb{E}_{\mathbf{w}} [\sigma'(\mathbf{w}^\top \mathbf{x}) \sigma'(\mathbf{w}^\top \mathbf{x}')].$$

Key point: in the wide limit, $K_t \approx K_0$ remains *essentially constant* during training (lazy regime).

Refs: (Neal, 1996; Lee et al., 2019)

Gradient flow & chain rule: Let $f_t(x_i) := f(x_i; \theta_t)$. Then

$$\frac{d}{dt} f_t(x_i) = \nabla_{\theta} f(x_i; \theta_t)^{\top} \dot{\theta}_t = -\nabla_{\theta} f(x_i; \theta_t)^{\top} \nabla_{\theta} L(\theta_t).$$

Gradient flow & chain rule: Let $f_t(x_i) := f(x_i; \theta_t)$. Then

$$\frac{d}{dt} f_t(x_i) = \nabla_{\theta} f(x_i; \theta_t)^{\top} \dot{\theta}_t = -\nabla_{\theta} f(x_i; \theta_t)^{\top} \nabla_{\theta} L(\theta_t).$$

Loss gradient (squared loss):

$$L(\theta) = \frac{1}{2} \sum_{j=1}^n (f(x_j; \theta) - y_j)^2, \quad \nabla_{\theta} L(\theta_t) = \sum_{j=1}^n (f_t(x_j) - y_j) \nabla_{\theta} f(x_j; \theta_t).$$

Training dynamics: constant kernel

Substitute and define the (time-dependent) NTK.

$$\frac{d}{dt}f_t(x_i) = - \sum_{j=1}^n \underbrace{\nabla_{\theta} f(x_i; \theta_t)^{\top} \nabla_{\theta} f(x_j; \theta_t)}_{=: K_t(x_i, x_j)} (f_t(x_j) - y_j).$$

Training dynamics: constant kernel

Substitute and define the (time-dependent) NTK.

$$\frac{d}{dt}f_t(x_i) = - \sum_{j=1}^n \underbrace{\nabla_{\theta} f(x_i; \theta_t)^{\top} \nabla_{\theta} f(x_j; \theta_t)}_{=: K_t(x_i, x_j)} (f_t(x_j) - y_j).$$

Vectorized form:

$$\dot{\hat{f}}_t = -K_t(\hat{f}_t - y).$$

Training dynamics: constant kernel

Substitute and define the (time-dependent) NTK.

$$\frac{d}{dt}f_t(x_i) = - \sum_{j=1}^n \underbrace{\nabla_{\theta} f(x_i; \theta_t)^{\top} \nabla_{\theta} f(x_j; \theta_t)}_{=: K_t(x_i, x_j)} (f_t(x_j) - y_j).$$

Vectorized form:

$$\dot{\hat{f}}_t = -K_t(\hat{f}_t - y).$$

Constant-kernel (NTK) regime. If $K_t \approx K_0 \equiv K$ (infinite width / lazy),

$$\dot{\hat{f}}_t = -K(\hat{f}_t - y) \quad \Rightarrow \quad \hat{f}_t = y + e^{-Kt}(\hat{f}_0 - y).$$

Refs: (Jacot et al., 2018; Lee et al., 2019)

Lazy regime: parameter drift is small, $\|\theta_t - \theta_0\| \ll \|\theta_0\|$.

- Features $\phi(\mathbf{x})$ and kernel K stay (approximately) constant.
- Training reduces to kernel regression with fixed K .

Limitation: suppresses *feature learning* (representation change).

Aim: quantify *when* lazy holds/breaks and *how* to model beyond it.

Diagnosing the transition to feature learning

Some signals to consider

- **Kernel drift:** Does the NTK matrix K_t change during training? Compare K_t to K_0 on the (same) data. Bigger change \Rightarrow more feature learning.

Diagnosing the transition to feature learning

Some signals to consider

- **Kernel drift:** Does the NTK matrix K_t change during training? Compare K_t to K_0 on the (same) data. Bigger change \Rightarrow more feature learning.
- **Feature drift:** Do the tangent features $\phi_t(x) = \nabla_{\theta} f(x; \theta_t)$ move on a small fixed set \mathcal{S} ? Track the average change from $t = 0$.

Diagnosing the transition to feature learning

Some signals to consider

- **Kernel drift:** Does the NTK matrix K_t change during training? Compare K_t to K_0 on the (same) data. Bigger change \Rightarrow more feature learning.
- **Feature drift:** Do the tangent features $\phi_t(x) = \nabla_{\theta} f(x; \theta_t)$ move on a small fixed set \mathcal{S} ? Track the average change from $t = 0$.

How to (often) push out of lazy

- larger learning rate
- smaller width
- more depth / biases / normalization

Beyond linearization I: quadratic / higher-order

$$f(\mathbf{x}; \boldsymbol{\theta}) \approx f(\mathbf{x}; \boldsymbol{\theta}_0) + \phi(\mathbf{x})^\top \Delta \boldsymbol{\theta} + \frac{1}{2} \Delta \boldsymbol{\theta}^\top H_f(\mathbf{x}) \Delta \boldsymbol{\theta}, \quad \Delta \boldsymbol{\theta} = \boldsymbol{\theta} - \boldsymbol{\theta}_0.$$

- **Mechanism (Bai and Lee (2020)):** construct regimes where the linear term is suppressed so the *quadratic* term governs the dynamics; extendable to $k > 2$ (“higher-order NTKs”).
- **Findings:** with the linear term suppressed, progress comes from *feature changes*; this adaptive regime is easy to optimize and can beat NTK in sample use on simple tasks.

See: “Beyond Linearization: On Quadratic and Higher-Order Approximation of Wide Neural Networks.”

Beyond linearization II: adaptive / time-varying kernels

- Zhang et al. (2024) replace the fixed NTK with a *time-varying* kernel K_t that evolves during training (“kernel drift”).
- Features adapt during training and increasingly align with label-relevant directions (growing alignment).
- They provide a prototype of an over-parameterized Gaussian sequence model to analyze feature learning beyond the NTK picture.

See: “Towards a Statistical Understanding of Neural Networks: Beyond the NTK Theories.”

Beyond NTK III: finite depth/width corrections

- Hanin and Nica (2019) study networks where depth d and width n grow together.
- Key finding: the NTK is **not deterministic** at init — its variance scales roughly $\exp(c d/n)$.
- Even the first SGD step can change K_t significantly \Rightarrow kernels evolve, enabling *weak feature learning*.
- Proposed **weak feature learning regime**: $0 < d/n \ll 1$ where training is stable but K_t still moves.

See: Hanin & Nica, “Finite Depth and Width Corrections to the NTK.”

Summary & discussion

- Infinite width as a clean baseline; NTK via linearization at initialization.
- Constant-kernel training dynamics: $\dot{f}_t = -K(f_t - y)$ with solution $f_t = y + e^{-Kt}(f_0 - y)$.
- Lazy training \Rightarrow features (and K) stay essentially fixed.
- How to spot leaving lazy: *kernel drift* ($K_t \neq K_0$) and *feature drift* on a probe set.
- Beyond NTK in the literature:
 - *Quadratic / higher-order* near init (Bai and Lee, 2020).
 - *Adaptive / time-varying kernels* and alignment (Zhang et al., 2024).
 - *Finite depth/width corrections*: NTK variance grows with d/n ; even early updates can move K_t (weak feature learning) (Hanin and Nica, 2019).

References

- Y. Bai and J. D. Lee. Beyond linearization: On quadratic and higher-order approximation of wide neural networks. In *International Conference on Learning Representations*, 2020.
- B. Hanin and M. Nica. Finite depth and width corrections to the neural tangent kernel, 2019. URL <https://arxiv.org/abs/1909.05989>.
- A. Jacot, F. Gabriel, and C. Hongler. Neural tangent kernel: Convergence and generalization in neural networks. In *Advances in Neural Information Processing Systems*, 2018.
- J. Lee, L. Xiao, S. S. Schoenholz, Y. Bahri, R. Novak, J. Sohl-Dickstein, and J. Pennington. Wide neural networks of any depth evolve as linear models under gradient descent. In *Advances in Neural Information Processing Systems*, 2019.
- R. M. Neal. *Priors for infinite networks*. PhD thesis, University of Toronto, 1996.
- H. Zhang, J. Lai, Y. Li, Q. Lin, and J. S. Liu. Towards a statistical understanding of neural networks: Beyond the neural tangent kernel theories. *arXiv preprint arXiv:2412.18756*, 2024.