

Design Patterns

Object Oriented Programming

<http://softeng.polito.it/courses/09CBI>



SoftEng
<http://softeng.polito.it>

Version 3.8.1
© Marco Torchiano, 2021






This work is licensed under the Creative Commons Attribution–NonCommercial–NoDerivatives 4.0 International License.

To view a copy of this license, visit

<http://creativecommons.org/licenses/by-nc-nd/4.0/>.

You are free: to copy, distribute, display, and perform the work

Under the following conditions:

-  **Attribution.** You must attribute the work in the manner specified by the author or licensor.
-  **Non-commercial.** You may not use this work for commercial purposes.
-  **No Derivative Works.** You may not alter, transform, or build upon this work.
 - For any reuse or distribution, you must make clear to others the license terms of this work.
 - Any of these conditions can be waived if you get permission from the copyright holder.

Your fair use and other rights are in no way affected by the above.

Pattern

A reusable **solution**
to a known **problem**
in a well defined **context**

...just one of the possible definitions

3

Pattern

- Context
 - ♦ A (design) situation giving rise to a (design) problem
 - Problem
 - ♦ Set of forces repeatedly arising in the context
 - Force: any relevant aspect of the problem (E.g., requirements, constraints, desirable properties)
 - Solution
 - ♦ A proven resolution of the problem
 - ♦ Configuration to balance forces
 - Structure with components and relationships
 - Run-time behaviour
-

4

Example

SOCIAL PATTERN

- Context:
 - ♦ At the supermarket several customers crowd the gastronomy desk to get their fresh cut of ham
 - Problem:
 - ♦ Customers quarrel to have their turn first
 - ♦ Order of arrival should be obeyed
 - ♦ It is hard to spot who arrived earlier or later
 - Solution:
 - ♦ Provide numbered tickets the customer take as soon as they arrive and which they are called by
-

5

History

- Initially proposed by Christopher Alexander
 - He described patterns for architecture (of buildings)
 - ♦ *The pattern is, in short, at the same time a thing, which happens in the world, and the rule which tells us how to create that thing and when we create it. It is both a process and a thing ...*
-

6

Types of Software Patterns

- Architectural Patterns
 - ♦ Address system wide structures
- Design Patterns
 - ♦ Leverage higher level mechanisms
- Idioms
 - ♦ Leverage language specific features

7

Architectural pattern

- Expresses a fundamental structural organization schema for software systems
- Provides a set of predefined components with their responsibilities
- Defines the rules and guidelines for organizing the relationships between the components

8

Example

ARCHITECTURAL PATTERN

- Context:
 - ♦ several programs that are used in sequence read from input and write sequentially to output
 - Problem:
 - ♦ there are a lot of intermediate files used for communication between programs
 - Solution:
 - ♦ adopt a pipe & filter architecture feeding a program with the result of the previous one
-

9

Design pattern

- Provides a scheme for refining components of a software system or their relationships
 - Describes a commonly recurring structure of communicating components
-

10

Example

DESIGN PATTERN

- Context:
 - ♦ A class library providing few functionalities contains a lot of classes
- Problem:
 - ♦ The user is exposed to the internal complexity of the library
- Solution:
 - ♦ Create a new **façade** class that interacts with the user and hide all the details

11

Idiom

- Is a low-level pattern specific to a programming language
- Describes how to implement particular aspects of components or the relationships between them
- Leverages the features of a programming language

12

Example

IDIOM

- Context:
 - ♦ An attribute is constant and should be globally available to many classes
- Problem:
 - ♦ Opening access would allow unauthorized modifications
 - ♦ The attribute is repeated in every object
- Solution:
 - ♦ Make it **public static final**

13

Pattern Description

- Name
- Problem
- Context
- Forces
- Solution
- Force Resolution
- Design Rationale

Coplien

- Name
- Intent
- Motivation
- Applicability
- Structure
- Participants
- Collaborations
- Consequences
- Implementation
- Related Patterns

GoF

14

Pattern language

- Pattern do not exist in isolation
 - ♦ Two or more patterns are applied together
 - ♦ A pattern is used to implement part of another pattern
 - ♦ A pattern can introduce a problem solved by another
- We have Pattern Languages
 - ♦ Or pattern systems

15

Pattern Language

- Collection of patterns together with guidelines for
 - ♦ Implementation
 - ♦ Combination
 - ♦ Practical use
- Should
 - ♦ Count enough patterns
 - ♦ Describe patterns uniformly
 - ♦ Present relationships

16


Example

- MVC is implemented using
 - ♦ Observer
 - ♦ Iterator

17

Design Patterns (GoF)


- Describe the structure of components
- Most widespread category of pattern
- First category of patterns proposed for software development



18

Design Patterns (GoF)

- Creational
 - ♦ E.g. Abstract Factory, Singleton
- Structural
 - ♦ E.g. Façade, Composite
- Behavioral
 - ♦ *Class*: e.g. Template Method
 - ♦ *Object*: e.g. Observer



19

Design patterns

- Description of communicating objects and classes that are customized to solve a general design problem in a particular context
- A design pattern names, abstracts, and identifies the key aspects of a common design structure that make it useful for creating a reusable object-oriented design

20

Description

- Name and classification
 - Intent
 - ♦ Also known as
 - Motivation
 - Applicability
 - Structure
 - Participants
 - Collaborations
 - Consequences
 - Implementation
 - Sample code
 - Known uses
 - Related patterns
-

21

Pattern classification

- Purpose
 - ♦ Creational
 - ♦ Structural
 - ♦ Behavioral
 - Scope
 - ♦ Class
 - ♦ Object
-

22

Pattern classification

		Purpose		
		Creational	Structural	Behavioral
Scope	Class	1	1	2
	Object	4	6	10

23

Pattern selection

- Consider how patterns solve problems
- Scan intent sections
- Study how pattern interrelate
- Study patterns of like purpose
- Examine a cause of redesign
- Consider what should be variable in your design

24

Using a pattern

- Read through the pattern
- Go back and study
 - ♦ Structure
 - ♦ Participants
 - ♦ Collaborations
- Look at the sample code

25

Using a pattern

- Choose names for participants
 - ♦ Meaningful in the application context
- Define the classes
- Choose operation names
 - ♦ Application specific
- Implement operations

26

Creational patterns

- Factory Method
- Abstract Factory
- Builder
- Prototype
- Singleton


27

Abstract Factory

- Context
 - ♦ A family of related classes can have different implementation details
- Problem
 - ♦ The client should not know anything about which variant they are using / creating


28

Abstract Factory Example



29

Abstract Factory




30

Singleton

- Context:
 - ♦ A class represents a concept that requires a single instance
- Problem:
 - ♦ Clients could use this class in an inappropriate way

31

Singleton Pattern



```
private Singleton() { }  
private static Singleton instance;  
public static Singleton getInstance() {  
    if(instance==null)  
        instance = new Singleton();  
    return instance;  
}
```


Singleton Example

- `java.awt.Toolkit`
 - ♦ Singleton + FactoryMethod

java.awt::Toolkit
-Toolkit() +getDefaultToolkit(): Toolkit ...


33

Builder object

- Context
 - ♦ An object of a complex class has to be created
- Problem
 - ♦ The creation entails complex interaction with the object
 - ♦ Different variation of the target object might be created


34

Builder Pattern




35

Builder example



36

Example Measure builder



Note: Simplified version w.r.t. GoF

37

Structural patterns

- Structural patterns are concerned with how classes and objects are composed to form larger structures.

38

GoF structural patterns

- Adapter
- Bridge
- Composite
- Decorator
- Facade
- Flyweight
- Proxy


39

Adapter

- Context:
 - ♦ A class provides the features required by another class but its interface is not the one expected
- Problem:
 - ♦ The integration of the provider class should be possible without modifying it
 - Its source code could be not available
 - It is already used as it is somewhere else


40

Adapter



41

Adapter example



42

Java Listener Adapter

- In Java GUI, events are handled by Listeners
- Listener classes need to implement Listener interfaces
 - ♦ Include several methods
 - ♦ They all should be implemented

43


Java Listener Adapter

```
class MyListener{
    public void KeyPressed(..){}
    public void KeyReleased(..){
        // ... handle event
    }
    public void KeyTyped(..){} }
```

```
class MyListener{
    public void KeyReleased(..){
        // ... handle event
    }
}
```

44

Java Listener Adapter



45

Structural Class Patterns

- Adapter pattern
 - ♦ Inheritance plays a fundamental role
 - ♦ Only example of structural class pattern


46

Composite

- Context:
 - ♦ You need to represent part-whole hierarchies of objects
- Problem
 - ♦ Clients are complex
 - ♦ Difference between composition objects and individual objects.

47

Composite




48

Composite Example

- Arithmetic expressions representation
 - ♦ Operators
 - ♦ Operands
- Evaluation of expressions

49

Composite Example



50

Composite Example

```
abstract class Expression {  
    public abstract int evaluate();  
    public abstract String print();  
}
```

51

Composite Example

```
class Value {  
    private int value;  
  
    public Value(int v) {  
        value = v;  
    }  
    public int evaluate() {  
        return value;  
    }  
    public String print() {  
        return new String(value);  
    }  
}
```

52

Composite Example

```
class Operation {
    private char op; // +, -, *, /
    private Expression left, right

    public Operation(char op,
        Expression l, Expression r){
        this.op = op;
        left = l;
        right= r;
    }
    ...
}
```

53

Composite Example

```
class Operation {
    ...
    public evaluate(){
        switch(op){
            case '+': return
                left.evaluate() +
                right.evaluate();
            break;
            ...
        }
    }
    ...
}
```

54

Composite Example

```
class Operation {  
...  
    public print() {  
        return left.print() + op +  
            right.print();  
    }  
}
```


55

Facade

- Context
 - ♦ A functionality is provided by a complex group of classes (interfaces, associations, etc.)
- Problem
 - ♦ How is it possible to use the classes without being exposed to the details

56

Facade



57

Behavioral patterns

- Behavioral patterns are concerned with algorithms and the assignment of responsibilities between objects.
- Not just patterns of objects or classes but also the patterns of communication.
 - ♦ Complex control flow that's difficult to follow at run-time.
 - ♦ Shift focus away from flow of control to let concentrate just on the way objects are interconnected.

58

GoF behavioral patterns

Object-level

- ◆ Chain of Responsibility
- ◆ Command
- ◆ Iterator
- ◆ Mediator
- ◆ Memento
- ◆ Observer
- ◆ State
- ◆ Strategy
- ◆ Visitor

Class-level

- ◆ Template Method
- ◆ Interpreter

59

Mechanisms

- Encapsulating variation
- Objects as arguments
- Information circulation policies
- Sender and Receiver decoupling

60

Encapsulating Variation

- A varying aspect of a program
- Captured by an object
 - ♦ Other delegate operations to the “variant” object

61

Argument Objects

- Often an object is passed as argument
 - ♦ Hides complexity from clients
 - ♦ Concentrate the “active” code in one class

62

Information circulation

- Responsibility of how to circulate information may be:
 - ♦ Distributed among different parties.
 - ♦ Encapsulated in a single object.

63

Communication decoupling

- Decoupling senders and receivers is a key to:
 - ♦ Reduce coupling
 - ♦ Improve reusability
 - ♦ Enforce layering and structure


64

Observer

- Context:
 - ♦ The change in one object may influence one or more other objects
- Problem
 - ♦ High coupling
 - ♦ Number and type of objects to be notified may not be known in advance

65

Observer



66


Observer – Consequences

- + Abstract coupling between Subject and Observer
- + Support for broadcast communication
- Unanticipated updates

Observer–Observable

- Allow a standardized interaction between an objects that needs to notify one or more other objects
 - Defined in package `java.util`
 - Class **Observable**
 - Interface **Observer**
-

Observer–Observable



Java Observer–Observable

```
class Observable{
    void addObserver(..) {}
    void deleteObserver(..) {}
    void deleteObservers() {}
    int countObservers() {}
    void setChanged() {}
    void clearChanged() {}
    boolean hasChanged() {}
    void notifyObservers() {}
    void notifyObservers(..) {}
}
```

Observer–Observable

- Class **Observable** manages:
 - ♦ registration of interested observers by means of method **addObserver()**
 - ♦ sending the notification of the status change to the observer(s) together with additional information concerning the status (event object).
 - Interface **Observer** allows:
 - ♦ Receiving standardized notification of the observer change of state through method **update()** accepts two arguments:
 - Observable object that originated the notification
 - additional information (the event object)
-

Observer–Observable

- Sending a notification from an observable element involves two steps:
 - ♦ record the fact the the status of the Observable has changed, by means of method **setChanged()**,
 - ♦ send the actual notification while providing the additional information (the event object), by means of method **notifyObservers()**
-

Inheritance vs. composition

Reuse can be achieved via:



- **Inheritance**

- ♦ The reusing class has the reused methods available as own methods.
- ♦ Clients can invoke directly inherited methods


- **Composition**

- ♦ The reusing class has the reused methods available in an included object (attribute)
 - ♦ The reusing class must provide methods that accept clients requests and delegate to the included object
-

Inheritance vs. Composition




Observer w/Inheritance



75

Observer w/Composition



76

Observer subject w/inheritance

```
public class Subject
    extends Observable {

    String prop="ini";

    public void setProp(String val){
        setChanged();
        property = val;
        notifyObservers("theProp");
    }

}
```

77

Observer subject w/composition

```
public class Subject {
    PropertyChangeSupport pcs =
        new PropertyChangeSupport(this);
    String prop="ini";

    public void setProp(String val) {
        String old = property;
        property = val;
        pcs.firePropertyChange("theProp",old,val);
    }
    // delegation:
    public void addObs(PropertyChangeListener l){
        pcs.addPropertyChangeListener("theProp",l);
    }
}
```

78

Observer with inheritance

```
public class Concerned
    implements Observer {

    @Override
    public void update(Observable src,
                      Object arg) {
        System.out.println("Variation of " +
                           arg);
    }
}
```

79


Observer with composition

```
public class Concerned
    implements PropertyChangeListener {

    @Override
    public void propertyChange(
        PropertyChangeEvent evt) {
        System.out.println("Variation of " +
                           evt.getPropertyName());
    }
}
```

80

Observer Example




81

Template Method

- Context:
 - ♦ An algorithm/behavior has a stable core and several variation at given points
- Problem
 - ♦ You have to implement/maintain several almost identical pieces of code


82

Template Method



83

Template Method Example



84

Example: Sorter

```
public abstract class Sorter {  
    public void sort(Object v[]){  
        for(int i=1; i<v.length; ++i)  
            for(int j=0; j<v.length-i; ++j){  
                if(compare(v[j],v[j+1])>0){  
                    Object o=v[j];  
                    v[j]=v[j+1]; v[j+1]=o;  
                } } }  
    }  
    abstract int compare(Object a, Object b);  
}
```

85

Example: StringSorter

```
class StringSorter extends Sorter {  
    int compare(Object a, Object b){  
        String sa=(String)a;  
        String sb=(String)b;  
        return sa.compareTo(sb);  
    }  
}
```

```
Sorter ssrt = new StringSorter();  
String[] v={"g","t","h","n","j","k"};  
ssrt.sort(v);
```


86

Strategy

- Context
 - ♦ Many classes or algorithm has a stable core and several behavioral variations
- Problem
 - ♦ Several different implementations are needed.
 - ♦ Multiple conditional constructs tangle the code.


87

Strategy



88

Strategy example: Comparator



89

Comparator

- Interface `java.util.Comparator`

```
public interface Comparator<T>{
    int compare(T a, T b);
}
```

- Semantics (as comparable): returns
 - ♦ a negative integer if **a** precedes **b**
 - ♦ 0, if **a** equals **b**
 - ♦ a positive integer if **a** succeeds **b**

90

Comparator

```
class StudentCmp
    implements Comparator<Student>{
public int compare(Student a,Student b){
    return a.id - b.id;
}
}
```

```
Student[] sv = { new Student(11) ,
                  new Student(3) ,
                  new Student(7) };
Arrays.sort(sv, new StudentCmp());
```

91

Strategy Consequences

- + Avoid conditional statements
- + Algorithms may be organized in families
- + Choice of implementations
- + Run-time binding
- Clients must be aware of different strategies
- Communication overhead
- Increased number of objects

92


Iterator pattern



- Context
 - ♦ A collection of objects must be iterated
- Problem
 - ♦ Multiple concurrent iterations are possible
 - ♦ The internal storage must not be exposed
- Solution
 - ♦ Provide an iterator object, attached to the collection, that can be advanced independently

93

Iterator pattern



94

Visitor

- Context


- ♦ An object structure contains many classes with differing interfaces.
- ♦ Many different operations need to be performed on the objects

- Problem

- ♦ The operations on the objects depend on their concrete classes
- ♦ Classes could be polluted with several operations


95

Visitor



96

Visitor Example



97

Visitor Consequences

- + Adding new operations is very easy
- + Behavior is partitioned
- + Can visit class hierarchies
- + State can be accumulated
- Difficult to add new concrete elements
- Break of encapsulation

98

References

- M.Fowler, K. Scott, UML Distilled, 3rd ed. Addison–Wesley, 2003.
- E. Gamma, R. Helm, R. Johnson, and J. Vlissides, *Design Patterns: Elements of Reusable Object–Oriented Software*. Reading, MA: Addison–Wesley, 1995.
- E.Freeman, E.Freeman, K.Sierra, B.Bates. Head First Design Patterns, O'Reilly, 2004