Date of publication xxxx 00, 0000, date of current version xxxx 00, 0000.

Digital Object Identifier 10.1109/ACCESS.2024.0429000

StaticKD: Distilling a Multilingual IPTC News Topic Classifier into a Static Token-Logit Table for Lightweight CPU Inference

OBI KASTANYA[1] AND ANANTA DWI PRAYOGA ALWY[1]

[1]Department of Informatics Engineering, Sepuluh Nopember Institute of Technology, Surabaya, Indonesia (e-mail: 6025252015@student.its.ac.id; 6025252007@student.its.ac.id)

Corresponding author: Obi Kastanya (e-mail: 6025252015@student.its.ac.id).

This work received no specific funding.

ABSTRACT Filtering news by the International Press Telecommunications Council (IPTC) Media Topic taxonomy requires a classifier cheap enough for a multilingual article stream. The open multilingual IPTC classifier based on XLM-RoBERTa-large needs 1,190 to 2,816 milliseconds per article on one processor core. StaticKD uses this classifier as teacher and gives every vocabulary token one score for each of the 17 top-level IPTC topics. Classification only requires tokenizing an article and averaging its token scores. The student is initialized from multilingual static embeddings (one fixed vector per token) and learns from teacher outputs on 285,999 articles in 69 languages. The evaluation uses a new test set of 12,744 articles in 47 languages. Its labels come from human annotators or newsroom editors and not from a model that reads the article. StaticKD reaches a macro-F1 of 0.545 on this set and keeps 91.1% of the teacher score (0.598). The 34-megabyte model classifies 539 articles per second per core and runs about 682 times faster than the 8-bit quantized teacher. It is more accurate than fastText and a linear support vector machine trained on the same labels. A Model2Vec classifier trained on these labels is equally accurate within 0.01 macro-F1 but needs a file 15 times larger. Five-seed ablations show that accuracy comes mainly from multilingual training data and pre-trained cross-lingual embeddings. The same ablations show that the top teacher label works as well as the full distribution. StaticKD is weakest on languages absent from both its training data and the teacher's pre-training data.

INDEX TERMS Efficient inference, knowledge distillation, multilingual text classification, news topic classification, static embeddings.

I. INTRODUCTION

NEWS analytics pipelines need topic filtering to keep irrelevant news from adding cost in later processing stages. News articles have to be classified into standardized topic categories before filtering. Such categories include those of the Media Topic taxonomy of the International Press Telecommunications Council (IPTC). The IPTC taxonomy divides news topics into 17 top-level categories, which contain many subcategories [1], [2].

The first open multilingual IPTC classifier was released by Kuzman and Ljubešić [2]. GPT-4o labeled articles in four languages, and the labels then served as data for fine-tuning XLM-RoBERTa-large [3]. The resulting model performs on par with GPT-4o on a human-annotated test set. A follow-up study by the same group concluded that fine-tuned encoders are more practical than large language models (LLMs) for large-scale annotation [4]. An encoder with 559.9 million parameters remains expensive without a graphics processing unit (GPU). The present study targets servers without a GPU, where the classifier shares central processing unit (CPU) cores with the rest of the pipeline. The model needs 2,816 ms per article on one CPU core. Its fastest CPU configuration is an Open Neural Network Exchange (ONNX) export quantized to 8-bit integers (int8), and this configuration still needs 1,190 ms. Topic classification alone would then occupy 14.7 (ONNX int8) to 33.7 (PyTorch) CPU cores for a stream of one million articles per day (Section VI-B). Inference accounts for a large share of the computing demand and energy use of machine learning in production. Google reported that 60% of its machine learning energy use came from inference [5]. Neither of the two earlier studies reports this inference cost.

Such a pipeline needs a topic classifier that covers many

languages and runs in milliseconds per article on an ordinary CPU. The classifier also has to be small and have few dependencies. Small distilled transformers [6], [7] run about one order of magnitude faster. MiniLM-L6 runs 21 times faster than the ONNX int8 teacher in the CPU benchmark of this study. Int8 quantization alone gives a 2.3-fold speedup over PyTorch fp32. The fastText classifier [8] is faster still, but it learns its word vectors from scratch and therefore does not support cross-lingual transfer. The lack of transfer matters here because the IPTC training labels released with the open classifier cover only four languages [9]. A corpus labeled automatically by a multilingual teacher also cannot contain every language of a news stream. None of the available IPTC classifiers is both multilingual and this cheap.

The StaticKD method proposed in this paper distills [10] the XLM-R-large IPTC classifier into a simpler student. Three properties of the problem make this possible. A teacher that works across languages can label unlabeled news in any language at no annotation cost. Multilingual static embeddings distilled from sentence encoders [11], [12], [13] give each token one fixed vector and place translation equivalents close to each other. Looking up such a vector costs almost nothing. News topics are also strongly tied to vocabulary, which explains why bag-of-words representations remain competitive for topic classification [14]. The student therefore averages the embeddings of the tokens in an article and then applies one linear layer. Both steps are linear, so the linear layer can be applied once to every embedding before deployment. Applying the layer before deployment is called folding in this paper. Folding turns the model into a table that stores 17 topic scores (logits) per token. Classifying an article then reduces to tokenizing it and averaging the table rows of its tokens. The computation runs in NumPy without a deep learning library. Fig. 2 in Section VI-B compares the accuracy and speed of StaticKD with those of the other models.

A multilingual claim also requires a multilingual evaluation with labels that do not come from the teacher. The human-annotated test set of Kuzman and Ljubešić is not public and covers four languages. SIB-200 [15] covers 205 languages, but its items are short sentences and its taxonomy is not IPTC. The present study fills this gap by building a unified test set of 12,744 articles in 47 languages. Some of its articles are 2024–2026 news pages whose publishers record the newsroom section of the article in the page metadata (schema.org [16]). The pages were combined with public datasets that carry human annotations or publisher categories [17], [18], [19], [20]. Each label is an editorial decision of a publisher or an annotator. Every label was then mapped onto the official IPTC taxonomy. The process involved no model that read the article text.

The study answers four research questions (RQs). RQ1 asks how much of the teacher accuracy StaticKD retains on labels that do not come from the teacher. Three baselines of similar speed are compared with it: fastText, a support vector machine (SVM) with term frequency–inverse document frequency (TF-IDF) features, and the classifier of the Model2Vec library. The other models in the comparison are the more expensive small transformers MiniLM-L6 and DistilmBERT. RQ2 concerns the inference cost of the teacher on CPU and how far StaticKD reduces that cost. RQ3 examines which parts of the training recipe matter for this small student. The tested parts are soft labels, multilingual data, embedding initialization, embedding fine-tuning, token dropout, temperature, and ensembling. RQ4 looks for the languages, labels, and label sources on which StaticKD is weak and for the factors behind these weaknesses.

The contributions of this paper are as follows.

1) StaticKD, a recipe that starts from multilingual static embeddings and distills a multilingual transformer teacher into a table of 17 logits per token. The final model takes 34 MB and needs only the `numpy` and `tokenizers` libraries. It processes 539 articles per second per core. An ensemble of several trained students is folded into the same single table and therefore adds no inference cost.
2) A multilingual IPTC test set of 12,744 articles in 47 languages, with editorial labels that do not come from the teacher. The test set comes with a section-to-IPTC mapping table, which was checked automatically and reviewed manually by two researchers in a joint session. Duplicates across sources were removed, and contamination was checked against all training data. The confidence intervals account for the dependence between articles from the same site. Other IPTC classifiers can be evaluated on the same test set.
3) Findings on where the accuracy of the student comes from, supported by ablations with five seeds per variant. Analyses by language, label, label origin, and source dataset give further support. Languages that are absent from the training data are also analyzed. Accuracy and CPU-only cost were measured for ten configurations from seven model families, including StaticKD. Each process was pinned to the fast cores of a hybrid CPU.
4) A release of the code, a notebook that reproduces every number in this paper, the models, and the test-set manifest.

Section II reviews related work. Section III describes StaticKD, and Section IV describes the data and the test set. The baselines and the evaluation protocol are given in Section V. The results are presented in Section VI and discussed together with the limitations of the study in Section VII. Section VIII concludes the paper.

II. RELATED WORK

A. MULTILINGUAL NEWS TOPIC CLASSIFICATION AND THE IPTC SCHEME

Datasets for news topic classification usually define a dataset-specific taxonomy and cover only one language or one region. Human annotators labeled the news articles of MasakhaNEWS [17] with seven categories. The dataset covers 16 languages widely spoken in Africa, including English

and French. L3Cube-IndicNews for 10 Indian languages [19] and a Bangla news dataset [20] take labels from publisher site categories. MN-DS [18] is the only public dataset annotated directly with top-level IPTC topics. Its articles are in English only. SIB-200 [15] covers 205 languages, but its data consist of Flores-200 sentences with seven non-IPTC topics. Kuzman and Ljubešić [2] showed that GPT-4o labels can replace human annotation for training an IPTC classifier. A later study by the same group found that fine-tuned encoders are more practical than LLMs for large-scale annotation [4]. The only open multilingual IPTC classifier is an encoder with 559.9 million parameters. No inexpensive IPTC classifier has yet been evaluated on real news in many languages.

B. DISTILLING TRANSFORMER CLASSIFIERS INTO COMPACT STUDENTS

Knowledge distillation (KD) trains a cheap student model to imitate the output distribution of an expensive teacher model [10], [21]. The logit vectors of the teacher and the student are both divided by a temperature τ before the softmax. A higher τ flattens the distribution and thus also shows the student how much probability the teacher assigns to the wrong classes. The full distribution is called a soft label, whereas its top class alone is called a hard label. Students for text classification are almost always transformers such as DistilBERT [6] or MiniLMv2 [7]. The same holds for cross-lingual distillation that transfers teacher knowledge to languages with little data [22]. The prior work closest to StaticKD is Sparse Distillation [23]. It distills RoBERTa-large into a deep averaging network [24] with a large n-gram table. The resulting model runs hundreds of times faster on English single-sentence classification tasks. The StaticKD table is not trained from scratch but starts from multilingual static embeddings that are already aligned across languages. Each token stores only 17 numbers because the linear head is folded. StaticKD targets news documents in 69 languages, and its evaluation also covers languages that are missing from the distillation data.

The success of distillation depends on the capacity gap between teacher and student. The gap widens as the teacher becomes larger and more expressive than the student. The optimal teacher size for language models even follows an empirical law with respect to the student size [25]. Temperature is treated as an important hyperparameter that can be learned [26]. The Kullback–Leibler (KL) divergence can be split into a target-class part and a non-target part (dark knowledge) [27]. A recent analysis [28] shows that KL distorts the ranking of classes when the capacities of the teacher and the student do not match. High agreement between student and teacher does not always come with better generalization [29]. Nearly all of these findings come from deep students. StaticKD faces a gap from 559.9 million parameters to one linear layer over averaged embeddings. No study has yet characterized how temperature and soft labels behave at such an extreme gap.

C. STATIC EMBEDDINGS AND EFFICIENT CPU INFERENCE

A static embedding gives each token one fixed vector that does not depend on the surrounding words. The vector of a text is simply the mean of its token vectors. Such embeddings are extracted from sentence transformers by Model2Vec [11] and by Wada et al. [12]. The mean of these embeddings is a competitive sentence embedding. Model2Vec has a multilingual variant named potion-multilingual, which is distilled from BGE-M3 [13] and covers 101 languages. The Model2Vec library also provides a classifier trainer that adds a 512-unit hidden layer and learns from hard labels [11]. Static embeddings are usually evaluated as general-purpose embeddings, not as distillation students for a specific taxonomy. A survey of efficient natural language processing (NLP) methods recommends reporting inference cost together with accuracy [30]. Few studies report CPU latency at low thread counts with a quantized teacher as a point of comparison.

D. TEST SETS WITH EDITORIAL LABELS, CONTAMINATION, AND SAMPLE DEPENDENCE

Publisher site categories have been used as topic labels before [19], usually for one publisher or one region. Many news sites also record the section of each article in the `articleSection` field of the machine-readable schema.org page metadata [16]. The field has not yet been mapped to a standard taxonomy across dozens of languages. Leakage between training and test data also has to be controlled. Near-duplicate removal with MinHash [31] has become standard practice [32]. Significance tests in NLP such as the paired bootstrap [33] usually assume independent samples [34], whereas articles from the same site depend on each other. The cluster bootstrap [35] handles this dependence by resampling clusters instead of documents. The position of StaticKD relative to these approaches is summarized in Table 1.

III. THE STATICKD METHOD

A. STUDY OVERVIEW

The study consists of three main stages: building the StaticKD student by distillation, measuring and comparing accuracy on labeled articles that neither the teacher nor the student has seen, and measuring the inference cost on CPU.

Fig. 1 shows the StaticKD pipeline that this study builds. The teacher classifies 285,999 unlabeled articles in 69 languages and produces logits for the 17 top-level IPTC topics (Sections IV-B and III-C). Logits are the raw scores that a model outputs for each class before the scores are converted into probabilities. The StaticKD model is trained to imitate the teacher distribution over the 17 IPTC topics (Section III-D). The transformer-based baselines (MiniLM-L6 and DistilmBERT) are trained by gradient descent like StaticKD and use the same loss on the full distribution. The standard training procedures of fastText, TF-IDF + SVM, and Model2Vec accept class labels but not probability distributions. The three baselines therefore learn only from the top teacher label. One further fastText model is trained with

TABLE 1. Position of StaticKD Relative to Related Approaches

Approach	Model at inference time	Multilingual	Cross-lingual transfer	No deep learning library	CPU cost reported	IPTC labels
Kuzman & Ljubešić [2]	XLM-R-large (559.9M parameters)	yes	yes	no	no	yes
DistilBERT, MiniLMv2 [6], [7]	6-layer transformer	partly	yes	no	partly	no
Sparse Distillation [23]	deep averaging network + n-gram table	no (en)	no	yes	yes	no
Model2Vec [11], Wada et al. [12]	static embeddings, optional MLP classifier	yes	yes	yes	partly	no
fastText [8]	bag of n-grams	per language	no	yes	yes	no
StaticKD (proposed)	table of 17 logits per token	yes	yes	yes	yes	yes

the GPT-4o labels of the EMMediaTopic dataset [9], which was released together with the teacher. The GPT-4o-trained fastText model tests how a cheap classifier performs without teacher labels on multilingual news (Section V-A).

Teacher labels do not serve as ground truth in this study. A close match between the scores of the student and the teacher indicates only how closely the student imitates the teacher. Prediction accuracy is evaluated on a separate test set (Section IV-C). The test set groups news articles by the original editorial labels of each page. The labels were taken from information such as the section and breadcrumb fields in the schema.org JSON-LD metadata. An LLM mapped the editorial labels onto the 17 IPTC topics, and articles with ambiguous categories were excluded. Two researchers then checked the mapping together. The CPU benchmark of the third stage runs every model on the same sample of test articles (Section V-C).

B. PROBLEM FORMULATION

A model predicts one label $y \in \mathcal{Y}$ among the 17 top-level IPTC topics for a news article d in any language. The input is the title and body truncated to the first 512 words as in [2]. The teacher f_T outputs logits $\mathbf{z}^T(d) \in \mathbb{R}^{17}$. The goal is a student f_S whose inference costs $O(n)$ additions for n tokens and needs neither matrix multiplication nor a deep learning library. Its accuracy against independent labels should be as close as possible to that of f_T.

C. TEACHER AND DISTILLATION LABELS

The teacher is the IPTC classifier of [2], published as classla/multilingual-IPTC-news-topic-classifier. It is an XLM-RoBERTa-large model with 24 layers, 559.9 million parameters, and an input limit of 512 XLM-R tokens. The 512-word input exceeds this limit for 60.7% of the test articles. The teacher reads about 287 of the 438 words of such an article (medians). The full logit vector $\mathbf{z}^T(d) \in \mathbb{R}^{17}$ of the teacher was stored for every distillation document. Labeling was run once in fp16 on an NVIDIA RTX 4050 Laptop GPU (6 GB), with batches sorted by text length. The teacher labeled 50.1 documents per second on a fixed sample of 5,000 documents. Labeling all distillation data thus took about 1.58 GPU hours. The teacher label distribution on CC-News 2019–2021 is plausible (*politics* 16.5%, *economy* 12.7%, *sport* 11.6%, *weather* 1.3%). The mean confidence per language ranges from 0.90 to 1.00.

D. THE STATICKD STUDENT

The student in this study is built on the multilingual static embedding model potion-multilingual-128M of Model2Vec [11], hereafter called potion. A document d is tokenized into $t_1, \ldots, t_n$ with the Unigram tokenizer of potion so that every token has a pre-trained embedding. The tokenizer contains 500,353 tokens. Special tokens are not used, and unknown tokens are dropped. The document length is capped at 1,024 tokens. The cap only serves to bound the cost because averaging does not depend on position. Only 5.4% of the test articles exceed it. Each token has an embedding $\mathbf{e}_t \in \mathbb{R}^{256}$, and

$$\mathbf{h}(d) = \frac{1}{n}\sum_{i=1}^{n} \mathbf{e}_{t_i}, \qquad \mathbf{z}^S(d) = W\,\mathrm{drop}(\mathbf{h}(d)) + \mathbf{b}, \quad (1)$$

with $W \in \mathbb{R}^{17\times 256}$ and dropout 0.1 during training. The embedding matrix E is initialized from potion. The potion model itself was distilled from BGE-M3 [13] and covers 101 languages. The potion initialization places the tokens of these 101 languages in one shared space before training starts. Section VI-C compares this initialization with a random one.

The student learns from the stored teacher logits with the loss

$$\mathcal{L}_{\mathrm{KD}} = \tau^2\,\mathrm{KL}\big(p^T \,\big\|\, p^S\big), \qquad \tau = 1, \quad (2)$$

where $p^T = \mathrm{softmax}(\mathbf{z}^T/\tau)$ and $p^S = \mathrm{softmax}(\mathbf{z}^S/\tau)$ are the teacher and student distributions, respectively. The value $\tau = 1$ was chosen during development. The results for $\tau \in \{0.5, 2, 4\}$ are reported in Section VI-C. The parameters E, W, and $\mathbf{b}$ are trained together. The embedding matrix E uses SparseAdam ($\eta = 10^{-3}$), which updates only the rows of tokens that occur in the current batch. Tokens that never occur in the training documents therefore keep the potion embeddings. Section VII returns to this property. AdamW ($\eta = 3 \cdot 10^{-3}$, weight decay 10^{-4}) is used for W and $\mathbf{b}$. Training runs for 6 epochs with a batch size of 64. Training also applies token dropout as a cheap augmentation. Each token of a training document is dropped with probability 0.2 at every step so that the model does not rely on a few keywords. Internal validation uses 3% of the distillation data (8,579 documents) to keep the epoch with the highest agreement with the teacher.

E. FOLDING, TABLE ENSEMBLE, AND COMPACT VARIANT

The classification head is linear, so (1) can be rewritten as

$$W\Big(\frac{1}{n}\sum_i \mathbf{e}_{t_i}\Big) + \mathbf{b} = \frac{1}{n}\sum_i T_{t_i} + \mathbf{b}, \quad (3)$$




FIGURE 1. StaticKD pipeline. The teacher labels an unlabeled news corpus once, offline. The student learns to imitate the teacher distribution. Its linear head is then folded into a token table, so inference only looks up and averages table rows. The final evaluation uses a test set whose labels do not come from the teacher.

with the table $T = EW^\top \in \mathbb{R}^{|V|\times 17}$. The folding step computes T once after training. Row T_t holds the 17 topic scores that token t contributes to every article that contains it. The deployed model consists only of T (fp16), $\mathbf{b}$, and the tokenizer. Algorithm S1 in the supplementary material lists the whole inference procedure. The same argument holds for an ensemble because Equation (3) is linear in T. Averaging the logits of K students trained with different seeds gives the same result as one student with table $\bar{T} = \frac{1}{K}\sum_k T^{(k)}$ and bias $\bar{\mathbf{b}}$. The student was trained with three seeds (0, 1, and 2) during development. The final StaticKD model averages the tables of these three seeds ($K = 3$). It has 8.5 million parameters and a size of 34 MB.

The table itself takes 16 MB, but most of the random-access memory (RAM) goes to the internal structure of the Unigram tokenizer. A compact variant shrinks this structure by removing token pieces that occur fewer than 10 times in the distillation data. It keeps single characters and has a vocabulary of 335,441 tokens and a model size of 23 MB. The hyperparameters of all models are listed in Table S1 of the supplementary material.

IV. DATA AND TEST SET

A. DATA SETS AND THEIR ROLES

Table 2 lists the data sets used in this study. The development set is the development split of EMMediaTopic (1,000 articles in four languages with GPT-4o labels). All parameter settings and recipe choices for StaticKD were made on this set. The recipe was fixed *before* the test set was built. The LLM check set also informed two of these choices: the temperature $\tau = 1$ and the three-seed ensemble (Section III-D). The set contains 320 articles in 16 languages labeled by an LLM (Claude) with the prompt of [2]. The teacher was trained on labels that an LLM (GPT-4o) produced with the same prompt, so these labels are not independent of the teacher. No reported result uses this set.

B. DISTILLATION DATA AND DEVELOPMENT SET

The distillation data and the development set both draw on EMMediaTopic 1.0 [2], [9], which Kuzman and Ljubešić released together with the teacher model. EMMediaTopic was labeled with GPT-4o and consists of articles in four languages

TABLE 2. Data Sets of the Study and Their Roles

Set	Docs	Lang.	Labels	Used for
Distillation data	285,999	69	teacher	training the students
internal validation	8,579	–	teacher	choosing the epoch
Development (EMMediaTopic)	1,000	4	GPT-4o	choosing the recipe
CC-News held-out	12,554	63	teacher	agreement, unseen sites
Unified test set	12,744	47	editorial	all accuracy results
LLM check set	320	16	Claude	informal check only
English section sample	754	1	JSON-LD	label validity only

(Catalan, Greek, Croatian, and Slovenian). A total of 21,000 annotated articles were taken and divided into a training split of 20,000 and a development split of 1,000 articles. Kuzman and Ljubešić used the training split to train the teacher. The same split also forms part of the distillation data for the student. The development split was never used to train the teacher or the student. It guided the hyperparameter search of the teacher [2] and serves in this study as the development set for choosing the StaticKD recipe.

A large part of the distillation data comes from CC-News 2019–2021, a multilingual dataset [36] built from the news archive of Common Crawl. The test set was drawn from CC-News for a different range of years (CC-NEWS 2024–2026, Section IV-C). CC-News 2019–2021 was processed with the following steps.

1) Verify the language with the fastText language identification model [8] and keep only documents whose metadata language agrees with the identified language.
2) Keep documents whose title and body reach 75 words in total (200 characters for ja, zh, th, my) and truncate the text to 512 words.
3) Keep at most 150 documents per site.
4) Form a held-out split by domain: all documents of some sites are set aside, with at most 20% per language.
5) Add 156,157 documents from training sites only (at most 5,000 per language and 400 per site).

The distillation data contain 285,999 documents in 69 languages from 2,960 sites, with a median of 269 words. The number of documents per site was capped to avoid bias from similar content within one site. A few multilingual sites (for example bbc.com) were set aside in one language but also appear in the distillation data in another language. Articles

from such sites were removed from the held-out split. The resulting held-out set contains 12,554 documents in 63 languages from 217 sites that never occur in the distillation data. It can only measure *agreement* with the teacher because it has no independent category labels. Agreement is the share of documents whose top predicted label is the same as the top label of the teacher.

C. UNIFIED TEST SET CONSTRUCTION

The largest source is the CC-NEWS 2024–2026 dataset, sampled as one archive file (WARC) per month from January 2024 to August 2026 (32 files) [37]. The schema.org JSON-LD blocks [16] of each article page supplied metadata fields such as `articleSection`, `BreadcrumbList`, `inLanguage`, `datePublished`, `isAccessibleForFree`, and `articleBody`. The text was taken from `articleBody` only when it had at least 30 words. The text of articles without such an `articleBody` came from the HTML content through the Trafilatura library [38]. The site filter removed articles from sites that already appear in the distillation data or in an evaluation set. The remaining 399,468 articles come from new sites.

The remaining articles come from public datasets. MasakhaNEWS [17] and MN-DS [18] are labeled by humans. L3Cube-IndicNews (LDC split) [19], Bangla news [20], and IndoNews [39] carry publisher categories.

Section and category labels record where the newsroom placed an article when it was published. Such labels are called *editorial labels* in this paper. Editorial labels do not follow the IPTC standard, so the section names have to be translated onto the official IPTC Media Topic tree (1,085 active nodes). The section names were first normalized for case and diacritics and then mapped conservatively by an LLM (Claude Opus 5.5). The LLM mapped a name only if the content under that section fit a single top-level topic. The mapping links 814 section names to 79 IPTC nodes. An automatic check verified that every target node exists in the IPTC tree, is not retired, and lies under the intended top-level topic. Articles whose sections mapped to different labels were rejected. The mapping table drafted by the LLM was then reviewed manually by two researchers in a joint session. The table holds 916 rules: the 814 valid mapped names and 102 further rules for ambiguous, language-specific, or rejected names. The review covered every rule except 48 names that are identical to the target IPTC node name or its English plural and were accepted automatically.

Quality and leakage filters were applied in order.

1) Publication date on or after 1 January 2024 (CC-NEWS only).
2) Not behind a paywall.
3) Declared language agrees with fastText language identification when fastText supports the language.
4) At least 75 words.
5) Deduplication of uniform resource locators (URLs), identical texts, and near-duplicates (MinHash [31], Jaccard ≥ 0.7 [32]) across all sources.
6) Contamination: an article was dropped when $\geq 30\%$ of its word 8-grams occurred in any of about 300 thousand training or evaluation documents. The filter removed 50 articles, mostly from MasakhaNEWS, which also draws on BBC.

TABLE 3. Composition of the Unified Test Set by Source

Source	Label origin	Articles	Languages	Sites/sources
CC-NEWS 2024–2026	JSON-LD section	6,050	29	1,092
MasakhaNEWS [17]	human annotation	3,339	16	6
L3Cube-IndicNews [19]	publisher category	2,361	10	1
MN-DS [18]	human annotation	755	1	127
Bangla news [20]	publisher category	139	1	1
IndoNews	publisher category	100	1	1
Total		12,744	47	1,227

Sampling took at most 50 articles for each pair of language and label. Human-labeled sources had priority, followed by publisher categories and then JSON-LD sections. The number of articles per site was not capped. Languages with fewer than 30 articles were dropped. Whole sites were resampled when confidence intervals were computed (Section V-B) because articles from the same site tend to be similar. Section VI-A also repeats the comparison with at most five articles per site.

The final test set contains 12,744 articles in 47 languages from 1,227 sites or sources. All 17 labels occur in it. The median article length is 313 words. Human annotators labeled 4,094 of these articles (32.1%). Publisher categories cover 2,600 (20.4%) and JSON-LD sections 6,050 (47.5%). The label type of an article (human annotation, publisher category, or JSON-LD section) is called its *label origin*. No distillation data exist for 13 languages (e.g., ha, yo, ig, bn, and pa). Another 9 languages have fewer than 500 distillation documents, and 25 have at least 500. The effective number of sites $1/\sum_s q_s^2$ measures site diversity, where q_s is the share of the articles of a language that come from site s. A source dataset without URLs counts as one site. Thirteen languages have at least 10 effective sites by this measure. Another 27 languages come almost entirely from one publisher. Table 3 summarizes the composition of the article sources. Fig. S1 in the supplementary material shows the number of articles of each language per label.

D. VALIDITY OF THE EDITORIAL LABELS

Two thirds of the test labels are section and category labels, which record newsroom decisions rather than annotation that follows a labeling guideline. The check below tests whether such labels behave like human labels in the same language. It compares how well one and the same teacher agrees with each label type. The teacher serves only as a fixed reference. Much noisier section labels would make the teacher agree less with section labels than with human labels in the same language.

The English part of the test set contains only human labels because the sampling preferred human-labeled sources (Section IV-C). A comparison within English therefore uses a separate sample drawn from 306 sites outside the test set.

The sample contains 754 English CC-NEWS articles with JSON-LD section labels and at most 50 articles per label. The accuracy of the teacher is 0.646 on the section labels (macro-F1 0.617) and 0.559 on the human labels of MN-DS and MasakhaNEWS (macro-F1 0.565). The teacher is more accurate on the section labels for 12 of the 17 labels (Wilcoxon $p = 0.033$). The ranking of label difficulty also correlates between the two label types ($\rho = 0.63, p = 0.007$). Both label types have the same hard labels: *society*, *human interest*, and *religion*. English section labels are thus not noisier than human labels by this measure.

The test set itself allows a comparison in French. The teacher reaches an accuracy of 0.716 on 208 French articles with section labels and 0.500 on 200 human-labeled MasakhaNEWS articles. The direction is the same as in English.

The lower agreement on the human-labeled sources is examined per category in languages covered by XLM-R pretraining. The median agreement per category between the teacher and the mapped label is 0.46 for MasakhaNEWS and 0.50 for MN-DS. It is higher for L3Cube (0.81) and CC-NEWS sections (0.87). The lowest agreement occurs for source categories that are broader than the IPTC target. One example is the *politics* category of MasakhaNEWS, where only 45% of the articles are predicted as *politics*. The main alternative is *conflict* (29%). Agreement is also low for labels whose boundaries are unclear even to human annotators, such as *society* in MN-DS. The finding matches the low inter-annotator agreement reported for that label [2]. Such mismatches reflect differences between the category scheme of a source and IPTC. Comparisons between models are unaffected because every model is scored against the same labels. Absolute scores are read as agreement with the editorial categorization.

V. EXPERIMENTAL SETUP

A. BASELINES

All baselines marked + KD used the same distillation data (285,999 documents) and targets from the same teacher. The fastText + KD baseline [8] was trained on the top teacher label with word tokens and character n-grams or with XLM-R subwords. Its quantized variant (`.ftz`) was included as well. A fastText model was also trained only on the GPT-4o labels of the EMMediaTopic training split. It serves as a reference trained on the same labeled data as the teacher [2]. The non-neural baseline TF-IDF + SVM + KD comes from Kuzman and Ljubešić. It uses TF-IDF features with a support vector classifier and was trained on the top teacher label over XLM-R subwords. A grid search on the development set chose the hyperparameters of TF-IDF + SVM + KD and of both fastText + KD models. The search covered 5 configurations for TF-IDF + SVM and 18 for each fastText model. The quantized model took the configuration of the subword model. All values are listed in Table S1 of the supplementary material. The Model2Vec classifier + KD was trained on the top teacher label with the classifier trainer of the Model2Vec library [11] with its default settings. It fine-tunes the same potion embeddings that StaticKD starts from. The classifier also learns a weight for each token and adds a hidden layer of 512 units. MiniLM-L6 + KD uses mMiniLMv2-L6-H384, which is distilled from XLM-R-large [7]. The temperature $\tau \in \{1, 2\}$ for this model was chosen on the development set. The same recipe with $\tau = 1$ was applied to DistilmBERT + KD with `distilbert-base-multilingual-cased` [6]. Both transformers read at most 256 tokens. The 256-token limit truncates 91.1% of the test articles to about 142 words for MiniLM-L6 and 93.2% to about 116 words for DistilmBERT. A sensitivity check retrained both models with 512 tokens (Section VI-A). Both were exported to ONNX fp32 for the CPU benchmark. The ONNX int8 teacher was exported from the teacher with dynamic int8 quantization and is the fastest teacher configuration on CPU.

Sparse Distillation [23] is the prior method closest to StaticKD. It was not run as a separate baseline (Section VII-E). Two other experiments still cover parts of the method. The fastText + KD baseline trained a bag-of-n-grams model with averaging and a linear head on the same teacher labels. The random-initialization ablation (Section V-D) trained the embedding table from scratch as Sparse Distillation does.

B. EVALUATION PROTOCOL AND STATISTICAL TESTS

The label distribution is imbalanced, so the main metric is macro-F1 over the labels present in the reference. It is computed in the same way as in the evaluation code of [2]. The evaluation also reports accuracy, agreement with the teacher on the held-out set, and macro-F1 per language. The per-language macro-F1 is averaged over languages so that large languages do not dominate.

The 95% confidence intervals were computed by a percentile bootstrap of 1,000 resamples. The resampling unit on the test set is the site, or the source dataset when an article has no URL. Such a site-cluster bootstrap [35] draws whole sites so that related articles from one site do not make the intervals too narrow. The 1,227 clusters of the test set differ in size. The two largest clusters (bbc.com and L3Cube-IndicNews) hold 37.3% of the articles. Let q_c be the share of cluster c. The effective number of clusters $1/\sum_c q_c^2$ is then only 13.8. A leave-one-source-out check therefore recomputed the macro-F1 of nine models once without each of the six test-set sources. The development set was resampled by document. Two models tested on the same documents were compared with a paired (cluster) bootstrap of 2,000 resamples for Δmacro-F1 [33] and an exact McNemar test for accuracy [40]. Holm correction [41] was applied within each set. Each ablation variant ran with five seeds and the final recipe with ten. The same paired bootstrap compared each variant with the final recipe. Every resample scored all seeds of the variant and of the final recipe on the same articles. The tested quantity is the difference between the two seed means. Holm correction covered the 14 variants of Section V-D. A difference that is not significant does not show that two models are equivalent. Claims of equivalence rest

on two one-sided tests (TOST) [42] over the same bootstrap distribution. Two models count as equivalent when the 90% interval of Δmacro-F1 lies within ±0.01. The equivalence margin is less than half of the gap between StaticKD and MiniLM-L6. A Wilcoxon signed-rank test on per-language macro-F1 and accuracy [34] checked whether a difference is consistent across languages.

Subgroup analyses split the results by language, script, and region. The label and its origin defined further splits. The remaining subgroups were defined by site diversity, the amount of distillation data of the language, and teacher pre-training coverage. Pre-training coverage refers to whether the language is among the 100 languages used to pre-train XLM-R [3]. Spearman correlations measured the relation between per-language properties and performance, and a Kruskal–Wallis test compared scripts. The *p*-values of these seven tests were Holm-corrected together. The per-language analysis used two quantities. The *accuracy gap* is the StaticKD accuracy minus the teacher accuracy, so a negative gap means that StaticKD is less accurate. The *token coverage* of a language is computed over all token occurrences in its test articles. Its value is the share of occurrences whose token occurs at least 10 times in the distillation data. Training seldom updates the embeddings of less frequent tokens (Section III-D). Calibration was measured with the expected calibration error (ECE, 15 bins) [43] because the cascade mode in Section V-C routes articles by the confidence of StaticKD.

C. EFFICIENCY PROTOCOL

The benchmark ran only on CPU with the GPU hidden. Each model ran in a fresh process with the thread count pinned in every library (OMP, MKL, OpenBLAS, ONNX Runtime, `tokenizers`). Latency (p50 and p95) was measured with one article per call, as in a streaming setting. Throughput was measured with batches of 64, or 8 for transformers. Model RAM is the increase in resident set size after the model is loaded. All models used the same text sample, drawn at random from the unified test set. The teacher and the transformers used 100 documents for latency and 96 documents for throughput, while the light models used 500 and 3,000 documents. The whole benchmark was repeated in three separate sessions on an idle machine. The tables report the median of the three sessions. The teacher stops at 512 tokens, whereas StaticKD reads up to 1,024 tokens per article. The speed comparison therefore does not favor StaticKD. The cascade mode lets StaticKD decide the articles on which its top probability is at least a threshold θ. The remaining articles are passed to the ONNX int8 teacher. Let s be the share of articles decided by StaticKD, and let r_S and r_T be the single-core throughputs of StaticKD and the teacher. The effective throughput of the cascade is then $1/(1/r_S + (1-s)/r_T)$.

The machine is a laptop with an Intel Core Ultra 7 155H, 31 GB of RAM, and Windows 11. Its CPU is hybrid and has 6 performance cores (P-cores), 8 slower efficiency cores (E-cores), and 2 low-power E-cores. The operating system moves unpinned threads to the slow cores. Each process was therefore pinned to physical P-cores: logical CPU 0 for one core and logical CPUs 0, 10, 12, and 14 for four cores. The pinned setup approximates a small server with uniform cores.

D. ABLATION DESIGN

Table 7 lists all 60 runs of the final recipe and its ablations. Each ablation variant changes one factor of the final recipe. One variant replaces the soft labels with hard labels. Two variants reduce the training data, either to EMMediaTopic only (4 languages, 10 epochs) or to 130 thousand documents without the extra CC-News 2019–2021 data. Other variants freeze the embeddings or draw random embeddings with the same standard deviation as potion. The remaining variants train without token dropout, use a 512-unit multilayer perceptron (MLP) head, or set $\tau \in \{0.5, 2, 4\}$. Twelve further runs during development tested four additions to the recipe with three seeds each. The four additions are bigram features, idf-weighted pooling, documents weighted by teacher confidence, and an extra loss on the GPT-4o labels. None of the additions differs significantly from the final recipe on the development set. No addition changes the test macro-F1 by more than 0.004. The recipe and Table 7 therefore exclude the four additions.

E. IMPLEMENTATION DETAILS

An average StaticKD run took 5.2 minutes on the RTX 4050 GPU. The implementation uses Python 3.12, NumPy 2.5, PyTorch 2.6, transformers 5.17, `tokenizers` 0.23, ONNX Runtime 1.30, scikit-learn 1.9, and fastText 0.9.2. The seed, library versions, and training history of every run are stored with the model.

VI. RESULTS

A. ACCURACY OF ALL MODELS (RQ1)

StaticKD keeps 91.1% of the teacher macro-F1 on the unified test set and 92.6% on the development set. The scores are 0.545 [0.490–0.605] for StaticKD and 0.598 [0.546–0.643] for the teacher (Table 4). Both scores are lower than the development scores (0.761 and 0.822). The gap arises because most of the test set lies outside the languages, sources, and period of the teacher training data. The predictions of StaticKD match those of the teacher on 81.1% of the held-out documents in 63 languages. A single student without ensembling reaches 0.542 ± 0.004 on the test set (10 seeds).

MiniLM-L6 starts from a distillation of XLM-R-large. Its score (0.566) lies between StaticKD and the teacher. DistilmBERT (0.534) does not differ significantly from StaticKD, although its cost is higher. Three baselines run at a speed similar to that of StaticKD. Both fastText + KD and TF-IDF + SVM + KD fall below StaticKD. The Model2Vec classifier starts from the same potion embeddings and reaches 0.547. The last two rows show what happens when there are no teacher labels for other languages. The fastText model trained only on the GPT-4o labels of four languages reaches 0.665 on the development set but only 0.086 on the test set.

TABLE 4. Main Results. Macro-F1 [95% CI] and Accuracy on the Development Set (EMMediaTopic Dev, GPT-4o Labels), Agreement with the Teacher on CC-News Held-Out, and Results on the Unified Test Set (47 Languages, Independent Labels). Test CIs from the Site-Cluster Bootstrap

	dev (4 languages)		held-out	unified test (47 languages)			
Model	Macro-F1 [95% CI]	Accuracy	Agreement	Macro-F1 [95% CI]	Accuracy	Macro-F1/language	% teacher
Teacher XLM-R-large	0.822 [0.779–0.851]	0.859	–	0.598 [0.546–0.643]	0.700	0.705	100.0%
Teacher XLM-R-large, ONNX int8	0.823 [0.781–0.852]	0.858	–	0.600 [0.547–0.646]	0.699	0.702	100.3%
DistilmBERT + KD	0.753 [0.710–0.785]	0.801	0.799	0.534 [0.481–0.618]	0.623	0.602	89.4%
MiniLM-L6 + KD	0.785 [0.737–0.815]	0.820	0.825	0.566 [0.511–0.624]	0.667	0.661	94.6%
StaticKD (proposed)	**0.761 [0.717–0.792]**	0.800	0.811	**0.545 [0.490–0.605]**	0.641	0.622	91.1%
StaticKD-compact	0.754 [0.710–0.786]	0.797	0.802	0.484 [0.421–0.597]	0.544	0.507	81.0%
fastText + KD, subword, quantized	0.729 [0.688–0.760]	0.768	0.740	0.439 [0.370–0.561]	0.515	0.465	73.4%
fastText + KD, subword	0.737 [0.701–0.765]	0.772	0.754	0.447 [0.385–0.566]	0.527	0.480	74.7%
fastText + KD, word	0.750 [0.713–0.779]	0.791	0.758	0.445 [0.380–0.563]	0.515	0.474	74.5%
TF-IDF + SVM + KD	0.755 [0.719–0.786]	0.798	0.776	0.486 [0.431–0.585]	0.567	0.522	81.3%
Model2Vec classifier + KD	0.744 [0.701–0.772]	0.780	0.805	0.547 [0.495–0.599]	0.642	0.619	91.5%
fastText, GPT-4o labels, subword	0.665 [0.613–0.700]	0.729	0.260	0.086 [0.069–0.119]	0.150	0.118	14.4%
fastText, GPT-4o labels, word	0.651 [0.601–0.693]	0.738	0.307	0.106 [0.085–0.150]	0.181	0.142	17.7%

TABLE 5. Paired Tests of StaticKD Against Other Models on the Unified Test Set. Δ = StaticKD − Comparison Model. p Is Holm-Corrected Over the Comparisons. b/c = Documents Correct Only for StaticKD / Only for the Comparison Model

StaticKD vs	Δmacro-F1 [95% CI]	p bootstrap	Δaccuracy	McNemar b/c	p McNemar
Teacher XLM-R-large	−0.053 [−0.065, −0.033]	<0.001	−0.059	654/1400	<0.001
Teacher XLM-R-large, ONNX int8	−0.055 [−0.067, −0.035]	<0.001	−0.058	644/1386	<0.001
DistilmBERT + KD	+0.010 [−0.026, +0.041]	1.000	+0.018	1372/1143	<0.001
MiniLM-L6 + KD	−0.021 [−0.038, −0.008]	0.005	−0.026	866/1197	<0.001
StaticKD-compact	+0.060 [+0.003, +0.100]	0.042	+0.097	1345/110	<0.001
fastText + KD, subword, quantized	+0.106 [+0.037, +0.145]	<0.001	+0.126	2135/532	<0.001
fastText + KD, subword	+0.098 [+0.036, +0.134]	<0.001	+0.114	1979/529	<0.001
fastText + KD, word	+0.099 [+0.037, +0.141]	<0.001	+0.126	2140/536	<0.001
TF-IDF + SVM + KD	+0.059 [+0.009, +0.093]	0.040	+0.074	1667/719	<0.001
Model2Vec classifier + KD	−0.002 [−0.009, +0.010]	1.000	−0.001	438/447	0.788
fastText, GPT-4o labels, subword	+0.458 [+0.415, +0.496]	<0.001	+0.491	6597/344	<0.001
fastText, GPT-4o labels, word	+0.439 [+0.393, +0.475]	<0.001	+0.460	6252/391	<0.001

The paired tests in Table 5 confirm this ranking. The Δmacro-F1 of StaticKD against the teacher is −0.053 [−0.065, −0.033]. MiniLM-L6 keeps a significant lead (−0.021 [−0.038, −0.008], $p = 0.005$). StaticKD and DistilmBERT do not differ significantly (+0.010, $p = 1.000$). The 90% interval [−0.023, +0.036] is too wide to show equivalence (TOST $p = 0.428$). The McNemar test favors StaticKD over DistilmBERT in accuracy ($p < 0.001$) but treats articles from the same site as independent. StaticKD is ahead of the quantized fastText + KD by +0.106 [+0.037, +0.145]. Its advantage over TF-IDF + SVM is +0.059 [+0.009, +0.093] ($p = 0.040$). The Model2Vec classifier is the only light model that matches StaticKD. The Δmacro-F1 between the two models is −0.002 [−0.009, +0.010] with a 90% interval of [−0.008, +0.008] inside the ±0.01 equivalence margin (TOST $p = 0.025$).

The macro-F1 of StaticKD is higher than that of fastText + KD in 40 of 47 languages (Wilcoxon $p < 0.001$). The advantage over TF-IDF + SVM is narrower. StaticKD has the higher macro-F1 in 31 of 47 languages (Wilcoxon $p = 0.003$). Per-language accuracy gives a different picture. StaticKD is higher in 24 languages and lower in 22 (Wilcoxon $p = 0.127$), so the accuracy of the two models is close. Per-language tests find no consistent difference in either metric between StaticKD and DistilmBERT (Wilcoxon $p = 0.604$ for macro-F1 and 0.322 for accuracy) or the Model2Vec classifier ($p = 0.358$ and 0.534). StaticKD beats the teacher in only 7 of 47 languages.

The model ranking was also checked against the cluster structure of the test set and against the input length of the transformers. A subset with at most five articles per site and language–label pair keeps 8,139 articles. StaticKD obtains 0.587 on it and the teacher 0.627. Only the order of StaticKD and the Model2Vec classifier (0.583) changes on this subset. Leaving out one source at a time places StaticKD between third and fifth of the nine models (Table S2 in the supplementary material). Only the Model2Vec classifier and DistilmBERT change places with it. Every fastText and TF-IDF model stays at least 0.028 below StaticKD. Retraining with 512-token inputs raises the test macro-F1 of MiniLM-L6 and DistilmBERT to 0.580 and 0.547. MiniLM-L6 stays ahead of StaticKD (−0.035 [−0.049, −0.021], $p < 0.001$). DistilmBERT still does not differ significantly from it (−0.002 [−0.029, +0.022], $p = 0.779$).

B. CPU EFFICIENCY (RQ2)

The teacher is too slow on CPU for a large stream of articles. StaticKD removes this cost almost entirely (Table 6, Fig. 2, and Fig. S2 in the supplementary material). The PyTorch fp32 teacher needs 2,816 ms per article on one core and reaches a

TABLE 6. CPU Efficiency on Pinned P-Cores (Sample From the Unified Test Set, 1c/4c = 1/4 Cores)

Model	Latency p50 / p95, 1c (ms)	Throughput 1c (doc/s)	Throughput 4c (doc/s)	Model RAM (MB)	File (MB)	Dependencies
Teacher XLM-R-large	2,816 / 2,894	0.34	0.97	2,950	2,136	torch, transformers
Teacher XLM-R-large, ONNX int8	1,190 / 1,229	0.79	2.53	1,375	537	onnxruntime, transformers
DistilmBERT + KD	193 / 202	5.05	15.6	1,059	516	onnxruntime, transformers
MiniLM-L6 + KD	56.5 / 61.9	16.9	48.8	1,235	408	onnxruntime, transformers
StaticKD	2.01 / 3.31	539	1,827	501	34	numpy, tokenizers
StaticKD-compact	1.78 / 3.17	601	2,005	277	23	numpy, tokenizers
fastText + KD, subword, quantized	1.93 / 3.21	545	1,393	300	18	fasttext, tokenizers
fastText + KD, subword	2.07 / 3.62	489	1,184	1,122	839	fasttext, tokenizers
TF-IDF + SVM + KD	2.96 / 4.49	433	865	828	166	scikit-learn, tokenizers
Model2Vec classifier + KD	1.99 / 3.22	568	1,822	1,091	507	model2vec, scikit-learn




FIGURE 2. Test macro-F1 on the unified test set against single-core CPU throughput (log scale).

throughput of 0.34 articles per second. The best CPU configuration for the teacher is ONNX int8 (1,190 ms per article and 0.79 articles per second). Classifying one million articles per day would take 14.7 cores (ONNX int8) to 33.7 cores (PyTorch) for this step alone.

StaticKD needs 2.01 ms per article and can process 539 articles per second per core. Its speed is about 682 times that of the ONNX int8 teacher and 1,572 times that of the PyTorch teacher. MiniLM-L6 is about 32 times slower. The StaticKD file is 16 times smaller than that of the ONNX int8 teacher. A load of one million articles per day needs 0.02 cores. StaticKD uses 501 MB of RAM (mostly for the tokenizer structure), while the compact variant uses 277 MB. Tokenization takes 98% of the single-thread prediction time and produces 579 tokens per article on average. Averaging the table rows alone runs at 26,843 articles per second. The speed of StaticKD is thus limited by the tokenizer, not by the model.

The light models reach similar speeds on one core, from 433 articles per second for TF-IDF + SVM to 601 for the compact variant. The quantized fastText + KD is smaller (18 MB) and uses less RAM (300 MB) than StaticKD but reaches a test macro-F1 of only 0.439. The Model2Vec classifier is the only light model that matches the accuracy of StaticKD (Fig. 2). It needs 507 MB on disk and 1,091 MB of RAM.

C. ABLATION, TEMPERATURE, AND ENSEMBLING (RQ3)

Table 7 reports the ablation results with five seeds per variant. Most of the accuracy comes from two components: multilingual distillation data and the pre-trained embeddings. A student distilled on EMMediaTopic alone (4 languages) loses 0.051 in test macro-F1 and 0.077 in held-out agreement. Random initialization in place of potion lowers the test macro-F1 more than any other variant (0.120, $p < 0.001$). Only these two variants differ significantly from the final recipe in test macro-F1.

Freezing the embeddings restricts training to the linear head on top of potion and gives mixed results. The development score drops by 0.035 ($p = 0.040$) and the held-out agreement by 0.020 ($p < 0.001$). The test macro-F1 rises by 0.014, but the interval of this gain includes zero ([−0.004, +0.024], $p = 1.000$). Table 8 traces the gain to languages with little distillation data (+0.059) and to languages without distillation data (+0.037). The frozen embeddings are slightly weaker in languages with at least 500 documents (−0.007). The final recipe had already been fixed on the development set before this effect was observed. Section VII explains why that set cannot reveal the effect.

None of the other variants changes the test macro-F1 significantly. Hard labels from the teacher raise the test macro-F1 by 0.005 ($p = 1.000$) and lower the development score by 0.006 ($p = 1.000$). The 90% interval of the test difference lies inside the equivalence margin ([−0.001, +0.009], TOST $p = 0.017$). Hard labels therefore work as well as soft labels. Reducing the data to 130 thousand documents lowers the test score by 0.002 ($p = 1.000$). Removing token dropout gives +0.001 ($p = 1.000$) and an MLP head that cannot be folded +0.009 ($p = 0.780$). The data and dropout variants also pass the equivalence test. The MLP head fails it because its 90% interval reaches +0.012.

A higher temperature does not help (Fig. S3 in the supplementary material). The common choice of $\tau = 2$ [10] lowers the held-out agreement by 0.007 ($p < 0.001$) compared with $\tau = 1$. Neither the test macro-F1 nor the development score changes significantly (−0.005 and −0.006, both $p = 1.000$). The test difference passes the equivalence test at both $\tau = 2$ and $\tau = 0.5$. The value $\tau = 4$ lowers the development score and the held-out agreement significantly. Its test score falls by 0.014 but not significantly ($p = 0.836$).

The ensemble results were averaged over seed combina-

TABLE 7. Ablations and Temperature (One Student, No Ensemble). Mean ± Standard Deviation Over Seeds. * = Different From the Final Recipe (Paired Bootstrap, Holm, $p < 0.05$). ΄ = Test Macro-F1 Minus That of the Final Recipe [95% CI]. † = Equivalent Within ±0.01 (TOST)

Variant	Seeds	Dev macro-F1	Held-out agreement	Test macro-F1	Δ test macro-F1 [95% CI]
Final recipe					
Final recipe (one seed)	10	0.755±0.010	0.808±0.001	0.542±0.004	–
Component ablation					
Hard teacher labels (cross-entropy)	5	0.749±0.007	0.805±0.001	0.547±0.004	+0.005 [−0.002, +0.010]†
EMMediaTopic only (4 languages, 20k)	5	0.723±0.006*	0.730±0.001*	0.491±0.002*	−0.051 [−0.064, −0.036]
130k documents (no extra CC-News)	5	0.736±0.009*	0.799±0.002*	0.541±0.002	−0.002 [−0.008, +0.002]†
Randomly initialized embedding	5	0.715±0.005*	0.739±0.004*	0.422±0.006*	−0.120 [−0.166, −0.047]
Frozen embedding (linear head only)	5	0.720±0.001*	0.788±0.001*	0.557±0.002	+0.014 [−0.004, +0.024]
No token dropout	5	0.757±0.004	0.808±0.001	0.544±0.002	+0.001 [−0.001, +0.003]†
512-unit MLP head (cannot be folded)	5	0.762±0.009	0.813±0.002*	0.551±0.006	+0.009 [−0.000, +0.012]
Temperature					
$\tau = 0.5$	5	0.750±0.004	0.807±0.002	0.546±0.005	+0.004 [−0.002, +0.007]†
$\tau = 2$	5	0.748±0.003	0.801±0.001*	0.537±0.001	−0.005 [−0.010, +0.008]†
$\tau = 4$	5	0.723±0.004*	0.791±0.001*	0.529±0.002	−0.014 [−0.020, +0.001]

TABLE 8. Macro-F1 of Selected Variants by the Amount of Distillation Data in the Language of the Article (Test Set, Mean Over Seeds)

Variant	Dev	Sufficient (≥500)	Few (<500)	None (0)
Final recipe (one seed)	0.755	0.615	0.482	0.403
Frozen embedding (linear head only)	0.720	0.607	0.541	0.440
Randomly initialized embedding	0.715	0.567	0.182	0.161
EMMediaTopic only (4 languages, 20k)	0.723	0.559	0.466	0.351
Hard teacher labels (cross-entropy)	0.749	0.617	0.482	0.410
512-unit MLP head (cannot be folded)	0.762	0.613	0.484	0.421
$\tau = 2$	0.748	0.612	0.476	0.363

tions (Fig. S4 in the supplementary material). Three seeds instead of one raise the test macro-F1 from 0.542 to 0.544 and the held-out agreement from 0.808 to 0.810. Ten seeds give 0.546. The gain is small but free at inference time because an ensemble of any size folds into one table.

D. ANALYSIS BY LANGUAGE, LABEL, AND SOURCE (RQ4)

Table 9 and Fig. S5 in the supplementary material report the share of the teacher score that StaticKD keeps. The share varies more with the amount of distillation data in the language of the article than with the type of label. The share ranges across label origins from 89.5% for publisher categories to 95.8% for JSON-LD sections. It falls from 97.5% in languages with at least 500 distillation documents to 72.3% in languages without distillation data. The Model2Vec classifier is slightly ahead of StaticKD in the languages without distillation data (0.429 against 0.402). The two classifiers differ by at most 0.011 in every other subgroup of Table 9.

Table S3 in the supplementary material splits the test set by source. MN-DS is the only source that is annotated directly with IPTC topics. StaticKD keeps 97.4% of the teacher score on MN-DS (0.535 against 0.549). The macro-F1 of the teacher itself is lower on this source than on any other source. StaticKD keeps the smallest share on MasakhaNEWS (80.0%). The human labels of MasakhaNEWS follow a non-IPTC scheme, and 10 of its 16 languages are absent from the distillation data. Bangla is also absent from the distillation data and shows most clearly what the pre-trained embeddings contribute. Both fastText + KD and TF-IDF + SVM collapse on Bangla news (0.191 and 0.010). StaticKD reaches 0.748 on the same articles.

The accuracy of StaticKD is close to that of the teacher in a typical language. The median per-language accuracy gap is −0.024 (Fig. 3). Table S4 in the supplementary material relates this gap to properties of the language. The analysis on the held-out set uses 53 languages with at least 20 documents each. The agreement of StaticKD with the teacher rises with teacher confidence ($\rho = 0.71$, $p < 0.001$). Its relation to the log amount of distillation data ($\rho = 0.31$) is not significant after Holm correction ($p = 0.067$). Agreement does not differ significantly across scripts (Kruskal–Wallis $H = 10.37$, $p = 0.067$). The accuracy gap on the test set narrows as the amount of distillation data grows ($\rho = 0.52$, $p < 0.001$). The weak spot of StaticKD is a group of African languages. StaticKD reaches a mean accuracy of only 0.407 on languages that lie outside XLM-R pre-training and are also absent from the distillation data (ig, lg, ln, pcm, rn, sn, ti, yo). The teacher reaches 0.643 on the same languages.

Four Indian languages (bn, ml, or, pa) show how StaticKD behaves on text whose tokens hardly ever appeared in training. At least 68% of the token occurrences in these languages come from tokens that appear fewer than 10 times in the distillation data. StaticKD still reaches a mean accuracy of 0.624 there compared with 0.738 for the teacher. The compact variant removes these rare tokens from the tokenizer, and its accuracy on these four languages falls to 0.013. Accuracy in the other languages is 0.578 for the compact variant and 0.640 for the full StaticKD.

Fig. S6 in the supplementary material shows the results per label. The hardest labels for StaticKD are *society* (0.16), *disaster* (0.29), *human interest* (0.32), and *conflict* (0.37). StaticKD does best on *sport* (0.88), *weather* (0.84), and *education* (0.75). The largest gaps to the teacher occur for *environment* (−0.17), *religion* (−0.15), and *arts* (−0.08). The most frequent confusions are *society* → *human interest*, *human interest* → *arts*, and *society* → *politics*, with 20% each.

The table also shows which tokens carry the topic signal of an article. The specificity of a token is the largest difference between one entry of its table row and the mean of the other

TABLE 9. Test Macro-F1 by Subgroup. Last Column: StaticKD Macro-F1 as a Percentage of the Teacher Macro-F1 in the Same Subgroup

Subgroup	n	Teacher	DistilmBERT	MiniLM	**StaticKD**	Model2Vec	fastText (q)	TF-IDF+SVM	fastText GPT	% teacher
Label origin										
human annotation	4,094	0.463	0.436	0.436	0.414	0.414	0.328	0.393	0.027	90%
publisher category	2,600	0.702	0.498	0.674	0.629	0.632	0.300	0.330	0.063	90%
JSON-LD section	6,050	0.651	0.629	0.634	0.624	0.618	0.582	0.609	0.136	96%
Distillation data of the language										
sufficient ($\geq$500)	7,644	0.633	0.617	0.616	0.618	0.611	0.575	0.593	0.116	98%
few ($<$500)	2,243	0.537	0.344	0.496	0.478	0.475	0.195	0.227	0.037	89%
none (0)	2,857	0.557	0.452	0.502	0.402	0.429	0.176	0.230	0.048	72%
Region										
Africa	3,044	0.697	0.532	0.576	0.542	0.550	0.325	0.408	0.085	78%
South Asia	2,681	0.575	0.410	0.544	0.509	0.510	0.241	0.276	0.046	88%
East/Southeast Asia & Middle East	1,574	0.636	0.620	0.621	0.622	0.612	0.555	0.629	0.085	98%
Europe	5,445	0.653	0.637	0.638	0.638	0.631	0.598	0.610	0.136	98%
Teacher pre-training coverage										
outside XLM-R pre-training	1,750	0.719	0.586	0.620	0.501	0.495	0.346	0.457	0.086	70%
in XLM-R pre-training	10,994	0.609	0.549	0.585	0.576	0.572	0.471	0.503	0.096	95%
Site diversity										
diverse ($\geq$10)	5,225	0.657	0.642	0.643	0.642	0.637	0.601	0.616	0.134	98%
single publisher ($<$3)	6,204	0.517	0.387	0.475	0.433	0.435	0.224	0.287	0.045	84%
medium (3–10)	1,315	0.559	0.556	0.539	0.543	0.532	0.503	0.533	0.089	97%




FIGURE 3. Left: StaticKD accuracy against teacher accuracy per test language (color shows the distillation data of the language, size the number of articles). Right: held-out agreement per language against the amount of distillation data for StaticKD and fastText + KD.

TABLE 10. Cascade StaticKD $\rightarrow$ ONNX Int8 Teacher on the Test Set (Effective Single-Core Throughput)

θ	StaticKD share	Accuracy on share	Macro-F1	Accuracy	doc/s
0 (StaticKD only)	100.0%	0.641	0.545	0.641	539
0.5	80.8%	0.732	0.586	0.690	4.09
0.6	74.0%	0.760	0.593	0.697	3.02
0.7	67.4%	0.788	0.600	0.702	2.41
0.8	60.3%	0.813	0.602	0.703	1.98
0.9	51.7%	0.839	0.602	0.703	1.63
Teacher only	0.0%	–	0.600	0.699	0.79

16 entries. Keeping only the 10% most specific tokens of each article leaves the test macro-F1 almost unchanged (0.543 with about 58 tokens per article against 0.545 with all tokens). A random 10% of the tokens gives only 0.435.

E. CALIBRATION AND CASCADE MODE

The ECE of StaticKD is lower than that of the teacher. It is 0.041 on the development set and 0.139 on the test set against 0.090 and 0.245 for the teacher. The test set lies outside the training distribution, and both models become overconfident there (Fig. S7 in the supplementary material). The cascade mode in Table 10 lets StaticKD decide articles with a confidence of at least θ and passes the rest to the teacher. StaticKD decides 60.3% of the articles at $\theta = 0.8$ with an accuracy of 0.813. The cascade reaches an overall accuracy of 0.703 and a macro-F1 of 0.602 against 0.699 and 0.600 for the teacher alone. Its effective throughput is 1.98 articles per second per core and 2.5 times that of the teacher (0.79).

VII. DISCUSSION

A. WHAT A TOKEN TABLE RETAINS

The results in Sections VI-A and VI-B show that a table lookup keeps about nine tenths of the teacher macro-F1. The lookup cuts inference time by about three orders of magnitude. The finding agrees with [14], which showed that order-free representations are already competitive for topic classification. The token analysis in Section VI-D explains why a table suffices. Almost all of the topic signal in an

article is carried by a small share of topic-specific tokens. The remaining gap to the teacher lies in a few labels and in languages that are underrepresented in the distillation data (Table 9). StaticKD falls furthest behind the teacher on *environment*, *religion*, and *arts* (Fig. S6 in the supplementary material). The lowest StaticKD scores occur on a different set of labels: *society*, *disaster*, *human interest*, and *conflict*. The teacher also finds these labels among the hardest. *Society* and *human interest* are known to be difficult even for human annotators [2]. The low scores on these labels are therefore not specific to the student.

Both transformers learn from the same distillation data, but only MiniLM-L6 closes part of the gap to the teacher (Table 5). The two models have different origins: MiniLM comes from a distillation of XLM-R-large and DistilmBERT from mBERT. The contrast points to the quality of the initial multilingual representation because both students have six layers. Both models run 32 to 107 times slower than StaticKD on one core.

The Model2Vec classifier reaches the same test macro-F1 as StaticKD within the equivalence margin of ± 0.01. It starts from the same potion embeddings and learns from the top teacher label on the same data. It also learns a weight for each token and adds a hidden layer of 512 units. The ablations in Section VI-C show no gain from these extras either. Hard labels are equivalent to soft labels in test macro-F1, and the MLP head gives no significant gain there. The accuracy of both models likely comes mainly from the shared embeddings and the teacher-labeled data rather than from the head. The two models run at a similar speed but differ in deployed form. StaticKD folds into one table of 34 MB that needs only `numpy` and `tokenizers`. The Model2Vec classifier keeps the full embeddings and its MLP in a 507-MB file and needs about twice the RAM of StaticKD (Table 6).

B. WHERE THE ACCURACY COMES FROM

The ablations of RQ3 show where the knowledge of the student comes from. The largest contribution comes from the pre-trained multilingual initialization. Random initialization costs 0.120 in test macro-F1, whereas removing the multilingual data costs 0.051. The multilingual distillation data labeled by the teacher make the second-largest contribution. Sparse Distillation [23] also relies on a large amount of teacher-labeled text. The most direct evidence for the role of the initialization comes from the compact variant. Some Indian languages such as bn, pa, and or (Odia) hardly occur in the distillation data. Most token occurrences in these languages come from tokens seen fewer than 10 times in the distillation data. The embeddings of these tokens stay close to the potion values because training rarely or never updates such embeddings. The mean accuracy of StaticKD in these languages is still 0.624, but it falls to 0.013 once the compact tokenizer removes these tokens. Transfer to languages without data therefore relies on embeddings that training hardly changes. Such embeddings lie in the same space as the trained ones, so the linear head learned from data-rich languages still applies.

Freezing the embeddings raises the mean scores of languages with little or no distillation data (Table 8). Fine-tuning moves the embeddings of tokens from the training languages and fits the model better to these languages. Frozen embeddings give a lower development score for this reason. Tokens from other languages stay at the positions assigned by potion. The head of the model has adapted to the moved embeddings, so these tokens fit it less well. The final recipe still uses fine-tuning because it was selected on a development set in the training languages. Such a development set cannot reveal this effect. Freezing gives no significant gain on the whole test set but is worth testing for a deployment that targets languages without distillation data.

Soft labels, by contrast, add little or nothing. Hard teacher labels are equivalent to soft labels at $\tau = 1$ within ± 0.01 macro-F1, and no higher temperature improves on $\tau = 1$ (Section VI-C). The pattern fits the literature on the capacity gap [25], [28]. A possible explanation is that one linear layer over averaged embeddings cannot represent the inter-class structure in the tail of the teacher distribution (dark knowledge) [27]. A high τ asks the student to imitate a distribution shape beyond its capacity.

C. WEAK LANGUAGES AND MODEL SELECTION

Per-language performance rises with how well a language is represented in the distillation data and the pre-training data. Held-out agreement does not differ significantly across scripts (Kruskal–Wallis $p = 0.067$). The weakest results appear in African languages outside XLM-R pre-training that are also absent from the distillation data: ig, lg, ln, pcm, rn, sn, ti, and yo. The teacher still reaches an accuracy of 0.643 on these languages, perhaps thanks to subwords shared with other languages and to sentence context. StaticKD reaches only 0.407. The cheapest fix requires no change of architecture. News in these languages can be labeled by the teacher and added to the distillation data. Adding such news is supported by the data ablation and by the correlation between the accuracy gap and the amount of data ($\rho = 0.52$).

Agreement with the teacher does not always predict accuracy on editorial labels. Cutting the data to 130 thousand documents lowers the agreement by 0.009 ($p < 0.001$) but leaves the test macro-F1 equivalent to that of the final recipe. The frozen-embedding variant scores 0.020 lower in held-out agreement but 0.014 higher in test macro-F1, although this test gain is not significant. Student selection should not rely on agreement with the teacher alone. It should use labels that do not come from the teacher and a development set outside the training distribution, in line with [29].

Test scores should be read with the nature of the labels in mind. An article about a criminal case that involves an athlete can rightly sit in a sports section, while a model labels it *crime*. IPTC allows several topics per article, so both answers are plausible. Comparisons between models remain fair because all models are scored against the same labels.

D. PRACTICAL IMPLICATIONS

Sparse Distillation [23] uses an n-gram table trained from scratch. StaticKD replaces it with pre-trained multilingual embeddings folded into 17 logits per token. The replacement makes the model smaller and lets it transfer to languages that are missing from the distillation data.

Inference is a recurring cost in a news pipeline because every incoming article has to be classified. StaticKD suits a real-time pipeline on servers without a GPU. Its output probabilities are better calibrated than those of the teacher, with a test ECE of 0.139 against 0.245. The better calibration makes a cascade mode possible. Such a cascade suits batch jobs that need teacher-level accuracy. The compact variant lowers RAM, but it is only advisable when all target languages are already covered by the distillation data.

E. LIMITATIONS

Section labels from JSON-LD cover 47.5% of the test articles and publisher categories 20.4%. Section conventions differ from one publisher to another. A section also reflects one editorial view of an article that may cover several topics at once. The mapping table was built conservatively, validated against the IPTC tree, and reviewed by two researchers in a joint session. A joint review gives no measure of agreement between reviewers. The articles themselves were not re-annotated by humans. Absolute scores on these labels therefore measure agreement with the way publishers categorize articles. The limitation holds especially for labels with unclear boundaries, such as *society*, *human interest*, and *lifestyle*.

MasakhaNEWS labels were assigned by human annotators under a non-IPTC scheme and then mapped to IPTC. Direct annotation with IPTC topics exists only in MN-DS, which is entirely in English. The multilingual IPTC test set of Kuzman and Ljubešić [2] is not public.

The number of labels that occur in each language is uneven. The median is 7 labels per language, and the African languages cover only four or five broad topics. Per-language scores cannot be compared directly between languages with different label coverage because macro-F1 is computed over the labels present. Publisher diversity is also limited. Twenty-seven languages come from practically one publisher: BBC/VOA for the African languages, L3Cube for the Indian languages, and a single site for several CC-NEWS languages. Claims about these languages hold only for those publishers. The site-cluster bootstrap widens the confidence intervals of these languages accordingly. All test-set intervals rest on a small number of independent sources because the whole test set has an effective number of only 13.8 clusters.

The teacher bounds the performance of the student from above and passes its errors and biases to the student. The held-out set measures agreement with the teacher, not correctness.

The tuning budget was not equal across models. The StaticKD recipe was fixed on the development set before the test set was built. The fastText and TF-IDF baselines were tuned on the same set with small grids. The Model2Vec classifier used the library defaults. The transformers followed a standard fine-tuning recipe in which only τ of MiniLM-L6 was searched. Sparse Distillation [23] was not run as a baseline. It differs from fastText + KD and from the random-initialization ablation in the hidden layers of its deep averaging network, its soft-logit targets, and its billion-parameter n-gram table designed for English. MiniLM-L6 and DistilmBERT read at most 256 tokens in the main comparison. The limit leaves both models less than half of the text of most test articles. Retraining both with 512 tokens raises the test macro-F1 by 0.014 and 0.012 without changing the outcome of the comparison with StaticKD (Section VI-A).

The whole benchmark ran on one machine in three sessions whose single-core throughput deviated from the median by at most 7%. Latency of the teacher and the transformers was measured on only 100 documents. Absolute numbers will differ on a server but ratios between models measured under the same protocol remain informative.

StaticKD reaches a mean accuracy of only 0.407 on African languages that are absent from both the distillation data and the pre-training data (Section VII). A topic filter based on this model could misclassify or drop news in these languages more often. Accuracy should be monitored per language during deployment. Articles with low confidence should be routed to the teacher through the cascade mode.

The scope of this study is limited to top-level IPTC labels and single-label classification. Labels at deeper levels and multi-topic articles have not been tested.

VIII. CONCLUSION

The open multilingual IPTC classifier needs 1.2 to 2.8 seconds per article on one CPU core. StaticKD distills this classifier into a table of 17 logits per token. The table is initialized from multilingual static embeddings and then trained on 285,999 teacher-labeled articles in 69 languages. The evaluation uses 12,744 test articles in 47 languages whose labels do not come from the teacher. StaticKD reaches a macro-F1 of 0.545 on this set (91.1% of the teacher score). It processes 539 articles per second per CPU core and is about 682 times faster than the ONNX int8 teacher. The 34-MB model also needs no deep learning library.

The accuracy of this small student comes mainly from multilingual distillation data and pre-trained multilingual embeddings. Soft labels are no better than hard labels. The Model2Vec classifier trained on the same teacher labels is equivalent to StaticKD in test macro-F1, but its file is 15 times larger. Frozen embeddings lower the development score and give higher mean scores in languages with little or no distillation data. The gain on the whole test set is not significant. StaticKD is weakest on languages that appear in neither the distillation data nor the pre-training data of the teacher. Its hardest labels are *society*, *disaster*, *human interest*, and *conflict*. The test set of this study can be reused to evaluate other IPTC classifiers.

The distillation data should be extended to the weak languages, especially the African languages outside XLM-R pre-training. Fine-tuning could also use a regularizer that

keeps the embeddings close to the pre-trained space. Such a regularizer might give in-distribution accuracy and cross-lingual transfer at the same time. Tokenization takes 98% of the inference time of StaticKD. The next source of speed is therefore a faster tokenizer such as a direct word-to-table lookup. Vocabulary pruning has to keep the rare tokens that languages with little or no distillation data depend on. Several problems remain open: cheap non-linear heads with quantized embeddings, hierarchical classification down to IPTC level 2, multi-label classification, and human IPTC annotation of a multilingual sample of the test set.

CODE, MODEL, AND DATA AVAILABILITY

The code for this study is available at [TODO: GitHub URL and Zenodo DOI]. It covers data collection, test-set construction, teacher labeling, training, evaluation, and benchmarking. The same location provides a notebook that reproduces every number, table, and figure in this paper. The section-to-IPTC mapping table is also released with the code. The StaticKD models are available at [TODO: Hugging Face URL]. The test set is released as a manifest of article URLs or IDs, labels, label origins, and text hashes. A reconstruction script comes with the manifest. The article texts themselves are not redistributed because of publisher copyright and the licenses of the source datasets. EMMediaTopic is available from the CLARIN.SI repository [9]. Table S5 in the supplementary material lists the licenses of the assets used and released in this study.

ACKNOWLEDGMENT

The authors thank the Department of Informatics Engineering, Sepuluh Nopember Institute of Technology, for supporting this research. The authors used Claude Opus 5.5 (Anthropic) under their direction to explore design options for the method and to run the exploratory and final experiments. It also wrote the experiment code, processed data (including the first draft of the section-to-IPTC mapping table), and drafted parts of the manuscript text. The authors wrote and revised the manuscript themselves, reviewed and verified all code, data, and results, and take full responsibility for its content and claims.

REFERENCES

[1] International Press Telecommunications Council (IPTC), "Media topics – IPTC NewsCodes," [Online]. Available: https://iptc.org/standards/media-topics/, 2024.

[2] T. Kuzman and N. Ljubešić, "LLM teacher-student framework for text classification with no manually annotated data: A case study in IPTC news topic classification," *IEEE Access*, vol. 13, pp. 35 621–35 633, 2025.

[3] A. Conneau, K. Khandelwal, N. Goyal, V. Chaudhary, G. Wenzek, F. Guzmán, E. Grave, M. Ott, L. Zettlemoyer, and V. Stoyanov, "Unsupervised cross-lingual representation learning at scale," in *Proc. 58th Annu. Meeting Assoc. Comput. Linguistics (ACL)*, 2020, pp. 8440–8451.

[4] T. Kuzman Pungeršek, P. Rupnik, I. Porupski, V. Dinić, and N. Ljubešić, "State of the art in text classification for South Slavic languages: Fine-tuning or prompting?" in *Proc. Workshop Shaping Multilingual, Multimodal AI for the Social Sciences and Humanities (LLMs4SSH) at LREC 2026*, 2026, pp. 1–17.

[5] S. Luccioni, Y. Jernite, and E. Strubell, "Power hungry processing: Watts driving the cost of AI deployment?" in *Proc. ACM Conf. Fairness, Accountability, and Transparency (FAccT)*, 2024, pp. 85–99.

[6] V. Sanh, L. Debut, J. Chaumond, and T. Wolf, "DistilBERT, a distilled version of BERT: Smaller, faster, cheaper and lighter," arXiv:1910.01108 (NeurIPS 2019 EMC^2 Workshop), 2019.

[7] W. Wang, H. Bao, S. Huang, L. Dong, and F. Wei, "MiniLMv2: Multi-head self-attention relation distillation for compressing pretrained transformers," in *Findings Assoc. Comput. Linguistics: ACL-IJCNLP 2021*, 2021, pp. 2140–2151.

[8] A. Joulin, E. Grave, P. Bojanowski, and T. Mikolov, "Bag of tricks for efficient text classification," in *Proc. 15th Conf. European Chapter Assoc. Comput. Linguistics (EACL), Vol. 2: Short Papers*, 2017, pp. 427–431.

[9] T. Kuzman and N. Ljubešić, "News topic dataset EMMediaTopic 1.0," Slovenian language resource repository CLARIN.SI, http://hdl.handle.net/11356/1991, 2025.

[10] G. Hinton, O. Vinyals, and J. Dean, "Distilling the knowledge in a neural network," NIPS Deep Learning and Representation Learning Workshop, arXiv:1503.02531, 2015.

[11] S. Tulkens and T. van Dongen, "Model2Vec: Fast state-of-the-art static embeddings," Software, Zenodo, 2024, concept DOI (all versions); version 0.9.0 was used. [Online]. Available: https://github.com/MinishLab/model2vec.

[12] T. Wada, Y. Hirakawa, R. Shimizu, T. Kawashima, and Y. Saito, "Static word embeddings for sentence semantic representation," in *Proc. Conf. Empirical Methods Natural Language Process. (EMNLP)*, 2025, pp. 6195–6211.

[13] J. Chen, S. Xiao, P. Zhang, K. Luo, D. Lian, and Z. Liu, "M3-Embedding: Multi-linguality, multi-functionality, multi-granularity text embeddings through self-knowledge distillation," in *Findings Assoc. Comput. Linguistics: ACL 2024*, 2024, pp. 2318–2335.

[14] L. Galke and A. Scherp, "Bag-of-words vs. graph vs. sequence in text classification: Questioning the necessity of text-graphs and the surprising strength of a wide MLP," in *Proc. 60th Annu. Meeting Assoc. Comput. Linguistics (ACL), Vol. 1: Long Papers*, 2022, pp. 4038–4051.

[15] D. I. Adelani, H. Liu, X. Shen, N. Vassilyev, J. O. Alabi, Y. Mao, H. Gao, and E.-S. A. Lee, "SIB-200: A simple, inclusive, and big evaluation dataset for topic classification in 200+ languages and dialects," in *Proc. 18th Conf. European Chapter Assoc. Comput. Linguistics (EACL), Vol. 1: Long Papers*, 2024, pp. 226–245.

[16] R. V. Guha, D. Brickley, and S. Macbeth, "Schema.org: Evolution of structured data on the web," *Commun. ACM*, vol. 59, no. 2, pp. 44–51, 2016.

[17] D. I. Adelani, M. Masiak, I. A. Azime, J. Alabi, A. L. Tonja, C. Mwase, O. Ogundepo, B. F. P. Dossou, A. Oladipo, D. Nixdorf *et al.*, "MasakhaNEWS: News topic classification for African languages," in *Proc. 13th Int. Joint Conf. Natural Language Process. and 3rd Conf. Asia-Pacific Chapter Assoc. Comput. Linguistics (IJCNLP-AACL), Vol. 1: Long Papers*, 2023, pp. 144–159.

[18] A. Petukhova and N. Fachada, "MN-DS: A multilabeled news dataset for news articles hierarchical classification," *Data*, vol. 8, no. 5, p. 74, 2023.

[19] A. Mirashi, S. Sonavane, P. Lingayat, T. Padhiyar, and R. Joshi, "L3Cube-IndicNews: News-based short text and long document classification datasets in Indic languages," in *Proc. 20th Int. Conf. Natural Language Process. (ICON)*, 2023, pp. 442–449.

[20] T. Hossain, A.-R. Islam, M. H. K. Mehedi, A. A. Rasel, M. Abdullah-Al-Wadud, and J. Uddin, "BanglaNewsClassifier: A machine learning approach for news classification in Bangla newspapers using hybrid stacking classifiers," *PLOS ONE*, vol. 20, no. 6, p. e0321291, 2025.

[21] C. Yang, Y. Zhu, W. Lu, Y. Wang, Q. Chen, C. Gao, B. Yan, and Y. Chen, "Survey on knowledge distillation for large language models: Methods, evaluation, and application," *ACM Trans. Intell. Syst. Technol.*, vol. 16, no. 6, pp. 1–27, 2025.

[22] R. Piperno, L. Bacco, F. Dell'Orletta, M. Merone, and L. Pecchia, "Cross-lingual distillation for domain knowledge transfer with sentence transformers," *Knowledge-Based Systems*, vol. 311, p. 113079, 2025.

[23] Q. Ye, M. Khabsa, M. Lewis, S. Wang, X. Ren, and A. Jaech, "Sparse distillation: Speeding up text classification by using bigger student models," in *Proc. Conf. North American Chapter Assoc. Comput. Linguistics: Human Language Technologies (NAACL-HLT)*, 2022, pp. 2361–2375.

[24] M. Iyyer, V. Manjunatha, J. Boyd-Graber, and H. Daumé III, "Deep unordered composition rivals syntactic methods for text classification," in *Proc. 53rd Annu. Meeting Assoc. Comput. Linguistics and 7th Int. Joint*

Conf. Natural Language Process. (ACL-IJCNLP), Vol. 1: Long Papers, 2015, pp. 1681–1691.
[25] C. Zhang, Q. Li, D. Song, Z. Ye, Y. Gao, and Y. Hu, "Towards the law of capacity gap in distilling language models," in *Proc. 63rd Annu. Meeting Assoc. Comput. Linguistics (ACL), Vol. 1: Long Papers*, 2025, pp. 22 504–22 528.
[26] Z. Li, X. Li, L. Yang, B. Zhao, R. Song, L. Luo, J. Li, and J. Yang, "Curriculum temperature for knowledge distillation," in *Proc. AAAI Conf. Artif. Intell.*, vol. 37, no. 2, 2023, pp. 1504–1512.
[27] B. Zhao, Q. Cui, R. Song, Y. Qiu, and J. Liang, "Decoupled knowledge distillation," in *Proc. IEEE/CVF Conf. Comput. Vis. Pattern Recognit. (CVPR)*, 2022, pp. 11 943–11 952.
[28] Y. Wang, W. Niu, X. Yao, L. You, and W. Fei, "Rethinking the dark knowledge and Kullback-Leibler divergence loss in knowledge distillation under capacity mismatching," in *Proc. AAAI Conf. Artif. Intell.*, vol. 40, no. 31, 2026, pp. 26 688–26 696.
[29] S. Stanton, P. Izmailov, P. Kirichenko, A. A. Alemi, and A. G. Wilson, "Does knowledge distillation really work?" in *Advances in Neural Information Processing Systems (NeurIPS)*, vol. 34, 2021, pp. 6906–6919.
[30] M. Treviso, J.-U. Lee, T. Ji, B. van Aken, Q. Cao, M. R. Ciosici, M. Hassid, K. Heafield, S. Hooker, C. Raffel, P. H. Martins, A. F. T. Martins, J. Z. Forde, P. Milder, E. Simpson, N. Slonim, J. Dodge, E. Strubell, N. Balasubramanian, L. Derczynski, I. Gurevych, and R. Schwartz, "Efficient methods for natural language processing: A survey," *Trans. Assoc. Comput. Linguistics*, vol. 11, pp. 826–860, 2023.
[31] A. Z. Broder, "On the resemblance and containment of documents," in *Proc. Compression and Complexity of SEQUENCES*, 1997, pp. 21–29.
[32] K. Lee, D. Ippolito, A. Nystrom, C. Zhang, D. Eck, C. Callison-Burch, and N. Carlini, "Deduplicating training data makes language models better," in *Proc. 60th Annu. Meeting Assoc. Comput. Linguistics (ACL), Vol. 1: Long Papers*, 2022, pp. 8424–8445.
[33] P. Koehn, "Statistical significance tests for machine translation evaluation," in *Proc. Conf. Empirical Methods Natural Language Process. (EMNLP)*, 2004, pp. 388–395.
[34] R. Dror, G. Baumer, S. Shlomov, and R. Reichart, "The hitchhiker's guide to testing statistical significance in natural language processing," in *Proc. 56th Annu. Meeting Assoc. Comput. Linguistics (ACL), Vol. 1: Long Papers*, 2018, pp. 1383–1392.
[35] C. A. Field and A. H. Welsh, "Bootstrapping clustered data," *J. Roy. Statist. Soc. B*, vol. 69, no. 3, pp. 369–390, 2007.
[36] CloverSearch, "cc-news-mutlilingual: Common Crawl news split by language and year," Hugging Face Datasets. [Online]. Available: https://huggingface.co/datasets/CloverSearch/cc-news-mutlilingual.
[37] Common Crawl Foundation, "CC-NEWS: News crawl archive," https://commoncrawl.org/blog/news-dataset-available, WARC files 2024-01 to 2026-08, accessed Sep. 2026, 2026.
[38] A. Barbaresi, "Trafilatura: A web scraping library and command-line tool for text discovery and extraction," in *Proc. 59th Annu. Meeting Assoc. Comput. Linguistics and 11th Int. Joint Conf. Natural Lang. Process.: System Demonstrations*, 2021, pp. 122–131.
[39] Jakarta Artificial Intelligence Research, "IndoNews: Indonesian news topic classification dataset (liputan6)," Hugging Face dataset `jakartaresearch/indonews`, 2021.
[40] Q. McNemar, "Note on the sampling error of the difference between correlated proportions or percentages," *Psychometrika*, vol. 12, no. 2, pp. 153–157, 1947.
[41] S. Holm, "A simple sequentially rejective multiple test procedure," *Scand. J. Statist.*, vol. 6, no. 2, pp. 65–70, 1979.
[42] D. J. Schuirmann, "A comparison of the two one-sided tests procedure and the power approach for assessing the equivalence of average bioavailability," *J. Pharmacokinetics Biopharmaceutics*, vol. 15, no. 6, pp. 657–680, 1987.
[43] C. Guo, G. Pleiss, Y. Sun, and K. Q. Weinberger, "On calibration of modern neural networks," in *Proc. 34th Int. Conf. Mach. Learn. (ICML)*, ser. Proc. Mach. Learn. Res., vol. 70, 2017, pp. 1321–1330.

OBI KASTANYA [TODO: author biography]

ANANTA DWI PRAYOGA ALWY [TODO: author biography]