Supplementary Material for "StaticKD: Distilling a Multilingual IPTC News Topic Classifier into a Static Token-Logit Table for Lightweight CPU Inference"

Obi Kastanya and Ananta Dwi Prayoga Alwy

This document contains the algorithm, tables, and figures that the main text refers to as Algorithm S1, Table S1–S4, and Fig. S1–S7.

Algorithm S1 StaticKD Inference for One Article

Require: article text d; tokenizer; table $\bar{T} \in \mathbb{R}^{|V| \times 17}$; bias $\bar{\mathbf{b}} \in \mathbb{R}^{17}$

1: $(t_1, \ldots, t_n) \leftarrow$ first 1,024 tokens of tokenize(d), without unknown tokens

2: $\mathbf{z} \leftarrow \frac{1}{n} \sum_{i=1}^{n} \bar{T}_{t_i} + \bar{\mathbf{b}}$ ▷ look up and average table rows

3: **return** $\arg\max_y z_y$ ▷ one of the 17 IPTC topics

TABLE S1
HYPERPARAMETERS OF ALL MODELS

Component	Value
StaticKD	
initial embedding	potion-multilingual-128M (500,353 × 256)
max. tokens / vector dropout	1,024 / 0.1
loss, τ	KL, $\tau = 1$
token dropout	0.2
optimizer embedding / head	SparseAdam 10^{-3} / AdamW $3 \cdot 10^{-3}$, wd 10^{-4}
batch, epoch, validation	64, 6, 3% of data (selects the epoch)
ensemble	mean of 3 seed tables
fastText	
word tokens (fixed)	dim 100, lr 0.5, 15 epoch
subword tokens (fixed)	dim 100, lr 0.5, 15 epoch
GPT-4o labels	dim 100, lr 0.5, 25 epoch
word n-grams, loss	2, softmax, 2M buckets
tokens	words (+ character 2–5-grams) or XLM-R subwords
quantization	`quantize`, cutoff 300k, retrain
TF-IDF + SVM	
features	XLM-R subword uni+bigrams, min. df 3, max. 1,000,000, sublinear tf
classifier (fixed)	LinearSVC, $C = 0.50$
MiniLM-L6 / DistilmBERT + KD	
optimizer	AdamW $5 \cdot 10^{-5}$, wd 0.01, warmup 6%, linear, fp16
batch, epoch, max. tokens	32, 2, 256
τ	$\{1, 2\}$, chosen on dev

TABLE S2
TEST MACRO-F1 BY SOURCE OF THE UNIFIED TEST SET. MN-DS IS THE ONLY SOURCE ANNOTATED DIRECTLY WITH IPTC TOPICS. MASAKHANEWS IS HUMAN-ANNOTATED UNDER ITS OWN SCHEME. LAST COLUMN: STATICKD AS A PERCENTAGE OF THE TEACHER

Source	Label origin	n	Lang.	Teacher	DistilmBERT	MiniLM	**StaticKD**	fastText (q)	TF-IDF+SVM	% teacher
CC-NEWS 2024–2026	JSON-LD section	6,050	29	0.651	0.629	0.634	0.624	0.579	0.609	96%
MasakhaNEWS [1]	human annotation	3,339	16	0.695	0.545	0.582	0.556	0.341	0.434	80%
L3Cube-IndicNews [2]	publisher category	2,361	10	0.709	0.501	0.680	0.639	0.328	0.342	90%
MN-DS [3]	human annotation	755	1	0.549	0.546	0.535	0.535	0.493	0.461	97%
Bangla news [4]	publisher category	139	1	0.835	0.730	0.817	0.748	0.150	0.010	90%
IndoNews	publisher category	100	1	0.885	0.846	0.856	0.862	0.852	0.873	97%




Fig. S1. Articles in the unified test set per language and label (at most 50 per language–label pair). The label origin in brackets is the dominant one for that language.

TABLE S3
FACTORS BEHIND PER-LANGUAGE PERFORMANCE

Test	Statistic	p
Spearman: agreement vs log(distillation data)	$\rho = 0.31$	0.022
Spearman: agreement vs number of training sites	$\rho = 0.29$	0.033
Spearman: agreement vs teacher confidence	$\rho = 0.71$	<0.001
Kruskal–Wallis: across scripts	$H = 10.37$	0.065
Spearman (test): accuracy gap vs log(data)	$\rho = 0.52$	<0.001
Spearman (test): StaticKD accuracy vs token coverage	$\rho = 0.50$	<0.001
Spearman (test): accuracy gap vs token coverage	$\rho = 0.49$	<0.001

TABLE S4
LICENSES OF THE ASSETS USED AND RELEASED

Asset	License
Teacher `classla/multilingual-IPTC-news-topic-classifier`	CC BY-SA 4.0
Embeddings `minishlab/potion-multilingual-128M`	MIT
MasakhaNEWS	CC BY-NC 4.0
MN-DS, L3Cube-IndicNews, IndoNews	CC BY 4.0
Bangla news [4]	not stated on the dataset card
EMMediaTopic 1.0	CC BY-SA 4.0
CC-News 2019–2021, CC-NEWS 2024–2026	Common Crawl terms of use
StaticKD code (release)	MIT
StaticKD models (release)	CC BY-SA 4.0 (inherited from the teacher)
Test-set manifest (release)	CC BY-SA 4.0




Fig. S2. Latency per article, model RAM, and file size (log scale).




Fig. S3. Effect of the distillation temperature. Each dot is one seed. The line connects the means.




Fig. S4. Effect of the table ensemble size (mean ± standard deviation over seed combinations).




Fig. S5. Test macro-F1 by label origin (left) and by the amount of distillation data in the language of the article (right).




Fig. S6. F1 per label on the test set (left) and the StaticKD confusion matrix normalized per reference label (right).




Fig. S7. Reliability diagram of StaticKD on the development and test sets.

REFERENCES

[1] D. I. Adelani, M. Masiak, I. A. Azime, J. Alabi, A. L. Tonja, C. Mwase, O. Ogundepo, B. F. P. Dossou, A. Oladipo, D. Nixdorf *et al.*, "MasakhaNEWS: News topic classification for African languages," in *Proc. 13th Int. Joint Conf. Natural Language Process. and 3rd Conf. Asia-Pacific Chapter Assoc. Comput. Linguistics (IJCNLP-AACL), Vol. 1: Long Papers*, 2023, pp. 144–159.

[2] A. Mirashi, S. Sonavane, P. Lingayat, T. Padhiyar, and R. Joshi, "L3Cube-IndicNews: News-based short text and long document classification datasets in Indic languages," in *Proc. 20th Int. Conf. Natural Language Process. (ICON)*, 2023, pp. 442–449.

[3] A. Petukhova and N. Fachada, "MN-DS: A multilabeled news dataset for news articles hierarchical classification," *Data*, vol. 8, no. 5, p. 74, 2023.

[4] T. Hossain, A.-R. Islam, M. H. K. Mehedi, A. A. Rasel, M. Abdullah-Al-Wadud, and J. Uddin, "BanglaNewsClassifier: A machine learning approach for news classification in Bangla newspapers using hybrid stacking classifiers," *PLOS ONE*, vol. 20, no. 6, p. e0321291, 2025.