

JAVATM PROGRAMMING

Chapter 4: More Object Concepts





Objectives

- Understand blocks and scope
- Overload a method
- Avoid ambiguity
- Create and call constructors with parameters
- Use the `this` reference



Objectives (cont'd.)

- Use static fields
- Use automatically imported, prewritten constants and methods
- Use composition and nest classes



Understanding Blocks and Scope

- **Blocks**
 - Use opening and closing curly braces
 - Can exist entirely within another block or entirely outside of and separate from another block
 - Cannot overlap
 - Types:
 - **Outside block** (or **outer block**)
 - **Inside block** (or **inner block**)
 - **Nested** (contained entirely within the outside block)

Understanding Blocks and Scope (cont'd.)




Figure 4-1 A method with nested blocks

Understanding Blocks and Scope (cont'd.)

- Scope
 - The portion of a program within which you can refer to a variable
 - **Comes into scope**
 - Variable comes into existence
 - **Goes out of scope**
 - Variable ceases to exist



Understanding Blocks and Scope (cont'd.)

- **Redeclare the variable**
 - You cannot declare the same variable name more than once within a block
 - An illegal action

Understanding Blocks and Scope (cont'd.)

```
public static void invalidRedeclarationMethod()
{
    int aValue = 35;
    int aValue = 44;
    {
        int anotherValue = 0;
        int aValue = 10;
    }
}
```

Invalid redeclaration of aValue because it is in the same block as the first declaration

Invalid redeclaration of aValue; even though this is a new block, this block is inside the first block

Figure 4-5 The `invalidRedeclarationMethod()`

Understanding Blocks and Scope (cont'd.)

- **Override**

- Occurs when you use the variable's name within the method in which it is declared
 - The variable takes precedence over any other variable with the same name in another method
- **Shadowing:** locally declared variables always mask or hide other variables with the same name elsewhere in the class

Understanding Blocks and Scope (cont'd.)

```
public class OverridingVariable
{
    public static void main(String[] args)
    {
        int aNumber = 10;
        System.out.println("In main(), aNumber is " + aNumber);
        firstMethod();
        System.out.println("Back in main(), aNumber is " + aNumber);
        secondMethod(aNumber);
        System.out.println("Back in main() again, aNumber is " + aNumber);
    }
    public static void firstMethod()
    {
        int aNumber = 77;
        System.out.println("In firstMethod(), aNumber is "
            + aNumber);
    }
    public static void secondMethod(int aNumber)
    {
        System.out.println("In secondMethod(), at first " +
            "aNumber is " + aNumber);
        aNumber = 862;
        System.out.println("In secondMethod(), after an assignment " +
            "aNumber is " + aNumber);
    }
}
```

aNumber is declared in main().

Whenever aNumber is used in main(), it retains its value of 10.

This aNumber resides at a different memory address from the one in main(). It is declared locally in this method.

This aNumber also resides at a different memory address from the one in main(). It is declared locally in this method.

Figure 4-6 The OverridingVariable class

Understanding Blocks and Scope (cont'd.)



```
C:\Java>java OverridingVariable
In main(), aNumber is 10
In firstMethod(), aNumber is 77
Back in main(), aNumber is 10
In secondMethod(), at first aNumber is 10
In secondMethod(), after an assignment aNumber is 862
Back in main() again, aNumber is 10
C:\Java>
```

Figure 4-7 Output of the OverridingVariable application



Overloading a Method

- **Overloading**
 - Using one term to indicate diverse meanings
 - Writing multiple methods with the same name but with different arguments
 - The compiler understands the meaning based on the arguments used with the method call
 - It is convenient for programmers to use one reasonable name
 - For tasks that are functionally identical
 - Except for argument types

Overloading a Method (cont'd.)

```
public static void calculateInterest(double bal, double rate)
{
    double interest;
    interest = bal * rate;
    System.out.println("Simple interest on $" + bal +
        " at " + rate + "% rate is " + interest);
}
```

Figure 4-12 The calculateInterest() method with two double parameters

Automatic Type Promotion in Method Calls

- If an application contains just one version of a method:
 - Call the method using a parameter of the correct data type or one that can be promoted to the correct data type
 - Order of promotion:
 - `double`, `float`, `long`, `int`

Automatic Type Promotion in Method Calls (cont'd.)

```
public static void simpleMethod(double d)
{
    System.out.println("Method receives double parameter");
}
```

Figure 4-14 The simpleMethod() method with a double parameter



Learning About Ambiguity

- **Ambiguous** situation
 - When the compiler cannot determine which method to use
- **Overload** methods
 - Correctly provide different parameter lists for methods with the same name
- **Illegal** methods
 - Methods with identical names that have identical argument lists but different return types

Creating and Calling Constructors with Parameters

- Java automatically provides a constructor method when class-created default constructors do not require parameters
- Writing your own constructor method:
 - Ensures that fields within classes are initialized to appropriate default values
 - Constructors can receive parameters
 - Used for initialization purposes

Creating and Calling Constructors with Parameters (cont'd.)

- When you write a constructor for a class, you no longer receive the automatically provided default constructor
- If a class's only constructor requires an argument, you must provide an argument for every object of the class



Overloading Constructors

- Use constructor parameters to initialize field values, or any other purpose
- If constructor parameter lists differ, there is no ambiguity about which constructor method to call

Overloading Constructors (cont'd.)


```
public class Employee
{
    private int empNum;
    Employee(int num)
    {
        empNum = num;
    }
    Employee()
    {
        empNum = 999;
    }
}
```

Figure 4-22 The Employee class that contains two constructors




Learning About the `this` Reference

- Instantiating an object from a class
 - Memory is reserved for each instance field in the class
 - It is not necessary to store a separate copy of each variable and method for each instantiation of a class
- In Java:
 - One copy of each method in a class is stored
 - All instantiated objects can use one copy



Learning About the `this` Reference (cont'd.)

- **Reference**
 - An object's memory address
 - Implicit
 - Automatically understood without actually being written



Learning About the `this` Reference (cont'd.)

- **`this` reference**
 - The reference to an object
 - Passed to any object's nonstatic class method
 - A reserved word in Java
- You do not need to use the `this` reference in methods you write in most situations

Learning About the `this` Reference (cont'd.)





Figure 4-24 Two versions of the `getEmpNum()` method, with and without an explicit `this` reference



Learning About the `this` Reference (cont'd.)

- **`this` reference** (cont'd.)
 - Implicitly received by instance methods
 - Use to make classes work correctly
 - When used with a field name in a class method, the reference is to the class field instead of to the local variable declared within the method

Using the `this` Reference to Make Overloaded Constructors More Efficient

- Avoid repetition within constructors
- Constructor calls other constructor
 - `this()`
 - More efficient and less error-prone

```

public class Student
{
    private int stuNum;
    private double gpa;
    Student(int num, double avg)
    {
        stuNum = num;
        gpa = avg;
    }
    Student(double avg)
    {
        stuNum = 999;
        gpa = avg;
    }
    Student(int num)
    {
        stuNum = num;
        gpa = 0.0;
    }
    Student()
    {
        stuNum = 999;
        gpa = 0.0;
    }
}

```

Each constructor contains similar statements.

Figure 4-30 Student class with four constructors

```

public class Student
{
    private int stuNum;
    private double gpa;
    Student(int num, double avg)
    {
        stuNum = num;
        gpa = avg;
    }
    Student(double avg)
    {
        this(999, avg);
    }
    Student(int num)
    {
        this(num, 0.0);
    }
    Student()
    {
        this(999, 0.0);
    }
}

```

Each of these calls to this() calls the two-parameter version of the constructor.

Figure 4-31 The Student class using this in three of four constructors



Using `static` Fields

- **Class methods**
 - Do not have the `this` reference
 - Have no object associated with them
- **Class variables**
 - Shared by every instantiation of a class
 - Only one copy of a `static` class variable per class



Using Constant Fields

- Create named constants using the keyword `final`
 - Make its value unalterable after construction
- Can be set in the class constructor
 - After construction, you cannot change the `final` field's value

Using Constant Fields (cont'd.)

```
public class Student
{
    private static final int SCHOOL_ID = 12345;
    private int stuNum;
    private double gpa;
    public Student(int stuNum, double gpa)
    {
        this.stuNum = stuNum;
        this.gpa = gpa;
    }
    public void showStudent()
    {
        System.out.println("Student #" + stuNum +
            " gpa is " + gpa);
    }
}
```

Figure 4-35 The Student class containing a symbolic constant



Using Automatically Imported, Prewritten Constants and Methods

- Many classes are commonly used by a wide variety of programmers
- **Package or library of classes**
 - A folder that provides a convenient grouping for classes
 - Many contain classes available only if they are explicitly named within a program
 - Some classes are available automatically

Using Automatically Imported, Prewritten Constants and Methods (cont'd.)

- **java.lang** package
 - Implicitly imported into every Java program
 - The only automatically imported, named package
 - The classes it contains are **fundamental classes** (or basic classes)
- **Optional classes**
 - Must be explicitly named

Using Automatically Imported, Prewritten Constants and Methods (cont'd.)

- `java.lang.Math` class
 - Contains constants and methods used to perform common mathematical functions
 - No need to create an instance
 - Imported automatically
 - Cannot instantiate objects of type `Math`
 - The constructor for the `Math` class is private

Method	Value That the Method Returns
<code>abs(x)</code>	Absolute value of <code>x</code>
<code>acos(x)</code>	Arc cosine of <code>x</code>
<code>asin(x)</code>	Arc sine of <code>x</code>
<code>atan(x)</code>	Arc tangent of <code>x</code>
<code>atan2(x, y)</code>	Theta component of the polar coordinate (<code>r</code> , <code>theta</code>) that corresponds to the Cartesian coordinate <code>x</code> , <code>y</code>
<code>ceil(x)</code>	Smallest integral value not less than <code>x</code> (ceiling)
<code>cos(x)</code>	Cosine of <code>x</code>
<code>exp(x)</code>	Exponent, where <code>x</code> is the base of the natural logarithms
<code>floor(x)</code>	Largest integral value not greater than <code>x</code>
<code>log(x)</code>	Natural logarithm of <code>x</code>
<code>max(x, y)</code>	Larger of <code>x</code> and <code>y</code>
<code>min(x, y)</code>	Smaller of <code>x</code> and <code>y</code>
<code>pow(x, y)</code>	<code>x</code> raised to the <code>y</code> power
<code>random()</code>	Random <code>double</code> number between 0.0 and 1.0
<code>rint(x)</code>	Closest integer to <code>x</code> (<code>x</code> is a <code>double</code> , and the return value is expressed as a <code>double</code>)
<code>round(x)</code>	Closest integer to <code>x</code> (where <code>x</code> is a <code>float</code> or <code>double</code> , and the return value is an <code>int</code> or <code>long</code>)
<code>sin(x)</code>	Sine of <code>x</code>
<code>sqrt(x)</code>	Square root of <code>x</code>
<code>tan(x)</code>	Tangent of <code>x</code>

Table 4-1 Common Math class methods

Importing Classes That Are Not Imported Automatically

- Use prewritten classes
 - Use the entire path with the class name
 - Import the class
 - Import the package that contains the class

Importing Classes That Are Not Imported Automatically (cont'd.)

- **Wildcard symbol**
 - An alternative to importing the class
 - Import the entire package of classes
 - Asterisk wildcard
 - Can be replaced by any set of characters
 - Represents all classes in a package
 - There is no disadvantage to importing extra classes
 - Importing each class by name can be a form of documentation

Using the `LocalDate` Class

- `LocalDate` class
 - No time zone information included with this class (local date only)
 - Static methods `now()` and `of()`
 - Class constructors are non-public
 - Various methods provided to perform date arithmetic
- **Enumeration**
 - Data type that consists of a list of values, such as:
 - JANUARY, FEBRUARY, MARCH etc.

Using the LocalDate Class (cont'd.)

```
import java.time.*;
public class LocalDateDemo
{
    public static void main(String[] args)
    {
        LocalDate today = LocalDate.now();
        LocalDate graduationDate = LocalDate.of(2018, 5, 29);
        System.out.println("Today is " + today);
        System.out.println("Graduation is " + graduationDate);
    }
}
```

Figure 4-37 The LocalDateDemo application




Figure 4-38 Execution of the LocalDateDemo application

Using the LocalDate Class (cont'd.)

```
import java.time.*;
import java.util.Scanner;
public class DeliveryDate
{
    public static void main(String[] args)
    {
        Scanner input = new Scanner(System.in);
        LocalDate orderDate;
        int mo;
        int day;
        int year;
        final int WEEKS_FOR_DELIVERY = 2;
        System.out.print("Enter order month ");
        mo = input.nextInt();
        System.out.print("Enter order day ");
        day = input.nextInt();
        System.out.print("Enter order year ");
        year = input.nextInt();
        orderDate = LocalDate.of(year, mo, day);
        System.out.println("Order date is " + orderDate);
        System.out.println("Delivery date is " +
            orderDate.plusWeeks(WEEKS_FOR_DELIVERY));
    }
}
```

Figure 4-39 The DeliveryDate application

Understanding Composition and Nested Classes

- **Composition**
 - Describes the relationship between classes when an object of one class data field is within another class
 - Called a **has-a relationship**
 - Because one class “has an” instance of another
- Remember to supply values for a contained object if it has no default constructor

Understanding Composition and Nested Classes (cont'd.)




Figure 4-43 The School class



Nested Classes

- **Nested classes**
 - A class within another class
 - Stored together in one file
- Nested class types
 - **static member classes**
 - **Nonstatic member classes**
 - **Local classes**
 - **Anonymous classes**



You Do It

- Demonstrating Scope
- Overloading Methods
- Creating Overloaded Constructors
- Using the `this` Reference to Make Constructors More Efficient
- Using Static and Nonstatic `final` fields
- Using the Java Web Site



Don't Do It

- Don't try to use a variable that is out of scope
- Don't assume that a constant is still a constant when passed to a method's parameter
- Don't overload methods by giving them different return types
- Don't think that *default constructor* means only the automatically supplied version
- Don't forget to write a default constructor for a class that has other constructors



Summary

- Variable's scope
 - The portion of a program in which you can reference a variable
- Block
 - Code between a pair of curly braces
- Overloading
 - Writing multiple methods with the same name but different argument lists
- Store separate copies of data fields for each object
 - But just one copy of each method



Summary (cont'd.)

- `static` class variables
 - Shared by every instantiation of a class
- Prewritten classes
 - Stored in packages
- `import` statement
 - Notifies the Java program that class names refer to those within the imported class
- A class can contain other objects as data members
- You can create nested classes that are stored in the same file