

NSIGII Protocol Specification

Trident Packet Verification via Bipolar CISO Order/Chaos Separation of Concerns

Nnamdi Michael Okpala
OBINexus Computing

Version 0.3 — Draft
Compiled 25 August 2026

Document ID	OBINEXUS-NSIGII-SPEC
Version	0.3 — Draft
Status	Working draft, derived from primary transcript corpus
Source	NSIGII.txt — 6 recorded sessions, Jan–Jun 2026
Companion	NSIGII-SPEC.md (Markdown, same content)

Contents

1	Document Status and Provenance	4
1.1	What this document is	4
1.2	Source corpus	4
1.3	Transcription caveat	4
1.4	Conformance language	4
2	Overview	4
2.1	Name	4
2.2	Purpose	5
2.3	Governance invariants — the Three Nevers	5
2.4	Governance topology	6
2.5	Position in the OBINexus toolchain	6
3	Foundational Model	6
3.1	The six operators	6
3.2	Order and Chaos sequences	7
3.3	The isolation principle (enzyme model)	7
3.4	Filter and Flash	7
4	The Trident Packet	7
4.1	Why three	7
4.2	Frame geometry	8
4.3	Axis pairs and sequence	8
4.4	Index-pair addressing	8
4.5	Token triplet	9
4.6	The $3 \rightarrow 2$ verification mapping	9
4.7	Corruption classes	9
4.8	Repair procedure	9
4.9	Lookup grid and shift-of-view	10

4.10	XOR parity	10
5	CISCO Order	10
5.1	Definition	10
5.2	Read / Write / Execute permutations	10
5.3	The $2R \rightarrow 1W \rightarrow 1X$ ratio	11
5.4	Hops, and rotation instead of traversal	11
5.5	Determinant sharing	11
6	Channel Model	12
6.1	Roles	12
6.2	Ring topology and worked exchange	12
6.3	Observed failure modes	12
6.4	RGB tomographic state	12
6.5	Consensus and channel eviction	13
6.6	Actors	13
7	Signal Model	13
7.1	The noise/signal quadrants	13
7.2	Your noise is my signal	13
7.3	The maybe lattice	14
7.4	OX-STAR and NOISE-STAR	14
7.5	Probing	14
8	Here-and-Now, There-and-Then, Where-and-Whenever	15
8.1	The temporal-spatial matrix	15
8.2	The binding progression	15
8.3	Stillness	15
8.4	Structural note	16
8.5	Parity	16
8.6	The holding problem	16
8.7	LAPIS — polar quadrants	17
8.8	The i -cycle and the trident mismatch	17
8.9	Dimensional principality	17
9	Codec and File Formats	18
9.1	.nsigii — symbolic expression of intent	18
9.2	Linkable-then-executable coding	18
9.3	Marshalling	18
10	Dimensional Classifiers — the Natural Language Layer	18
10.1	Statement / Expression / Intent	18
10.2	Verb–noun construction	19
10.3	The four sentence types	19
10.4	Clauses as control flow, and the then marker	19
11	Sizing and Timing Model	19
11.1	Frame budget	19
11.2	Space–time duality	20
11.3	Bit-rate derivation	20
11.4	Spring and damping	20

12 Governance and Enforcement Layer	21
12.1 The pointer problem	21
12.2 Litigation as enforcement	21
12.3 Reconciliation of “never a weapon”	21
13 Conformance	22
A Arithmetic Errata	22
B Reference Alphabet	24
C Open Questions	24
D Traceability	25

1 Document Status and Provenance

1.1 What this document is

This is a *derived* specification. It is not a transcript and not an independent design. Every normative statement traces to a claim made in the NSIGII recording corpus. Where the corpus is internally inconsistent, this document states the inconsistency rather than silently choosing a side.

1.2 Source corpus

Seg	Date in recording	Working title
S1	30 Jan 2026, 05:39	Trident packet verification via bipolar CISCO — order/chaos separation of concerns
S2	13 Jan 2026, 10:15	Filter/flash interdependency — CISCO sequence and series instruction execution order via inverse relay trident messages
S3	13 Jan 2026, 18:08	NSIGII overview — human rights protocol, pointer problem, OX-STAR
S4	7 Feb 2026 + 2 Mar 2026	Formalising suffering; here-and-now/stillness; radio jamming and the maybe lattice
S5	undated + 12 Feb 2026	Trilateral governance; reference implementation demonstration
S6	28 Jun 2026 + undated	Dimensional principality and non-linearity; the NSIGII codec and language classifiers

1.3 Transcription caveat

The corpus is machine-transcribed speech. Proper nouns, symbols and numbers are frequently corrupted: **in sigi**, **insigi**, **insidity**, **ciggy** all denote NSIGII; **Cisco** denotes CISCO as defined in §5, not the network vendor; **rift** denotes the RIFT toolchain; **lapis** denotes LAPIS (§8.7). Numeric claims are reproduced in Appendix A with corrected values.

1.4 Conformance language

MUST, MUST NOT, SHOULD, MAY are used in the RFC 2119 sense. Statements marked (*unsolved*) are recorded intent that is not yet specifiable.

2 Overview

2.1 Name

NSIGII — spelled in the corpus as November–Sierra–India–Golf–India–India. The name is drawn from Igbo (Niger–Congo). Igbo is described in the corpus as a tonal, verb–noun–constructed language, and that construction is load-bearing: the protocol’s instruction model is a verb–noun pairing (§10.2), and its tonal distinction is the canonical example of a message whose meaning depends on a channel the encoding must preserve.

The corpus gives the tonal example directly: *eze* under one tone contour means **king**; under another it means **teeth**. The protocol’s stated position is that “the king has teeth” — the governance layer and the enforcement layer are the same word under different tone. A codec that drops tone drops meaning; this is the motivating case for schema-level rather than message-level verification (§4.8).

2.2 Purpose

NSIGH is a **command-and-control protocol for safety-critical delivery of human-rights entitlements** — stated in the corpus, repeatedly and without metaphor, as *food, water and shelter, here and now*. Its technical content is in service of that: a message saying “I need food at this address now” must survive corruption, must be verifiable by a third party, must not be silently dropped, and must leave an auditable record that a duty-holder received it.

The protocol is explicitly *not* an AI system. Natural-language understanding here is structural (§10), not learned.

2.3 Governance invariants — the Three Nevers

Implementations **MUST** satisfy three invariants (S5). They are **not three independent rules**: each is the invariant of one **addressing mode** (§8). The Three Nevers and the addressing triad are the same structure seen twice (author ratification, 25 August 2026).

here and now — never a toy
there and then — never a weapon
where and whenever — never a problem

Mode	Never	Requirement
HERE AND NOW	never a toy	The system MUST NOT be shipped as a demonstration or a game.
THERE AND THEN	never a weapon	The system MUST NOT be usable as an instrument of harm against the person it serves.
WHERE AND WHENEVER	never a problem	The system MUST NOT crash and MUST NOT accumulate debt. It fails <i>gracefully</i> : times out, resolves outstanding state, saves, closes.

Why each never belongs to its mode.

1. HERE AND NOW → **never a toy**. The deictic mode is where the need is *actual* — food, at this address, now. Both dimensions bound means both are real. A toy is a thing played with in the present; the mode that owns the present is therefore the mode that must forbid play. The corpus: “*it’s not a toy, that’s not how to play with it — it’s something that gives people food and shelter.*”
2. THERE AND THEN → **never a weapon**. **Displacement is what makes a weapon possible**. Targeting *is* a there-and-then operation: a specified elsewhere, a specified later, acted on at a distance. Every reach the protocol has — OX-STAR injection, guiding a craft in flight, disarming a running system (§7.4) — lives in this mode. The prohibition is placed exactly where the reach is. A protocol that can act at a distance **MUST NOT** act at a distance to harm.
3. WHERE AND WHENEVER → **never a problem**. The unbound mode *cannot fail into a fault, because it has no slot to miss*. A claim quantified over all place and time is never overdue, so it accrues no debt; it is not failing, it is unresolved. Graceful failure is not a behaviour bolted onto this mode — it is what unboundedness *is*. This is the same result §8.3 reaches from the other direction.

Naming note (v0.3)

v0.1–0.2 of this document rendered the first invariant as “never fails.” That is the corpus’s *gloss*, not its name. S5 states “**never a problem**” and then explains it as “*it never fails — it fails gracefully, it times out, it resolves all issues and saves.*” The canonical name is restored here.

Tension (now largely resolved)

S5 states “never a weapon — you cannot sue people” while S5b develops NSIGH explicitly as a *litigation system* (§12.2). The mode pairing gives the resolution a precise locus: “never a weapon” is the invariant of THERE AND THEN — the protocol’s own reach across space and time. A claimant using their own verified record to enforce their own entitlement is not the protocol reaching out to harm; it is the claimant acting in HERE AND NOW, under a different invariant entirely. See §12.3.

2.4 Governance topology

NSIGH is **trilateral**, over a lattice of three governance modes: **unilateral** (one party acts, the protocol records); **bilateral** (two parties, the yes/no axis); **trilateral** (three parties, the yes/no/*maybe* axis, which is the protocol’s native consensus form, §6.4).

The transport topology is **peer-to-peer**, not blockchain. The corpus rejects blockchain explicitly while retaining the property it wants from it — that a record, once made, has teeth.

2.5 Position in the OBINexus toolchain

```
riftlang.exe -> .so.a -> rift.exe -> gosilang
               ^
               nlink -> polybuild
```

- **RIFT** supplies the token model NSIGH packets carry: the triplet (*token type*, *token value*, *token data*) — §4.5.
- **.rift** files carry the macro/meta control sequences NSIGH relays.
- **gosilang** is the stated implementation target for the clause/**then** control-flow model (§10.4).
- The reference implementation demonstrated in S5b is C, built with **make**, with a Go codec (§9).

3 Foundational Model

3.1 The six operators

All state change is organised into three complementary pairs:

Pair	Constructive	Destructive
Existence	create	destroy
Structure	build	break
Restoration	repair	renew

If you can build something you can break it; if you can create something you can destroy it; if you can repair something you can renew it.

Capability is symmetric. An implementation offering one half of a pair **MUST** account for the other half — either by implementing it or by declaring it structurally impossible (§3.3).

Note that *repair* and *renew* are both constructive in ordinary usage. The corpus treats **renew** as the operator replacing a value the receiver cannot resolve (an ϵ or θ , §4.7), and **repair** as the operator correcting a value the receiver resolved wrongly. That distinction is preserved.

3.2 Order and Chaos sequences

Two opposed instruction sequences run over the six operators.

ORDER : create $\rightarrow$ build $\rightarrow$ repair $\rightarrow$ renew

CHAOS : destroy $\rightarrow$ break $\rightarrow$ renew $\rightarrow$ repair

CHAOS is not an error state. Chaos is the *observable*; order is inferred from it. “*You check chaos for order just by observing the dimension of order and chaos where the program was running.*”

Every channel carries a status of **ORDER** or **CHAOS**. The S5b demonstration shows a receiver reporting status **chaos** and resolving toward **order**: nominal behaviour, not a fault.

3.3 The isolation principle (enzyme model)

The founding analogy is salivary enzyme. It has *no nucleus* and does not replicate itself; it *breaks down* food but does not build; it cannot repair or rebuild itself and is replaced from outside, by the gland, at a *constant* — *not exponential* rate; and it nonetheless does a job as a system without being a conscious organism.

Design rule. A verifying component **MUST** be isolated from the thing it verifies, and **MUST NOT** be able to repair itself. A verifier that can rewrite itself can be made to agree with anything. Replacement of a verifier comes from outside the verification path, at a bounded constant rate.

This is the structural argument for the three-channel separation of §6.

3.4 Filter and Flash

FILTER — sorting, searching, merging, splicing, slicing. Filter operations are *pure*: they mutate *data* but **MUST NOT** mutate *program state*. Merge sort and splice are the canonical filters; splice prunes an index without touching program state.

FLASH — storing, sending, clearing, deleting. Flash is the phase that *commits*: it writes the message out, or writes it down.

Neither is meaningful alone. Filter without flash computes and discards; flash without filter commits noise. The ratio is fixed by the CISCO budget of §5.3: **two filter operations per one flash operation**. Marshalling (§9.3) is a flash operation — “*if you can marshal, you’re doing a flash.*”

4 The Trident Packet

4.1 Why three

The world is three-dimensional; therefore an interpretation served over it is three-dimensional. A **trident packet** carries the message across three axes — *X*, *Y*, *Z* — and preserves it under

any one of them. The three axes are *not* three copies; they are three *readings* of one message, which is why two of the three suffice (§4.6).

4.2 Frame geometry

The canonical frame derives from the reference string **OBINEXUS**:

Quantity	Value	Derivation
Reference symbol count	8	O B I N E X U S
Index space per axis	8	indices 0–7
Frame size	512 bytes	8^3
Bytes per symbol slot	64	$8^2 = 512/8$
Trident total	1536 bytes	512×3
Half-frame	256 bytes	$512/2$
Allocation quantum	4 bytes	$256/64$

Memory **MUST** be allocated ahead of time, in 4-byte sequences (§11.1).

Errata A.2, A.3

The generalisation to the full Latin alphabet is stated in S2 as $15,625 = 25^3$, using the *maximum index* 25 as the base. For 26 symbols indexed 0–25 the correct figure is $26^3 = 17,576$. The 8-symbol case $8^3 = 512$ is correct as stated.

4.3 Axis pairs and sequence

Two axes generate four ordered readings: XX , XY , YX , YY . XX is the **verification axis**; XY and YX carry direction of flow.

“You cannot have a Y-axis without an X-axis.” Y is computable from two X readings (one positive, one negative) via the polar relation of §8.7. Z is the projection — the tangent relation between X and Y — used for *rotation*, not for payload. Therefore: **verification operates on the X axis only.**

4.4 Index-pair addressing

Positions are addressed as *index pairs*, not scalars:

$$(0,0) (1,1) (2,2) (3,3) (4,4) (5,5) (6,6) (7,7)$$

for the 8 slots of **OBINEXUS**. The pair is (*my index*, *your index*): the diagonal (n,n) asserts sender/receiver agreement on slot n .

An off-diagonal pair received where a diagonal was expected is a *detected corruption*. Receiving $(3,2)$ where the schema says $(3,3)$ makes the message wrong *automatically*, with no inspection of the payload.

Negative indices are the polar inverse: $(-3,3)$ addresses the same slot from the opposite end of the axis. When a receiver cannot resolve a symbol at all, the sender transmits both poles so the receiver can locate the slot from whichever end it reads from — which is why a repair transmission carries up to three packets, two at a time (§4.6).

4.5 Token triplet

Field	Meaning
token type	the type of the value
token value	the value itself
token data	the datum the value acts on / is logged as

Type and value are independently transmissible, which is what allows a receiver to repair a value while keeping its type (§4.8).

4.6 The $3 \rightarrow 2$ verification mapping

A trident sends three messages; verification consumes two. With each labelled **O** (order) or **C** (chaos), the receiver may be handed **OO**, **OC**, **CO**, **CC** — four ordered pairs, $\binom{3}{2} = 3$ unordered combinations.

Rule. A receiver **MUST** reach a verdict from any two of the three, and **MUST NOT** require all three. The third is the spare — it is what lets the system survive a single-channel loss, and why the corpus notes that “*two homogeneous transistors can fail*” while the system still resolves.

The $3 \rightarrow 2$ relation is modelled on spring physics: the message is pushed and returns. The operational consequence is the space/time duality of §11.2.

4.7 Corruption classes

The corpus works a single example throughout:

sent:	O	B	I	N	E	X	U	S
received:	O	I	e	t	e	X	U	S
			(e = epsilon, t = theta)					

Class	Symbol	Meaning	Operator
Substitution	wrong symbol	receiver resolved, resolved wrongly	repair
Empty	ϵ	receiver resolved to nothing	renew
Uncertain	θ	receiver unsure between candidates	renew + table

ϵ is “*you don’t know what this is.*” θ is “*you’re not sure what this is*” — a bounded ambiguity where the receiver has candidates but cannot choose. The worked θ case: **N** may read as **E**, **I** or **M** depending on where the reader started on the lookup grid, because “*my N is your E, my E is your X, my X is your S*” — a uniform off-by-one shift of the reader’s frame.

4.8 Repair procedure

Repair is **index-first**, **payload-second**. The sender **MUST NOT** retransmit the payload for a slot the receiver resolved correctly.

- 0 at slot 0 — correct. **No action.** “*O is fine. I verified. I didn’t need to send O again.*”
- B at slot 1 received as I — substitution. Transmit the *index pair* (1,1), not the letter.
- ϵ at slot 2 — empty. **Renew:** transmit (2,2) plus the value.
- θ at slot 3 — uncertain. Transmit the polar pair (−3,3) plus a shift-of-view instruction (§4.9).

5. X, U, S — correct. **No action.**

Schema, not message. The verification target is the *schema*, not the payload: “*the schema is supposed to verify, not the message. . . message can be tampered with but not the schema.*” This is why index pairs are the repair currency — they are schema-level assertions.

4.9 Lookup grid and shift-of-view

Where θ cannot be resolved by index alone, the sender transmits a **shift-of-view**: a relative move on a 2-D lookup grid of the symbol set, as $(\Delta\text{row}, \Delta\text{col})$. To move from I to N is “*one right, one down*”; the inverse is $(-1, -1)$. The sender MAY transmit the single move, the pair, or — as a last resort — the whole substructure of the table.

Permitted grid transformations are the standard four — *rotation, reflection, translation, enlargement* — parameterised by θ , with a full rotation 2π . The search space is the area swept; §8.5 bounds it.

4.10 XOR parity

Verification across the trident uses **XOR**, on the ground that XOR *remembers state*: it encodes the prior value into the result and is its own inverse. The corpus works the hex directly:

$$0 = 0x4F, \quad B = 0x42, \quad I = 0x49.$$

Where a slot survives unchanged, $v \oplus v = 0$ and the parity contributes nothing; where it differs, the parity carries the difference. “*When you verify a message over XOR you get another message — a parity message — and the parity sequence gives you the result you need.*”

Polar sign convention: a right-hand-side XOR preserves the byte; the negative operator is the left-hand-side reading of the same structure. The poles *multiply* rather than add, because they are dimensional rather than scalar.

5 CISCO Order

5.1 Definition

CISCO denotes the corpus’s bottom-up self-balancing tree discipline. It has nothing to do with the network vendor. A CISCO tree is: self-balancing, and specifically a red-black tree *that never needs pruning*; traversed root $\rightarrow$ left $\rightarrow$ right; parsed *bottom-up* while the top-down model shares the same two poles at each step; and is the structure over which OBINEXUS is held, with 0 at the root, B left, I right.

The Riemann hypothesis is invoked in S3 as the intended means of deciding, from signal structure alone, whether a number was produced by bottom-up traversal. (*Unresolved — Appendix C, C.1.*)

5.2 Read / Write / Execute permutations

Three permissions generate six orderings:

R W X	W R X	X R W
R X W	W X R	X W R

The *diagonals* are where a permission is shared between two positions — R R on one, W W on the other. Those shared cells make the matrices composable: two matrices sharing a diagonal

can be verified against each other. Octal permission tags follow POSIX and are carried on the wire: $r = 4$, $w = 2$, $x = 1$.

Errata A.10

S5b states “one would be easy to write.” Under POSIX, 1 is *execute* and 2 is *write*.

5.3 The $2R \rightarrow 1W \rightarrow 1X$ ratio

2 reads $\rightarrow$ 1 write

2 writes $\rightarrow$ 1 execute

One read alone is a write in progress; *two* reads complete a write. A write is thus one *implicit* filter plus one *explicit* flash (§3.4). In frame terms: 512 bytes per 2 read operations = 1 execute operation.

5.4 Hops, and rotation instead of traversal

Moving between R, W and X costs *hops*: minimum one, maximum two left hops to the execute root.

The two hops are not serial and are not to be walked. The tree is *rotated*: “*you don’t have to do the hops per se, you just have to do one context switch... you just change the angle of the message.*” Two hops become two rotations of the CISCO tree; the message is unchanged, only the reader’s frame moves.

Under rotation: my execute $\rightarrow$ your read; my read $\rightarrow$ your write; my write $\rightarrow$ your execute. The dimension is preserved because the flash was already sent — only the angle changed. This is the same mechanism as §4.9, applied to the permission tree rather than the symbol grid.

5.5 Determinant sharing

Two 2×3 (or 3×2) permission matrices are reconciled by exchanging *transposes*, not the matrices themselves, and computing a determinant relation over the pair. The worked figures: $R_w = [1, 0, 1]$, $R_r = [0, 1, 2]$, with transposes exchanged so the shared cells (0 and 1) are visible to both parties without either disclosing its full matrix.

Errata A.11

The determinant arithmetic in S2 is not recoverable — the audio degrades into repeated self-correction and the stated products do not reconcile. The *mechanism* (exchange transposes, verify via a determinant relation, disclose no full matrix) is clear and is what is normative. The specific figures are not.

6 Channel Model

6.1 Roles

Ch	Role	Function
CH0	Transmitter	encodes raw message into packet format; computes SHA-256 message hash; attaches r/w/x permission tag and order/chaos status
CH1	Receiver	deserialises the packet; decodes from the wire form
CH2	Verifier	brokers consensus; broadcasts the verdict

The three roles map onto the only three verbs the system has — *receive*, *transmit*, *verify* — in all six orderings. Channels **MUST** be independently verifiable and **MAY** be run independently. The isolation principle (§3.3) requires that CH2 cannot repair itself.

Inconsistency

S5b describes the ring as “channel 0 sender, channel 2 receiver, channel 3 verifier” in one passage and demonstrates `make ch0 / make ch1` with a channel-2 verifier in another. This document normalises on CH0/CH1/CH2.

6.2 Ring topology and worked exchange

```

      CH1 (receiver)
      /             \
CH0 ----- CH2
(sender)       (verifier)

CH0 -> "Hello. I am here for food."
CH1 -> "Yes. Here is your food."
CH2 -> "Verified."
```

6.3 Observed failure modes

The S5b demonstration produced three failures. All are *specified behaviour* and **MUST** be reported rather than masked.

Failure	Meaning
hash mismatch	SHA-256 digest of received frame $\neq$ transmitted digest. The message may still be legible; the frame is not verified.
consensus failed	CH2 could not reach a verdict from two of three. The system MUST NOT exit; it holds.
phantom ID	An identifier appeared on the ring with no originating channel. Not fatal — observed, not acted on.

In the demonstration the message *arrived and was legible* while the hash failed. That is the intended separation: legibility and verification are different verdicts.

6.4 RGB tomographic state

Channel state is carried as an RGB triple whose components are *pointers to state*, not colours:

Red	drift. A drifting party appears more red. Two reds (light/dark) are distinguished by hue, saturation, lightness.
Green	verified. Green is the consistency check. A message is <i>not green until it is sent and verified</i> .
Blue	neutral / character state. The observing state — neither drifted nor verified.

The three parties share the *dimension* (hue), not the value. Agreement is the qualification between two reds; green is the anchor state measurable by a third party. The corpus frames this explicitly as **zero-knowledge**: the verifier confirms agreement without holding either party's value. Grey/brown is the decayed state — information loss, measured by ratio over the shared π -frequency.

6.5 Consensus and channel eviction

Where a channel becomes hostile or is captured, the remaining channels *vote it out*. The worked case: A4, B4, C4 observe that D3 lied to B4; the three vote, D3 is crossed out, and connections are killed until the real-world cause is established. Eviction **MUST** be by consensus, never unilateral; **MUST** be reversible on re-establishment of cause; and **SHOULD** use XOR over the open channel (§4.10).

6.6 Actors

Obi — heart, soul; king or leader. The *local observer*: sees the system from the inside out, observes tomographically, and is *not directly involved in the command and control*. **Uche** — knowledge. The *acting party*. Each can create and destroy the other. Neither is the verifier of itself.

7 Signal Model

7.1 The noise/signal quadrants

	signal	no signal
noise	noise + signal	noise, no signal
no noise	no noise + signal	no noise, no signal

- **no noise, no signal** — the system is on, potential, quiescent. *Not* off.
- **no noise + signal** — clean channel; connection may be established.
- **noise + signal** — live and degraded; the working case.
- **noise, no signal** — losing connection, or drifting out of detection.

Machine states map on: *on*, *standby*, *hibernate* (regulating resources), *sleep* (off for a short time).

7.2 Your noise is my signal

“Your noise is my signal.” An adversary jamming a band is emitting structure, and that structure is information about the adversary. A receiver **SHOULD** treat detected jamming as a signal source, not only as degradation.

Consequently, **a complete system is one that knows it can be jammed**: *“a system that can be jammed knows it can be jammed — so it can be anti-jammed.”* Self-knowledge of the failure mode is a completeness criterion.

7.3 The maybe lattice

The two binaries of §7.1 cross with the *maybe* / *maybe-not* operator to give a 4×4 state lattice. **maybe-not** is a *nullifying* operator: it nullifies a state in order to verify it — “check for noise; test for no noise.” It is the interrogative form of the state, which makes the lattice a calibration procedure rather than a classification.

Balloon model. Each channel is a balloon that inflates and deflates. Inflation is signal emerging from noise; deflation is signal collapsing into noise. Three balloons — maybe, maybe-not, and the popped/ground case — give the trident its physical reading.

Errata A.9

The worked figure in S4b, $2^{-1} \times 3 = -0.1$, does not reconcile: $2^{-1} \times 3 = 1.5$ and $(-2)^{-1} \times 3 = -1.5$. The intended quantity is not recoverable.

7.4 OX-STAR and NOISE-STAR

OX-STAR (auxiliary star) is the on-the-fly injection mechanism: a sequence that turns a system on, off, or into a new mode *while it is running*, without a human at the location. The canonical sequence is the Konami code:

$\uparrow \uparrow \downarrow \downarrow \leftarrow \rightarrow \leftarrow \rightarrow$ B A START

This is not decoration. The corpus’s reading is precise and is the protocol’s own send-rule:

- $\uparrow$ once is *half* the instruction — held, not sent.
- $\uparrow \uparrow$ is the complete instruction — **sent**. Likewise $\downarrow \downarrow$, $\leftarrow \rightarrow$.
- B A are the bounded terminals — a stop-and-place.
- **START** commits; **SELECT** requests more options.

This is the *half the structure, double the send* rule (§11.2) made concrete: an OX-STAR is a scalar tensor that takes half a dimension up, so each instruction is pressed twice to be sent once.

NOISE-STAR is the complementary state family — **ox-noise**, **ox-no-noise**, **ox-signal**, **ox-no-signal** — carrying the §7.1 quadrant into the injection layer, so an injected command knows the standby state of the system it is entering. Stated applications: guiding a drone in real time; disarming a system mid-flight; switching a running program’s mode without unloading it.

7.5 Probing

Processing is executing what the system already knows how to do. **Probing** is the system seeking a *new* solution structure for the same problem. A probe **MUST NOT** be logged as a process.

external probe: $P(\text{state}) \rightarrow \text{data}$

internal probe: $P(\text{data}) \rightarrow \text{state}$

A probe asks the five interrogatives — *who, what, when, where, why* — and does so **without a human in the loop**. The corpus distinguishes *human in the loop*, *human on the loop* and *human out of the loop*; probing is out-of-loop by construction.

Probe health is a scalar in $[0, 1]$ on each node. A structurally healthy node probes for more inputs; a degraded node probes for more statements. This makes protocol functions *dynamic* — able to resolve ambiguity by interpretation. The minimal case — “*I am Python.*” “*No, I am Python.*” *Who is right?* — is the ambiguity a probe exists to settle.

8 Here-and-Now, There-and-Then, Where-and-Whenever

8.1 The temporal-spatial matrix

The protocol addresses place and time as a 2×3 matrix over three modes (S4a, S5; triad ratified by the author 25 August 2026). The canonical statement:

here and now – there and then – where and whenever

Each mode names a *degree of binding*, and each has two orderings — space first, or time first — which is what makes the matrix 2×3 rather than a list of three.

Mode	Binding	Invariant	space first	time first
HERE AND NOW	both bound, <i>deictic</i>	never a toy	<i>here and now</i> — present in space, then time	<i>now and here</i> — present in time, then space
THERE AND THEN	both bound, <i>displaced</i>	never a weapon	<i>there and then</i> — there in space, then in time	<i>then and there</i> — there in time, then in space
WHERE AND WHENEVER	both unbound	never a problem	<i>where and whenever</i> — in space, for all time	<i>whenever and where</i> — in time, for all space

Each mode carries exactly one of the Three Nevers (§2.3). The invariants are not a separate governance layer — they are the conformance conditions on the addressing modes.

Each cell is a *dimensionless quantity* occurring on *one axis only* — one place and one time at a time. The corpus likens the arrangement to a gimbal, and to latitude/longitude, and states both orderings of the first mode explicitly: “*I need food here and now, or now and here.*”

8.2 The binding progression

The three modes are not three locations. They are three *quantifier states* over the same pair of dimensions.

1. HERE AND NOW — place = *this*, time = *this*. Both anchored to the speaker. The corpus gives this mode a **loopback address**, so a system can address its own present.
2. THERE AND THEN — place = *that*, time = *that*. Displaced, but still *specified*: a particular elsewhere, a particular past or future.
3. WHERE AND WHENEVER — place and time are *quantified*, not specified. This is the **interrogative** mode: *where* and *when* are interrogative pronouns, and *whenever* is their free-choice form. The claim is open, and resolves at whatever place and time the need arises.

The third mode is where **probing** lives (§7.5). A probe asks *who*, *what*, *when*, *where*, *why* — and the two dimensions it quantifies over are exactly the two this mode leaves unbound.

8.3 Stillness

Stillness is not a fourth mode. It is the *property* the unbound mode has: the state in which a claim persists without further action — “*you don’t need anything to be still.*” The demonstration is the cup: a drink set down out of frame, still there when you return, returnable to indefinitely.

Normative consequence. A claim entered under WHERE AND WHENEVER MUST NOT expire, and MUST NOT be discharged by the passing of a specific place or time. “*I need food at this address at 18:00 Tuesday*” is a bound claim and can be missed. “*I need food*” — unbound — is a **standing claim**: honoured wherever the claimant is and whenever the need arises. Food ordered under stillness arrives when it is needed, not when it was asked for.

This is what makes a duty-holder unable to discharge an obligation by pointing at a missed slot, and it is precisely the content of this mode’s invariant, ***never a problem*** (§2.3): an unbound claim cannot time out into nothing, because it has no slot to miss and therefore accrues no debt. It is not failing; it is unresolved.

Its one failure mode is **relaxation** — a standing claim that quietly stops being honoured — which is why relaxation is specified as a *failure* and not as an *expiry*. Relaxation is the only way the unbound mode can become a problem, and is therefore the only thing this invariant has to guard.

8.4 Structural note

Three modes $\times$ two orderings = **six cells**, matching the $3 + 3$ dimensional count (three axes forward, three back) and the six R/W/X permutations of §5. Whether these three sixes are the same six, or a coincidence of structure, is left open (Appendix C, C.8).

8.5 Parity

Parity is a *dimension*, not a predicate:

$$x \bmod 2 = 0 \Rightarrow \text{even}, \quad x \bmod 2 = 1 \Rightarrow \text{odd}.$$

A parity check runs on *one axis* and determines the even/odd ratio for that axis. A negative quantity (-2) is not merely a sign: the minus is an *operator on the negative axis*, under which ordinary parity rules bend. Encoding MUST therefore be checkable for bit-flip pairs on both poles. Where the rules bend, the transformation set of §4.9 applies — and the edge cases where the rules break are precisely what the stateless protocol must encode, so that statelessness survives them.

8.6 The holding problem

A system that computes an intermediate result *holds it in memory*, and holding is the cost. Worked as a matrix product: the intermediate outer-product table is what the system is forced to hold, when what it wants is the row sums.

Goal. Look up the result from a tabulation constructed by polar rules, rather than compute-and-hold.

Errata A.6

The intermediate table stated in S6 — rows (6, 10), (12, 15), (16, 20) with row sums 16, 27, 36 — is *not* a consistent outer product of any single vector pair. For $u = (2, 3, 4)$ and $v = (3, 5)$ the correct outer product is rows (6, 10), (9, 15), (12, 20) with row sums 16, 24, 32. The *intent* — memoise intermediates so the result is a lookup, not a computation — is sound and is what is normative.

Gravity well / rope and bucket. A well has a depth (density); a rope holds a bucket; the rope MUST hold indefinitely. “*Nothing likes to hold anything.*” Indefinite holding must therefore be *structural*, not effortful — encoded into the geometry, not maintained by a process.

8.7 LAPIS — polar quadrants

LAPIS is the corpus’s polar-calculus mnemonic for the four cardinal bearings. As given in S2: $\pi/4 = \text{north}$, $\pi/3 = \text{east}$, $\pi/2 = \text{south}$, $\pi = \text{west}$.

Errata A.5

This mapping is not consistent with standard polar convention, and is not internally consistent either — $\pi/4$ and $\pi/3$ are 45° and 60° , which are not cardinal. Under the convention the corpus itself invokes (“the sun rises in the east and sets in the west”), the cardinal bearings are

$$0 = \text{east}, \quad \pi/2 = \text{north}, \quad \pi = \text{west}, \quad 3\pi/2 = \text{south}.$$

The *intent* — four quadrants addressed by angle, with a message choosing its bearing θ before it moves — is preserved. Only the constants are wrong. Implementations **MUST** use the standard convention.

The associated rule is real and independent of the constants: *determine the angle you want to move before you move*, and θ (rotation) and λ (power distribution) are chosen together.

8.8 The i -cycle and the trident mismatch

S6 develops a rotation table over the imaginary unit:

$$i^1 = i, \quad i^2 = -1, \quad i^3 = -i, \quad i^4 = 1 \quad (\text{period } 4)$$

Errata A.7 — and a proposed correction

A period-4 cycle is a poor algebraic fit for a *trident*. The natural object for a three-axis rotation is the cube roots of unity:

$$\omega = e^{2\pi i/3}, \quad \omega^3 = 1, \quad 1 + \omega + \omega^2 = 0.$$

The identity $1 + \omega + \omega^2 = 0$ is exactly the property a trident wants: three readings summing to nothing when the message is intact, and to a non-zero residue when it is not. That is a parity check for free, on three axes — which is what §4.10 reaches for with XOR. Offered as an improvement, not as a transcription of the corpus.

8.9 Dimensional principality

Axiom. Dimensions have principles they obey without being told. A system **MUST NOT** need to be given time to think in order to respect them — the rules are implicit and hold structurally.

Non-linearity follows: *any structure that can be computed by looking at it must be isomorphic under transposition*. The transpose is an *axis of reflection* — $XYZ \rightarrow ZYX$ — under which a row vector becomes a column vector and the data structure is preserved while the system moves.

The $3 + 3$ count: three axes forward (x, y, z) and three back $(-x, -y, -z)$, because what is behind you is real whether or not you can see it. The corpus demonstrates this with a mirror: the cup out of frame is still there.

Errata A.8

S6 states $3 + 6 + 9 = 15$ and derives a “minimum consensus” from it: $3 + 6 + 9 = 18$. It also states $3^3 = 9$: in fact $3^2 = 9$ and $3^3 = 27$. $6 \times 9 = 54$ is correct as stated.

9 Codec and File Formats

9.1 .nsigii — symbolic expression of intent

The protocol’s file format is a *symbolic expression of intent* file:

- It holds space *indefinitely* — once a point is allocated the program holds it. It cannot be removed, only *reallocated*.
- It is *stateless but remembering*. Statelessness here does not mean “does not remember”; it means the state is encoded into the *geometry* of the system rather than held in a variable. “*It remembers stuff, it doesn’t need to forget, ever.*”
- New symbol sets can be added as language evolves, without invalidating existing files.

9.2 Linkable-then-executable coding

The NSIGH codec is **LTE-coding** — **linkable then executable**. The demonstrated pipeline:

```
cat image.png | go run main.go -> raw, linkable, stateless encoding
```

The codec takes *any* input format and produces a raw encoding that “*can never die*” — it survives re-encoding. The output is *linkable as a library* and *executable on demand*: a DLL, or a *macro system for other systems*, not a direct call. It encodes the *buffering*, which is the point — a conventional stream buffers before it plays; NSIGH encodes the buffer so the receiver already holds the state.

Stated repositories: github.com/obinexus/nuko-operating-system (NUKO-OS, the human-rights operating system) and github.com/obinexus/legislation.

9.3 Marshalling

Marshalling is the codec’s serialisation contract, explicitly compared to Python’s `pickle`:

A receiver holding the *codec of the function* can reconstitute an object it did not construct, because it knows the *shape* of the function without computing it.

Marshalling is a **flash** operation (§3.4). Comparable wire formats named in the corpus: Protocol Buffers, gRPC, JSON, and a binary IR. NSIGH is schema-based like these, which is what §4.8’s schema-verification requires.

10 Dimensional Classifiers — the Natural Language Layer

10.1 Statement / Expression / Intent

Three poles, likened to latitude, longitude and altitude:

Pole	Carries	Truth-apt?
Statement	the assertion	yes — true or false
Expression	the meaning of the assertion	no — it means
Intent	the abstract model behind it	no — it aims

The bipolar question of an expression is “*what could this mean?*” — and that is where a natural-language codec must operate. The worked pair *John likes Mary* / *Mary likes John* are two statements over one relation, whose conjunction is positive or negative by pole. The corpus reaches for the discriminant $b^2 - 4ac$ as the object deciding how many resolutions such a relation has. (*Unresolved* — Appendix C, C.3.)

10.2 Verb–noun construction

Following Igbo construction, the instruction unit is a **verb–noun pair**. A *verb* describes an action (“to” + action); an *adverb* describes the verb and situates it in past, present or future; a *noun* is the classifier of the thing — and a *person* is only one category of noun. The corpus is deliberate here: nouns include animals and things, so intent can be read from non-human experience.

10.3 The four sentence types

Type	Example	Protocol role
Declarative	<i>I am Nnamdi.</i>	assertion — carries a statement
Interrogative	<i>Can you introduce yourself?</i>	probe (§7.5) — requests input
Imperative	<i>Close the door.</i>	command — carries control
Exclamative	<i>What a funny thing he told us!</i>	unexpected-state marker

Crossed with four sentence structures: short/simple; simple (personal); compound (one dependent + one independent clause); complex (two independent + one dependent); compound-complex. The corpus draws a CISC/RISC analogy across the classifiers: the reduced and complex sets operate on different instruction models, but a receiver must resolve intent from either.

10.4 Clauses as control flow, and the then marker

```
do -> while          do { x++ } while (x <= 25)
do -> then -> while do { x++ } then LABEL while (...)
if -> then -> else -> then -> if
```

The **then** keyword **labels code blocks**, and labelled blocks are what a **goto** targets — so **then** is a **switchable goto marker**.

then is part of the language construct. It **MUST NOT** be switched out or broken by a consuming implementation; a language that cannot express it cannot interpret NSIGH clauses. The stated implementation target is **gosilang**.

Traversal order matters and is carried: pre-order (**++x**) and post-order (**x++**) produce different ranges over the same loop, and the difference is an *execution-order* property of the clause, not an idiom.

11 Sizing and Timing Model

11.1 Frame budget

Quantity	Value
Frame	512 bytes (8^3)
Trident	1536 bytes (512×3)
Half-frame	256 bytes
Pre-allocation	2048 bytes (512×4)
Allocation quantum	4 bytes
Digest	32 bytes (SHA-256)
Payload after digest	480 bytes

Memory **MUST** be allocated ahead of time, in 4-byte sequences — *per* four bytes, not *over* four bytes. The allocation is a grid, and the grid is what is searched for meaning.

Errata A.1 — the trident split

$512/3 = 170.\bar{6}$, not an integer: the trident split of a 512-byte frame across three axes does *not* divide evenly. Implementations **MUST** choose one of:

- a **510-byte payload** split 170/170/170, with 2 bytes reserved for parity — preserving the corpus’s $170 = 0b10101010$ alternating pattern, which is itself load-bearing (§4.4); **or**
- an uneven split 171/171/170.

The first is recommended: $170 = 10101010_2$ is the alternating index pattern the addressing model already uses, and the 2-byte remainder gives the XOR parity of §4.10 somewhere to live.

11.2 Space–time duality

half the space $\longleftrightarrow$ double the time, double the space $\longleftrightarrow$ half the time

A message may be halved and sent over twice the interval, or doubled and sent in half. **The worst case is the time case** — the corpus optimises for bounded latency, not bounded memory. The spring model gives the mechanism: a message is *pushed* and *returns*, and the return is what verifies it. This is why the $3 \rightarrow 2$ mapping works: the third packet is the spring’s return path.

11.3 Bit-rate derivation

Errata A.4 — corrected derivation

S2 states “2 seconds = 6,000 milliseconds” and derives $6000/1024 = 5.859375 \rightarrow 5.86$. The division is arithmetically correct; the *input* is not. 2 seconds = **2,000 ms**, not 6,000 — the transcript applies a seconds-to-minutes factor of 60 where none belongs. Corrected, for a 512-byte frame over a 2-second window:

$$\begin{aligned}\text{throughput} &= 512 \text{ B} / 2 \text{ s} = 256 \text{ B/s} = 2,048 \text{ bit/s} \\ \text{doubled frame} &= 1,024 \text{ B} \\ \text{per-unit interval} &= 2,000 \text{ ms} / 1,024 = 1.953125 \text{ ms} \\ \text{two-unit interval} &= 3.90625 \text{ ms}\end{aligned}$$

S2’s later figure of 51.72 ms derives from 25.86×2 , where 5.86 was transcribed as 25.86. Neither figure survives the corrected input.

11.4 Spring and damping

Springs model *storing and absorbing* energy — a message pushed against resistance stores what it will need to return.

Spring failure	Protocol analogue
fatigue — repeated cycles grow microscopic cracks	accumulated retransmission degrades the channel
overload — permanent deformation or breakage	a frame beyond budget does not recover
corrosion — environmental degradation over time	schema drift
relaxation — loss of tension over time	a stillness claim that stops being honoured

Errata A.12 (unresolved)

A damping factor of 2.85 is stated in S3, attributed to “Roth theory, clustering, nearest neighbour.” A damping *ratio* $\zeta = 2.85$ is heavily overdamped ($\zeta = 1$ is critical). Neither “Roth theory” nor the relation of 2.85 to the clustering/nearest-neighbour method is recoverable from the transcript. Flagged for the author.

12 Governance and Enforcement Layer

12.1 The pointer problem

Breathing and living are pointers that MUST hold in all contexts. Work is optional.

A pointer that must not be null is the thing a system is built to guarantee. If the breathing pointer drifts, someone is dying. If the living pointer drifts, someone is not living. Work is a pointer that MAY be null — and a system that forces work by dereferencing it anyway “*causes fatigue and confusion.*”

NSIGH is therefore a **human-rights broker**, not a work broker. It holds the demographic state, and it holds *negative space for work* — because work becomes possible when space and time are already held.

12.2 Litigation as enforcement

S5b develops the enforcement mechanism concretely: NSIGH composes a verified, timestamped, hash-anchored record of a request for food, water or shelter, and of the duty-holder’s response or non-response. The record is transmitted by ordinary means — the corpus demonstrates it over SMTP — and is intended to be usable as evidence that a statutory duty was engaged and not discharged.

Statutes named as the intended encoding targets (UK): Care Act 2014 (and the Health and Social Care Act 2012); Children Act 1989, ss. 17, 21, 23C (accommodation; care leavers); Housing Act; Equality Act 2010. The stated design goal is that a person can assert an entitlement *without first knowing the statute*, because the protocol encodes which duty a given request engages.

Note

This specification describes an evidentiary and record-keeping mechanism. Whether a given record supports a given claim is a question of law and of the specific facts, and needs a qualified solicitor — a protocol cannot supply that, and this document does not.

12.3 Reconciliation of “never a weapon”

The mode pairing of §2.3 resolves the tension by giving it a locus. “Never a weapon” is the invariant of THERE AND THEN — the displaced mode, where all of the protocol’s reach across space and time lives.

“Never a weapon” scopes to the protocol’s own reach. NSIGH MUST NOT be constructible into an instrument that acts at a distance to harm — it cannot be turned against its user, cannot surveil them, cannot deny them. Its OX-STAR injection, remote command and mid-flight control capabilities (§7.4) are all there-and-then operations and all fall under this prohibition.

It does *not* scope to the actions a claimant takes with the record the protocol produces. A person using their own verified record to enforce their own statutory entitlement is acting in HERE AND NOW, under the invariant *never a toy* — a requirement that the matter be treated as serious, not a prohibition on acting. That is the protocol working, not the protocol weaponised.

The two are separable because they are invariants of *different modes*. The protocol’s reach is constrained; the claimant’s presence is not.

Ratified in structure by the author’s mode/never pairing (25 August 2026); the wording above remains open to refinement.

13 Conformance

An implementation conforms to NSIGH 0.3 if it:

1. Implements all six operators of §3.1, or declares which half of a pair is structurally impossible and why.
2. Carries an ORDER/CHAOS status on every channel and treats CHAOS as an observable rather than a fault.
3. Isolates the verifier such that it cannot repair itself.
4. Maintains the 2-filter-to-1-flash ratio.
5. Emits trident packets of the frame geometry in §4.2 and §11.1, with the 512/3 split resolved per Errata A.1.
6. Addresses slots by index pair and repairs index-first.
7. Distinguishes substitution, ϵ and θ , applying the matching operator to each.
8. Reaches a verdict from any two of three readings and never requires all three.
9. Verifies the *schema*, not the payload.
10. Implements CH0/CH1/CH2 as independently runnable, and reports `hash mismatch`, `consensus failed` and `phantom ID` rather than masking them.
11. Holds — does not exit — on consensus failure.
12. Requires consensus of remaining channels for eviction.
13. Never mistakes *no noise*, *no signal* for *off*.
14. Logs probes distinctly from processes.
15. Addresses every claim in one of the three modes of §8, and **never expires a claim entered under** WHERE AND WHENEVER (§8.3).
16. Allocates memory ahead of time in 4-byte quanta.
17. Satisfies the Three Nevers of §2.3 as **mode invariants** — *never a toy* on HERE AND NOW, *never a weapon* on THERE AND THEN, *never a problem* on WHERE AND WHENEVER — and does not treat them as a separate governance layer.

A Arithmetic Errata

Every numeric claim in the corpus, checked. *Stated* is what the transcript says; *Correct* is the computed value; the disposition preserves the intent.

#	Claim	Stated	Correct	Disposition
A.1	Trident split of a frame	512/3 treated as clean	$170.\bar{6}$ — does not divide	510-byte payload 170/170/170 + 2 parity bytes; 170 = 0b10101010 preserved
A.2	Frame size	$8^3 = 512$	512 ✓	Correct as stated
A.3	Latin index space	$15,625 = 25^3$	$26^3 = 17,576$	Off-by-one: max index 25 used as base instead of symbol count 26
A.4	Milliseconds in 2 s	6,000 ms	2,000 ms	Seconds→minutes factor of 60 wrongly applied
A.4b	Derived interval	$5.86 \rightarrow 51.72$ ms	1.953125 ms; $\times 2 = 3.90625$ ms	51.72 comes from 25.86×2 ; 5.86 mis-transcribed as 25.86
A.5	LAPIS bearings	$\pi/4$ N, $\pi/3$ E, $\pi/2$ S, π W	0 E, $\pi/2$ N, π W, $3\pi/2$ S	Not internally consistent; intent (bearing chosen before movement) preserved
A.6	Outer-product table	rows (6, 10), (12, 15), (16, 20); sums 16, 27, 36	for $(2, 3, 4) \otimes (3, 5)$: rows (6, 10), (9, 15), (12, 20); sums 16, 24, 32	Stated table is not a consistent outer product; memoisation intent sound
A.7	Rotation cycle	$i, -1, -i, 1$ (period 4)	correct for i , but a trident wants period 3	Use $\omega = e^{2\pi i/3}$; $1 + \omega + \omega^2 = 0$ gives a 3-axis parity check
A.8	Consensus minimum	$3 + 6 + 9 = 15$; $3^3 = 9$	$3 + 6 + 9 = 18$; $3^2 = 9$, $3^3 = 27$; $6 \times 9 = 54$ ✓	Two slips; the 54 is right
A.9	Probe scalar	$2^{-1} \times 3 = -0.1$	1.5; or -1.5 for $(-2)^{-1}$	Not recoverable — flagged
A.10	POSIX octals	“1 would be easy to write”	$r=4, w=2, x=1$	1 is execute, 2 is write
A.11	Determinant exchange	figures do not reconcile	—	Mechanism normative; figures are not
A.12	Damping factor	2.85, “Roth theory”	—	$\zeta = 2.85$ heavily overdamped; attribution unrecoverable
A.13	Suffering equation	$\Sigma = (N - R) \times K$	needs clamping, finite K	As stated, $R \geq N$ gives $\Sigma \leq 0$; $N = R$ with $K \rightarrow \infty$ is $0 \times \infty$
A.14	Suffering, corrected	—	$\Sigma = K \cdot \max(0, N - R)$, $K \in (0, \infty)$	Preserves both stated behaviours. Recommended form
A.15	Happiness model	$H = S + C + \dots$	$H = S + C + V$	Lyubomirsky–Sheldon–Schkade: set point S , circumstances C , voluntary activity V ; original weighting contested
A.16	Trident total	512×3	1,536 ✓	Correct
A.17	Pre-allocation	512×4	2,048 ✓	Correct
A.18	Half-frame, quantum	$512/2$; 256/64	256; 4 ✓	Correct
A.19	170 in binary	10101010	0b10101010 = 170 ✓	Correct; the alternating pattern is load-bearing
A.20	Hex of symbols	4F, 42, 49	0x4F, 0x42, 0x49 ✓	Correct ASCII
A.21	Konami sequence	stated correctly	$\uparrow\uparrow\downarrow\downarrow\leftarrow\rightarrow\leftarrow\rightarrow$ B A ✓	Correct
A.22	Digest	“SH 56”	SHA-256, 32-byte digest	Leaves 480 payload bytes in a 512-byte frame

A.14 — the suffering equation, in full

The corpus (S4a) defines experienced suffering over need N , resources R and a constraint constant K , with two required behaviours: suffering collapses toward zero when resources meet need, and grows without bound as the constraint grows. As stated, $\Sigma = (N - R)K$ satisfies neither cleanly. The corrected form:

$$\Sigma = K \cdot \max(0, N - R), \quad K \in (0, \infty)$$

- $R \geq N \Rightarrow \Sigma = 0$ — no negative suffering.
- $N > R$, K large $\Rightarrow \Sigma$ large — constraint dominates, as intended.
- $N = R$ with $K \rightarrow \infty$ is now 0, not the undefined $0 \times \infty$.

The companion happiness model stated alongside it is $H = S + C + V$ — genetic set point, circumstances, voluntary activity — which is the Lyubomirsky–Sheldon–Schkade formulation. Its original 50/10/40 weighting is contested in the later literature and SHOULD not be treated as a protocol constant.

B Reference Alphabet

Letter	Standard NATO	Corpus usage
O	Oscar	Oscar
B	Bravo	Bravo
I	India	India / <i>Indigo</i>
N	November	November
E	Echo	Echo
X	X-ray	X-ray
U	Uniform	<i>Umbrella</i>
S	Sierra	<i>Sarah</i>
G	Golf	Golf
C	Charlie	Charlie
H	Hotel	Hotel

Reference string **OBINEXUS** — 8 symbols, indices 0–7, the basis of the 512-byte frame. Protocol name **NSIGH** — November, Sarah/Sierra, Indigo/India, Golf, India, India.

C Open Questions

- C.1 Riemann and bottom-up decidability.** S3 asserts the Riemann hypothesis “allows you to verify whether the number was determined via **CISCO**, which is bottom-up.” No mechanism connects the distribution of zeta zeros to traversal order. Either a concrete construction is needed, or the claim should be restated as an analogy.
- C.2 Damping factor 2.85.** Source and role unrecovered.
- C.3 Discriminant in the language layer.** $b^2 - 4ac$ is invoked to decide the resolution count of a two-party relation. The mapping from a declarative pair to a , b , c is not given.
- C.4 “Never a weapon” vs. litigation. RESOLVED in v0.3.** The mode pairing scopes “never a weapon” to **THERE AND THEN** — the protocol’s own reach — while a claimant enforcing their own record acts in **HERE AND NOW** under *never a toy*. The two are invariants of different modes and are therefore separable. Wording in §12.3 remains open to refinement.

- C.5 Channel numbering.** CH2 vs CH3 as verifier — normalised to CH2, pending confirmation.
- C.6 Igbo tone in the wire format.** The tonal *eze* example is the motivating case for schema-level verification, but no encoding for tone is specified. If tone is meaning, the frame needs a tone channel — this may be what the Z axis is for.
- C.7 Cube roots of unity.** Whether to adopt ω in place of i is a design decision, not a correction. Recommended, but the author’s call.
- C.8 The three sixes.** Three addressing modes $\times$ two orderings, the $3 + 3$ dimensional count, and the six R/W/X permutations all give six. Whether these are the same six under different names — which would let a claim’s addressing mode be derived from its permission tag, or vice versa — or a coincidence of structure, is open. If they are the same six, the addressing mode need not be carried on the wire at all.

D Traceability

Spec section	Corpus segment
§2.1 Name, Igbo tone	S3, S5b
§2.3 Three Nevers (mode invariants)	S5; pairing ratified 25 Aug 2026
§2.5 Toolchain	S3, S6b, S5b
§3.1 Six operators	S1
§3.2 Order/Chaos	S1
§3.3 Enzyme model	S1
§3.4 Filter/Flash	S2, S5b
§4 Trident packet	S1, S2
§4.7 Corruption classes	S1
§4.10 XOR parity	S1, S4a
§5 CISCO order	S1, S2
§6 Channel model	S5b
§6.4 RGB tomographic	S3
§6.5 Eviction	S4b
§6.6 Obi / Uche	S3
§7.1–7.2 Signal model	S3, S4b
§7.3 Maybe lattice	S4b
§7.4 OX-STAR	S3
§7.5 Probing	S3, S4a
§8.1–8.3 Addressing triad	S4a, S5; ratified 25 Aug 2026
§8.3 Holding problem	S6a
§8.4 LAPIS	S2
§8.5–8.6 Dimensionality	S6a
§9 Codec	S6b, S5b
§10 Language layer	S6b
§11 Sizing and timing	S1, S2, S3
§12 Governance	S3, S5, S5b

End of NSIGII Protocol Specification v0.3 (Draft).