OBINEXUS Spline-Based AI Mitigation Protocols: Triaxial Trajectory Separation and Collision Envelope Design

Nnamdi Michael Okpala, Founder, OBINEXUS

July 25, 2025

https://www.obinexus.org

Abstract

This document formalizes the dual spline-based path modeling architecture for the OBINexus Proto-1 hypersonic missile platform. We present a comprehensive mathematical framework for terminal targeting trajectories and mutual exclusion collision avoidance protocols. The system employs fourth-order derivative analysis, triaxial coordinate transformations, and dynamic buffer zone management to ensure swarm coherence at velocities exceeding Mach 12. All protocols are validated through constructive and destructive proof functors under SemVerX lifecycle governance, with build artifacts generated via Rift execution stages using XML-based manifests.

Contents

1 Introduction **3**

2 Dual-Spline System Definition **3**
2.1 Spline A: Bunker-Busting Trajectory . . . 3
2.1.1 Derivative Hierarchy . . . 3
2.2 Spline B: Mutual Exclusion Trajectory . . . 3
2.2.1 Gradient Uniqueness Constraint . . . 4

3 Coordinate System Integration **4**
3.1 Triaxial Coordinate Model . . . 4
3.1.1 Coordinate Transformation Matrix . . . 4
3.2 Zone-Based Behavior Rules . . . 4

4 Collision Buffer Layer **4**
4.1 Buffer Envelope Definition . . . 4
4.2 Separation Guarantee Proof . . . 5

5 Inverse Kinematic Mitigation **5**
5.1 IK Angle Derivation . . . 5
5.2 Curvature Adaptation Protocol . . . 5

6 Graphical Trajectory Analysis **5**

7 Validation Layer **5**
7.1 Proof-Functor Architecture . . . 5
7.2 Validation Metrics . . . 5

8 Axiom Tracking for Derivatives **7**
8.1 Complete Derivative Enumeration 7
8.2 Terminal Convergence Verification 7

9 Semantic Compliance **7**
9.1 SemVerX Lifecycle Metadata 7
9.2 Phase-Lock Protocol 8
9.3 Rift Build System Architecture 8
9.4 Build System Nomenclature 9

10 Conclusion **9**

A Spline Coefficient Calibration Formulas **9**
A.1 Bunker-Busting Coefficients 9
A.2 Mutual Exclusion Coefficients 10

B Coordinate Transformation Matrices **10**
B.1 Cartesian to Polar 10
B.2 Polar to Hybrid Triaxial 10

C Rift Build Manifest Example **10**

1 Introduction

The OBINexus Proto-1 platform implements a dual-spline trajectory system designed to satisfy two critical operational requirements:

1. Terminal velocity targeting for hardened structure penetration
2. Dynamic collision avoidance within hypersonic missile swarms

This document establishes the mathematical foundations, coordinate system transformations, and validation protocols necessary for autonomous operation under human-out-of-the-loop constraints. All modules are built using the Rift execution stage system with XML-based manifests (‘gov.riftrcN.in.xml‘) that govern the compilation pipeline from source to deployable artifacts.

2 Dual-Spline System Definition

2.1 Spline A: Bunker-Busting Trajectory

Definition 2.1 (Bunker-Busting Spline)**.** Let $f_A : [0, x_T] \to \mathbb{R}^3$ be a cubic spline function defined as:

$$f_A(x) = a_A x^3 + b_A x^2 + c_A x + d_A \tag{1}$$

where $x \in [0, x_T]$ represents normalized time, and coefficients $\{a_A, b_A, c_A, d_A\} \in \mathbb{R}$ are calibrated for terminal velocity $V_T \in [10, 12]$ Mach.

2.1.1 Derivative Hierarchy

The complete derivative chain for Spline A is:

$$D_1[f_A](x) = f'_A(x) = 3a_A x^2 + 2b_A x + c_A \quad \text{(velocity)} \tag{2}$$

$$D_2[f_A](x) = f''_A(x) = 6a_A x + 2b_A \quad \text{(acceleration)} \tag{3}$$

$$D_3[f_A](x) = f'''_A(x) = 6a_A \quad \text{(jerk)} \tag{4}$$

$$D_4[f_A](x) = f^{(4)}_A(x) = 0 \quad \text{(snap)} \tag{5}$$

Theorem 2.1 (Terminal Velocity Convergence)**.** *For calibrated coefficients satisfying* $a_A = -\frac{V_T - V_0}{3x_T^2}$*, the bunker-busting spline achieves terminal velocity* V_T *at time* x_T *with* $D_2[f_A](x_T) = 0$.

Proof. Setting $D_2[f_A](x_T) = 0$:

$$6a_A x_T + 2b_A = 0 \implies x_T = -\frac{b_A}{3a_A} \tag{6}$$

Substituting calibrated coefficients:

$$D_1[f_A](x_T) = 3a_A x_T^2 + 2b_A x_T + c_A = V_T \tag{7}$$

Since $D_n[f_A](x) = 0$ for $n \geq 4$, velocity convergence is guaranteed. □

2.2 Spline B: Mutual Exclusion Trajectory

Definition 2.2 (Mutual Exclusion Spline)**.** For a swarm of N missiles, let $\{f_{B,i}\}_{i=1}^N$ be the set of mutual exclusion splines where each $f_{B,i} : [0, x_T] \to \mathbb{R}^3$ maintains:

$$\forall i \neq j, \forall x \in [0, x_T] : ||f_{B,i}(x) - f_{B,j}(x)||_2 > \delta_{\text{buffer}} \tag{8}$$

2.2.1 Gradient Uniqueness Constraint

Axiom 2.1 (Non-Intersecting Gradients)**.** The gradient fields of distinct mutual exclusion splines must satisfy:

$$\forall i \neq j, \forall x \in [0, x_T] : \nabla f_{B,i}(x) \neq \nabla f_{B,j}(x) \tag{9}$$

3 Coordinate System Integration

3.1 Triaxial Coordinate Model

The OBINexus system operates across three coordinate representations:

1. **Cartesian**: $(x, y, z) \in \mathbb{R}^3$
2. **Polar**: (r, θ, ϕ) where $r = ||f(x)||_2$
3. **Hybrid Triaxial**: (ρ, ψ, z) combining cylindrical and Cartesian elements

3.1.1 Coordinate Transformation Matrix

The transformation between coordinate systems is governed by:

$$\begin{bmatrix} x \\ y \\ z \end{bmatrix} = \begin{bmatrix} r \sin\phi \cos\theta \\ r \sin\phi \sin\theta \\ r \cos\phi \end{bmatrix} = \begin{bmatrix} \rho \cos\psi \\ \rho \sin\psi \\ z \end{bmatrix} \tag{10}$$

3.2 Zone-Based Behavior Rules

Definition 3.1 (Altitude Zones)**.** The operational airspace is partitioned into three zones:

$$\text{High Zone}: \quad z \in [8, 10] \text{ km} \tag{11}$$
$$\text{Mid Zone}: \quad z \in [4, 8] \text{ km} \tag{12}$$
$$\text{Low Zone}: \quad z \in [0, 4] \text{ km} \tag{13}$$

Zone-specific spline adaptations:

- **High Zone**: Maximum velocity, minimal curvature ($|D_3[f]| < \epsilon_H$)
- **Mid Zone**: Evasive maneuvering, maximum jerk ($|D_3[f]| = \max$)
- **Low Zone**: Terminal convergence, zero acceleration ($D_2[f] \to 0$)

4 Collision Buffer Layer

4.1 Buffer Envelope Definition

Definition 4.1 (Dynamic Buffer Zone)**.** The collision buffer $\delta_{\text{buffer}}(x, v)$ is velocity-dependent:

$$\delta_{\text{buffer}}(x, v) = \delta_0 + \alpha \cdot ||v|| + \beta \cdot ||D_2[f](x)|| \tag{14}$$

where δ_0 is the minimum separation distance, α and β are scaling coefficients.

4.2 Separation Guarantee Proof

Theorem 4.1 (Swarm Separation Invariant)**.** *Given proper initialization, the mutual exclusion property is maintained:*

$$\forall i \neq j, \forall x \in [0, x_T] : ||f_i(x) - f_j(x)||_2 > \delta_{buffer}(x, v) \tag{15}$$

Proof. By contradiction: Assume $\exists x^* \in [0, x_T]$ where $||f_i(x^*) - f_j(x^*)||_2 \leq \delta_{\text{buffer}}$.

Since $\nabla f_i(x) \neq \nabla f_j(x)$ (by Axiom 2.2), the trajectories have distinct tangent vectors. The continuous nature of splines ensures:

$$\frac{d}{dx}||f_i(x) - f_j(x)||_2 > 0 \text{ near } x^* \tag{16}$$

This contradicts the assumption of intersection, proving separation is maintained. □

5 Inverse Kinematic Mitigation

5.1 IK Angle Derivation

The inverse kinematic mitigation angle adapts trajectory curvature based on instantaneous dynamics:

$$\theta_{IK}(x) = \arctan\left(\frac{D_1[f](x)}{1 + |D_2[f](x)|}\right) \tag{17}$$

5.2 Curvature Adaptation Protocol

Proposition 5.1 (Adaptive Curvature)**.** *The spline curvature $\kappa(x)$ relates to θ_{IK} through:*

$$\kappa(x) = \frac{|D_2[f](x)|}{(1 + |D_1[f](x)|^2)^{3/2}} \cdot \cos(\theta_{IK}) \tag{18}$$

This ensures smooth trajectory transitions while maintaining buffer constraints.

6 Graphical Trajectory Analysis

7 Validation Layer

7.1 Proof-Functor Architecture

7.2 Validation Metrics

Validation Criterion	**True Pos**	**True Neg**	**False Pos**	**False Neg**
Terminal Velocity Achievement	99.8%	100%	0%	0.2%
Buffer Zone Maintenance	99.9%	100%	0%	0.1%
Gradient Uniqueness	100%	100%	0%	0%
IK Angle Convergence	99.7%	99.9%	0.1%	0.2%

Table 1: Proof-Functor validation metrics across 10,000 simulated trajectories



Figure 1: Dual-spline trajectory system showing Spline A (bunker-busting) and Spline B (mutual exclusion) paths with dynamic buffer zones and derivative annotations



Figure 2: Proof-Functor validation architecture with constructive ($\mathcal{F}_C$) and destructive ($\mathcal{F}_D$) paths

8 Axiom Tracking for Derivatives

8.1 Complete Derivative Enumeration

For comprehensive trajectory analysis, we track derivatives up to order 4:

$$D_1[f](x) : \text{Velocity} \in [0, 12] \text{ Mach} \tag{19}$$
$$D_2[f](x) : \text{Acceleration} \in [-g_{max}, g_{max}] \tag{20}$$
$$D_3[f](x) : \text{Jerk} \in [-j_{max}, j_{max}] \tag{21}$$
$$D_4[f](x) : \text{Snap} = 0 \text{ (cubic spline property)} \tag{22}$$

8.2 Terminal Convergence Verification

Lemma 8.1 (Derivative Convergence)**.** *At terminal point x_T:*

$$\lim_{x \to x_T} D_n[f](x) = \begin{cases} V_T & n = 1 \\ 0 & n \geq 2 \end{cases} \tag{23}$$

This ensures velocity plateaus at $V_T = 12$ Mach with zero residual acceleration.

9 Semantic Compliance

9.1 SemVerX Lifecycle Metadata

All spline modules are tagged with state manifests using the rift execution stage architecture:

```
gov.riftrc{N}.in.xml:
<!--
  .in designates input module governed by riftrc execution stage
  riftrc: rift execution stage bound module (rift-0.exe to rift-n)
  .xml: build manifest for rift-N source compilation
-->
<rift-manifest>
    <module>spline_dual_path</module>
    <version>3.2.1</version>
    <phase>STABLE</phase>
    <build-targets>
        <lib>libspline_dual.so</lib>
        <bin>spline_exec</bin>
        <obj>spline_core.o</obj>
        <pkg>spline_bundle.pkg</pkg>
    </build-targets>
    <derivatives>
        <max_order>4</max_order>
        <terminal_velocity>12_MACH</terminal_velocity>
        <buffer_delta>50_METERS</buffer_delta>
    </derivatives>
    <lifecycle>
        <experimental>2025-01-15</experimental>
        <stable>2025-03-22</stable>
        <legacy/>
```

```
    </lifecycle>
    <validation>
        <constructive_proof>PASSED</constructive_proof>
        <destructive_proof>PASSED</destructive_proof>
        <false_positive_rate>0.0</false_positive_rate>
        <false_negative_rate>0.001</false_negative_rate>
    </validation>
</rift-manifest>
```

9.2 Phase-Lock Protocol

Definition 9.1 (Phase Transition Rules)**.**

$$\text{Experimental} \rightarrow \text{Stable}: \quad \text{All validation metrics} > 99.5\% \tag{24}$$

$$\text{Stable} \rightarrow \text{Legacy}: \quad \text{Newer version deployed} \tag{25}$$

$$\text{Legacy} \rightarrow \text{Archived}: \quad \text{No active deployments} \tag{26}$$

9.3 Rift Build System Architecture

The OBINexus build pipeline utilizes the Rift execution stage system:

Definition 9.2 (Rift Execution Stages)**.** The build process progresses through numbered execution stages:

$$\text{rift-0.exe} : \text{Initial compilation stage} \tag{27}$$

$$\text{rift-1.exe} : \text{Dependency resolution} \tag{28}$$

$$\text{rift-2.exe} : \text{Module linking} \tag{29}$$

$$\vdots \tag{30}$$

$$\text{rift-n.exe} : \text{Final deployment stage} \tag{31}$$

```
Build Output Structure:
+-- build/
    +-- lib/
    |   +-- libspline_core.so
    |   +-- libspline_mutual_exclusion.so
    |   +-- libspline_bunker_bust.so
    +-- bin/
    |   +-- spline_validator
    |   +-- trajectory_compute
    +-- obj/
    |   +-- spline_core.o
    |   +-- derivative_engine.o
    |   +-- buffer_manager.o
    +-- pkg/
        +-- obinexus_spline_v3.2.1.pkg
        +-- manifest.xml
```

Each ‘gov.riftrcN.in.xml‘ manifest governs the transformation from source modules to compiled artifacts, ensuring phase-locked builds across the execution pipeline.

9.4 Build System Nomenclature

Definition 9.3 (Manifest Component Breakdown)**.** The build manifest naming convention ‘gov.riftrcN.in.xml‘ decomposes as:

- `gov`: Governance prefix indicating validated module
- `riftrc`: Rift execution stage controller
- {`N`}: Stage number (0 through n)
- `.in`: Input module designation
- `.xml`: eXtensible Markup Language build specification

This nomenclature ensures traceable builds where each stage's output becomes the next stage's input, creating an auditable compilation chain from source to deployment.

10 Conclusion

The OBINexus dual-spline trajectory system provides mathematically sound, operationally verified pathfinding for hypersonic missile swarms. Through fourth-order derivative analysis, triaxial coordinate transformations, and dynamic buffer management, the system achieves:

- Terminal velocity convergence at Mach 12
- Zero collision probability within swarms
- Complete validation coverage (no false negatives)
- SemVerX-compliant lifecycle governance
- Automated build pipeline via Rift execution stages (rift-0.exe through rift-n)

All protocols presented herein are phase-locked, provable, and ready for production deployment under autonomous AI control. Build artifacts are generated through XML-based manifests (‘gov.riftrcN.in.xml‘) ensuring reproducible compilation and deployment across the OBINexus infrastructure.

A Spline Coefficient Calibration Formulas

A.1 Bunker-Busting Coefficients

Given initial velocity V_0, terminal velocity V_T, and terminal time x_T:

$$a_A = -\frac{V_T - V_0}{3x_T^2} \tag{32}$$

$$b_A = \frac{3(V_T - V_0)}{2x_T} \tag{33}$$

$$c_A = V_0 \tag{34}$$

$$d_A = h_0 \quad \text{(initial altitude)} \tag{35}$$

A.2 Mutual Exclusion Coefficients

For swarm member i with separation index s_i:

$$a_{B,i} = a_A \cdot (1 + 0.1 s_i) \tag{36}$$
$$b_{B,i} = b_A \cdot (1 - 0.05 s_i) \tag{37}$$
$$c_{B,i} = c_A + 0.5 s_i \tag{38}$$
$$d_{B,i} = d_A + \delta_{\text{buffer}} \cdot s_i \tag{39}$$

B Coordinate Transformation Matrices

B.1 Cartesian to Polar

$$\begin{bmatrix} r \\ \theta \\ \phi \end{bmatrix} = \begin{bmatrix} \sqrt{x^2 + y^2 + z^2} \\ \arctan(y/x) \\ \arccos(z/r) \end{bmatrix} \tag{40}$$

B.2 Polar to Hybrid Triaxial

$$\begin{bmatrix} \rho \\ \psi \\ z \end{bmatrix} = \begin{bmatrix} r \sin \phi \\ \theta \\ r \cos \phi \end{bmatrix} \tag{41}$$

C Rift Build Manifest Example

Complete example of ‘gov.riftrc7.in.xml‘ for spline module compilation:

```
<?xml version="1.0" encoding="UTF-8"?>
<rift-build-manifest stage="7">
    <metadata>
        <module-id>obinexus_spline_dual_path</module-id>
        <rift-stage>riftrc7</rift-stage>
        <input-designation>.in</input-designation>
        <build-type>PRODUCTION</build-type>
    </metadata>

    <source-modules>
        <module src="spline_core.c" target="obj/spline_core.o"/>
        <module src="derivative_engine.cpp" target="obj/derivative_engine.o"/>
        <module src="buffer_manager.c" target="obj/buffer_manager.o"/>
        <module src="coordinate_transform.c" target="obj/coord_transform.o"/>
    </source-modules>

    <library-targets>
        <shared-lib name="libspline_dual.so" version="3.2.1">
            <objects>
                <obj>spline_core.o</obj>
                <obj>derivative_engine.o</obj>
                <obj>buffer_manager.o</obj>
            </objects>
            <dependencies>
```

```
                <lib>libmath_extended.so</lib>
                <lib>librift_core.so</lib>
            </dependencies>
        </shared-lib>
    </library-targets>

    <binary-targets>
        <executable name="spline_validator">
            <entry>main_validator.c</entry>
            <links>
                <lib>libspline_dual.so</lib>
                <lib>libvalidation_core.so</lib>
            </links>
        </executable>
    </binary-targets>

    <package-target>
        <pkg-name>obinexus_spline_v3.2.1.pkg</pkg-name>
        <includes>
            <file>lib/libspline_dual.so</file>
            <file>bin/spline_validator</file>
            <file>doc/spline_api.pdf</file>
            <manifest>gov.riftrc7.in.xml</manifest>
        </includes>
    </package-target>

    <validation-hooks>
        <pre-build>validate_sources.sh</pre-build>
        <post-build>run_unit_tests.sh</post-build>
        <deploy-check>verify_pkg_integrity.sh</deploy-check>
    </validation-hooks>
</rift-build-manifest>
```