

Reducing Programs to Objects

Ver: 0.0.0

YEGOR BUGAYENKO, Huawei, Russia

C++, Java, C#, Python, Ruby, and JavaScript are the most powerful object-oriented programming languages if language power is defined as the number of *features* available to a programmer. EO, on the other hand, is an object-oriented programming language with a reduced set of features: it has nothing but objects and mechanisms of their composition and decoration. This paper asks the following research question: “Which known features are possible to implement using only objects?”

1 Introduction

We selected the most complex features and demonstrated how each of them may be represented in EO [?] objects¹.

Other features are more trivial, which is why they are not presented in this paper, such as operators, loops, variables, code blocks, constants, and selection.

The work of [?] explains the design of EO standard library of objects, which are used below.

2 Goto

Goto is a one-way imperative transfer of control to another line of code. There are only two possible cases of goto jumps: forward and backward.

2.1 Backward Jump

A “backward” jump in C language can be mapped to EO recursion:

<pre>#include "stdio.h" void f() { int i = 1; again: i++; if (i < 10) goto again; printf("Finished!"); }</pre>	<pre>malloc.empty > [] > f seq * > [i] i.put 1 again i io.stdout "Finished!" seq * > [ii] > again ii.put (ii.as-number.plus 1) if. ii.as-number.lt 10 again ii true</pre>
---	--

2.2 Forward Jump

A “forward” jump in C language can be mapped to EO:

¹LA_TE_X sources of this paper are maintained in REPOSITORY GitHub repository, the rendered version is 0.0.0.

<pre> int f(int x) { int r = 0; if (x == 0) goto exit; r = 42 / x; exit: return r; } </pre>	<pre> malloc.empty > [x] > f seq * > [r] >> r.put 0 if. x.eq 0 true r.put (42.div x) number r.get </pre>
---	---

According to the Böhm–Jacopini theorem [?], any use of the `GOTO` operator may be replaced by a combination of sequence (the `seq` object), selection (the `if` attribute), and iteration (the `while` object). Relying on this fact, we may conclude that any C code that uses `GOTO` may be represented in EO.

2.3 Multiple Returns

Some structured programming languages allow a function to exit at an arbitrary place, not only at the end, using `return` statements, for example:

```

void abs(int x) {
    if (x > 0) {
        return x;
    }
    return -1 * x;
}

```

This can be mapped to the following EO code using `go.to` object:

```

[x] > abs
go.to > @
[g] >>
    seq * > @
    if.
        x.gt 0
        g.forward x
        true
    g.forward
    -1.times x

```

The dataization of `forward` will exit the `go.to` object wrapping the entire code in the “function” `abs`.

3 Pointers

This section is not valid, must be rewritten!

A pointer is an object in many programming languages that stores a memory address. Pointers may point to data memory or program memory.

3.1 Pointers to Data

This is an example of C code, where the pointer `p` is first incremented by seven times `sizeof(book)` (which is equal to 108) and then de-referenced to become a struct `book` mapped to memory. Then, the `title` part of the struct is filled with a string and the `price` part is returned as a result of the function `f`:

```
#include "string.h"
struct book {
    char title[100];
    long long price;
};
int f(struct book* p) {
    struct book b = *(p + 7);
    strcpy(b.title, "Object Thinking");
    return b.price;
}
```

This code can be mapped to the following EO code:

```
[ptr] > book
  ptr > @
  ptr.block > title
    100
  [b] (b.as-string > @)
  ptr.block > price
    8
  [b] (b.as-int > @)
pointer. > p1
  heap 1024
  0
  108
[p] > f
  seq * > @
  book (p.add 7) > b
  b.title.write
    ("Object Thinking").as-bytes
  b.price
```

Here, `p1` is an object that can be used as an argument of `f`. It is a copy of an abstract object `heap.pointer`, which expects two parameters: 1) an absolute address in memory and 2) the size of the memory block it points to, in bytes. Its attribute `block` expects two attributes: 1) the number of bytes in the heap and 2) an abstract object that can encapsulate `bytes` that were just read from memory.

The object `heap` is an abstraction of a random access memory.

3.2 Pointers to Code

A pointer may not only refer to data in the heap but also to executable code in memory (there is no difference between “program” and “data” memory in both x86 and ARM architectures). This is an example of a C program that calls a function referenced by a function pointer, providing two integer arguments to it:

```
int foo(int x, int y) {
    return x + y;
}
int f() {
    int (*p)(int, int);
    p = &foo;
    return (*p) (7, 42);
}
```

This code can be mapped to the following EO code:

```
[x y] > foo
x.plus y > @
[] > f
  cage 0 > p
  seq * > @
    p.write
      [x y]
      foo x y > @
  p.@ 7 42
```

It is important to note that the following code cannot be represented in EO:

```
int f() {
    int (*p)(int);
    p = (int (*)(int)) 0x761AFE65;
    return (*p) (42);
}
```

Here, the pointer refers to an arbitrary address in program memory, where some executable code is supposed to be located.

3.3 Variables in Stack

This C function, which returns seven (tested with GCC), assumes that variables are placed in the stack sequentially and uses pointer de-referencing to access them:

```
int f() {
    long long a = 42;
    long long b = 7;
    return *(&a - 1);
}
```

This code can be mapped to the following EO code:

```
[p] > long64
  p.block > @
    8
    [b] (b.as-int > @)
[] > f
  seq * > @
    malloc. > stack
      heap 32 > h
      16
      long64 stack > b
      b.write (7.as-bytes)
      long64 stack > a
      a.write (42.as-bytes)
      long64 (a.p.sub 1) > ret!
      h.free stack
      ret
```

Here, the atom `malloc` allocates a segment of bytes in the `heap`. Later, the atom `free` releases it. The attribute `ret` is made constant to avoid its recalculation after it is “returned” (this mechanism is explained in Section 7 where destructors are discussed).

4 Procedures

A subroutine is a sequence of program instructions that performs a specific task, packaged as a unit. In different programming languages, a subroutine may be called a routine, subprogram, function, method, or procedure. In this PHP example, a function `max` is defined:

```
function max($a, $b) {
  if ($a > $b) return $a;
  return $b;
}
```

It can be mapped to the following EO code:

```
[a b] > max
  go.to > @
    [g] >>
      seq * > @
        if.
          a.gt b
          g.forward a
          true
        b
```

This example also demonstrates how `go.to` object can be used to simulate the behavior of the `return` statement from within the body of a method.

5 Impure Functions

This section is not valid, must be rewritten!

A function is pure when, among other qualities, it does not have side effects: no mutation of local static variables, non-local variables, mutable reference arguments, or input/output streams. This PHP function is impure:

```
$a = 42;
function inc($a) {
    $a = $a + 1;
    return $a;
}
inc(inc($a)); // $a == 44
```

It may be mapped to a constant EO object:

```
memory 42 > a
[x] > inc!
    seq * > @
        x.write
        x.plus 1
inc
    inc a
```

6 Classes

This section is not valid, must be rewritten!

A class is an extensible program code template for creating objects, providing initial values for state (member variables) and implementations of behavior (member functions or methods). The following program contains a Ruby class with a single constructor, two methods, and one mutable member variable:

```
class Book
  def initialize(i)
    @id = i
    puts "New book!"
  end
  def path
    "/tmp/${@id}.txt"
  end
  def move(i)
    @id = i
  end
end
```

It can be mapped to the following EO code, where a class becomes an object factory:

Reducing Programs to Objects

```
[i] > book
  cage i > id
[] > ruby-init
  tt.sprintf > @
    "New book!"
[] > path
  tt.sprintf > @
    "/tmp/%s.txt"
  id
[i] > move
  id.write i > @
```

Here, the constructor is represented by the object `ruby-init`, which finishes the initialization of the object. Making an “instance” of a book would look like this:

```
book 42 > b
b.ruby-init
b.move 7
b.path
```

7 Destructors

This section is not valid, must be rewritten!

In C++ and some other languages, a destructor is a method that is called for a class object when that object passes out of scope or is explicitly deleted. The following code will print both `Alive` and `Dead` texts:

```
#include <iostream>
class Foo {
public:
  Foo() { std::cout << "Alive"; }
  ~Foo() { std::cout << "Dead"; };
};
int main() {
  Foo f = Foo();
}
```

It may be translated to EO as such:

```

[] > foo
[] > constructor
    io.stdout "Alive" > @
[] > destructor
    io.stdout "Dead" > @
[] > main
foo > f
seq * > @
    f.constructor
    f.destructor

```

There is no garbage collection in EO, so a destructor must be explicitly “called” when an object passes out of scope or is deleted.

8 Exceptions

Exception handling is the process of responding to the occurrence of exceptions—anomalous or exceptional conditions requiring special processing—during the execution of a program. This C++ program utilizes exception handling to avoid segmentation fault due to null pointer de-referencing:

```

#include <iostream>
class Book { public: int price(); };
int price(Book* b) {
    if (b == NULL) throw "NPE!";
    return (*b).price() * 1.1;
}
void print(Book* b) {
    try {
        std::cout << "The price: " << price(b);
    } catch (char const* e) {
        std::cout << "Error: " << e;
    }
}

```

This mechanism may be implemented in EO:


```

[] > book
[] > price ?
[b] > price
  if. > @
    b.eq 0
    error "NPE!"
    b.price.times 1.1
[b] > print
  try > @
    [] >>
      io.stdout > @
      tt.sprintf *1
      "The price: %d"
      price b
    [e] >>
      io.stdout > @
      tt.sprintf *1
      "Error: %s"
      e
  true

```

Here, the object `try` expects three arguments: 1) an abstract object to be dataized, 2) an abstract object to be copied with one argument, in case dataization returns an encapsulated object, and 3) an object to be dataized anyway (similar to Java `finally` block).

In the object `price`, we get the object `error`, which, if dataized, causes the termination of dataization and a non-conditional jump to the “catch” object of the `try`. The mechanism is similar to “checked” exceptions in Java, where a method’s signature must declare all types of exceptions the method may throw.

8.1 Many Exception Types

This section is not valid, must be rewritten!

A Java method may throw a number of either checked or unchecked exceptions, for example:

```

void f(int x) throws IOException {
  if (x == 0) {
    throw new IOException();
  }
  throw new RuntimeException();
}

```

This would be represented in EO as such:

```
[x] > f
  if. > @
    x.eq 0
    error "IOException"
    error "RuntimeException"
```

To catch both exceptions the object `f` would be used like this:

```
try
  []
  try > @
    []
    f 5 > @
    [e1]
    io.stdout e1 > @
    []
    nop > @
  [e2]
  io.stdout e2 > @
  []
  nop > @
```

9 Anonymous Functions

Anonymous functions can be passed into methods as arguments. For example, in this Ruby code a “block” (a name Ruby uses for anonymous functions) is passed:

```
def scan(lines)
  lines.each do |t|
    if t.starts_with? '#' yield t
  end
end
scan(array) { |x| puts x }
```

This mechanism may be implemented in EO:

```
[lines b] > scan
  lines.each > @
    [t] >>
      if. > @
        t.starts-with "#"
        b t
        true
scan
  array
  [x] >>
    io.stdout x > @
```

Here, the anonymous function is passed to the object `scan` as an argument `b`. The “call” of this function is the dataization of its copy, performed by the `if` atom.

10 Generators

This section is not valid, must be rewritten!

A generator is a routine that can be used to control the iteration behavior of a loop. For example, this PHP program will print the first ten Fibonacci numbers:

```
function fibonacci(int $limit):generator {
    yield $a = $b = $i = 1;
    while (++$i < $limit) {
        $b = $a + $b;
        yield $b - $a;
        $a = $b;
    }
}
foreach (fibonacci(10) as $n) {
    echo "$n\n";
}
```

This mechanism may be implemented in EO:

```
[limit f] > fibonacci
memory 0 > a
memory 0 > b
memory 0 > i
seq * > @
  a.write 1
  b.write 1
  f 0
  while.
    seq (i.write (i.plus 1)) (i.lt limit)
    [idx]
      seq * > @
        b.write (a.plus b)
        a.write (b.minus a)
        f (b.minus a)
      true
fibonacci > @
10
[n]
  io.stdout > @
  tt.sprintf "%d\n" n
```

Here, the generator is turned into an abstract object `fibonacci` with an extra parameter `f`, which is specified with an abstract object argument that prints what is given as `n`.

11 Types and Type Casting

This section is not valid, must be rewritten!

A type system is a logical system comprising a set of rules that assign a property called a type to various constructs of a computer program, such as variables, expressions, functions, or modules. The main purpose of a type system is to reduce possibilities for bugs in computer programs by defining interfaces between different parts of a computer program, and then checking that the parts have been connected in a consistent way. In this example, a Java method `add` expects an argument of type `Book` and compilation would fail if another type is provided:

```
class Cart {
    private int total;
    void add(Book b) {
        this.total += b.price();
    }
}
```

The restrictions enforced by the Java type system at compile time through types `Cart` and `Book` may be represented in EO using decorators, for example:

```
[] > original-cart
memory 0 > total
[b] > add
    total.write (total.plus (b.price))
[] > cart
original-cart > @
[b] > add
    if.
        b.subtype-of (tt.text "Book")
        @.add b
    []
    error "Type mismatch, Book expected" > @
```

Here, it is expected that the parameter `b` is defined in a “class” that has a `subtype-of` attribute, which may also be provided by a decorator (a simplified example):

```
[] > original-book
  memory 0 > price
>[] > book
  original-book > @
  [t] > subtype-of
    t.eq "Book" > @
>[] > price
  @.price > @
```

This decoration may be simplified through a “fluent” supplementary object:

```
type "Cart" > cart-type
.super-types "Object" "Printable"
.method "add" "Book"
cart-type original-cart > cart
```

Here, the `type` object implements all necessary restrictions that the Java type system may provide for the type `Cart` and its methods.

Type casting, which is a mechanism for changing an expression from one data type to another, may also be implemented through the same decorators.

12 Reflection

This section is not valid, must be rewritten!

Reflection is the ability of a process to examine, introspect, and modify its own structure and behavior. In the following Python example, the method `hello` of an instance of class `Foo` is not called directly on the object but is first retrieved through reflection functions `globals` and `getattr`, and then executed:

```
def Foo():
    def hello(self, name):
        print("Hello, %s!" % name)
obj = globals()["Foo"]()
getattr(obj, "hello")("Jeff")
```

It may be implemented in EO by encapsulating additional meta information in classes explained in Section 6.

12.1 Monkey Patching

This section is not valid, must be rewritten!

Monkey patching is making changes to a module or class while the program is running. This JavaScript program adds a new method `print` to the object `b` after the object has already been instantiated:

```
function Book(t) { this.title = t; }
var b = new Book("Object Thinking");
b.print = function() {
  console.log(this.title);
}
b.print();
```

This program may be translated to EO, assuming that `b` is being held by an attribute of a larger object, for example `app`:

```
[] > app
  cage 0 > b
  b' > copy
  seq * > @
    b.write
      [] > book
      [t] > new
        memory "" > title
        title.write t > @
  copy.<
  b.write
    [] > book
    [t] > new
      seq * > @
      []
      copy > @
      [] > print
      io.stdout (^ .title)
  b.print
```

Here, the modification to the object `book` happens by making a copy of it, creating a decorator, and then storing it where the original object was located.

13 Static Methods

A static method (or static function) is a method defined as a member of an object but accessible directly from an API object's constructor, rather than from an object instance created via the constructor. For example, this C# class consists of a single static method:

```
class Utils {
  public static int max(int a, int b) {
    if (a > b) return a;
    return b;
  }
}
```

It may be converted to the following EO code, since a static method is nothing more than a “global” function:

```
[a b] > utils-max
  if. > @
    a.gt b
    a
    b
```

14 Inheritance

This section is not valid, must be rewritten!

Inheritance is the mechanism of basing a class upon another class while retaining similar implementation. In this Java code class `Book` inherits all methods and non-private attributes from class `Item`:

```
class Item {
  private int p;
  int price() { return p; }
}
class Book extends Item {
  int tax() { return price() * 0.1; }
}
```

It may be represented in EO like this:

```
[] > item
  memory 0 > p
[] > price
  p > @
[] > book
  item > i
[] > tax
  (ms.number (i.price)).as-float.times 0.1 > @
```

Here, composition is used instead of inheritance.

14.1 Prototype-Based Inheritance

This section is not valid, must be rewritten!

So-called prototype-based programming uses generalized objects, which can then be cloned and extended. For example, this JavaScript program defines two objects, where `Item` is the parent object and `Book` is the child that inherits the parent through its prototype:

```

function Item(p) { this.price = p; }
function Book(p) {
  Item.call(this, p);
  this.tax = function () {
    return this.price * 0.1;
  }
}
var t = new Book(42).tax();
console.log(t); // prints "4.2"

```

This mechanism of prototype-based inheritance may be translated to the following EO code, using the mechanism of decoration:

```

[p] > item
memory 0 > price
[] > new
  price.write p > @
[] > book
  [p] > new
    item p > @
    [] > tax
      times. > @
      as-float.
      ms.number (~.price)
      0.1
io.stdout
  tt.sprintf
    "%f"
  tax.
  book.new 42

```

14.2 Multiple Inheritance

This section is not valid, must be rewritten!

Multiple inheritance is a feature of some object-oriented computer programming languages in which an object or class can inherit features from more than one parent object or parent class. In this C++ example, the class **Jack** has both **bark** and **listen** methods, inherited from **Dog** and **Friend** respectively:

Reducing Programs to Objects

```
#include <iostream>
class Dog {
    virtual void bark() {
        std::cout << "Bark!";
    }
};
class Friend {
    virtual void listen();
};
class Jack: Dog, Friend {
    void listen() override {
        Dog::bark();
        std::cout << "Listen!";
    }
};
```

It may be represented in EO like this:

```
[] > dog
[] > bark
    io.stdout "Bark!" > @
>[] > friend
[] > listen
>[] > jack
    dog > d
    friend > f
    [] > listen
        seq * > @
            d.bark
            io.stdout "listen!"
```

Here, inherited methods are explicitly listed as attributes in the object `jack`. This is very close to what would happen in the virtual table of a class `Jack` in C++. The EO object `jack` just makes it explicit.

15 Method Overloading

This section is not valid, must be rewritten!

Method overloading is the ability to create multiple functions with the same name but different implementations. Calls to an overloaded function will run a specific implementation of that function appropriate to the context of the call, allowing one function call to perform different tasks depending on context. In this Kotlin program two functions are defined with the same name, while only one of them is called with an integer argument:

```
fun foo(a: Int) {}
fun foo(a: Double) {}
foo(42)
```

It may be represented in EO like this:

```
[args...] > foo
  (args.at 0) > a0
  if.
    a0.subtype-of "Int"
    first-foo a0
    second-foo a0
foo 42
```

This code expects arguments of `foo` to be equipped with the type system suggested in Section 11. The attribute `subtype-of` will help dispatch the call to the right objects.

16 Java Generics

This section is not valid, must be rewritten!

Generics extend Java's type system to allow a type or method to operate on objects of various types while providing compile-time type safety. For example, this Java class expects another class to be specified as `T` before use:

```
class Cart<T extends Item> {
  private int total;
  void add(T i) {
    total += i.price();
  }
}
```

It may be represented in EO like this:

```
[] > cart
memory 0 > total
[i] > add
  total.write > @
  total.plus (i.price)
```

As the example demonstrates, the presence of generics in class declarations may be ignored, since EO is a language without types and type checking.

17 C++ Templates

This section is not valid, must be rewritten!

Templates are a feature of the C++ programming language that allows functions and classes to operate with generic types, allowing a function or class to work with many different data types without being rewritten for each one.

Reducing Programs to Objects

```
template<typename T> T max(T a, T b) {  
    return a > b ? a : b;  
}  
  
int x = max(7, 42);
```

It may be represented in EO like this:

```
[a b] > max  
  if. > @  
    a.gt b  
    a  
    b  
max 7 42 > x
```

As the example demonstrates, the presence of templates may be ignored since EO is a language without types and type checking.

18 Mixins

This section is not valid, must be rewritten!

A mixin is a class that contains methods for use by other classes without having to be the parent class of those other classes. The following code demonstrates how a Ruby module is included in a class:

```
module Timing  
  def recent?  
    @time - Time.now < 24 * 60 * 60  
  end  
end  
  
def News  
  include Timing  
  def initialize(t)  
    @time = t  
  end  
end  
  
n = News.new(Time.now)  
n.recent?
```

This code may be represented in EO by just copying the method `recent?` to the object `News` as if it was defined there.

19 Annotations

This section is not valid, must be rewritten!

In Java, an annotation is a form of syntactic metadata that can be added to source code; classes, methods, variables, parameters, and Java packages may be annotated. Later, annotations may be retrieved through the Reflection API. For example, this program analyzes the annotation attached to the class of the provided object and changes the behavior depending on one of its attributes:

```

interface Item {}
@Ship(true) class Book { /*...*/ }
@Ship(false) class Song { /*...*/ }
class Cart {
    void add(Item i) {
        /* add the item to the cart */
        if (i.getClass()
            .getAnnotation(Ship.class)
            .value()) {
            /* mark the cart as shippable */
        }
    }
}

```

The code may be represented in EO using classes suggested in Section 6:

```

[] > book
  ship true > a1
[] > new
  [] > @
[] > song
  ship FALSE > a1
[] > new
  [] > @
[] > cart
  [i] > add
    # Add the item to the cart
    if. > @
      i.a1.value
      # Mark the cart shippable
      true
      FALSE

```

Annotations become attributes of objects, which represent classes in EO, as explained in Section 6: `book.a1` and `song.a1`.

20 Traceability

This section is not valid, must be rewritten!

A certain amount of semantic information may be lost during the translation from a more powerful programming language to EO objects, such as, for example, names, line numbers, comments, etc. Moreover, it may be useful to have the ability to trace EO objects back to the original language constructs from which they were derived. For example, a simple C function:

Reducing Programs to Objects

```
int f(int x) {  
    return 42 / x;  
}
```

It may be mapped to the following EO object:

```
[x] > f  
  [] > @  
    "src/main.c:1-1" > source  
    42.div x > @  
    "src/main.c:0-2" > source
```

Here, the synthetic **source** attribute represents the location in the source code file with the original C code. It is important to ensure during translation that the name **source** does not conflict with a possibly similar name in the object.

21 Conclusion

We demonstrated how some language features often present in high-level object-oriented languages, such as Java or C++, may be expressed using objects. We used EO as a destination programming language because of its minimalistic semantics: it has no language features aside from objects and their composition and decoration mechanisms.