Wiki

This Wiki explains the uses of the functions that can be used for the GUI, allowing for the GUI programmer to quickly find what function they need and how it can be used in order to speed up development

Us	erManager	2
	getUserProfileImage	2
	getUserProfiles	2
	getNumberOfUserProfiles	2
	moveNewUserProfileToUserFolder	3
	clearTemporaryProfileImageHolder	3
	getUserJsonPath	3
	changeUserPassword	3
	deleteUserFolder	4
	changeUserPassword	4
Tools		4
	getRecipelmage	4
	getDietImage	5
	linkTagAndDietIcons	5
	loadImage	5
	getNumberOfRecipesForSpecificDiet	6
Search		6
	getRecipeSearchResults	6
	getIngredientSearch	6

UserManager

\sim		D١	/IF	۱۸/.
	, –	\neg	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	vv:

This class contains code relating to the login flow

getUserProfileImage

OVERVIEW:

Used for getting a users image

TAKES:

1. String id

This is the user id that you want the image for

RETURNS:

1. Image

This is the users image if they have one if not it returns the default image

getUserProfiles

OVERVIEW:

Used for getting the users names, images and ids

TAKES:

RETURNS:

1. List<DataStructures.StringImageIdPair>

This is a custom data class which contains **String** username, **String** userld, **Image** image. Variables can be retrieved via **getText()**, **getId()**, **getImage()**

getNumberOfUserProfiles

OVERVIEW:

Used for getting the number of users in the system

TAKES:

RETURNS:

1. Int numberOfProfiles

moveNewUserProfileToUserFolder
OVERVIEW:
Used for when a new user is created to move their profile picture If added form temporary folder to the user folder
TAKES:
1. String userId
RETURNS:
clearTemporaryProfileImageHolder
OVERVIEW:
When 'Create New User' is selected in the login menu or at the start of the program, it should clear the temporary image if the last time the program was run the user creation process wasn't completed, but an image was uploaded.
TAKES:
RETURNS:
getUserJsonPath
OVERVIEW:
Used for getting the path to the specified users json
TAKES: 1. String userID
RETURNS: 1. String userJsonPath
changeUserPassword

TAKES:

OVERVIEW:

1. **User** user , **String** currentPassword, **String** newPassword

RETURNS: 1. E

changed

1. Boolean

If the current passwords don't match False, else True and the password was

deleteUserFolder

OVERVIEW:

Used for deleting a specific user folder

TAKES:

1. String userld

RETURNS:

changeUserPassword

OVERVIEW:

Used for changing a users password

TAKES:

1. User user, String currentPassword, String newPassword

RETURNS:

1. Boolean

Changed or not based on if the currentPassword matched the one in the system

Tools

OVERVIEW:

Contains general functions that can be used throughout the program

getRecipeImage

OVERVIEW:

Used for getting the image for a recipe

TAKES:

1. (String recipeName)

This image name can be gotten by using recipe.generateImageName();

RETURNS:

1. Image

getDietImage

OVERVIEW:

Used for getting the image for a diet

TAKES:

1. (String dietName)

This name can be gotten by using diet.getName();

RETURNS:

1. Image

linkTagAndDietIcons

OVERVIEW;

Used for when displaying a recipe (**DO NOT USE when displaying the partial information in the recipe search function only when showing the whole recipe page**): pairs the diets and tags with their related icons

TAKES:

1. (Recipe recipe)

This is the recipe that you want to display

RETURNS:

1.List<DataStructures.StringImagePair>

This is a custom data class which contains **String** text (the diet/tag), **Image** image. Variables can be retrieved via **getText()**, **getImage()**

loadImage

OVERVIEW:

This function is used for loading in a user selected image and storing it in the given path

TAKES:

1. (String userld, BufferedImage image)

This is used when using JFrame to get the image via directory

2. (String imagePath)

This is used when the image is already in the users profile directory

RETURNS:				
1. NULL				
2. NULL				
getNumberOfRecipesForSpecificDiet				
OVERVIEW;				
TAKES:				
1. (String diet, ArrayList <recipe> recipes)</recipe>				
This is the recipe that you want to display				
RETURNS: 1. Int				
This is the number of recipes for that specific diet				
Search				
OVERVIEW:				
Contains the two search functions				
getRecipeSearchResults				
OVERVIEW:				
Used for searching via the name, level or diet of a recipe/s				
TAKES: 1. (String query, ArrayList <recipe> recipeHolder, ArrayList<integer> userSavedRecipes, String userSavedDiet, Boolean showAllRecipes)</integer></recipe>				
showAllRecipes is for if a user wants to see all recipes not just ones on their diet				
RETURNS: 1. ArrayList <recipe> returnedRecipes</recipe>				

OVERVIEW:

getIngredientSearch

Used for searching via ingredients

TAKES:

1. (ArrayList<Recipe> recipeHolder, ArrayList<DataStructures.StringIntPair> ingredientQuery, String userSavedDiet, Boolean showAllRecipes)

showAllRecipes is for if a user wants to see all recipes not just ones on their diet **RETURNS:**

1. **ArrayList<Recipe>** returnedRecipes