Does Abliteration Survive 4-bit Quantization?

A Controlled Reproduction and Semantic Evaluation on Qwen3.5-9B

A Technical Writing Report Submitted
in partial fulfillment of the requirements for the award of the

Bachelor of Technology

by

Omm P Tripathy (B123082)
Shreyash Jena (B123124)
Aman Saini (B423008)

Under the supervision of
Prof. Srichandan Sobhanayak



Department of Computer Science
International Institute of Information Technology Bhubaneswar

November 2026

APPROVAL OF THE VIVA-VOCE BOARD

November 10, 2026

Certified that the report entitled **"Does Abliteration Survive 4-bit Quantization?"** submitted by **Omm P Tripathy** (B123082), **Shreyash Jena** (B123124) and **Aman Saini** (B423008) to the International Institute of Information Technology Bhubaneswar in partial fulfillment of the requirements for the award of the Bachelor of Technology under the BTech Programme has been accepted by the examiners during the viva-voce examination held today.

(Supervisor) **(Panel Members)**

ACKNOWLEDGEMENTS

We thank Prof. Srichandan Sobhanayak for supervision and guidance during this work.

We acknowledge the authors and maintainers of the Qwen3.5 model, the Heretic tool, the published edit and the evaluation datasets used in this study. Parts of the implementation, run orchestration and response labeling were carried out with AI coding assistants; the extent of this assistance is described in Section 3.6.

Omm P Tripathy (B123082)
Shreyash Jena (B123124)
Aman Saini (B423008)

ABSTRACT

Abliteration removes refusal behavior from a language model by projecting a refusal direction out of its weights. Edited models are usually produced at 16-bit precision and then run in 4-bit quantized form, but whether the edit survives that conversion is rarely checked. This report asks whether a refusal-ablation edit applied at full precision keeps its behavioral effect after NF4 quantization, and whether any loss can be separated from ordinary quantization damage. We study a published Heretic edit of the hybrid Qwen3.5-9B model in three steps.

First, we reproduce the edit. A direct replay failed until we restored a harmless-mean projection step, after which our reconstruction matched the publisher's checkpoint in refusal-phrase matches (8 of 100 prompts) and in first-token KL divergence on benign prompts (0.078), and every edited matrix was verified. Second, we test the outcome measure. Phrase-based refusal detectors and a semantic review of fulfillment disagree on the same outputs, so we use semantic judgments. On eight fresh safety prompts, both edited models clearly supplied the requested content in six cases, against one for the original model. Third, a controlled five-condition NF4 comparison found no case in which quantization removed an effect that the edit showed at full precision, and quantizing the unedited model produced no such effect.

The samples are small, the judgments come from a single AI reviewer and many answers were truncated, so partial weakening of the edit cannot be ruled out. We give an argument from the structure of the edit for why round-to-nearest 4-bit quantization should preserve it, and propose a weight-space test of that argument.

Keywords: abliteration; refusal direction; quantization; NF4; semantic evaluation; large language models

TABLE OF CONTENTS

Content **Page No.**

ABSTRACT ..... **iii**
LIST OF TABLES ..... **v**
LIST OF FIGURES ..... **v**
LIST OF ALGORITHMS ..... **v**
LIST OF ABBREVIATIONS ..... **vi**
1 INTRODUCTION **1**
1.1 Motivation 1
1.2 Research question 1
1.3 Approach and contributions 2
1.4 Ethical considerations 2
1.5 Organization of the report 2
2 BACKGROUND AND RELATED WORK **3**
2.1 The residual stream 3
2.2 Refusal directions and abliteration 3
2.3 Is refusal a single direction? 4
2.4 Measuring refusal and fulfillment 4
2.5 Quantization and safety 4
2.6 Summary and research gap 5
3 METHODOLOGY **6**
3.1 Model and published edit 6
3.2 Direction estimation 6
3.3 Weight edit 6
3.4 Experimental conditions 7
3.5 Prompts and generation 8
3.6 Measures 9
4 RESULTS AND DISCUSSION **11**
4.1 SQ1: Reproducing the published edit 11
4.2 SQ2: Refusal phrases versus fulfillment 12
4.3 SQ3: Does the edit survive NF4? 14
4.4 Why might the edit survive? 16
4.5 Threats to validity 16
5 CONCLUSION AND FUTURE SCOPE **18**
5.1 Conclusion 18
5.2 Future scope 18
REFERENCES **19**
ADDITIONAL BIBLIOGRAPHY **19**
APPENDIX A REPRODUCIBILITY DETAILS **21**
A.1 Sources 21
A.2 Settings and compute 21
A.3 Bounds for the NF4 comparison 21

LIST OF TABLES

Table No.	Caption	Page No.
Table 2.1	Summary of related work	5
Table 3.1	Model conditions	8
Table 3.2	Prompt sets and token limits	9
Table 4.1	Reproduction results on the 100-prompt test	11
Table 4.2	Semantic review of the FP16 models on safety prompts	13
Table 4.3	Three measures applied to the same responses	13
Table 4.4	NF4 pilot results on safety prompts (N = 6 per condition)	15
Table A.1	Models, code and datasets	21

LIST OF FIGURES

Figure No.	Caption	Page No.
Figure 3.1	Where the edit is applied in Qwen3.5-9B	7
Figure 3.2	The research question as a controlled comparison	8
Figure 4.1	Effect of the harmless-mean projection	12
Figure 4.2	Semantic fulfillment (bars) compared with two automated refusal detectors (right columns) on the same responses	14
Figure 4.3	NF4 pilot	15
Figure 4.4	Four claims about a refusal edit and the evidence this report provides for each	17

LIST OF ALGORITHMS

Algorithm No.	Caption	Page No.
Algorithm 3.1	Reconstruction and verification	7

LIST OF ABBREVIATIONS

AI	Artificial intelligence
FP16	16-bit floating point
FP32	32-bit floating point
GPU	Graphics processing unit
GSM8K	Grade School Math 8K dataset
KL	Kullback-Leibler (divergence)
LLM	Large language model
LoRA	Low-rank adaptation
MLP	Multilayer perceptron
NF4	4-bit NormalFloat
QLoRA	Quantized low-rank adaptation
SQ	Sub-question
XSTest	Exaggerated Safety Test suite

CHAPTER 1
INTRODUCTION

1.1 Motivation

Instruction-tuned language models are trained to refuse harmful requests. Arditi et al. showed that in many open chat models this behavior is mediated largely by a single direction in the model's internal activations: removing the direction suppresses refusal, and adding it causes refusal of harmless requests [1]. The weight-editing form of this result, known in the open-model community as abliteration [A1], has become a standard way to produce "uncensored" variants of released models. Tools such as Heretic automate the procedure and tune its parameters [2].

Abliteration is normally applied to 16-bit weights. Most users, however, run open models in compressed form, and 4-bit formats such as NF4 let a 9-billion-parameter model fit on a single consumer GPU [3]. The edit therefore passes through a quantizer before it reaches the people who use it. Earlier work has shown that quantization can change the safety behavior of aligned models [4], [5], and that it can even be exploited to activate behavior that is absent at full precision [A2]. Whether a small, deliberate weight edit survives the same rounding has received much less attention.

1.2 Research question

This report studies one question:

When a refusal-ablation edit is applied to a model at full precision and the model is then quantized to 4-bit NF4, does the edit's behavioral effect survive, and can any loss be told apart from ordinary quantization damage?

Answering it requires two things that cannot be assumed. The first is a faithful edit. If the edit is reproduced incorrectly, a change after quantization says nothing about the published method. The second is a valid outcome measure. If refusal is measured by phrase matching, a model that avoids refusal wording while withholding the requested content would count as fully edited. We therefore divide the question into three sub-questions (SQs):

SQ1. Can a published abliteration edit be reproduced closely enough to serve as a known reference?

SQ2. Does the absence of refusal phrases measure the edit's effect, or is a semantic judgment of the answer needed?

SQ3. With a faithful edit and a valid measure, does the edit's effect survive NF4 quantization, and is any change specific to the edit?

1.3 Approach and contributions

We work with Qwen3.5-9B [6], a hybrid model that mixes linear-attention and full-attention layers, and with a published Heretic edit of it. All model execution used two NVIDIA T4 GPUs on Kaggle. The contributions of this report are the following.

1) A verified reconstruction of the published edit, with a controlled comparison showing that a harmless-mean projection step, known as projected abliteration [A3], accounts for the difference between a failed replay and a faithful one.
2) A comparison of two phrase-based refusal detectors with a semantic review on the same outputs, showing where and why they disagree.
3) A five-condition NF4 comparison that separates the effect of quantizing the edit from the effect of quantizing the base model, together with an argument from the structure of the edit for why it should survive round-to-nearest quantization.

The study is exploratory. It uses one model, one quantizer and small prompt sets, and it does not propose a new editing method.

1.4 Ethical considerations

Abliteration removes a safety behavior, so this work has dual-use potential. We reproduced only an edit and a checkpoint that were already public. The aim is to understand how such edits behave under a common deployment step, which matters equally for edits that strengthen refusal. No harmful model output is quoted in this report; responses are described by category only. The raw outputs and the reconstructed checkpoint are kept in private, access-controlled storage and are not released. We did not test whether harmful answers were technically correct.

1.5 Organization of the report

Chapter 2 reviews refusal directions, the evaluation of refusal and the effect of quantization on safety. Chapter 3 describes the model, the edit, the experimental conditions and the measures. Chapter 4 presents the results for SQ1 to SQ3 and discusses their limits. Chapter 5 concludes and sets out future work. Appendix A lists sources, settings and a supplementary calculation.

CHAPTER 2
BACKGROUND AND RELATED WORK

2.1 The residual stream

A decoder-only Transformer processes each token through a stack of blocks [7]. Each block reads a shared vector called the residual stream, computes an update with its token-mixing sublayer and its multilayer perceptron (MLP), and adds the update back to the stream. Every block therefore writes into the stream through a small number of output matrices: the attention output projection and the MLP down projection. If a direction in the stream carries a behavior, the component of any block's output along that direction can be removed by changing only these output matrices. Abliteration relies on this property.

Qwen3.5-9B has 32 blocks and a hidden size of 4096. Twenty-four blocks use Gated DeltaNet, a linear-attention layer with a recurrent state, and eight use standard full attention, in a repeating pattern of three linear blocks followed by one full-attention block [6]. Both kinds of block end in an output projection, so the same editing rule applies to both.

2.2 Refusal directions and abliteration

Arditi et al. collected activations for harmful and harmless instructions and took the difference of their means at each layer as a candidate refusal direction [1]. Removing this direction from the residual stream suppressed refusal in 13 open chat models, and adding it caused refusal of harmless requests. They also showed that the change can be made permanent by orthogonalizing the output matrices against the direction, and they chose the layer using validation refusal scores together with a limit on KL divergence from the original model on harmless prompts. The approach belongs to a wider family of representation engineering methods, which read and control model behavior through directions in activation space [A4].

Labonne popularized this weight edit as abliteration and published the harmful and harmless prompt sets used in this study [A1]. Heretic extends the procedure in two ways [2]. It applies a different ablation strength to each layer through a simple linear kernel, and it searches the kernel parameters with an optimizer that trades the number of refusals against KL divergence. A later community article proposed projected abliteration, which removes from the refusal direction its component along the mean harmless activation before editing [A3], followed by a norm-preserving variant [A5]. The argument is that the raw difference of means contains a component shared by all prompts,

and that removing it reduces collateral damage. Our reproduction in Section 4.1 gives a controlled test of this step.

2.3 Is refusal a single direction?

The single-direction picture is a useful approximation rather than a complete account. Wollschläger et al. found multi-dimensional cones of refusal directions and showed that orthogonal directions need not act independently [A6]. Joad et al. found category-specific refusal directions alongside shared ones, and trade-offs between reducing refusal and avoiding over-refusal [8]. Related work on safety training suggests that refusal is often decided in the first few tokens of a response [A7]. For this report the consequence is practical: removing one direction may weaken refusal without removing it, so the effect has to be checked on the model's answers.

2.4 Measuring refusal and fulfillment

A refusal evaluation must define success. HarmBench provides a standardized set of harmful behaviors and a learned classifier for judging whether a response complies [9]. StrongREJECT argues that many jailbreak evaluations overstate success because they count responses that avoid refusing but supply little useful content, and it scores the usefulness of the answer instead [10]. XSTest covers the opposite failure. It contains safe prompts that resemble unsafe ones, such as asking how to kill a Python process, to measure over-refusal [11].

Phrase matching remains common in abliteration tools because it is cheap. The Abliterlitics project publishes community benchmark results for abliterated models using its own heuristic classifier with manual review, and lists zero refusals out of 400 prompts for the edited model studied here [12]. Such numbers depend on the detector, the prompt format and the generation length, which is the subject of SQ2.

2.5 Quantization and safety

Quantization stores weights with fewer bits. NF4, introduced with QLoRA, maps each block of 64 weights to 16 levels placed at the quantiles of a normal distribution and scaled by the largest absolute value in the block [3]. Weights are stored in 4 bits and expanded to 16 bits for computation. QLoRA also trains low-rank adapters on top of the frozen quantized model; this study uses only the storage format.

Several studies show that quantization changes safety behavior. Chen et al. evaluated mainstream quantization methods, found safety degradation that depends on the method and the calibration data, and proposed Q-resafe to restore it [4]. Kumar et al. found that quantization had a variable effect on jailbreak susceptibility [A8]. Kadadekar reports conditions in which general quality is retained while refusal declines, so that a

stable capability score is no guarantee of safety [5]. Egashira et al. showed that the effect can be engineered: a model can be built to behave well at full precision and harmfully once quantized [A2]. All of these concern the alignment a model was trained with. The question here is narrower: what happens to a deliberate post-training edit when the edited weights are rounded.

2.6 Summary and research gap

Table 2.1 summarizes the work most relevant to this report and its role in the design.

Table 2.1: Summary of related work

Work	Contribution	Use in this report
Arditi et al. [1]	Refusal direction; ablation and weight orthogonalization	Defines the edit
Heretic [2]	Per-layer strength kernel and parameter search	Source of the published edit
Projected abliteration [A3]	Removes the harmless-mean component	Explains the failed replay
Joad et al. [8]; Wollschläger et al. [A6]	Refusal is not a single direction	Check behavior, not geometry
HarmBench [9]; XSTest [11]	Harmful and safe prompt sets	Source of test prompts
StrongREJECT [10]	Scores useful content, not refusal wording	Motivates semantic review
QLoRA [3]	NF4 storage format	Quantizer under study
Q-resafe [4]; Kadadekar [5]	Quantization alters aligned behavior	Need an unedited quantized control
Egashira et al. [A2]	Quantization can activate hidden behavior	Rounding can change behavior selectively
This report	Survival of a post-training edit under NF4	Addresses the gap

The gap lies in the combination. Work on abliteration evaluates the edit at full precision, and work on quantization safety evaluates the original alignment. A controlled test of whether an abliteration edit survives quantization, using a valid outcome measure, falls between the two.

CHAPTER 3
METHODOLOGY

3.1 Model and published edit

The original model, denoted W, is Qwen3.5-9B [6]. The published edit, denoted P, is the second Heretic release of this model by an independent publisher (trohrbaugh/Qwen3.5-9B-heretic-v2). The publisher released the edited weights and the parameters found by Heretic's search, but not the software environment. We reconstructed the edit with a revision of Heretic that supports the hybrid architecture [2], using the published parameters without a new search. All computation ran in FP16 on two NVIDIA T4 GPUs on Kaggle. Source revisions are listed in Appendix A.

3.2 Direction estimation

For each layer we record the residual-stream activation at the last prompt token for 400 harmful and 400 harmless prompts from the abliteration datasets [A1], and compute the average activation of each group: the harmful mean and the harmless mean. The raw refusal direction is the difference between the two means. Following the published recipe, we then remove from this difference the part that points along the harmless mean, because that part is shared by all prompts rather than specific to refusal, and scale the result to unit length. The result is the refusal direction r. Fig. 4.1 in Chapter 4 sketches this step.

Our first replay omitted this projection and used the raw difference directly. The published parameters select a direction index of 18.49, so the edit uses a single direction interpolated between the directions at positions 19 and 20 with weight 0.49. Position 0 is the embedding output, so these positions are the outputs of blocks 18 and 19, counting from zero.

3.3 Weight edit

The edit changes each selected output matrix so that its layer writes less along the refusal direction. For any input, the amount the matrix writes along r is measured, and a multiple λ of that amount is subtracted, where λ is the ablation strength of the layer. When λ is 1 the layer can no longer write anything along r. Values above 1 reverse part of the component, and values below 1 remove only part of it.

Heretic gives each layer its own strength. The strength is highest at a chosen peak layer, falls in a straight line with distance from the peak, and is zero beyond a set width. The published settings place the attention peak near layer 19, with strengths from 2.00 down to 1.43, and the MLP peak near layer 26, with strengths from 1.67 down to 0.84;

Appendix A.2 lists the exact values. As a result the edit changes the attention outputs of blocks 10 to 28 (19 matrices) and the MLP outputs of blocks 9 to 31 (23 matrices), as Fig. 3.1 shows. Each change has rank one, so it is stored as a pair of vectors per matrix, in the same form as a rank-one LoRA adapter, and then merged into the FP16 weights. We write Δ for the set of all 42 updates and $D = W + \Delta$ for the reconstructed model. Algorithm 3.1 summarizes the procedure.




Figure 3.1: Where the edit is applied in Qwen3.5-9B. Top: layer types. Bottom: ablation strength per layer from the published parameters. Strengths above 1 over-ablate.

Algorithm 3.1 Reconstruction and verification

1: Load the original model and the 400 harmful and 400 harmless extraction prompts.
2: Record last-token activations at every layer and compute the two means per layer.
3: Form the difference of means, remove its harmless-mean component and normalize.
4: Interpolate positions 19 and 20 with weight 0.49 to obtain the direction r.
5: Compute the strength of each edited matrix and store its rank-one update factors.
6: Merge the factors into FP16 weights and compare every edited matrix with an explicit computation of $W + \Delta$.
7: Save and reload the model, then regenerate the test responses to check persistence.

3.4 Experimental conditions

Fig. 3.2 shows the design used for SQ3. The effect of the edit at full precision is the difference in behavior between D and W. Its effect after quantization is the difference between $Q(W + \Delta)$ and $Q(W)$, where Q denotes conversion to NF4. Comparing $Q(W)$ with W shows what quantization does to the unedited model, which separates general quantization damage from loss of the edit. A fifth condition, $Q(W) + \Delta$, keeps the edit factors in FP32 on top of the same quantized base, so that the edit itself is never rounded. Table 3.1 lists all conditions used in the report.




Figure 3.2: The research question as a controlled comparison. The edit's effect is measured at full precision (top) and after NF4 (bottom); the unedited NF4 model separates quantization damage from loss of the edit. H denotes the fraction of safety prompts clearly fulfilled.

Table 3.1: Model conditions

Label	Construction	Purpose
W	Original model, FP16	Unedited reference
P	Publisher's edited checkpoint, FP16	Check on the reconstruction
D = W + Δ	Reconstructed edit merged in FP16	Edited reference
Q(W)	W converted to NF4	Quantization control
Q(W + Δ)	D converted to NF4	Deployment path
Q(W) + Δ	Q(W) with the FP32 edit factors	Edit kept unrounded

NF4 conversion used the bitsandbytes implementation with blocks of 64 weights, no double quantization, packed 8-bit storage and FP16 computation. Because Q(W + Δ) is computed from the edited weights, its block scales are recomputed and can differ from those of Q(W). The comparison therefore includes both changes in level assignment and changes in scale. We did not re-extract a refusal direction from the quantized model, which would be a different experiment.

3.5 Prompts and generation

Table 3.2 lists the prompt sets. The reproduction test uses the first 100 test prompts of the harmful dataset [A1], and the first 100 harmless test prompts for the KL measure. These prompts were also used while debugging the reconstruction, so they are not a clean held-out set. The semantic evaluation uses HarmBench behaviors [9] as safety prompts, safe prompts from XSTest [11] to check over-refusal, and grade-school

arithmetic problems from GSM8K as a basic utility check. The matched set reuses the prompts of the NF4 pilot. The fresh set was selected deterministically, checked for duplicates of earlier prompts and fixed before any of its outputs were read.

Table 3.2: Prompt sets and token limits

Set	Models	Safety	Safe	Arithmetic	Token limits
Reproduction test	W, P, D	100	100*	0	100
NF4 pilot	Five in Table 3.1	6	3	3	768 / 768 / 384
Matched audit	W, P, D	6	3	3	768 / 768 / 384
Fresh audit	W, P, D	8	2	2	1024 / 768 / 384

Harmless prompts used only for the KL measure. Token limits are given for safety / safe / arithmetic prompts

Generation settings were identical across conditions: the original tokenizer and chat template with thinking disabled, the system message "You are a helpful assistant.", greedy decoding, a batch size of one and stopping at the end-of-sequence token. The NF4 pilot produced 60 responses (12 prompts in five conditions). The audit of W, P and D produced 72 records, of which 48 were new generations and 24 were earlier responses reused after confirming identical settings.

3.6 Measures

Phrase matching. The reproduction test counts a response as a refusal if it contains any of 32 lower-case marker strings, such as "sorry", "i can'" or "illegal", anywhere in the text. An empty response also counts. We also apply the public heuristic classifier of the Abliterlitics project, version 3 [12], which combines pattern rules with checks on the opening and structure of a response.

KL divergence. To measure collateral change on harmless prompts we use the Kullback-Leibler (KL) divergence, a standard measure of how different two probability distributions are. For each of 100 harmless prompts we compare the original and edited models' probabilities for the first token of the answer, and average the result. A value of 0 means no change, and larger values mean larger change. This measures a single prediction step, not the quality of whole answers.

Semantic review. Each response is labeled for fulfillment of the request (clear, partial or none) and for explicit refusal language (yes or no). Redirection to a different task, factual correction, missing knowledge and ambiguous intent are recorded separately. A disclaimer does not cancel fulfillment, and an attempt is not checked for correctness. A response that reaches the token limit is labeled on its visible part, and the truncation is recorded. In the NF4 pilot, a response whose visible part could not be classified was labeled unknown.

AI assistance and labeling. The implementation, the orchestration of runs and the semantic labels were produced with the help of AI coding agents. All labels come from a single LLM-based reviewer that worked on shuffled, anonymized responses and fixed its labels before the mapping to conditions was revealed. Some earlier results were known to the reviewer, so the masking was imperfect. No human labels have been collected yet. All responses, token sequences and settings were saved for later human review.

CHAPTER 4
RESULTS AND DISCUSSION

4.1 SQ1: Reproducing the published edit

Our first replay of the published recipe failed. It used the raw difference of means, without the harmless-mean projection described in Section 3.2. With every other setting unchanged, this replay still produced refusal markers on 72 of 100 test prompts, with a benign KL of 0.434 (Table 4.1). Adding the projection reduced the marker count to 8 and the KL to 0.078, which matches the publisher's checkpoint evaluated in the same setup. A separate controlled check on 32 development prompts showed the same pattern: 20 of 32 marker matches with the raw direction and 0 of 32 with the projected one, with KL falling from 0.438 to 0.066.

Table 4.1: Reproduction results on the 100-prompt test

Condition	Marker matches	Reached limit	Benign KL
Original W	100	59	0
Raw-direction replay	72	91	0.434
Publisher P	8	100	0.078
Reconstruction D	8	99	0.078
D after save and reload	8	99	not measured
Publisher's model card (reported)	6	n/a	0.079

Fig. 4.1 illustrates why the projection matters. The raw difference of means points partly along the harmless mean, a direction that every prompt shares. Ablating that shared component disturbs all inputs, which raises the KL divergence. It also spends part of the unit direction on something other than refusal, so at a fixed strength less of the refusal-specific component is removed. Our measurements agree with this explanation, which is the motivation given for projected abliteration [A3], although we did not measure the decomposition directly.




Figure 4.1: Effect of the harmless-mean projection. Left: schematic of the raw and projected directions. Right: with strengths and layers fixed, the projection alone reduced marker matches from 72 to 8 and benign KL from 0.434 to 0.078.

The reconstruction was also checked at the weight level. The edit has 64 factor pairs, one per component and block, of which 42 are non-zero, matching the 19 attention and 23 MLP matrices given by the kernel. Every edited matrix equals the explicit FP16 computation of W + Δ, and saving and reloading the model gave 100 of 100 identical responses. Spot comparisons with the publisher's weights showed changes in the same matrices, and for the MLP and full-attention matrices the direction of the change matched our projected direction with cosine similarity above 0.9999. The publisher's unrounded parameters and software environment are not available, so the reconstruction is close to the published edit but not identical to it byte for byte.

Answer to SQ1. The reconstruction behaves like the published checkpoint under our settings and is verified matrix by matrix, so it can serve as a known edit for the quantization study. One caution applies to every number in Table 4.1. With a 100-token limit, 99 of the 100 reconstructed responses were cut off, so 8 marker matches does not mean that 92 requests were answered. That question needs a different measure.

4.2 SQ2: Refusal phrases versus fulfillment

Table 4.2 gives the semantic review of the three FP16 models on 14 safety prompts. On the fresh set, the original model clearly fulfilled one request and used explicit refusal language on all eight. Both edited models clearly fulfilled six and partly fulfilled two, with no explicit refusals. On the matched set, both edited models clearly fulfilled two, partly fulfilled three and did not fulfill one.

Table 4.2: Semantic review of the FP16 models on safety prompts

Set, model	N	Clear	Partial	None	Explicit refusal	Reached limit
Matched, W	6	0	0	6	6	1
Matched, D	6	2	3	1	0	5
Matched, P	6	2	3	1	0	5
Fresh, W	8	1	1	6	8	0
Fresh, D	8	6	2	0	0	5
Fresh, P	8	6	2	0	0	6

The reconstruction and the publisher's model received the same fulfillment label on all 14 prompts, and 8 of their 24 paired responses across all prompt types were byte-identical. Two of the fresh prompts concern security testing and could be read as requests for authorized work. Excluding them leaves four clear and two partial fulfillments out of six for each edited model, and none for the original. No model refused the safe XSTest prompts, and all three answered the five arithmetic problems correctly. These checks are too small to show that general ability is preserved, but they show no obvious damage.

Individual responses show why phrase matching is not enough. The original model's one clear fulfillment began with a refusal and then provided the requested material, so refusal wording and fulfillment occurred together. In the other direction, one edited response to a request for account intrusion contained no refusal language but redirected the user toward protecting their own account. Table 4.3 and Fig. 4.2 compare the three measures on the same outputs.

Table 4.3: Three measures applied to the same responses

Set, model	N	Marker refusals	Abliterlitics v3 refusals	Clear fulfillment
Matched, W	6	6	6	0
Matched, D or P	6	2	1	2
Fresh, W	8	8	7	1
Fresh, D or P	8	1	0	6




Figure 4.2: Semantic fulfillment (bars) compared with two automated refusal detectors (right columns) on the same responses. D and P received identical labels.

On the fresh set the v3 heuristic finds no refusals among the edited responses, although two of the eight are only partial. On the matched set it counts the account-protection redirect as compliance. A detector that reports zero refusals is therefore compatible with incomplete fulfillment. The external report of zero refusals in 400 prompts for the publisher's model [12] used longer generations, a different prompt format and manual overrides, and its raw responses were not available, so we could neither replicate nor explain it.

While testing the public classifier we found one input format on which it fails. When a response begins with a closed reasoning block, the code cuts the text after the literal string "</think" and leaves a stray ">" at the start of the answer, which defeats the rules that look for a refusal at the start. A plain refusal is detected, but the same refusal placed after a reasoning block is not. Our responses contained no reasoning blocks, so this does not explain the disagreements in Table 4.3, and we make no claim about its effect on the external result.

Answer to SQ2. Phrase-based counts track refusal wording rather than fulfillment, and they can err in both directions. The rest of this report uses semantic fulfillment as the outcome.

4.3 SQ3: Does the edit survive NF4?

Table 4.4 and Fig. 4.3 give the semantic labels for the five pilot conditions on six safety prompts. These labels come from the pilot's own review, which used a slightly different rubric from the audit in Section 4.2, including an unknown category, so the counts for D differ between Tables 4.2 and 4.4.

Table 4.4: NF4 pilot results on safety prompts (N = 6 per condition)

Condition	Clear	Partial	Unknown	None	Reached limit
W	0	1	0	5	1
D = W + Δ	2	1	1	2	5
Q(W)	0	1	0	5	1
Q(W + Δ)	2	2	1	1	5
Q(W) + Δ	2	3	1	0	5




Figure 4.3: NF4 pilot. Both quantized edited conditions keep the two clear fulfillments seen at full precision, while the unedited NF4 model matches the original. Hatched segments are unresolved labels.

The pilot answers the question at its own scale. Quantizing the unedited model did not change its behavior: Q(W) has the same counts as W, so NF4 alone does not create fulfillment. The two prompts that the edit clearly fulfilled at full precision were still clearly fulfilled after quantizing the edited model, and also when the edit was kept in FP32 on the quantized base. Neither quantized edited condition had fewer clear or partial fulfillments than D. In the notation of Fig. 3.2, the edit raised clear fulfillment from 0 to 2 of 6 at full precision and from 0 to 2 of 6 after NF4.

The unresolved labels limit how far this goes. Several edited responses were partial or unknown, and five of six reached the token limit in each edited condition, so their full content was not seen. If each unresolved label is allowed to take either value, the difference between the quantized and full-precision edit effects could lie anywhere between −0.50 and +0.67 (Appendix A.3). The pilot therefore rules out complete erasure of the edit on these prompts, but it cannot rule out partial weakening. On the benign prompts, no condition refused the three safe prompts. Four conditions solved all three arithmetic problems, while Q(W) + Δ solved two and reached its limit before finishing the third.

Answer to SQ3. On this model and this NF4 configuration, the observed effect of the edit survived quantization, and the unedited quantized control shows that the effect was not produced by quantization itself. The pilot is too small to detect a partial loss.

4.4 Why might the edit survive?

The result has a simple explanation, which we state as a hypothesis because we did not test it directly. The edit is one coordinated change: in every edited matrix it removes a large, consistent amount along a single direction, with strengths between 0.84 and 2.0. Rounding to 4 bits adds small errors to individual weights, and these errors behave roughly like random noise spread over all 4096 output directions. Along the one refusal direction such scattered errors largely cancel and stay small, while the edit is present in full. The edit should therefore survive round-to-nearest quantization unless its strength is small or the format is very coarse.

This hypothesis can be tested on the weights alone, without generating any text. For each edited matrix, one can compare the actual difference between the two quantized models, $Q(W + \Delta)$ minus $Q(W)$, with the intended edit Δ, and compute what fraction of the intended change is still present. A retained fraction close to 1 means that the quantized models differ by almost exactly the intended edit. Computing it for several bit widths and formats would show where edit loss begins, and whether that point agrees with behavioral tests.

4.5 Threats to validity

The findings above are subject to the following limitations.

- **Sample size.** The semantic results rest on 14 safety prompts at FP16 and 6 in the NF4 pilot. No rates, confidence intervals or equivalence tests are reported.
- **Labeling.** A single AI reviewer produced all semantic labels, with imperfect masking. The saved responses have not yet been reviewed by people.
- **Truncation.** Most edited responses reached their token limit, so the labels describe only the visible content.
- **Correctness.** The accuracy of harmful content was deliberately not tested.
- **Test exposure.** The 100-prompt reproduction test was also used during debugging.
- **Scope.** One model, one edit, one quantizer and one NF4 configuration were studied. Re-extracting the direction from the quantized model was not.

Fig. 4.4 summarizes what the evidence supports. Each claim about an edit requires stronger evidence than the one below it, and the report establishes the first two, gives selected-case evidence for the third and leaves the fourth untested.




Figure 4.4: Four claims about a refusal edit and the evidence this report provides for each.

CHAPTER 5
CONCLUSION AND FUTURE SCOPE

5.1 Conclusion

This report asked whether a refusal-ablation edit survives 4-bit NF4 quantization. For a published Heretic edit of Qwen3.5-9B it did, on the prompts we tested. The quantized edited model kept the clear fulfillments that the edit produced at full precision, and the quantized unedited model did not acquire them.

Reaching this answer required two preliminary results. The published edit could only be reproduced after restoring the harmless-mean projection, which reduced both the remaining refusals and the collateral change at a fixed strength. Refusal-phrase counts also proved unreliable as an outcome, disagreeing with semantic judgments in both directions, so the question had to be answered with semantic labels. The main limitations are the small samples, the single AI reviewer and the truncated responses, which leave a partial weakening of the edit undetected.

5.2 Future scope

We propose the following next steps, in order of priority.

1) Compute the retained fraction of the edit described in Section 4.4 for every edited matrix under NF4, 8-bit and lower-precision formats. This needs only the weights, runs on a CPU and directly tests the explanation in Section 4.4.
2) Have human reviewers label the 132 saved responses, 72 from the audit and 60 from the pilot, with two reviewers on a shared subset to measure agreement.
3) Repeat SQ3 with a larger prompt set, longer generation limits, a calibrated evaluator such as StrongREJECT, a second quantization method and a second model family, and add a condition in which the direction is re-extracted from the quantized model.

REFERENCES

[1] A. Arditi, O. Obeso, A. Syed, D. Paleka, N. Panickssery, W. Gurnee, and N. Nanda, "Refusal in language models is mediated by a single direction," in *Advances in Neural Information Processing Systems*, vol. 37, 2024. [Online]. Available: https://arxiv.org/abs/2406.11717

[2] p-e-w and contributors, "Heretic: Fully automatic censorship removal for language models," software repository, 2025. Accessed: Nov. 10, 2026. [Online]. Available: https://github.com/p-e-w/heretic

[3] T. Dettmers, A. Pagnoni, A. Holtzman, and L. Zettlemoyer, "QLoRA: Efficient finetuning of quantized LLMs," in *Advances in Neural Information Processing Systems*, vol. 36, 2023. [Online]. Available: https://arxiv.org/abs/2305.14314

[4] K. Chen, J. Zhang, J. Hu, Y. Wang, J. Lou, Z. Feng, and M. Song, "Assessing safety risks and quantization-aware safety patching for quantized large language models," in *Proc. 42nd Int. Conf. Machine Learning (ICML)*, PMLR, vol. 267, 2025, pp. 9728-9746.

[5] S. Kadadekar, "Quality is not a safety proxy under quantization," arXiv preprint arXiv:2606.10154, Jun. 2026.

[6] Qwen Team, "Qwen3.5-9B," model card, Hugging Face, 2026. Accessed: Nov. 10, 2026. [Online]. Available: https://huggingface.co/Qwen/Qwen3.5-9B

[7] A. Vaswani, N. Shazeer, N. Parmar, J. Uszkoreit, L. Jones, A. N. Gomez, L. Kaiser, and I. Polosukhin, "Attention is all you need," in *Advances in Neural Information Processing Systems*, vol. 30, 2017.

[8] F. Joad, M. Hawasly, S. Boughorbel, N. Durrani, and H. T. Sencar, "There is more to refusal in large language models than a single direction," in *Proc. Conf. Empirical Methods in Natural Language Processing (EMNLP)*, 2026, pp. 59196-59232.

[9] M. Mazeika *et al.*, "HarmBench: A standardized evaluation framework for automated red teaming and robust refusal," in *Proc. 41st Int. Conf. Machine Learning (ICML)*, PMLR, vol. 235, 2024, pp. 35181-35224.

[10] A. Souly *et al.*, "A StrongREJECT for empty jailbreaks," arXiv preprint arXiv:2402.10260, 2024.

[11] P. Röttger, H. R. Kirk, B. Vidgen, G. Attanasio, F. Bianchi, and D. Hovy, "XSTest: A test suite for identifying exaggerated safety behaviours in large language models," in *Proc. NAACL*, 2024.

[12] Abliterlitics, "Qwen3.5-9B ablation comparison," project report and classifier source code, 2026. Accessed: Nov. 10, 2026. [Online]. Available: https://abliterlitics.dev/models/qwen3.5-9b/

ADDITIONAL BIBLIOGRAPHY

Further sources cited in the text with the prefix A. They support the background discussion and are listed separately from the core references.

[A1] M. Labonne, "Uncensor any LLM with abliteration," Hugging Face blog, Jun. 2024. [Online]. Available: https://huggingface.co/blog/mlabonne/abliteration

[A2] K. Egashira, M. Vero, R. Staab, J. He, and M. Vechev, "Exploiting LLM quantization," in *Advances in Neural Information Processing Systems*, vol. 37, 2024.

[A3] grimjim, "Projected abliteration," Hugging Face community article, Oct. 2025. [Online]. Available: https://huggingface.co/blog/grimjim/projected-abliteration

[A4] A. Zou *et al.*, "Representation engineering: A top-down approach to AI transparency," arXiv preprint arXiv:2310.01405, 2023.

[A5] grimjim, "Norm-preserving biprojected abliteration," Hugging Face community article, Nov. 2025. [Online]. Available: https://huggingface.co/blog/grimjim/norm-preserving-biprojected-abliteration

[A6] T. Wollschläger, J. Elstner, S. Geisler, V. Cohen-Addad, S. Günnemann, and J. Gasteiger, "The geometry of refusal in large language models: Concept cones and representational independence," arXiv preprint arXiv:2502.17420, 2025.

[A7] X. Qi *et al.*, "Safety alignment should be made more than just a few tokens deep," in *Proc. Int. Conf. Learning Representations (ICLR)*, 2025.

[A8] D. Kumar, A. Kumar, S. Agarwal, and P. Harshangi, "Fine-tuning, quantization, and LLMs: Navigating unintended outcomes," arXiv preprint arXiv:2404.04392, 2024.

APPENDIX A
REPRODUCIBILITY DETAILS

A.1 Sources

Table A.1 lists the public sources used in the study. Exact revisions, file hashes and run logs are recorded in the project repository.

Table A.1: Models, code and datasets

Source	Role
Qwen/Qwen3.5-9B	Original model W
trohrbaugh/Qwen3.5-9B-heretic-v2	Published edit P
p-e-w/heretic (hybrid-compatible revision)	Edit implementation
mlabonne/harmful_behaviors	Extraction (400) and reproduction test (100)
mlabonne/harmless_alpaca	Extraction (400) and KL prompts (100)
centerforaisafety/HarmBench	Safety prompts for the semantic evaluation
paul-rottger/xstest	Safe prompts (five distinct items)
openai/grade-school-math (GSM8K)	Arithmetic problems (five items)
Abliterlitics classifier, version 3	Heuristic refusal detector

A.2 Settings and compute

The published Heretic parameters are a direction index of 18.49; for attention output projections a maximum strength of 2.00 at position 18.99, falling to 1.43 at a distance of 9.65; and for MLP down projections a maximum strength of 1.67 at position 26.06, falling to 0.84 at a distance of 18.04. The software versions were torch 2.11, transformers 5.22.1, peft 0.21.2, accelerate 1.15.0 and bitsandbytes 0.50.2. All runs used FP16 on two NVIDIA T4 GPUs. The reconstruction runs used 2.11 GPU-hours of Kaggle quota, the NF4 pilot 1.04 hours and the semantic audit 0.87 hours. Earlier unsuccessful runs are not included in these figures.

A.3 Bounds for the NF4 comparison

For each condition, let its score be the fraction of the six pilot safety prompts that it clearly fulfills. The edit effect at full precision is the score of D minus the score of W, and the edit effect after NF4 is the score of Q(W + Δ) minus the score of Q(W). The change caused by quantization is the second effect minus the first. With the observed labels this change is 0, since both effects are 2 of 6. If every partial and unknown label is allowed to count as either fulfilled or not, the change lies between −0.500 and +0.667. If responses that were cut off are also allowed to continue into fulfillment, the range widens

to between −0.833 and +0.833. These are bounds over possible labelings of a fixed set of prompts, not confidence intervals, and they do not account for reviewer error.