ChainProof Lite - Final Walkthrough

ChainProof Lite is a production-ready certificate verification system built for the Polygon blockchain. It combines SHA-256 cryptographic hashing with decentralized storage (IPFS) to create an immutable proof-of-authenticity for any digital document.

🏗️ Project Architecture

```
graph TD
    A[Admin/Issuer] -->|Upload PDF| B[Next.js API]
    B -->|Generate SHA-256| C[Hash]
    B -->|Upload Metadata| D[IPFS]
    C -->|Store on Chain| E[Polygon Smart Contract]
    F[Verifier/User] -->|Upload PDF| G[Verification Portal]
    G -->|Client-side Hashing| H[Query Contract]
    H -->|Match?| I{Result}
    I -->|Yes| J[Verified ✅]
    I -->|No| K[Tampered ❌]
```

🛡️ Security & Advanced Features

1. Fake Upload Prevention

We implemented **Role-Based Access Control (RBAC)** using OpenZeppelin's `AccessControl`. Only addresses with the `ISSUER_ROLE` can invoke the `issueCertificate` function.

2. Hash Collision & Replay Attacks

- **SHA-256**: Offers extreme collision resistance.
- **Uniqueness Check**: The smart contract prevents re-issuing an existing hash, stopping replay attacks where someone might try to re-register a stolen certificate under a new name.

3. Revocation Design

The contract includes a `revokeCertificate` function. Once revoked, the `verifyCertificate` view will return `isValid: false`, even if the file hash matches. This is critical for expired or invalidated credentials.

4. Handling Re-exported Certificates

The Problem: If a user re-exports a PDF from Chrome, the binary hash changes due to metadata shifts. **The Solution**: We store a `unique_id` in the IPFS metadata. For high-fidelity cases, we can implement "Content Hashing" (hashing only the text/images) instead of the whole file.

5. Scalability for 100,000+ Certificates

For mass production:

- **Merkle Trees**: Instead of storing 100k individual hashes ($$$ gas), we store 1 Merkle Root of 10k certificates in a single transaction (saves 99.99% gas).

🚀 Demo-Ready Components

- **Admin Dashboard**: Modern upload & hashing interface.
- **Verification Portal**: Premium trust-focused validation UI.
- **Smart Contract**: Optimized Solidity registry.

🛠️ Demo Instructions (Local Environment)

We have optimized the setup for a high-speed local demo using Hardhat.

✨ Premium UI Features

- **3D Hero Section**: A rotating blockchain cube built with Three.js (React Three Fiber) that reacts to user scroll.
- **Interactive Assets**: A floating, glowing certificate card that demonstrates the "On-Chain Verified" state.
- **Motion & Parallax**: Smooth entrance animations and parallax scroll effects powered by Framer Motion.
- **Dynamic Gradients**: Animated background gradients that create a modern, high-end feel.

1. The Infrastructure

- **Local Node**: Running on `http://127.0.0.1:8545` (Chain ID: `31337`).
- **Smart Contract**: Deployed at `0xe7f1725E7734CE288F8367e1Bb143E90bb3F0512`.

2. Running the Demo

1. **Issuer Flow**:
   - Go to `/admin`.
   - Connect MetaMask to **Localhost 8545**.
   - Upload a PDF. It will be hashed and pinned to IPFS.
   - Click **Finalize on Blockchain** to sign the transaction and store the proof.
2. **Verification Flow**:
   - Go to `/verify`.
   - Drag and drop the same PDF.
   - System re-hashes the file and queries the local contract.
   - **RESULT**: Verified ✅ with issuance date and issuer address!

3. Proof of Security (The "Tamper" test)

- Take the original PDF, open it, add a single dot or space, and save.
- Upload to `/verify`.
- **RESULT**: Tampered ❌ (Hash mismatch).