



VEKTRON SAE 0W-20
PREMIUM ENGINE OIL
FULLY SYNTHETIC HYBRID ENGINE OIL

Product Descriptions

VEKTRON SAE 0W-20 EV Hybrid is made by 100% synthetic base oil, optimized for hybrid passenger cars (gasoline based only). Also suitable for latest engine fitted new technologies including turbocharger, DOHC, GDI and vehicles requiring performance specifications API SP and ILSACGF-6. API SP specification was created to prevent the problem of LSPI (lowspeed pre-ignition) and T-GDI engines.

Applications

- Low viscosity lubricants are suitable for hybrid carb(gasoline based only)
- Vehicles equipped with DOHC, Turbocharger, GDI are suggested to apply API SP, ILSAC GF-6A engine oil

Features and Benefits

- This engine oil provides premium performance thanks to very stable and clean base oil properties
- High viscosity index ensures adequate oil film strength that hot operating condition
- EV HYBRID is formulated with latest cleaning agents that help to remove dirt and deposits actively

Performance Level

- API SP/ ILSACGF-6A
- API SP/ ILSACGF-6B (0W-16)

Typical Properties

Viscosity	40°C	ASTMD445	cSt	37.7	44.8
	100°C	ASTMD445	cSt	7.3	8.4
VI		ASTMD2270	-	161	171
HTHS		ASTMD4683	cP	2.4	2.7
FlashPoint		ASTMD92	°C	227	225
PourPoint		ASTMD97	°C	-40	-40

ROWE MINERALÖLWERK	VEKTRON SAE 0W-20
GMBH Borkensteiner Mühle	FULLY SYNTHETIC HYBRID ENGINE OIL 02.02.2019

This lubricant used as recommended and for the application for which has been designed does not present any particular risk. A material safety data sheet is obtainable via your commercial adviser.