



VEKTRON SAE 10W-40 **PREMIUM ENGINE OIL** **LPG AND GASOLINE ENGINE OIL**

Product Description

VEKTRON SAE LPG 10W-40 designed from 100% synthetic base oil, used in passenger cars equipped with gasoline, LPG engines. It suitables for recent technology engines (multivalve, Turbocharged, with/without catalytic converter) and vehicle equiring performance Specification API SN PLUS/ SN/CF

Applications

- Suitable used in LPG/LNG/CNG engine (10W-30,10W-40,15W-40, 20W-50)
- Vehicles with DOHC, Turbocharger, CRDI, Catalytic Converters
- Diesel vehicles equipped with after-treatment devices including EGR, DPF

Features and Benefits

- Rapid oil flow in cold condition assures easy start and good drivability
- High viscosity index ensures adequate oil film streng that hot operating condition
- **VEKTRON SAE LPG 10W-40** excellent clean up properties help to remove dirt and sludge from building up
- Improved fuel efficiency by minimization of friction

Performance Level

- API: SP/ ILSAC GF-6A
- API SN PLUS/ SN/CF ILSAC GF-5

Typical Properties

TEST ITEMS		Method	Unit	10W-30	10W-40
Specific Gravity		ASTMD1298	-	0.853	0.852
Viscosity	40°C	ASTMD445	cSt	67.99	79.16
	100°C	ASTMD445	cSt	11.86	13.58
Viscosity Index		ASTMD2270	-	172	176
Flash Point		ASTMD92	°C	236	246
Pour Point		ASTMD97	°C	-36	-39

ROWE MINERALÖLWERK GMBH

VEKTRON SAE LPG 10W-40

Borkensteiner Mühle 7 67308 Bubenheim

02.05.2019



This lubricant used recommended and forthe application for which it has been designed does not present any particular risk. Amaterial safety data sheet is obtain able via you rcommercial adviser.