



VEKTRON DIESEL SAE 5W-30 CK-4 PREMIUM FULLY SYNTHETIC LUBRICANTS

Product Description

VEKTRON DIESEL SAE 5W-30 CK-4 is formulated with VHVI grade base oil. It is ideal for vehicles and heavy equipment—whether turbocharged or naturally aspirated, for on-road or off-road use—including units fitted with exhaust after-treatment systems such as Diesel Particulate Filters (DPF). Optimized for EURO VI emission standards, this fully synthetic lightand passenger diesel engine oil meets ACEA commercial vehicle “E” classification requirements. It supports extended drain intervals, lowers emissions, and promotes longer engine service life.

Applications

- All turbocharged or normally aspirated diesel engines of vehicles operating in the most severe conditions
- Suitablebformost OEM sincluding Benz, Volvo, Cummins for EuroIV, V and VI engines
- Light Trucks, RVs, SUVs, Heavy Trucks, Buses withbdiesel engines.

Features and Potential Benefits

- Full synthetic base oil enhances the engine protection and engine oil life thanks to high stability and cleanliness
- This low SAPS (Sulfated Ash, Phosphorus and Sulfur) engine oil provides long life for exhaust after-treatment devices including diesel particulate filter
- Excellent detergent system helps keep pistons and other engine parts cleanfor long engine life
- Good thermal breakdown resistance ensures engine protection under modern engine’s severe conditions

Performance Level

- | | | |
|--------------------------|-----------------------|-------------------------|
| □ API:CK-4/CJ-4 | □ Volvo:VDS-4.5 | □ Cummins:CES20086 |
| □ ACEA:E9-16 | □ Mack:EO-S-4.5 | □ Caterpillar:ECF-3 |
| □ Mercedes-Benz:MB228.31 | □ Renault Truck:RLD-4 | □ DEUTZ:DQCIII-10LA |
| □ MTU:Category2.1 | □ Ford:WSS-M2C171-F1 | □ Detroit Diesel:93K222 |

Typical Properties

TestItems		Method	Unit	5W-30	10W-30	10W-40
SpecificGravity		ASTMD129	-	0.857	0.857	0.857
Viscosity	40°C	8 ASTM	cSt	78.13	98.95	103.4
	100°C	D445				
ViscosityIndex		ASTMD445	cSt	12.0	14.8	15.1
		ASTMD2270	-	148	155	153
FlashPoint		ASTMD92	°C	244	248	247
PourPoint		ASTMD97	°C	-34	-37	-34

ROWE MINERALÖLWERK
GMBH Borkensteiner Mühle
7 67308 Bubenheim

VEKTRON DIESEL SAE 5-30 CK-4 2022.08.14.

This lubricant used recommended and for the application for which it has been designed does not present any particular risk. A material safety data sheet is obtainable via your commercial adviser.