



VEKTRON SAE 5W-40 C3 GASOLINE/DIESEL PREMIUM FULLY SYNTHETIC

Product Description

VEKTRON SAE 5W-40 C3 GASOLINE/DIESEL is designed from **premium fully synthetic base oil**, used in passenger cars equipped with gasoline, diesel, and LPG engines. This is formulated to meet the engine oil requirement of European automobiles makers such as Volkswagen, BMW and Benz.

Applications

- Passenger cars with gasoline and diesel ang LPG engines.
- Vehicles with DOHC, Turbocharger, CRDI, Catalytic Converters
- Diesel vehicles equipped with after-treatment devices including EGR, DPF, GPF.

Features/Benefits

- This low SAPS (Sulfated Ash, Phosphorus and Sulfur) engine oil provides long life for exhaust after treatment devices including diesel particulate filter
- Synthetic oil flow in cold condition assures easy start and good drivability and prevent LSPI.
- Highviscosityindexensuresadequateoilfilmstrengthathotoperatingcondition
- **VEKTRON SAE 5W-40 C3 GASOLINE/DIESEL**'s excellent clean up properties help to remove dirt and sludge and varnish building up.

Performance Levels

- ACEA:C3-16
- API: SP, ILSAC GF-6A
- Mercedes-Benz:MB229.51/229.52
- BMW:LongLife-04
- Volkswagen:VW502.00/505.00/505.01

Typical Testing

Test Items		Method	Unit	5W-30	5W-40
Specific Gravity		ASTMD129	-	0.853	0.852
Viscosity	40°C	8 ASTM D445	cSt	67.99	79.16
	100°C	ASTMD445	cSt	11.86	13.58
Viscosity Index		ASTMD2270	-	172	176
Flash Point		ASTMD92	°C	236	246
Pour Point		ASTMD97	°C	-36	-39

ROWE MINERALÖLWERK
GMBH Borkensteiner Mühle
7 67308 Bubenheim

VEKTRON SAE 5W-40 C3
GASOLINE/DIESEL
19.06.2020



This lubricant used recommended and for the application for which it has been designed does not present any particular risk. A material safety data sheet is obtainable via your commercial adviser.