



VEKTRON ATF DEXRON® VI **PREMIUM FULLY SYNTHETIC** **AUTOMATIC TRANSMISSION FLUID**

Product Description

VEKTRON ATF DEXRON® VI is an innovative automatic transmission fluid based on an advanced synthetic technology allowing very high performance. It offers fuel economies thanks to low viscosity. This lubricant has been developed to meet the needs of modern transmission where higher efficiency is required. It is a low viscosity formulation that meets the more demanded OEM specifications.

Typical Properties Application

The latest generation of high efficiency 6/8 speeds automatic transmission.

Features and Benefits

Excellent viscosity stability in operation

Exceptional friction and anti-shudder performances

Enhanced fuel economy thanks to low viscosity and excellent low temperature performance

Good thermal stability and resistance to oxidation

Performance Levels

- Recommended for use where the following specifications are called for:
ATF(ATF II/III, JWS3309/3314/3324, TE-ML11A/11B, AW-1/2, M2C138-CJ, M2C166-H, M2C922-A1, K17, N402, LT 71141, HP), Alison(C2/C3/C4), Bentley(PY112995PA), BMW(400 272/275, 407 858/859, 024 249/359, 026922, 142516, 397114, 402413, 403248/249, 152426, 163514, 220438/440/442, 289720, 305396/397, 355599/601, 542290, 407765/807), FCA(092912AA, 043742AA, 127382AA, 157995AA/AB, 333587AA, 171866AA, 171869AA, 218925AA/AB), Ford/Lincoln/Mercury(LV, ULV, M, Syn, V, V Syn, SP, Premium, FRN5), GM(Z1, Dex, Dex-HP, Dex-B, Dex-IIC/D/E, Dex-IIIF/G/H, Dex-VI), Honda(DW-1/Type 3.0/Type 3.1, Z1), Hyundai/Kia(SP, SP-II/III/IV/SP-IV-M/SP-IV-M1/SP-IV-RR), Isuzu(9001, SCS), Jaguar(02JDE 26444, Fluid 8432, JLM 20238/20292/21044/WSS-M2C922-A1), JASO(M315 1A/1A-LV), Land Rover(ATF N402, AW-1 LV, JWS3309US), MAN(339A/D/F), Maserati(231603), Mazda(A7, F-1, FZ, M3, N1, S-1, T-IV), Mercedes/Daimler(MB 236.1/10/11/12/14/15/16/17/2/41/5), Mitsubishi(J2/3, PA, MA-1, AW, DII/III, SP/SP-II/III/IV), Nissan/Infinity(Matic -D/J/K/P/S/W/N402), Porsche(204 63, 205 28, 304 00, 54700, 205 09), PSA(9730AE, 169756), Renault(DP-0, Matic-D2, SATF-D), Rolls Royce(31493PA), Saab(160 393), Saturn(Dex-IIIG, T-IV), SSangyong(DSIH5M-52/66), Subaru(ATFWS), Suzuki (2326, 2384K, 3314, 3317, 5D06), Toyota (FZ, Type WS, NWS9638, T-IV, D-II, T, T-II/III), VW(052 533/990, 053 001, 055 005/025/162/540, 060 162/540), Volvo(161/521/540/621/640), ZF(Lifeguard fluid 5/6/8/9)

Typical Properties

Test Items		Method	Unit	Properties
SpecificGravity Viscosity	40°C	ASTMD1298	-	0.8442
		ASTM D445	cSt	30.3
	100°C	ASTMD445	cSt	6.1
ViscosityIndex		ASTMD2270	-	154
FlashPoint		ASTMD92	°C	220
PourPoint		ASTMD97	°C	-49

ROWE MINERALÖLWERK GMBH	VEKTRON ATF DEXRON ® VI
Borkensteiner Mühle 7 67308 Bubenheim	2026.06.01

This lubricant used recommended and for the application for which it has been designed does not present any particular risk. A material safety data sheet is obtainable via your commercial adviser.